FAPP

AD 2.1 AERODROME LOCATION INDICATOR AND NAME

FAPP - POLOKWANE INTERNATIONAL

AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	*ARP co-ordinates and site at AD*	235058.73S 0292723.36E
2	*Direction and distance from city*	360°, 5NM N of Polokwane
3	*Reference elevation/Reference temperature*	4076 FT / 24,6° C
4	*Geoid undulation at aerodrome elevation position*	56.6FT
5	*MAG VAR* *annual change*	16° W /2018 0°5' W
6	*AD operator, address, Telephone, Telefax, Email, AFS address and, if available, website address*	PUB AD CHF: Gateway Airport Authority Limited P.O. Box 1309 POLOKWANE, 0700 TEL: +27 15 288 0122 FAX: +27 15 288 0125 ATC: +27 15 288 0343 ATC FAX: +27 15 288 0344 MET: +27 15 288 0030, FAX +27 15 288 0030 Border Police: +27 15 288 7000 Border Police: +27 76 534 0337 Customs: +27 15 288 1585/6 Customs: +27 76 534 0337 Immigration: +27 15 288 0083, +27 83 773 5218 or +27 73 993 7642 AFS: FAPPZTZX
7	*Types of traffic permitted (IFR / VFR)*	IFR/ VFR
8	*Remarks*	NIL

AD 2.3 OPERATIONAL HOURS

1	*AD Operator*	MON - FRI: 0430 - 1630 SAT: 0700 - 1400; SUN: 0700 - 1630. Public Holidays will be notified accordingly via NOTAM.
2	*Customs and immigration*	Same as AD HOD. Available after hours preferably with prior notice giving the date and time of arrival or departure to the Port Officials
3	*Health and sanitation*	Available within AD hours with 2 HR PN
4	*AIS briefing office*	H24 Central AIS +27 86 025 9669, +27 11 928 6517 / 6593 / 6514
5	*ATS reporting office (ARO)*	MON - FRI: 0430 - 1630 SAT: 0700 - 1400; SUN: 0700 - 1630. TEL: +27 15 288 0343

6	*MET briefing office*	2230 - 1800.
7	*ATS*	MON-FRI: 0430-1630, SAT: 0800-1400, SUN: 0800-1630. HOD during Public Holiday's will be notified via NOTAM.
8	*Fuelling*	Jet A1 and AVGAS AVBL during AD operator hours of service. Outside AD operator HR, refuelling arrangements are to be made 60MIN prior to delivery time by ACFT OPR. For refuelling enquiries CTC: Jacques Pennells - Tel: +27 82 653 7956. Raschelle Pennells - Tel: +27 82 878 7610.
9	*Handling*	MON-FRI: 0430-1630, SAT: 0700 - 1400; SUN: 0700 - 1630. AVBL outside these hours only with prior arrangement.
10	*Security*	H24 security service
11	*De-icing*	NIL
12	*Remarks*	Services are available on request after stipulated hours with prior notice as stipulated for the specific service.

AD 2.4 HANDLING SERVICES AND FACILITIES

1	*Cargo-handling facilities*	Belt loader and Pallet dolly
2	*Fuel and Oil types*	AVGAS 100, JET Ai and certain oil types
3	*Fuelling facilities and capacity*	Fuel Bowsers JET At, AVGAS Fuel Tank
4	*De-icing facilities*	NIL
5	*Hangar space for visiting aircraft*	16 x 540 square metre 1 x 6450 square metre Prior arrangements to be made regarding hangars.
6	*Repair facilities for visiting aircraft*	NIL
7	*Remarks*	NIL

AD 2.5 PASSENGER FACILITIES

1	*Hotels*	Overnight accommodation: Hotels, Chalet and Lodges in Town within ten (10) KM radius.
2	*Restaurants*	Coffee shop and light meals available at the airport during airport hours. Variety of restaurants available within 10km radius of the airport and in the city of Polokwane.
3	*Transportation*	Buses, Taxis and Limousine available on request.

4	*Medical facilities*	First Aid at the airport. Clinic and hospital within 10KM of the airport.
5	*Bank and Post Office*	Banks available within 10km radius of the airport and in the city of Polokwane.
6	*Tourist office*	Basic Tourism Information available at the Airport Information Desk. Provincial Tourism Office available in the city: Contact: +27 15 293 3600 Email: info@golimpopo.com
7	*Remarks*	NIL

AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	*Aerodrome category for fire fighting*	CAT VII within AD HR. 1 Acting Chief fire officer. 9 or 10 responding personnel per shift, total 20.
2	*Rescue equipment*	2 fire fighting vehicles, 2 Power saws, 1 hydraulic jaws of life, 24400L water, 3416L per MIN foam discharge and 450KG DCP. 100% stock maintained and 200% in store. 680L premix on Rescue 1 and 50KG DCP on Rescue 1. Standard firefighting equipment are carried and operated on all fire tenders in accordance with ICAO and SACAA requirements for CAT 7 AD licence.
3	*Capability for removal of disabled aircraft*	Bronkhorst Crane Hire: TEL: +27 15 293 0927 CELL: Softy +27 82 717 1093 or Beauty +27 79 102 8003. ACFT operator to remove disabled aircraft from active RWY within 2 hours.
4	*Remarks*	SAR - Under the co-ordinatlng direction of the South-African Search and Rescue Organisation (SASAR) Memorandum of understanding with Polokwane Municipality Fire Brigade, Disaster management and Limpopo Emergency Medical services. Memorandum of Understanding with SAPS Diving Unit for rescue in difficult environment. RFFS simulator situated 100M north of TWY B.

AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	*Types of clearing equipment*	NIL
2	*Clearance priorities*	NIL
3	*Remarks*	Open all seasons

AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	*Designation, surface and strength of aprons*	A = Rigid, PCR 960/R/A/W/T B = Rigid, PCR 960/R/A/W/T C = Rigid, PCR 960/R/A/W/T D = Flexible, PCR 960/R/A/W/T
2	*Designation, width, surface and strength of taxiways*	A = 23m, Flexible, PCR 980/F/A/X/T B = 23m, Flexible, PCR 980/F/A/X/T C = 23m, Flexible, PCR 980/F/A/X/T D = 23m, Flexible, PCR 980/F/A/X/T E = 23m, Flexible, PCR 980/F/A/X/T
3	*ACL and elevation*	THR RWY 01, 4076FT THR RWY 19, 4013FT THR RWY 05, 4014FT THR RWY 23, 4035FT
4	*VOR checkpoints*	NIL
5	*INS checkpoints*	NIL
6	*Remarks*	Apron flood lights available.

AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	*Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands.*	1) Aircraft stand ID signs not provided on all stands 2) Taxing guidance signs and markings provided at all intersections and runway holding positions.
2	*RWY and TWY markings and LGT*	RWY 05/23 APCH, THR, RWY edge and RWY end, PAPI 05, displaced wingbar RWY 23 and wingbar 05 lit. TDZ not lit. TWY: centreline and holding positions at all TWY/RWY intersections marked and lit; TWY edge except TWY A lit; centreline and TWY holding positions at other locations marked only. Guard light on TWY B, C, D and E. TWY lead On/Off lights on TWY E. Stop bars at E TWY lit.
3	*Stop bar*	Provided at TWY E.
4	*Remark*	Marking aids: All runways - thresholds, Touch - down, RWY designator, RWY centre line and Holding points. No designated helipad. Aprons - Some parking bays numbered. Taxiways: A, B, C, D and E. For aerodrome restricted visibility refer to chart AD-02. Wind direction indicator AVBL and lit. Guard lights on TWY B, C, D and E.

AD 2.10 AERODROME OBSTACLES

In Area 2					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	12416 EXT TWR	S235252.16 E0292428.36	1299.38m	NIL INFO AVBL	NIL
NIL INFO AVBL	BEN HARRIS TWR	S235329.49 E0292439.40	1280.85m	NIL INFO AVBL	NIL
NIL INFO AVBL	EAGL SESH AME MAST	235139.81S 0292306.31E	1282.64m	NIL INFO AVBL	NIL
NIL INFO AVBL	FIRE SIMULATOR	235114.51S 0292718.43E	1239.82m	NIL INFO AVBL	NIL
NIL INFO AVBL	ILD BLD	235002.84S 0292806.84E	1228.18m	NIL INFO AVBL	NIL
NIL INFO AVBL	MOROPA MAKETE MAST	234715.67S 0293122.36E	1239.21m	NIL INFO AVBL	NIL
NIL INFO AVBL	PISHEGO TWR	235148.22S 0292323.73E	1299.85m	NIL INFO AVBL	NIL
NIL INFO AVBL	VODA MAST DEWET	235250.82S 0292856.36E	1332.58m	NIL INFO AVBL	NIL
NIL INFO AVBL	SBA PLK EXT29 TWR	235209.28S 0292545.86E	1264.17m	NIL INFO AVBL	NIL
NIL INFO AVBL	VODA TWR FUTURA	235219.35S 0292623.62E	1274.71m	NIL INFO AVBL	NIL
NIL INFO AVBL	VODA TWR LESEDI	235213.58S 0292536.31E	1256.48m	NIL INFO AVBL	NIL
NIL INFO AVBL	VODA TWR LUTHULI	235108.89S 0292426.57E	1257.70m	NIL INFO AVBL	NIL
NIL INFO AVBL	VODA TWR LITHULI PARK	235121.06S 0292451.10E	1264.72m	NIL INFO AVBL	NIL
NIL INFO AVBL	VODA TWR SESH IND	235017.66S 029235207E	1264.70m	NIL INFO AVBL	NIL
NIL INFO AVBL	VODA TWR TWEEFONTEIN	235004.31S 0293014.57E	1264.70m	NIL INFO AVBL	NIL

In Area 3					
OBST ID/ Designation	*OBST Type*	*OBST position*	*ELEV/HGT*	*Markings/type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL

AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	*Associated MET office*	FAPP
2	*Hours of service* *MET office responsible outside hours*	0230-1830 TEL: +27 15 288 0030 CELL: +27 72 458 5128 1830-0230: O R TAMBO TEL: +27 82 233 9600
3	*Office responsible for TAF preparation and periods of validity*	FAOR Domestic TAF: 11HR
4	*Type of trend forecast and interval of issuance*	FAOR, hourly
5	*Briefing / consultation provide*	NIL
6	*Flight documentation / language(s) used*	NIL
7	*Charts and other information available for briefing or consultation*	NIL
8	*Supplementary equipment available for providing information*	Aviation MET website
9	*ATS units provided with information*	TWR, APP
10	*Additional information (limitation of service, e.t.c.)*	Flight documentation and other Aviation related Information AVBL on web page http://aviation.weathersa,co.za,

AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	*TRUE &MAG BRG*	*Dimensions of RWY (M)*	*Strength (PCR) and surface of RWY and SWY*	*THR coordinates RWY end coordinates THR geoid undulation*	*THR elevation and highest elevation of TDZ of precision APP RWY*	*Slope of RWY-SWY*
1	*2*	*3*	*4*	*5*	*6*	*7*
01	359°T/013°M	2560 x 45	PCR 980/F/A/X/T	235137.47S 0292731.76E	4076FT	- 0,75%
19	179°T/193°M	2560 x 45	PCR 980/F/A/X/T	235014.26S 0292730.21E	4013FT	+ 0,75%
05	038°T/052°M	2320 x 45	PCR 980/F/A/X/T	235131.71S 0292649.72E	4014FT	+0.28%

Designations RWY NR	*TRUE &MAG BRG*	*Dimensions of RWY (M)*	*Strength (PCR) and surface of RWY and SWY*	*THR coordinates RWY end coordinates THR geoid undulation*	*THR elevation and highest elevation of TDZ of precision APP RWY*	*Slope of RWY-SWY*
1	*2*	*3*	*4*	*5*	*6*	*7*
23	218°T/232°M	2320 x 45	PCR 980/F/A/X/T	235032.06S 0292740.22E	4035FT	- 0,28%
SWY dimensions (M)	*CWY dimensions (M)*	*Strip dimensions (M)*	*RESA dimensions (M)*	*Location (which runway end) and description of arresting system (if any);*	*OFZ*	*Remarks*
8	*9*	*10*	*11*	*12*	*13*	*14*
100	1102	2880 x 150	240 X 90	NIL INFO AVBL	NIL INFO AVBL	See below.
100	45	2880 x 150	240 X 90	NIL INFO AVBL	NIL INFO AVBL	
855 X 45	915	3299 x 280	240 X 90	NIL INFO AVBL	NIL INFO AVBL	
NIL	60	3299 x 280	90 x 90	NIL INFO AVBL	NIL INFO AVBL	

Remarks 12
1) RWY 01 DEP to be REQ on start up due to restricted VIS of the RWY,
2) The full length DEP of RWY 23 to be done at pilots discretion due to the first 800M not being visible FM the TWR.
NB : Threshold of RWY 23 displaced due to slope, first 800M not visible from the TWR.
Safe APCH slope on 2%.
Circuit Procedures
(a) Circuit altitude: Piston engined aircraft - 5100 FT
Jet Engined aircraft - 5600 FT
(b) RWY 01 in use - Left hand circuit
RWY 19 in use - Right hand circuit
RWY 05 in use - Left hand circuit
RWY 23 in use - Right hand circuit

AD 2.13 DECLARED DISTANCES

RWY	*TORA (M)*	*TODA (M)*	*ASDA (M)*	*LDA (M)*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*
01	2560	3662	2660	2560	NIL
19	2560	2605	2660	2560	NIL
05	2320	3235	3175	2320	NIL
23	2320	2380	2320	2320	NIL

AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	*APCH LGT Type, LEN and INTST*	*THR LGT Colour and WBAR*	*VASIS (MEHT) PAPI*	*TDZ,LGT LEN*	*RWY Centre Line LGT LEN, spacing, colour, INTST*	*RWY Edge LGT, LEN, spacing, colour, INTST*	*RWY End LGT Colour and WBAR*	*SWY LGT LEN (M) colour*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*
01	NIL	NIL	NIL	NIL	NIL	NIL	NIL	NIL	NIL
19	NIL	NIL	NIL	NIL	NIL	NIL	NIL	NIL	NIL
05	SALS 450M	Green	PAPI 3º R/H	NIL	NIL	60M White 10 000 candela	Red	Amber	NIL
23	NIL	DTHR Green	PAPI 3º L/H	NIL INFO AVBL	NIL INFO AVBL	60M White 10 000 candela	Red	NIL	NIL
1) Runway Lighting available RWY 05/23. 2) PAPI AVBL on RWY 05/23.									

AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	*ABN/IBN location, characteristics and hours of operation*	NIL INFO AVBL
2	*LDI location & LGT and anemometer location and LGT*	NIL INFO AVBL
3	*TWY edge and centre line lighting*	TWY edge.
4	*Secondary power supply and switch-over time*	Uninterruptible power supply available to cover PAPIs, APCH lights, RWY end lights, THR lights and RWY edge lights.
5	*Remarks*	APN lights OPR automatically, on during SS and off during SR.

AD 2.16 HELICOPTER LANDING AREA

1	*Coordinates TLOF or THR of FATO / Geoid undulation*	NIL INFO AVBL
2	*TLOF / FATO elevation (m/ft)*	NIL INFO AVBL
3	*TLOF and FATO area dimensions, surface, strength, marking*	NIL INFO AVBL

4	*True BRG of FATO*	NIL INFO AVBL
5	*Declared distance available*	NIL INFO AVBL
6	*APP and FATO lighting*	NIL INFO AVBL
7	*Remarks*	RWY used for Helicopter operation. Taxi/Air Taxi to/ from Apron.

AD 2.17 ATS AIRSPACE

1	*Designation and lateral limits*	CTR (a) From a point at 233841.59S 0292352.82E a straight line to a point at 234832.85S 0293738.15E (b) Thence straight line to a point at 240752.97S 0292115.76E (c) Thence a straight line to a point at 235800.33S 0290729.35E (d) Thence a straight line back to the starting point at 233841.59S 0292352.82E
2	*Vertical limits*	GND - 7600FT ALT
3	*Airspace classification*	Class "C"
4	*ATS unit call sign* *Language(s)*	Polokwane English
5	*Transition altitude*	9000 FT
6	*Remarks*	NIL

AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	*Call sign*	*Channel(s)*	*Hours of operation*	*Remarks*
1	*2*	*3*	*4*	*5*
TWR/APP	Polokwane	119.75 MHz	MON-FRI: 0430-1630, SAT: 0800-1400, SUN: 0800-1630. HOD during Public Holiday's will be notified via NOTAM.	Standby/Secondary FREQ 118.0 MHz

AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, MAG VAR, Type of supported OPS (for VOR/ILS/ MLS, give declination)	*ID*	*Frequency*	*Hours of operation*	*Position of transmitting antenna coordinates*	*Elevation of DME transmitting antenna*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*
VOR/DME	PPV	114.5 MHz CH 92X 1116MHz REC 1179MHz TRANS	H24	235023.35S 0292738.04E	4023 FT	Co-located with VOR.

AD 2.20 LOCAL AERODROME REGULATIONS

Circuit ALT: Piston 5100 FT. Jet 5600 FT circuits on all RWY to the West of AD.

AD 2.21 NOISE ABATEMENT PROCEDURES

1. As per ENR 1.5.
2. No engine run-ups will be allowed on the Apron without permission from AD Operator.

AD 2.22 FLIGHT PROCEDURES

- IFR Departures from FAPI to call FAPP ATC for start.
- TFC BLW THE Polokwane TMA to BCST intentions on 124.8 MHz.
- All departures from FAPI to contact FAPP Tower either on Frequency 119.75 MHz or via telephone on +27 15 288 0343 before take-off to obtain clearance into controlled airspace. FAPI circuits to be conducted as follows:
1. RWY 08 - right circuits at 5100ft on FAPP QNH.
2. RWY 26 - left circuits at 5100ft on FAPP QNH.
3. All circuit traffic to remain East of R37 road.
- All departures from The Ranch hotel to contact FAPP Tower on Frequency 119.75 MHz or via telephone on +27 15 288 0343 before take-off to obtain clearance into controlled airspace.

AD 2.23 ADDITIONAL INFORMATION

1) Limited view of manoeuvring area from TWR. Any OBST and foreign object debris on RWY 01/19, TWY C, TWY D and RWY 05/23 N of RWY INT not visible from the TWR. Pilots to EXER CTN.
2) ATC not in contact with vehicles and personnel transitting through APN, A, B, C and D. ATC assumes no responsibility over these movements,.
3) All pilots to and from FAPP to take note of TFC operating in close proximity to FAPP and FAPI Airfield (5NM South East).
4) APCH fees in effect to all ACFT inside Polokwane airspace. For more INFO, CTC Operations manager Mr Christian Mtshweni +27 60 957 8494.
5) Refer to GEN 4.2 to obtain information on the billing and collection for FAPP
6) Bird warning: Bird sanctuary west of THR RWY 05. Increased bird activity at the airport.

AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome Chart	-AD-01
Restricted Visibility Chart	-AD-02
Instrument Approach Chart	-VOR-01
RNP RWY 05	-RNP-01
Data tabulation	-RNP-01A

THIS PAGE INTENTIONALLY LEFT BLANK