FASS

FASS AD 2.1 AERODROME LOCATION INDICATOR AND NAME

FASS - SISHEN

AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	*ARP co-ordinates and site at AD*	273900S 0230000E
2	*Direction and distance from city*	10 KM
3	*Reference elevation/Reference temperature*	3848 FT/30.5°
4	*Geoid undulation at aerodrome elevation position*	104.8 FT
5	*MAG VAR* *annual change*	19° W (2018) 0°5' W
6	*AD operator, address, Telephone, Telefax, Email, AFS address and, if available, website address.*	Sishen Iron Ore Mine Private Bag X 506, KATHU, 8446 E-MAIL: flysishen@angloamerican.com Airport Manager: Contact Person: Ms L Blaauw TEL: +2753 739 3267 CEL: +2771 877 0480 E-MAIL: liana.blaauw@angloamerican.com VHF 123.50 MHz Aerodrome Coordinator: Contact Person: Ms. J. Booys TEL: +2753 739 2012 E-MAIL: jacky.booys@angloamerican.com
7	*Types of traffic permitted (IFR / VFR)*	IFR/VFR
8	*Remarks*	All movements to the airport to be approved in writing by the Airport Manager.

AD 2.3 OPERATIONAL HOURS

1	*AD Operator*	AD Operational hours: MON-FRI DLY BTN 0445-1545
2	*Customs and immigration*	NIL
3	*Health and sanitation*	NIL INFO AVBL
4	*AIS briefing office*	NIL INFO AVBL
5	*ATS reporting office (ARO)*	NIL INFO AVBL
6	*MET briefing office*	NIL INFO AVBL
7	*ATS*	NIL
8	*Fuelling*	NIL
9	*Handling*	NIL INFO AVBL

10	*Security*	Security scanning & x-raying available as per AD Operational hours.
11	*De-icing*	NIL INFO AVBL
12	*Remarks*	NIL

AD 2.4 HANDLING SERVICES AND FACILITIES

1	*Cargo-handling facilities*	No baggage services AVBL. Baggage on/off loading is the responsibility of the flight crew.
2	*Fuel and Oil types*	No AVGAS or Jet A1 AVBL. Refuelling on apron strictly prohibited.
3	*Fuelling facilities and capacity*	No AVGAS or Jet A1 AVBL. Refuelling on apron strictly prohibited.
4	*De-icing facilities*	NIL INFO AVBL
5	*Hangar space for visiting aircraft*	NIL
6	*Repair facilities for visiting aircraft*	NIL
7	*Remarks*	NIL

AD 2.5 PASSENGER FACILITIES

1	*Hotels*	Hotels and guest houses AVBL in Kathu.
2	*Restaurants*	Restaurants AVBL in Kathu.
3	*Transportation*	Car Rental Services AVBL at AP.
4	*Medical facilities*	LenMed hospital AVBL in Kathu.
5	*Bank and Post Office*	Banks and Post Office AVBL in Kathu.
6	*Tourist office*	NIL INFO AVBL
7	*Remarks*	NIL

AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	*Aerodrome category for fire fighting*	CAT 4
2	*Rescue equipment*	1 Scania fire tender 6x6, water capacity of 9000L foam capacity 1200L, discharge rate roof monitor 7500L/MIN, bumper monitor 2650L/MIN, dry powder capacity 225KG. 1 x double assassin fire fighting trailer with 1 x 680L premix tank, 1 x 135KG Dry Chemical Powder tank, 1 x 65 millimeter discharge provided from premix tank with feed to 65 millimeter monitor. 1 x basic life support (fire chief), 1 x deputy fire chief (emergency care technician), 8 x fire fighters (6 per shift), all fire fighters are qualified BLS Medics.

3	*Capability for removal of disabled aircraft*	Contracted in as per AEMS mutual aid agreement, policies and procedures
4	*Remarks*	NIL

AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	*Types of clearing equipment*	NIL INFO AVBL
2	*Clearance priorities*	NIL INFO AVBL
3	*Remarks*	NIL

AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	*Designation, surface and strength of aprons*	Stands 1, 2, 3, 4, and 5 Asphalt PCR 100/F/A/X/T & LCN 32
2	*Designation, width, surface and strength of taxiways*	Length:15 meters Width: 23 meters Surface: Asphalt Strength: A&B PCR 100/F/A/X/T & LCN 32
3	*ACL location and elevation*	NIL INFO AVBL
4	*VOR checkpoints*	NIL INFO AVBL
5	*INS checkpoints*	NIL INFO AVBL
6	*Remarks*	Aircraft Movement: Pilots of Operators utilising Sishen Airport shall ensure that ACFT are parked safely on the designated apron as approved by airport manager and are manoeuvred in an orderly and safe manner. Passenger Movement: Pilots of Operators utilizing Sishen Airport are responsible for and shall ensure the safe management and movement of their respective passenger flown or to be flown on their ACFT to/from Sishen Airport, especially DRG embarkation and disembarkation by accompanying embarking and disembarking passengers to/from the terminal building. Operators' pilots and hostesses shall wear reflective vests when on apron.

AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	*Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands.*	1.1. Sishen Airport has five (5) power-In / power-out self parking ACFT parking stands on the apron designated 1 to 5. 1.2. ACFT parked on stand numbers 1, 2, 4 & 5 will be facing the terminal building at 90 degrees. 1.3. ACFT parking stands must be approached using either Taxiway Alpha - approach direction. RWY 35 or Taxiway Bravo - approach direction RWY 17 entering the parking stands from the apron taxilane provided at the rear of the apron and facing the terminal building after final parking. 1.4. Due to NO Marshalling service AVBL, a yellow Lead-In line, Alignment Bar and Stop Bar/Line is provided on each of the five parking stands to assist flight crew with self parking. ACFT will be regarded safely parked within the designated parking stand when the stop bar/line provided on the left side of the aircraft is aligned with the left shoulder of the captain of the ACFT indicating that the ACFT is safely positioned within the designated safety lines provided in solid white. 1.5 ACFT approved to operate to Sishen Airport are to park on the parking stand as indicated on their approved application. Pushback Procedures: 2.1. For the purpose of departure, the ACFT would taxi forward following the yellow lead-out lines towards the taxilane and then a LEFT or RIGHT turn towards taxiway Alpha or Bravo pending the runway to be used for take-off . 2.2. Taxi out of the parking stands is towards the terminal building and then a LEFT or RIGHT towards Taxiway Alpha of Bravo.
2	*RWY and TWY markings and LGT*	AVBL
3	*Stop bar*	NIL
4	*Remark*	Pilots and operators utilizing the AP shall ensure that ACFT are parked WI designated parking bays and are manoeuvred in an orderly and safe manner. All movements to the airport to be approved in writing by the Airport Manager.

AD 2.10 AERODROME OBSTACLES

In Area 2					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL	NIL	NIL	NIL	NIL	NIL

In Area 3					
OBST ID/ Designation	*OBST Type*	*OBST position*	*ELEV/HGT*	*Markings/type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL	NIL	NIL	NIL	NIL	NIL

AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	*Associated MET office*	For Sishen Airfield weather information on the ground either 3 x clicks on the radio microphone at 121 MHz or sms “vfass” to 36101 or visit www.vitalweather.co.za. Pilots are to report any irregularities with the weather station to the Airport Manager or Airport Coordinator mentioned in 2.2 (6).
2	*Hours of service* *MET office responsible outside hours*	NIL INFO AVBL
3	*Office responsible for TAF preparation and periods of validity*	NIL INFO AVBL
4	*Type of trend forecast and interval of issuance*	NIL INFO AVBL
5	*Briefing / consultation provide*	NIL INFO AVBL
6	*Flight documentation / language(s) used*	NIL INFO AVBL
7	*Charts and other information available for briefing or consultation*	NIL INFO AVBL
8	*Supplementary equipment available for providing information*	NIL INFO AVBL
9	*ATS units provided with information*	NIL INFO AVBL
10	*Additional information (limitation of service, e.t.c.)*	Unmanned

AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	*True BRG*	*Dimensions of RWY (M)*	*Strength (PCR) and surface of RWY and SWY*	*THR coordinates RWY end coordinates THR geoid undulation*	*THR elevation and highest elevation of TDZ of precision APP RWY*	*Slope of RWY-SWY*
1	*2*	*3*	*4*	*5*	*6*	*7*
17	154° (T)	2325 x 23	PCR 210/F/C/Y/U ASPH	273813.03S 0225934.03E	3835 FT	+0.55%
35	334 °(T)	2325 x 23	PCR 210/F/C/Y/U ASPH	273920.63S 0230012.02E	3876 FT	-0.55%
SWY Dimensions (M)	*CWY Dimensions (M)*	*Strip Dimensions (M)*	*RESA dimensions (M)*	*Location (which runway end) and description of arresting system (if any);*	*OFZ*	*Remarks*
8	*9*	*10*	*11*	*12*	*13*	*14*
6 x 23	228 x 100	2456 x 150	NIL INFO AVBL	NIL INFO AVBL	NIL	See below
6 x 23	207 x 100	2456 x 150	NIL INFO AVBL	NIL INFO AVBL	NIL	See below
Warning: Blasting at Sishen Mining Area, MON-SUN: 0600-1700 - within 1 NM radius 273900S 0230000E. Danger height 2000 FT GND NW corner. FAR 25 UNL/GND 2 NM SE. NOTE: RWY THR 17 turn pad removed permanently.						

AD 2.13 DECLARED DISTANCES

RWY	*TORA (M)*	*TODA (M)*	*ASDA (M)*	*LDA (M)*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*
17	2325	2553	2331	2325	NIL
35	2325	2532	2331	2325	NIL

AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY	*APCH LGT Type, LEN and INTST*	*THR LGT Colour and WBAR*	*VASIS (MEHT) PAPI*	*TDZ, LGT LEN*	*RWY Centre Line LGT, LEN, Spacing, colour INTST*	*RWY Edge LGT, LEN, Spacing, Colour, INTST*	*RWY End LGT Colour and WBAR*	*SWY LGT LEN (m) Colour*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*
17	NIL INFO AVBL	Green	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	Spacing: 100M White INTST: 10%	Red	NIL INFO AVBL	RWY lighting available
35	NIL INFO AVBL	Green	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	Spacing: 100M White INTST: 10%	Red	NIL INFO AVBL	RWY lighting available

AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	*ABN/IBN location, characteristics and hours of operation*	NIL INFO AVBL
2	*LDI location & LGT and anemometer location and LGT*	NIL INFO AVBL
3	*TWY edge and centre line lighting*	NIL INFO AVBL
4	*Secondary power supply and switch-over time*	NIL INFO AVBL
5	*Remarks*	NIL

AD 2.16 HELICOPTER LANDING AREA

1	*Coordinates TLOF or THR of FATO / Geoid undulation*	NIL INFO AVBL
2	*TLOF / FATO elevation (m/ft)*	NIL INFO AVBL
3	*TLOF and FATO area dimensions, surface, strength, marking*	NIL INFO AVBL
4	*True BRG of FATO*	NIL INFO AVBL
5	*Declared distance available*	NIL INFO AVBL
6	*APP and FATO lighting*	NIL INFO AVBL
7	*Remarks*	NIL

AD 2.17 ATS AIRSPACE

1	*Designation and lateral limits*	NIL
2	*Vertical limits*	NIL
3	*Airspace classification*	NIL
4	*ATS unit call sign* *Language(s)*	NIL
5	*Transition altitude*	NIL
6	*Remarks*	NIL

AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	*Call sign*	*Channel(s)*	*Hours of operation*	*Remarks*
1	*2*	*3*	*4*	*5*
NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL

AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, MAG VAR, Type of supported OPS (for VOR/ ILS/MLS, give declination)	*ID*	*Frequency*	*Hours of operation*	*Position of transmitting antenna coordinates*	*Elevation of DME transmitting antenna*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*
VOR	SSV	113.6 MHz	H24	273907.83S 0230010.99E	NIL INFO AVBL	NIL
DME	SSV	CH 83X	H24	273907.83S 0230010.99E	3887 FT AMSL	Co-located with VOR

AD 2.20 LOCAL AERODROME REGULATIONS

1) Pilots and operators wanting to make use of Sishen Airport shall apply with the Sishen Airport Manager for written approval at least 24 hours before estimated time of intended MOV by requesting application documentation via email to liana.blaauw@angloamerican.com, jacky.booys@angloamerican.com and flysishen@angloamerican.com.
2) Failure to obtain the required written approval shall result in the following penalties:

– A fine amounting to R 5000 shall be imposed upon the operator or the registered owner of the ACFT;
– The incident shall be reported to SACAA by Sishen Airport;
– Note that unauthorised MOV at the AD may jeopardise insurance cover over the ACFT and/or occupants;
– Sishen Airport Manager reserves the right to decline an application for operating to Sishen Airport, such as in the event that the ETA / ETD are outside of the operational hours of the aerodrome and apron parking space is fully booked. Approval of an application cannot be guaranteed.

3) The airport charges landing and PAX fees as per the guidelines for airport charges stipulated in the Government Gazette.
4) After hour access to the airfield property is restricted. The runway is AVBL for ACFT related EMERG at own discretion.
5) Pilots and operators utilising the AP are responsible and shall ensure the safe management and MOV of their respective PAX, especially DRG embarkation and disembarkation.
6) Pilots and hostesses shall wear reflector vests when on the apron.
7) Pedestrian pathways are provided from the access gate leading to the airside up to the edge of the apron taxi lane of each of the five aircraft parking stands. No passengers may board or disembark when another aircraft is in the process of parking or departing. Pilots are to lead their PAX to/from disembarkation and embarkation.
8) Talking on a cell phone while embarking / disembarking of ACFT is strictly prohibited. Pilots are to ensure this rule is enforced with PAX.
9) Sishen Airport is an unmanned airport without ATC. ACFT to broadcast on 123.5 MHz when in Sishen airspace.

AD 2.21 NOISE ABATEMENT PROCEDURES

NIL INFO AVBL

AD 2.22 FLIGHT PROCEDURES

1. All arrivals in IMC (Cloud base below TAA):
Cloud base below the TAA, all arriving aircraft shall route via the IAF for the RNAV (GNSS) RWY 17 and comply with the approach.
2. All departure in IMC (Cloud base below TAA):
Cloud base below the TAA, all aircraft shall plan to depart RWY 17.
3. All arrivals and departure in VMC (Cloud base above TAA/MSA):
For all arriving and departing aircraft, the prevailing wind will determine the runway is use.
The departing aircraft shall use the runway with the headwind component, all arriving aircraft will slot into the traffic pattern and shall land on the same RWY as the departing traffic.

AD 2.23 ADDITIONAL INFORMATION

NIL INFO AVBL

AD 2.24 CHARTS RELATED TO AN AERODROME

AD	-AD-01
Aircraft parking/Docking chart	-AD-02
Visual ARR Chart RWY 17/35	-VFR ARR-01
Visual DEP Chart RWY 17/35	-VFR DEP-01
RNAV (GNSS) RWY 17	-RNAV-01
Data tabulation	-RNAV-01A