FAUP

FAUP AD 2.1 AERODROME LOCATION INDICATOR AND NAME

FAUP - UPINGTON INTERNATIONAL

FAUP AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	*ARP co-ordinates and site at AD*	282403.68S 0211534.78E
2	*Direction and distance from city*	2.5 NM NE
3	*Elevation/Reference temperature*	2791 FT/30.5 C
4	*Geoid undulation at AD ELEV PSN*	102.2 FT
5	*MAG VAR /* *Annual change*	20°W (2018) 0°4' W
6	*AD Operator, address, telephone, telefax, e-mail, AFS address and, if available, website address*	Authority supervising the aerodrome and remarks: PUB AD CHF: Airports Company South Africa Ltd Upington International Airport Diedericks road P/Bag X 5936, Upington, 8800. Information Centre TEL: +27 54 337 7900 available 0500-1630 Local Airport Manager: Sakhumzi Baba TEL: +27 54 337 7912 E-mail: Sakhumzi.Baba@airports.co.za Manager Airfield Services: Conwill Willemse TEL: +27 54 337 7931 Cell: +27 82 829 0862 E-Mail: Conwill.Willemse@airports.co.za Manager Maintenance: George Brand TEL: +27 54 337 7905 Cell: +27 72 274 5726 E-Mail: George.Brand@airports.co.za Assistant Manager Fire and Rescue: Marius Valla Cell: +27 79 512 3396 E-Mail: Marius.Valla@airports.co.za RFFS Watch room: TEL: +27 54 337 7908 / 32 Acting Assistant Manager Security: Refilwe Kock TEL: +27 54 337 7928 Cell: +27 84 389 0458 E-mail: Refilwe.Kock@airports.co.za Senior Safety Compliance Officer: Gwen Wessels TEL: +27 54 337 7951 Cell: +27 66 398 2121 E-Mail: Gwen.Wessels@airports.co.za

		ATNS CO Ltd: P.O. Box 1810, Upington, 8800 ATC Cell: +27 66 512 2688 Tel: +27 54 331 1363 E-Mail: upatc@atns.co.za MET ADMIN TEL: +27 54 332 2187 MET TEL: +27 84 279 1161 E-Mail: faup@weathersa.co.za CUSTOMS P.O. Box 1801, Upington, 8800 Cell: +27 82 828 6655 or +27 79 694 3657 E-Mail: nsilwana@sars.gov.za Immigration P/Bag X5885, Upington, 8800 TEL: +27 86 661 6633 Cell: +27 76 987 3944 (After hours) FAX: +27 86 661 6633 E-Mail: corneliaminnies@dha.gov.za Ports of Entry: P/Bag X5986, Upington, 8800 TEL: +27 54 338 8411 Cell: +27 82 469 6329 E-Mail: leschan@saps.gov.za Department of Health: P/Bag X 5900, Upington, 8800 After hours: +27 73 883 7590 E-Mail: Moipone.sebate@health.gov.za
7	*Types of traffic permitted (IFR / VFR)*	IFR/VFR
8	*Remarks*	International airport status.

AD 2.3 OPERATIONAL HOURS

1	*AD Operator*	Admin: Office: MON-FRI: 06:00-1430 AD HOD: MON-FRI: 0500-1630, SAT: 0600-1130 and SUN 1000-1630. Public holidays same as corresponding weekday. Aerodrome available as an unmanned airfield outside the published HOD, apron office: MON-FRI: 0500-1630, SAT 0600-1130 and SUN 1000-1630, Public holidays same as corresponding weekdays. Aerodrome available as an unmanned airfield outside the published HOD.
2	*Customs and immigration* *Border Police (Ports of Entry)*	MON-FRI 0530-1400. H24 on call-out, immigration after hours applicable. Ref FAUP AD 2.20 MON-FRI 0530-1400. H24 on call-out, Ref FAUP AD 2.20
3	*Health and sanitation*	MON-FRI 0530-1400. On call-out TEL: +27 54 331 2120
4	*AIS briefing office*	Contact FAOR briefing on +27 86 035 9669 or +27 11 928 6518.
5	*ATS reporting office (ARO)*	As ATS
6	*MET briefing office*	NIL AVBL. Pilots to CTC FABL.

7	*ATS*	MON-FRI: 0500-1630, SAT: 0800-1130 and SUN: 0930-1630. Public holidays same as corresponding weekdays.
8	*Fuelling*	MON-FRI: 0500-1600, SAT: 0600-1100 and SUN: 0900-1600 Before and after these times call out fee applicable @ R2500-00 per call out. Cell: Work hours +27 72 218 5496 / +27 71 686 9814 David Swarts +27 76 627 7931 / +27 71 826 7388 Request can be e-mailed to david.swarts@pumaenergy.com All scheduled aircraft have priority for refuelling. Pilots to allow a minimum call time of 45 minutes.
9	*Handling*	Upington Ground Handling Co Ltd HOD: 24 HR per day. (on request) Operations Manager: Brandon Nel CELL: +27 79 059 2059 Pieter Wright CELL: +27 61 425 9939 Pieter@ughc.aero
10	*Security*	Airport Security: H24, TEL: +27 54 337 7907 SAPS in town: +27 54 337 3469 or +27 54 337 3400. SAPS (Border): HOD: 0600-1400 AVBL on Call-out. TEL: +27 54 338 8411 (Switchboard) or +27 82 416 9789 (Standby)
11	*De-icing*	NIL INFO AVBL
12	*Remarks*	Request for service outside AD HOD to be addressed as FLW: Fire Service: Manager Airfield Services ATC Services: At AD - Manager Airfield Services Airspace - ATNS Operations/CAMU Section. Refuelling: Puma Aviation as per NR 8 Handling: Upington GND Handling as per NR 9 Ad hoc extensions to airport and ATC (ATNS) hours of operation. After hours services rendered will be subject to payment of additional cost by the operator. The applicant must route his relevant request to the Airport Authority who must in consultation with the relevant ATNS ATSU Chief, approve or reject the request. Notification of the request must reach the Airport Authority at least 7 working days in advance of the intended effective date.

AD 2.4 HANDLING SERVICES AND FACILITIES

1	*Cargo-handling facilities*	FMC Main deck, Loader 16 tons FMC Lower deck, Loader 10 tons. GPU 28 Volt DC, 115-200 volt AC 400Hz. Tractor & Dollies, multipurpose steps and forklift.
2	*Fuel and Oil types*	AVGAS 100; AVTUR (JET A-1); OIL: AERO 100. Supplier: Puma Energy
3	*Fuelling facilities and capacity*	Hydrant refuelling system available
4	*De-icing facilities*	NIL INFO AVBL
5	*Hangar space for visiting aircraft*	NIL INFO AVBL
6	*Repair facilities for visiting aircraft*	NIL on AD. Limited on call out from town
7	*Remarks*	NIL

AD 2.5 PASSENGER FACILITIES

1	*Hotels*	NIL on AD. Hotels and guest houses available in town. CTC tourist info. (See AD 2.5 (6))
2	Restaurants	All restaurants in town.
3	*Transportation*	No public transport available. Car hire AVBL
4	*Medical facilities*	No ambulance at AD. AVBL within 5KM. Limited first aid kit facilities. Nearest hospitals: MediClinic (8KM). Provincial hospital (9KM).
5	*Bank and Post Office*	NIL at airport
6	*Tourist office*	TEL: Dawid Kruiper Tourist Info: +27 54 338 7000
7	*Remarks*	NIL

AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	*AD category for fire fighting*	Total of 10 fire fighters split into two shifts consisting of 5 fire fighters per shift. CAT 5 during AD hours, two alternating shifts 5 fire fighters minimum per shift. Can upgrade to CAT 6. CAT 6 minimum of 7 fire fighters. Change of Aerodrome category implemented by means of NOTAM, seven (07) days prior to commencement of cargo operations. Staff compliment, vehicles and equipment as per requirement for CAT 6.
2	*Rescue equipment*	CAT 5 - Equipment as per ICAO Doc 9137-AN/898 Part 1 Table 5.2 for CAT 3 - 5 airport category. CAT 6 - Equipment as per ICAO Doc 9137-AN/898 Part 1 Table 5.2 for CAT 6 - 7 (cargo aircraft reclassification) airport category. CAT 5 - 1 Fire truck carrying 8000L water, 1000L 6% foam concentrate, 250KG Dry Chemical Powder. CAT 6 - 2 Fire trucks
3	*Capability for removal of disabled aircraft*	MOU in place with: Kallie's Panel beaters with Equipment 50 tonne crane, 3.5 tonne telehandler and 4.5 tonne telehandler McDonalds Transport with equipment: 80 tonne crane and 9.5 ft lowbed.
4	*Remarks*	Aircraft above CAT 5 operating to the airport must apply 7 days prior to the expected date of operations as per AIC 40.1.1 of 01-07-15.

AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	*Types of clearing equipment*	NIL INFO AVBL
2	*Clearance priorities*	NIL INFO AVBL
3	*Remarks*	Occasional fog bound during winter.

AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	*Designation, surface and strength (PCR) of aprons*	Apron A surface: ASPH, Strength: PCR 520/R/B/W/U Apron A hard stand: Concrete, Strength: PCR 520/R/B/W/U Apron B surface: ASPH, Strength: PCR 520/R/B/W/U Apron B hard stand: Concrete, PCR 520/R/B/W/U
2	*Designation, surface and strength (PCR) of taxiways*	TWY A1 30M, B1 20M and E1 25M, strength ASPH PCR 520/F/B/X/U TWY G1: 30M PCR 520/F/B/X/U TWY F1 30M PCR 520/F/B/X/U TWY H1 20M PCR 520/F/B/X/U TWY E1: and G1 primarily for SAAF use PCR 520/F/B/X/U. RWY 08/26 width 30M and strength ASPH PCR 520/F/B/X/U doubles as a TWY. -RWY 26 SWY ASPH -TWY H, TWY F GA hangers, ASPH PCR 520/F/B/X/U.
3	*Altimeter checkpoint location and elevation*	Co-ordinates: 282438S 211550E Elevation: 840M
4	*VOR checkpoints*	116.5 MHz 282406.31S 0211537.48E 2745 FT Let down radial 168 intercepts centreline RWY35 approx. NM from TWR
5	*INS checkpoints*	NIL INFO AVBL
6	*Remarks*	NIL

AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	*Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands.*	Standard guidance signs and lines available on taxiways. Only guide in lines on Apron, follow the marshallers instructions. For aerodrome restricted visibility refer to chart AD - 02
2	*RWY and TWY markings and LGT*	Markings: RWY: THR, Centre Line, TDZ, Aiming Point. Edge LGTS. TWY: Centre Line, Holding Points. LIGHTS: RWY THR, END 7 EDGE LIGHTS, TWY A1, B1, G1, H1 Edge Lights: Colour: Blue, INTST: 30%.
3	*Stop bars*	NIL
4	*Remark*	NIL

AD 2.10 AERODROME OBSTACLES

In Area 2					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/ Type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	2 Steel towers	282700S0211802E 282647S0211758E	HGT 115 FT	NIL INFO AVBL	3 NM E of AD
NIL INFO AVBL	Vodacom mast	282840S0211527E	HGT 164 FT	red and white and lit at night	NIL
NIL INFO AVBL	Mast	NIL INFO AVBL	HGT 148 FT	unmarked	3.85 NM from THR RWY 35 and 435 M W of the extended centre-line RWY 35
NIL INFO AVBL	Mast	NIL INFO AVBL	HGT 164 FT	NIL INFO AVBL	radial 200, 5 DME UPV
NIL INFO AVBL	Power lines	NIL INFO AVBL	HGT 26.24 FT	NIL INFO AVBL	N to S, 250 M W THR SWY 26
NIL INFO AVBL	Cell C Mast	282721.90S 0211240.49E	HGT 31.37M	NIL INFO AVBL	NIL
NIL INFO AVBL	Flood light	282449.44S 0211945.80E	HGT 44.25M	NIL INFO AVBL	NIL
NIL INFO AVBL	Flood light	282504.73S 0211943.50E-	HGT 44.48M	NIL INFO AVBL	NIL
NIL INFO AVBL	Flood light	282654.34S 0211414.27E	HGT 44.20M	NIL INFO AVBL	NIL
NIL INFO AVBL	Flood light	282654.48S 0211332.26E	HGT 41.72M	NIL INFO AVBL	NIL
NIL INFO AVBL	Flood light	282645.88S 0211320.64E	HGT 38.05M	NIL INFO AVBL	NIL
NIL INFO AVBL	Flood light	282707.97S 0211233.54E	HGT 41.88M	NIL INFO AVBL	NIL
NIL INFO AVBL	Flood light	282713.65S 0211243.75E	HGT 42.358M	NIL INFO AVBL	NIL
NIL INFO AVBL	Flood light	282749.84S 0211148.36E	HGT 44.43M	NIL INFO AVBL	NIL
NIL INFO AVBL	Flood light	282718.67S 0211148.93E	HGT 44.94M	NIL INFO AVBL	NIL
NIL INFO AVBL	Flood light	282644.32S 0211151.46E	HGT 45.57M	NIL INFO AVBL	NIL
NIL INFO AVBL	Mast Voortrek-kers	282656.09S 0211457.62E	HGT 36.66M	NIL INFO AVBL	NIL

In Area 2					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/ Type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	Prop Struture site	282357.56S 0211605.07E	HGT 4M	NIL INFO AVBL	NIL
OBST: -Fence: 8 FT high running parallel to RWY 08/26, 75 M S of RWY centre line, Extending 223 M E to 407 M W of THR RWY 08 1) View problem from TWR. Due to the position of the RWY 17/35 and the associated strips, large portions are not visible from the TWR. Operators are to take note that although landing and take-off clearances are issued by ATC, these clearances are based only on those portions of the runway and the associated strips that are adequately visible to ATC at the time the clearance is issued, as well as the known and reported situation on the runway and the associated strips.					

In Area 3					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/ Type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL

AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	*Associated MET office*	FABL
2	*Hours of service* *MET Office outside hours*	0001 - 1800 & 2300 Forecasting 0330 - 1830 (+27 82 233 9100), FAOR (+27 82 233 9600/8800)
3	*Office responsible for TAF preparation* *Periods of validity*	FABL 24HR
4	*Trend forecast* *Interval of issuance*	Yes 3 Hourly
5	*Briefing / consultation provided*	NIL
6	*Flight documentation / Language(s) used*	Standard ICAO format English
7	*Charts and other information available for briefing or consultation*	NIL
8	*Supplementary equipment available for providing information*	NIL

9	*ATS units provided with information*	Yes
10	*Additional information (limitation of service, etc.)*	Flight documentation and other aviation related information AVBL on website page: http://aviation.weathersa.co.za

AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	*True BRG*	*Dimensions of RWY (M)*	Strength of the pavement classification rating (PCR) and surface of *RWY and SWY*	*THR coordinates RWY end coordinates THR geoid undulation*	*THR elevation and highest elevation of TDZ of precision APP RWY*	*Slope of RWY-SWY*
1	*2*	*3*	*4*	*5*	*6*	*7*
17	153°	4900 x 60	520/F/B/X/U ASPH	282247.40S 0211507.60E	2782FT	0.004 D
35	333°	4900 x 60	520/F/B/X/U ASPH	282509.80S 0211628.00E	2711FT	0.004 U
08	060°	834 x 30	520/F/B/X/U ASPH	282417.74S 0211529.01E	2748FT	0.002 U
26	240°	834 x 30	520/F/B/X/U ASPH	282404.15S 0211555.26E	2753FT	0.002 D
01	350°	2438 x 46	520/F/B/X/U ASPH	282446.64S 0211538.08E	2723FT	0.01 U
19	170°	2438 x 46	520/F/B/X/U ASPH	282328.75S 0211522.07E	2791FT	0.01 D

SWY Dimensions (M)	*CWY Dimensions (M)*	*Strip Dimensions (M)*	*RESA dimensions (M)*	*Location (which runway end) and description of arresting system (if any);*	*OFZ*	*Remarks*
8	*9*	*10*	*11*	*12*	*13*	*14*
360 x 60	360	5020 x 280	240 x 120	NIL INFO AVBL	NIL INFO AVBL	See below
360 x 60	360	5020 x 280	240 x 120	NIL INFO AVBL	NIL INFO AVBL	See below
95 x 30	150	954 x 150	90 x 90	NIL INFO AVBL	NIL INFO AVBL	See below
300 x 30	300	954 x 150	90 x 90	NIL INFO AVBL	NIL INFO AVBL	See below
0	60	2558 x 280	240 x 90	NIL INFO AVBL	NIL INFO AVBL	See below
0	60	2558 x 280	240 x 90	NIL INFO AVBL	NIL INFO AVBL	See below

Remarks 12
(1) Circuit - ALT: Turbine-powered ACFT 4500 FT ALT; reciprocating engine-powered ACFT 4000FT ALT
(2) Threshold RWY 26 displaced by 320 M and Threshold RWY 08 displaced by 675 M.
(3) 180 DEG turns only permitted at turning circles for HEAVY aircraft.
(4) A340-600 aircraft not permitted to operate at AD.
(5) RWY 08/26 available for take-off and landing during daylight and VMC. RWY to be used as a TWY during night and IMC.

AD 2.13 DECLARED DISTANCES

RWY Designator	*TORA (M)*	*TODA (M)*	*ASDA (M)*	*LDA (M)*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*
01	2438	2498	2438	2438	NIL
19	2438	2498	2438	2438	NIL
08	834	984	929	834	NIL
26	834	1134	1134	834	NIL
17	4900	5260	5260	4900	NIL
35	4900	5260	5260	4900	NIL

AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	*APCH LGT Type LEN INTST*	*THR LGT colour WBAR*	*VASIS (MEHT) PAPI*	*TDZ, LGT LEN*	*RWY Centre Line LGT LEN, spacing, colour, INTST*	*RWY Edge LGT LEN, spacing, colour, INTST*	*RWY End LGT colour WBAR*	*SWY LGT LEN (M) colour*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*
17	NIL	Green	PAPI 3° L	NIL	NIL	60M white 30%	Red	NIL	Last 600M yellow
35	NIL	Green	PAPI 3° L	NIL	NIL	60M white 30%	Red	NIL	Last 600M yellow
01	NIL	Green	PAPI 3° L	NIL	NIL	60M white 30%	Red	NIL	Last 600M yellow
19	NIL	Green	PAPI 3° L	NIL	NIL	60M white 30%	Red	NIL	Last 600M yellow
1) Remote switching of RWY, TWY A1 and TWY B1 and PAPI (brightness PAPI 3%). 5 rapid clicks on microphone button on 121.3 MHz switches RWY 17/35 & RWY 01/19 LGT on. All lighting switched on by the ABV PROC will remain on for 15MIN where upon they will automatically switch off. If required the PROC may be repeated for a further 15MIN. 2) RWY 17/35 & 01/19 lights controlled by ATC and can be set pending on conditions or requests from pilots, diiferent settings available: 3%, 10%, 30% (normal setting) & 100%. 3) Note: The use of RWY 08/26 is a non instrumental RWY for use in daylight operations only									

AD 2.15 OTHER LIGHTING SYSTEMS, SECONDARY POWER SUPPLY

1	*ABN/IBN location, characteristics and hours of operation*	NIL INFO AVBL
2	*LDI location and LGT Anemometer location and LGT*	NIL North of PAX apron: Yes North of PAX apron: NIL
3	*TWY edge and centre line lighting*	Edge: Blue
4	*Secondary power supply and switch-over time*	315 kVA Diesel powered generator as per ICAO requirements, 15 seconds change over time
5	*Remarks*	NIL

AD 2.16 HELICOPTER LANDING AREA

1	*Coordinates TLOF or THR of FATO Geoid undulation*	NIL INFO AVBL
2	*TLOF and/or FATO elevation M/FT*	NIL INFO AVBL
3	*TLOF and FATO area dimensions, surface, strength, marking*	NIL INFO AVBL
4	*True BRG of FATO*	NIL INFO AVBL
5	*Declared distance available*	NIL INFO AVBL
6	*APP and FATO lighting*	NIL INFO AVBL

Remarks
1) No dedicated helicopter landing area, Helicopters to taxi or air taxi along RWY 01/19, TWY A1 to the apron where it will be parked at a separate location away from fixed wing aircraft.
2) Helicopters utilizing the aerodrome are to land/depart from TWY A1.
2.1) Approved helicopter operations at the aerodrome private hangers will land on/depart from N via TWY H1 avoiding any flying over the building structures.
2.2) Pilots must call security/apron services on frequency 122.65 MHz before departure and after arrivals to indicate the registration, point of departure and designation and persons on board.
2.3) Coordinates for the helipad 282430.33S 0211512.12E height 838.27M.
2.4) Helipad restricted to daylight operations only.
2,5) No solo flights from or to this helipad for trainee pilots.

AD 2.17 ATS AIRSPACE

1	*Designation and lateral limits*	ATZ: Circle with radius 8NM centered on 282406.31S0211537.48E
2	*Vertical limits*	GND/6000 FT ALT
3	*Airspace classification*	Class C
4	*ATS unit call-sign* *Language*	Upington tower English
5	*Transition altitude*	5500FT

6	*Remarks*	- Class C-Except where otherwise authorized, no aircraft is to be operated within this airspace unless two-way radio contact is maintained with air traffic control. - All VFR pilots to comply with Mandatory VFR Routing for Upington as per SA AIP ENR 2.2. If unable to comply, pilots to contact ATC prior to the flight for alternative arrangements.

AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	*Call sign*	*Frequency*	*Hours of operation*	*Remarks*
1	*2*	*3*	*4*	*5*
TWR	Upington Tower	121.3 MHz transmits and receives	MON-FRI: 0500-1630, SAT: 0800-1130 and SUN: 0930-1630. Public holidays same as corresponding weekdays	Contact ATC for start-up and taxi clearance when parked on Apron A or Apron B
Apron Control	Upington Apron	122.65 MHz transmits and receives	As per fire and rescue services	Pilots to contact Upington Apron with regard to parking only.

AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, MAG VAR, Type of supported OP (for VOR/ILS/ MLS, give declination)	*ID*	*Frequency*	*Hours of operation*	*Position of transmitting antenna coordinates*	*Elevation of DME transmitting antenna*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*
VOR	UPV	116.5MHz	H24	282406.31S 0211537.48E	2754 FT	Letdown radial 168 intercepts centreline RWY35 APRX 1NM from THR.
UHF DME	UPV	116.5MHz CH112X	H24	282406.31S 0211537.48E	2754 FT	Channel 112X co-located with VOR. Due to lobeing affect caused by small aperture DME antenna will result in limited range

AD 2.20 LOCAL AERODROME REGULATIONS

1) Call out procedure for Across Border Flight Clearance (International Flights)
a) Arriving International Flights
-The pilot in charge of an arriving international flight must ensure that Customs and Excise Immigrations, Border Police and the Department of Health, as well as the Airport Manager are informed of the flight at least one hour before landing.The following Information must have been provided to the relevant authorities.
Aircraft Registration
Pilot name
Point of Origin
Landing clearance Reference number
Number of people on board; Time of arrival

-After arrival, taxi clearance will be given to the pilot to taxi to an allocated parking bay on the main apron, in front of the terminal building. No international flight is to park at any other location than on the main apron.
-All cargo flights will park on the cargo apron “Apron A”
-Representatives from the relevant authorities will meet the aircraft, on arrival, at the allocated parking bay. Neither the pilot, nor any passenger or cargo, may leave the aircraft prior to all the relevant authorities present.
b) Departing International flights
-All international flights departing from Upington Airport will do so from the main apron, and only after such flight has been cleared by all relevant clearing authorities.
-The pilot in charge of a departing international flight will ensure that his aircraft is cleared, and parked on an allocated bay on the main apron prior to the arrival of any of the clearing authorities.
-The pilot in charge of a departing international flight must ensure that the clearing authorities, as well as the Airport Manager, are informed of the planned flight, at least one and half hours prior to the planned time of departure. The following Information must have been provided to the relevant authorities.
Aircraft registration
Pilot name
Point of destination
Number of people on board
Cargo shipped
Time of departure (ETD)
-Representatives of the relevant authorities will meet the pilot or the charter company in the departure hall of the terminal building at least fort-five (45) minutes prior to the ETD, in order to process clearance.
-No international flight is to depart prior to the clearance have been given by all relevant authorities.
-No international flight is to depart from General aviation area.
All Pilots from yellow fever or malaria identified countries should allow call-out time for the Department of Health to ensure their ACFT is thoroughly sprayed with airline insecticide. All persons in the ACFT should only disembark after the Department of Health give permission for them to do so.
The pilot can disinfect the aircraft en route but should provide canister as proof before opening the aircraft door.
2) All aircraft with a maximum take-off weight greater than 4500 KG requiring RWY 17/35 for take-off or landing are to advise FAUP Tower on FREQ 121.3 MHz 15 minutes prior to ETA/ETD.
3) Fixed wing TFC and HEL are REQ to arrange PRKG on APN A prior to DEP DRG HR of SER. CTC +2754 3377 908 or +2754 3377 910.
4) All cross border FLT to CTC AP prior to DEP on any of the FLW CTC:
Conwill Willemse: Manager Airfield Services: +27 82 829 0862
Marius Valla: Fire and Rescue +27 79 512 3396
Refilwe Kock +27 84 389 0458
All FLT must indicate country of origin, ACFT type, ACFT REG, Date of ARR, ETA,PAX, Pilots to obtain occurrence REF NR FM the AP security AFT CTC.
All cross border flights to submit Foreign Operator Permit / Over flight and Landing permits to Airport Authority prior to operations.
All aircraft parked on Apron A and Apron B must request start-up and taxi clearance from Upington ATC on frequency 121.3 MHz and not Upington Apron.

AD 2.21 NOISE ABATEMENT PROCEDURES

1. Noise abatement procedures for jet aeroplanes irrespective of weight and for propeller and turbo aeroplanes with MTOW of or above 11 000KG.
2. Noise abatement procedures for propeller and turboprop aeroplanes with MTOW below 11 000KG.
3. Noise abatement procedures for helicopters.
4. Use noise abatement procedure as per AIP ENR 1.5.

AD 2.22 FLIGHT PROCEDURES

NIL INFO AVBL

AD 2.23 ADDITIONAL INFORMATION

1) Small bucks are roaming AD at NGT, creating an aviation hazard. All NGT OPS EXER CTN, especially outside ATC HR of SER, Game will be chased during ATC HR of SER.
2) Bird hazard on AD. Pilots to EXER CTN.
3) No aircraft is allowed to occupy the stop way on RWY 26 whilst RWY 08/26 is active with take-off and or landing

AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome Chart	-AD-01
Restricted Visibility Chart	-AD-02
Aerodrome Hotspot Chart	-AD-03
VOR RWY 35 Chart	-VOR-01
RNAV (GNSS) RWY 35	-RNAV-01
Data tabulation	-RNAV-01A

THIS PAGE INTENTIONALLY LEFT BLANK