FAUS

AD 2.1 AERODROME LOCATION INDICATOR AND NAME

FAUS - ULUSABA

AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	*ARP co-ordinates and site at AD*	244656.0S 0312113.0E
2	*Direction and distance from city*	+/- 62 KM N/E from Hazyview.
3	*Reference elevation/Reference temperature*	1380 FT / 26°C
4	*Geoid undulation at aerodrome elevation position*	13.25 FT
5	*MAG VAR* *annual change*	18°12' W / 0°7'W
6	*AD Operator, address, telephone, telefax, e-mail, AFS address and, if available, website address*	Ulusaba Private Game Reserve Wallingford Farm, Sabi Sands Nature Reserve Mpumalanga, South Africa TEL: +27 13 735 5460 / +27 71 870 8764 Email: reception@ulusaba.virgin.com Web: www.virginlimitededition.com
7	*Types of traffic permitted (IFR / VFR)*	VFR
8	*Remarks*	Private airfield, 24 hours prior notice required.

AD 2.3 OPERATIONAL HOURS

1	*AD Operator*	0700-1400
2	*Customs and immigration*	NIL
3	*Health and sanitation*	NIL
4	*AIS briefing office*	NIL
5	*ATS reporting office (ARO)*	NIL
6	*MET briefing office*	NIL
7	*ATS*	NIL
8	*Fuelling*	NIL
9	*Handling*	NIL
10	*Security*	NIL
11	*De-icing*	NIL
12	*Remarks*	NIL

AD 2.4 HANDLING SERVICES AND FACILITIES

1	*Cargo-handling facilities*	NIL
2	*Fuel and Oil types*	NIL
3	*Fuelling facilities and capacity*	NIL
4	*De-icing facilities*	NIL
5	*Hangar space for visiting aircraft*	NIL
6	*Repair facilities for visiting aircraft*	NIL
7	*Remarks*	NIL

AD 2.5 PASSENGER FACILITIES

1	*Hotels*	Ulusaba Rock Lodge & Ulusaba Safari Lodge
2	*Restaurants*	Ulusaba Rock Lodge & Ulusaba Safari Lodge
3	*Transportation*	Ulusaba lodges collection and drop off at the aerodrome
4	*Medical facilities*	Paramedic available
5	*Bank and Post Office*	NIL
6	*Tourist office*	NIL
7	*Remarks*	NIL

AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	*Aerodrome category for fire fighting*	CAT III
2	*Rescue equipment*	Minimum of five firefighters on duty, primary fire tender with 1200L of water, 16800L of foam, 25KG fire extinguisher and 2 x 6KG CO2. Secondary fire trailer with 600L of water and 135KG of dry powder. 2 Standby vehicles (2-5 MIN from air-field) with 200% dry powder and 600L of Hydrax powder.
3	*Capability for removal of disabled aircraft*	NIL
4	*Remarks*	RFFS available between the hours of 0600-1400

AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	*Types of clearing equipment*	Tractor and slasher
2	*Clearance priorities*	Twice a year
3	*Remarks*	Cleared up to 20 M from runway edge

AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	*Designation, surface and strength of aprons*	Apron available, Asphalt, PCN N/A.
2	*Designation, width, surface and strength of taxiways*	NIL
3	*ACL location and elevation*	NIL
4	*VOR checkpoints*	NIL
5	*INS checkpoints*	NIL
6	*Remarks*	NIL

AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	*Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands.*	NIL
2	*RWY and TWY markings and LGT*	Runway markings only
3	*Stop bar*	Holding point markings only
4	*Remark*	Aircraft to park in designated parking areas only.

AD 2.10 AERODROME OBSTACLES

In Area 2					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL	NIL	NIL	NIL	NIL	NIL

In Area 3					
OBST ID/ Designation	*OBST Type*	*OBST position*	*ELEV/HGT*	*Markings/type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL	NIL	NIL	NIL	NIL	NIL

AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	*Associated MET office*	NIL
2	*Hours of service* *MET office responsible outside hours*	NIL
3	*Office responsible for TAF preparation and periods of validity*	NIL
4	*Type of trend forecast and interval of issuance*	NIL
5	*Briefing / consultation provide*	NIL
6	*Flight documentation / language(s) used*	NIL
7	*Charts and other information available for briefing or consultation*	NIL
8	*Supplementary equipment available for providing information*	NIL
9	*ATS units provided with information*	NIL
10	*Additional information (limitation of service, e.t.c.)*	WDI: 244655.56S 0312115.88E

AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	*TRUE & MAG BRG*	*Dimensions of RWY (M)*	*Strength (PCN) and surface of RWY and SWY*	*THR coordinates RWY end coordinates THR geoid undulation*	*THR elevation and highest elevation of TDZ of precision APP RWY*	*Slope of RWY-SWY*
1	*2*	*3*	*4*	*5*	*6*	*7*
18	168°T/186°	1353 X 18	PCN N/A Asphalt	244636.56S 0312109.51E	1369FT	+0.06%
36	348°T/006°	1353 X 18	PCN N/A Asphalt	244719.25S 0312120.68E	1447FT	-0.06%

SWY dimensions (M)	*CWY dimensions (M)*	*Strip dimensions (M)*	*RESA dimensions (M)*	*Location (which runway end) and description of arresting system (if any);*	*OFZ*	*Remarks*
8	*9*	*10*	*11*	*12*	*13*	*14*
47M	47M	1465 X 41	NIL	NIL	NIL INFO	See below
47M	47M	1465 X 41	NIL	NIL	NIL INFO	See below
Remarks: No turning on the runway. No engine run-ups on the threshold of runway 36 are permitted. AD is not fenced. Pilots are to advise ETA prior to landing on FREQ 122.250 MHz- (Ulusaba Grounc) to ensure that animals are cleared from the runway before landing. Aircraft are to park in designated parking areas only.						

AD 2.13 DECLARED DISTANCES

RWY	*TORA (M)*	*TODA (M)*	*ASDA (M)*	*LDA (M)*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*
18	1353	1400	1400	1353	NIL
36	1353	1400	1400	1353	NIL

AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY	*APCH LGT Type and LEN INTST*	*THR LGT Colour WBAR*	*VASIS (MEHT) PAPI*	*TDZ, LGT LEN*	*RWY Centre Line LGT, Spacing, colour INTST*	*RWY Edge LGT, LEN, Spacing, Colour, WBAR*	*RWY End LGT Colour WBAR*	*SWY LGT LEN (m) Colour*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*
18	NIL	NIL	NIL	NIL	NIL	NIL	NIL	NIL	NIL
36	NIL	NIL	NIL	NIL	NIL	NIL	NIL	NIL	NIL

AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	*ABN/IBN location, characteristics and hours of operation*	NIL
2	*LDI location & LGT and anemometer location and LGT*	NIL
3	*TWY edge and centre line lighting*	NIL
4	*Secondary power supply and switch-over time*	NIL
5	*Remarks*	NIL

AD 2.16 HELICOPTER LANDING AREA

1	*Coordinates TLOF or THR of FATO / Geoid undulation*	24 46 55.68 S 031 21 13.14E FATO /TLOF Centre
2	*TLOF / FATO elevation (m/ft)*	429.1522105 M
3	*TLOF and FATO area dimensions, surface, strength, marking*	TLOF and FATO Dimensions: There are 2 Circles painted white and are 10M in diameter. Surface PCN N/A · Asphalt
4	*True BRG of FATO*	NIL INFO AVBL
5	*Declared distance available*	30 M
6	*APP and FATO lighting*	N/A- No Lighting
7	*Remarks*	Refer AD 2.20

AD 2.17 ATS AIRSPACE

1	*Designation and lateral limits*	NIL
2	*Vertical limits*	NIL
3	*Airspace classification*	NIL
4	*ATS unit call sign* *Language(s)*	NIL
5	*Transition altitude*	NIL
6	*Remarks*	NIL

AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	*Call sign*	*Channel(s)*	*Hours of operation*	*Remarks*
1	*2*	*3*	*4*	*5*
NIL	NIL	NIL	NIL	NIL

AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, MAG VAR, Type of supported OPS (for VOR/ ILS/MLS, give declination)	*ID*	*Frequency*	*Hours of operation*	*Position of transmitting antenna coordinates*	*Elevation of DME transmitting antenna*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*
NIL	NIL	NIL	NIL	NIL	NIL	NIL

AD 2.20 LOCAL AERODROME REGULATIONS

1. Private aerodrome, landing arrangements must be made and confirmed with Ulusaba Game Reserve prior to arrival (at least 24 hours).
2. The airfield is available to all aircraft bringing guests to the Ulusaba Game Reserve (Ulusaba Rock Lodge and Ulusaba Safari Lodge).
3. Prior permission is required if the aerodrome is utilised for guests to surrounding lodges.
4. No landing fees are applicable to all aircraft with Ulusaba Game Reserve guests, landing fees do apply if the aerodrome is used for surrounding lodges.
5. Ulusaba Ground is to be contacted at least 10 minutes prior to arrival on FREQ 122.25 MHz and an ETA must be provided to ensure that the aerodrome is cleared of animals.
6. No turning is permitted on the runway, turning areas are provided at each end of the runway for aircraft to be turned around on.
7. The designated apron is to be utilised for parking.

AD 2.21 NOISE ABATEMENT PROCEDURES

Ulusba Rock Lodge to the Southwest of the airfield and Ulubaba Safari Lodge to the South of the airfield. Surrounding lodges to the East of the aerodrome.

AD 2.22 FLIGHT PROCEDURES

1. Remain clear of the eastern side of the airfield.
2. All circuits and joining procedures are to be conducted to the west of the aerodrome.
3. Wide circuits should be flown to the West of the aerodrome to avoid the noise-sensitive areas to the Southwest of the aerodrome.
4. Airfield within the Sabi-Sands Special Rules Area unmanned radio broadcasts are to be completed on FREQ 128.35 MHz.
5. All outbound aircraft intending to climb above 6000FT must establish contact with Lowveld FIS on FREQ 119.0 MHz before getting airborne or at the latest passing 5000FT.

AD 2.23 ADDITIONAL INFORMATION

NIL

AD 2.24 CHARTS RELATED TO AN AERODROME

NIL