FAVG

FAVG AD 2.1 AERODROME LOCATION INDICATOR AND NAME

FAVG - VIRGINIA/DURBAN

FAVG AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	*ARP co-ordinates and site at AD*	294615.00S 0310337.00E
2	*Direction and distance from city*	5 NM NE
3	*Elevation/Reference temperature*	20FT/22º C
4	*Geoid undulation at AD ELEV PSN*	NIL INFO AVBL
5	*MAG VAR / Annual change*	NIL INFO AVBL
6	*AD Operator, address, telephone, telefax, e-mail, AFS address and, if available, website address*	Authority Supervising the Aerodrome and Remarks: PUB AD CHF: Ethekwini Municipality - Economic Development Unit, P O Box 201444, Durban North, 4016 TEL: (+27 31) 563 7101 / (+27 31) 311 4098 FAX: (+27 31) 563 7138 APM: Ms Duduzile Ntombela +27 78 181 9587 ATC: (+27 31) 563 4213 / (+27 31) 311 4098 Fax: (+27 31) 563 4213 AFS: FAVGZTZX
7	*Types of traffic permitted (IFR / VFR)*	VFR
8	*Remarks*	NIL

FAVG AD 2.3 OPERATIONAL HOURS

1	*AD operator*	Daily BTN 0400 - 2000.
2	*Customs and immigration*	NIL
3	*Health and sanitation*	NIL INFO AVBL
4	*AIS briefing office*	NIL INFO AVBL
5	*ATS reporting office (ARO)*	NIL INFO AVBL
6	*MET briefing office*	NIL INFO AVBL
7	*ATS*	HOD 0400-1700 MON-SAT and 0500-1500 SUN and HOL.
8	*Fuelling*	SHELL/East Coast Airways: HOD MON-SAT: 0500-1500; SUN: 0600-1300; PUBLIC HOL: 0600-1300. TEL (+27 31) 564 9344 AFT HR: CTC John on (+27 83) 208 8771 ENGEN/Sheltam: HOD MON-FRI: 0500-1600; SAT: 0600-1500; SUN 0700 - 1300. TEL: (+27 31) 563 8361.
9	*Handling*	NIL INFO AVBL
10	*Security*	NIL INFO AVBL

11	*De-icing*	NIL INFO AVBL
12	*Remarks*	NIL

FAVG AD 2.4 HANDLING SERVICES AND FACILITIES

1	*Cargo-handling facilities*	NIL INFO AVBL
2	*Fuel and Oil types*	AVGAS100, AVTUR. OIL: ASO W80, W100, 100. 100 ASHLESS, ASO W100, Red Band.
3	*Fuelling facilities and capacity*	NIL INFO AVBL
4	*De-icing facilities*	NIL INFO AVBL
5	*Hangar space for visiting aircraft*	NIL INFO AVBL
6	*Repair facilities for visiting aircraft*	NIL INFO AVBL
7	*Remarks*	NIL

FAVG AD 2.5 PASSENGER FACILITIES

1	*Hotels*	NIL INFO AVBL
2	Restaurants	NIL INFO AVBL
3	*Transportation*	NIL INFO AVBL
4	*Medical facilities*	NIL INFO AVBL
5	*Bank and Post Office*	NIL INFO AVBL
6	*Tourist office*	NIL INFO AVBL
7	*Remarks*	NIL

FAVG AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	*AD category for fire fighting*	CAT II. MON-SAT 0400-1700, SUN and HOL 0500-1700.
2	*Rescue equipment*	Fire extinguishing media of 1600 litres of water and 200 litres foam with 150 Kg dry chemical powder.
3	*Capability for removal of disabled aircraft*	Engineers of the relevant AMO based at the airport.
4	*Remarks*	1 Officer and 2 fire fighters, per shift. TEL: (+27 31) 563 7101, AFT HR or during EMERG CTC: Mr Kukard - (+27 83) 922 5941 or Mr Bryce - (+27 84) 668 8569. Durban Fire Department Emergency: TEL: (+27 31) 361 0000. This service not available for routine operations after hours.

FAVG AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	*Types of clearing equipment*	NIL INFO AVBL
2	*Clearance priorities*	NIL INFO AVBL
3	*Remarks*	NIL INFO AVBL

FAVG AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	*Apron surface and strength*	NIL INFO AVBL
2	*Designation, width, surface and strength of taxiways*	NIL INFO AVBL
3	*Altimeter checkpoint location and elevation*	NIL INFO AVBL
4	*VOR checkpoints*	NIL INFO AVBL
5	*INS checkpoints*	NIL INFO AVBL
6	*Remarks*	1 exit taxiway at the center of the runway, linking runway and taxiway. 50M X 10M, tarred.

FAVG AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	*Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands.*	NIL INFO AVBL
2	*RWY and TWY markings and LGT*	NIL INFO AVBL
3	*Stop bars*	NIL INFO AVBL
4	*Remark*	NIL INFO AVBL

FAVG AD 2.10 AERODROME OBSTACLES

In Area 2					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/ Type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	Radio mast	NIL INFO AVBL	70 / 115 FT	NIL INFO AVBL	3,5 NM SW
NIL INFO AVBL	Radio mast	NIL INFO AVBL	112 / 115 FT	NIL INFO AVBL	0,9 NM NNE
	Radio mast	NIL INFO AVBL	29 / 115 FT	NIL INFO AVBL	3,0 NM W
NIL INFO AVBL	Radio mast	NIL INFO AVBL	28 / 115 FT	NIL INFO AVBL	3,0 NM W
NIL INFO AVBL	Radio mast	NIL INFO AVBL	138 / 180 FT	NIL INFO AVBL	2,8 NM NE

In Area 3					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/ Type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL

FAVG AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	*Associated MET office*	FALE
2	*Hours of service* *MET Office outside hours*	No MET Station O R Tambo INTL TEL: 082 233 9600/8800
3	*Office responsible for TAF preparation* *Periods of validity*	FALE, on special request provided the availability of routine observations. 9-11 Hours
4	*Trend forecast* *Interval of issuance*	NIL 3 Hourly
5	*Briefing / consultation provided*	NIL
6	*Flight documentation / Language(s) used*	NIL
7	*Charts and other information available for briefing or consultation*	NIL
8	*Supplementary equipment available for providing information*	NIL
9	*ATS units provided with information*	NIL

10	*Additional information (limitation of service, etc.)*	Flight documentation and other Aviation related information AVBL on web page http://aviation.weathersa.co.za

FAVG AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	*True BRG*	*Dimensions of RWY (M)*	*Strength (PCN) and surface of RWY and SWY*	*THR coordinates RWY end coordinates THR geoid undulation*	*THR elevation and highest elevation of TDZ of precision APP RWY*
1	*2*	*3*	*4*	*5*	*6*
05	NIL INFO AVBL	925 x 22	ASPH LCN 32	NIL INFO AVBL	NIL INFO AVBL
23	NIL INFO AVBL	925 x 22	ASPH LCN 32	NIL INFO AVBL	NIL INFO AVBL
	Slope of RWY-SWY	*SWY Dimensions (M)*	*CWY Dimensions (M)*	*Strip Dimensions (M)*	*OFZ*
1	*7*	*8*	*9*	*10*	*11*
05	NIL INFO AVBL	152	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL
23	NIL INFO AVBL	152	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL

Remarks 12:
(1) The graded area to the SE of RWY 05/23 is only 27M from the RWY centre line.
(2) CWY intersection with RWY 23. 80M x 10M ASPH pavement. This section may only be used during take-off RWY 05 - not for landing TORA RWY 05: 1025M.

FAVG AD 2.13 DECLARED DISTANCES

RWY Designator	*TORA (M)*	*TODA (M)*	*ASDA (M)*	*LDA (M)*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*
05	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL
23	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL

FAVG AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	*APCH LGT Type LEN INTST*	*THR LGT colour WBAR*	*VASIS (MEHT) PAPI*	*TDZ LGT LEN*	*RWY Centre Line LGT Length, spacing, colour, INSTST*	*RWY Edge LGT LEN, spacing, colour, INSTST*	*RWY End LGT colour WBAR*	*SWY LGT LEN (M) colour*	*Remarks*
1	2	3	4	5	6	7	8	9	10
05	NIL	Green W/Bar	NIL	NIL	NIL	925M 60M White	Red W/Bar	NIL	
23	NIL	Green W/Bar	NIL	NIL	NIL	925M 60M White	Red W/Bar	NIL	

1) last 300M yellow.
2) The RWY lights will be switched off at 2000 to 0400 next morning.
3) No flying BTN 2000 and 0400 except with prior permission from Airport Manager subject to special circumstances.
4) RWY LGT BTN 0400-2000.

FAVG AD 2.15 OTHER LIGHTING SYSTEMS, SECONDARY POWER SUPPLY

1	*ABN/IBN location, characteristics and hours of operation*	NIL INFO AVBL
2	*LDI location and LGT Anemometer location and LGT*	NIL INFO AVBL
3	*TWY edge and centre line lighting*	NIL INFO AVBL
4	*Secondary power supply and switch-over time*	NIL INFO AVBL
5	*Remarks*	NIL INFO AVBL

FAVG AD 2.16 HELICOPTER LANDING AREA

1	*Coordinates TLOF or THR of FATO Geoid undulation*	NIL INFO AVBL
2	*TLOF and/or FATO elevation M/FT*	NIL INFO AVBL
3	*TLOF and FATO area dimensions, surface, strength, marking*	NIL INFO AVBL

4	*True BRG of FATO*	NIL INFO AVBL
5	*Declared distance available*	NIL INFO AVBL
6	*APP and FATO lighting*	NIL INFO AVBL
7	*Remarks*	REQUIREMENTS Helicopters are not permitted to:- i) Hover training on or near the runway (including the grass area between the runway and taxiway and near the hangars or buildings) unless the ATC has given that specific helicopter permission to do so. ii) Helicopters must fit in with the circuit traffic iii) A helicopter stationary on the runway or flight strip or in the hover renders the runway unsafe. iv) Hover training to be done at the designated helicopter pads or at the ATC discretion. v) Helicopters, once given take off clearance from the helicopter pad must proceed to the runway and take off as per ATC clearance. vi) The compass swing bay is not to be utilized as a hovering area or helipad. vii) Due to proximity of parked ACFT, the apron is not part of the manoeuvring area and does not fall under ATC jurisdiction, no permanent parking in front of the terminal building, only used as drop off and go for ACFT. viii) Pilots to exercise caution when taxiing due to close proximity of parked ACFT. HOLDING POINT It was established that to ease congestion at the holding point 23, a second holding point be demarcated. This in effect should leave a gap between the two points in which helicopters utilizing the Starlight helicopter pad can proceed without having to fly over aircraft holding at the holding point. Holding point two (2) is the furtherest one from the runway and on busy days the ATC will hold all aircraft at this point and let one at a time through to the first holding point. Once cleared for take off the ATC, at their discretion will let another aircraft through to holding point one (1). HELICOPTER OPERATIONS Helicopter operational hours are from 0400 to 1700 Monday, Wednesday and Friday. Helicopter training on Saturday is BTN 0400-1100, and on Tuesday and Thursday BTN 0400- 1800. No training permitted on Sundays and public holidays. Departing helicopters are expected to gain enough height as possible, to be clear of the residential areas on both sides of the aerodrome.

FAVG AD 2.17 ATS AIRSPACE

1	*Designation and lateral limits*	ATZ a) From a point at 294315.57S 0310334.05E clockwise along the arc of a circle, radius 3NM centred on 294615.99S 0310336.00E to a point at 294647.88S 0310012.43E. b) Thence a straight line, back to the starting point, at 294315.57S 0310334.05E.
2	*Vertical limits*	GND/1000 FT ALT
3	*Airspace classification*	Class C

4	*ATS unit call-sign* *Language*	English
5	*Transition altitude*	NIL INFO AVBL
6	*Remarks*	Aircraft flying in this ATZ must comply with the noise abatement procedures applicable in the Virginia circuit: (a) All circuits to be made seawards, thus when runway 23 is in use left-hand circuits must be flown and when runway 05 is in use right hand circuits must be flown. (b) All aircraft other than those piloted by pupils under training, must veer seawards of the line of flight immediately after take-off. (c) Aircraft being piloted by pupils under training must start veering seawards on reaching a height of 400 FT ALT.

FAVG AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	*Call sign*	*Frequency*	*Hours of operation*	*Remarks*
1	*2*	*3*	*4*	*5*
TWR	Virginia Tower	120.6 MHz transmits and receives	MON - SAT: 0400 - 1700. SUN/ PUB HOL: 0500 - 1500	NIL INFO AVBL
Note: All IFR TFC DEP FAVG outside of HR of duty of ATC must CTC Durban APCH on FREQ 125.75 MHz prior to departure for clearance to enter controlled airspace. If no CTC can be established on FREQ 120.6 MHz, ACFT are to get airborne and remain clear of controlled airspace and obtain clearance on FREQ 125.75 MHz to enter controlled airspace. All TFC DEP FM FAVG that enter the Durban TMA or fly to FALE are required to request startup prior to DEP.				

FAVG AD 2.19 RADIO NAVIGATION AND LANDING AIDS

NIL INFO AVBL

FAVG AD 2.20 LOCAL AERODROME REGULATIONS

(1) Use of AD by Tri-Axis Fixed Wing microlight ACFT permitted.
(2) Twin engined aircraft are to use ASPH TWY only at all times.
(3) The control tower penetrates the Transitional Surface.
(4) ACFT to park in designated areas only.

FAVG AD 2.21 NOISE ABATEMENT PROCEDURES

For noise abatement procedure, helicopters are to approach at higher altitude over the residential area (flying a normal approach path) and to cross the aerodrome boundary fence at no less than 300FT whenever practical and safe to do so.

FAVG AD 2.22 FLIGHT PROCEDURES

The following deemed separation between arriving and departing IFR flights at King Shaka International and Virginia airports is based upon a Safety Assessment conducted by ATNS and has been implemented to enhance efficiency as well as to ensure a safe, orderly and expeditious flow of air traffic within the FALE/FAVG area of responsibility.

FAVG geographical position is 3NM east of the approach/take-off path of runway 06/24 at FALE and as such restricts IFR traffic to and from both airports.

This procedure will require IFR traffic departing from or arriving at FAVG, on ATC clearances to remain seaward of the coastline on headings, and will be deemed to be separated from IFR departing and arriving traffic at King Shaka International Airport (FALE).

This deemed separation will only be applicable when Surveillance Radar is in operation at FALE.

In the absence of an IAP for IFR ACFT into FAVG the following PROC will apply, when WX minima restricts VMC descents into FAVG: inbound IFR ACFT to FAVG shall be accommodated on the ILS or VOR IAP to FALE to a minimum of 1000FT ALT. Should the ACFT not become VMC by 1000FT ALT, pilot will be requested to land at FALE.

Circuit: All circuits to be flown at 800FT and must be conducted seawards. Downwind legs over land not permitted.

FAVG AD 2.23 ADDITIONAL INFORMATION

Pilots must exercise caution due to flocks of birds on AD.

FAVG AD 2.24 CHARTS RELATED TO AN AERODROME

NIL

THIS PAGE INTENTIONALLY LEFT BLANK