FAWB

FAWB AD 2.1 AERODROME LOCATION INDICATOR AND NAME

FAWB - WONDERBOOM / PRETORIA

FAWB AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	*ARP co-ordinates and site at AD*	253919.11S 0281316.81E, On RWY 11/29 and RWY 06/24 intersection.
2	*Direction and distance from city*	6 NM N Pretoria
3	*Elevation/Reference temperature*	4095 FT / 32° C
4	*Geoid undulation at AD ELEV PSN*	80.3 FT
5	*MAG VAR /* *Annual change*	19°W (2018) 0°6' W
6	*AD operator, address, telephone, telefax, e-mail, AFS address and, if available, website address*	Postal Address: City of Tshwane P O Box 6338, Pretoria, 0001 TEL:+27 12 358 4040, FAX: +27 12 358 4141 E-mail: ndivhol@tshwane.gov.za APM: Mr Nnditsheni L. Madavha TEL: +27 12 358 5078 E-mail: nnditshenim@tshwane.gov.za Reception to FAWB: TEL: +27 12 358 5266 E-mail: wbainfo@tshwane.gov.za Safety and operations: TEL: +2712 358 2719e E-mail: wbasafety@tshwane.gov.za ATC: TEL: +27 12 543 1402, FAX: +27 12 543 0038 CELL: +27 66 432 1795 E-mail: wbatc@atns.co.za Rescue and Fire Services TEL: +27 12 543 1835/8112/3/4/5 CELL: +27 83 658 8917 E-mail: wbafire@tshwane.gov.za
7	*Types of traffic permitted (IFR / VFR)*	IFR/VFR
8	*Remarks*	Microlights only allowed on prior arrangement with APM and ATC. All visiting aircraft arrivals to park on apron and report to INFO desk to pay landing fees. All departing and arriving passengers to pass through main terminal building. All departing passengers to pay airport tax at INFO Desk and/or The Cash Management Office.

FAWB AD 2.3 OPERATIONAL HOURS

1	*AD Operator*	AD, MON-SUN: 0300-1800 AD Administration and Apron office: MON-FRI 0530-1400, public holidays and weekends closed.
2	*Customs and immigration*	NIL
3	*Health and sanitation*	NIL
4	*AIS briefing office*	H24, Contact O.R Tambo International AIM unit. TEL: +27 86 0359 669 or +27 11 928 6517/8
5	*ATS reporting office (ARO)*	H24, TEL: +27 86 0359 669 or +27 11 928 6517/8
6	*MET briefing office*	Printed aviation forecast is available. Forecast OR Tambo International TEL: +27 11 390 9329, +27 11 390 9330, +27 12 367 6210
7	*ATS*	TWR/APP: MON-SUN 0400-1800, Ground Movement Control: MON-SUN 0500-1700. Public Holidays to be notified by NOTAM. Nil services available after 1800.
8	*Fuelling*	AVGAS and JET A1 available during AD operational hours.
9	*Handling*	NIL ground handling company available. The following equipment is available: Tug, Portable water, waste truck, baggage wagons, and trolleys.
10	*Security*	AVSEC available. a) Passenger security: DLY 0400-1800. b) AD perimeter security: H24.
11	*De-icing*	NIL INFO AVBL
12	*Remarks*	NIL INFO AVBL

FAWB AD 2.4 HANDLING SERVICES AND FACILITIES

1	*Cargo-handling facilities*	NIL INFO AVBL
2	*Fuel and Oil types*	AVGAS and JET A1 available. Nil oil available.
3	*Fuelling facilities and capacity*	AVGAS quantity: 9000L JET A1 quantity: 7500L AVGAS refuelling only available on the main apron - kerbside. ACFT requiring JET A1 must proceed to main apron for refuelling. General aviation refuelling will be serviced by request, time depended on refueller availability. For payment information: TEL: +2712 358 5266 AFT HR: +2783 658 8917
4	*De-icing facilities*	NIL INFO AVBL

5	*Hangar space for visiting aircraft*	ACFT Manufacturing organisations number available from AD Admin.
6	*Repair facilities for visiting aircraft*	ACFT Manufacturing organisations number available from AD Admin.
7	*Remarks*	Bowser fuel to be arranged with fuel provider.

FAWB AD 2.5 PASSENGER FACILITIES

1	*Hotels*	International Inn. TEL: +27 12 543 0843 Guest houses available in the vicinity.
2	Restaurants	Villa San Giovanni TEL: +27 12 543 0843 Meals and pizzeria available.
3	*Transportation*	Taxis and car hire available at AD contact AD Admin for numbers.
4	*Medical facilities*	First Aid available. Hospitals: Eugene Marais - 10 KM, TEL: +27 12 334 2777 Montana Private Clinic - 4 KM, TEL: +27 12 523 3000 Ambulance available within 7 minutes
5	*Bank and Post Office*	ATM Only ABSA and FNB available.
6	*Tourist office*	In City TEL: +27 12 358 1430
7	*Remarks*	NIL INFO AVBL

FAWB AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	*AD category for fire fighting*	CAT 5: MON-SUN 0300-1800.
2	*Rescue equipment*	2 x Fire vehicles available. 6 x 6 vehicle: 15000L water and 1500L of foam compound with 317KG Dry Chemical powder. 4 x 4 vehicle: 6000L water and 850L foam compound with 225KG Dry Chemical Powder.Standard rescue and fire fighting equipment carried in accordance with ICAO requirements for CAT 5.
3	*Capability for removal of disabled aircraft*	Resources available to remove general aviation type aircraft and under 19-seater type aircraft.
4	*Remarks*	9 Man crew per shift. Contact details +2783 658 8917. Nil services available after 1800.

FAWB AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	*Types of clearing equipment*	NIL INFO AVBL
2	*Clearance priorities*	NIL INFO AVBL
3	*Remarks*	NIL INFO AVBL

FAWB AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	*Apron surface and strength*	SFC: Main APN: concrete Secondary APN: concrete, configured for general aviation type ACFT. Strength: PCR 890/R/B/W/T
2	*Taxiway width* *Taxiway surface* *Taxiway strength*	Width: 15 M except TWY D1 which is 22 M Surface: Asphalt. Strength: 22/F/B/X/T Strength: PCR 420/F/B/X/T
3	*Altimeter checkpoint location and elevation*	THR RWY 29: 4095 FT; THR RWY 11: 4038 FT THR RWY 06: 4070 FT; THR RWY 24: 4074 FT
4	*VOR checkpoints*	NIL INFO AVBL
5	*INS checkpoints*	NIL INFO AVBL
6	*Remarks*	ATC view of TWY F APRX 80 percent obscured due to hangars. No ATC CLR will be issued and Pilot to TAX at own discretion. Pilots to also EXER CTN when TAX to and FM THR RWY 06. ACFT tie-down points AVBL on Main and GS APN. ACFT operating within the AMO area operates at own risk as the area is not a maintained apron and parking area for ACFT. Risk of Foreign Objects ingestion due to maintenance activities in the specific area.

FAWB AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	*Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands.*	Taxiing guidance signs at all intersections, TWY signs and Holding position signs at each RWY. Guidelines within Apron. Follow guidelines from TWY centre guidelines to allocated parking bay. ID number painted on surface. Marshalling guidance at ACFT stands when required. ACFT to contact ATC on FREQ for start and taxi clearance. Landing flights to provide ATC with ACFT REG and parking bay with readback of taxi instruction.
2	*RWY and TWY markings and LGT*	RWY: THR, RWY Designation, RWY centreline and Holding point markings. TWY: All TWY centrelines markings. RWY LGT: RWY 11/29 - PAPI LGT, THR, Edge LGT and RWY End LGT. RWY 06/24 - NIL. TWY LGT: Reflective Edge markers.
3	*Stop bars*	NIL
4	*Remark*	Bays A1, A2 reserved for Medium ACFT. Bays B1 - B4 reserved for scheduled flights and medium ACFT only. PRKG bays B5 to B7 reserved for charter flights only, with a max PRKG period of 2HR. New C APN reserved for the PRKG of smaller ACFT, less than 5000KG. GS areas are to no longer be used for the PRKG of ACFT. **Warning**: Vehicle MOV on TWY C BTN A APN and C APN, Pilots to EXER CTN.

FAWB AD 2.10 AERODROME OBSTACLES

In Area 2					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/ Type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	Two NDB masts	NIL INFO AVBL	HGT 59 FT	OBST lights	143 M THR RWY 29
NIL INFO AVBL	Radio mast	NIL INFO AVBL	4306 / 115 FT	NIL INFO AVBL	4.7 NM SSW
NIL INFO AVBL	Radio mast	NIL INFO AVBL	4270 / 115 FT	NIL INFO AVBL	3.4 NM S
NIL INFO AVBL	Radio mast	NIL INFO AVBL	4132 / 115 FT	NIL INFO AVBL	4.4 NM SW
NIL INFO AVBL	Radio mast	NIL INFO AVBL	4788 / 184 FT	NIL INFO AVBL	3.6 NM SW
Pilots to EXER CTN when on final approach for RWY 24 due to high ground 2 NM from THR.					

In Area 3					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/ Type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL

FAWB AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	*Associated MET office*	O R Tambo INTL
2	*Hours of service* *MET Office outside hours*	NIL MET Station O R Tambo INTL TEL: +27 11 390 9329/30 or +27 12 367 6210.
3	*Office responsible for TAF preparation* *Periods of validity*	O R Tambo INTL 9-11 Hours
4	*Trend forecast* *Interval of issuance*	NIL 3 hourly
5	*Briefing / consultation provided*	NIL
6	*Flight documentation / Language(s) used*	NIL
7	*Charts and other information available for briefing or consultation*	NIL
8	*Supplementary equipment available for providing information*	NIL
9	*ATS units provided with information*	Ground Movement Control, TWR, APP

10	*Additional information (limitation of service, etc.)*	Hourly METAR prepared by ATS. Flight documentation and other Aviation related information AVBL on web page http://aviation.weathersa.co.za

FAWB AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	*TRUE BRG*	*Dimensions of RWY (M)*	*Strength (PCR) and surface of RWY and SWY*	*THR coordinates RWY end coordinates THR geoid undulation*	*THR elevation and highest elevation of TDZ of precision APP RWY*	*Slope of RWY-SWY*
1	*2*	*3*	*4*	*5*	*6*	*7*
11	092°T	1828 x 30	PCR 420/F/B/X/T ASPH	253911.07S 0281246.04E	4038 FT	+0.95%
29	272°T	1828 x 30	PCR 420/F/B/X/T ASPH	253913.80S 0281351.52E	4095 FT	- 0.95%
06	044°T	1267 x 22	PCR 380/F/B/X/T ASPH	253943.82S 0281258.48E	4070 FT	+ 0.07%
24	224°T	1267 x 22	PCR 380/F/B/X/T ASPH	253913.68S 0281329.44E	4073 FT	- 0. 07%
SWY dimensions (M)	*CWY dimensions (M)*	*Strip dimensions (M)*	*RESA dimensions (M)*	*Location (which runway end) and description of arresting system (if any);*	*OFZ*	*Remarks*
8	*9*	*10*	*11*	*12*	*13*	*14*
NIL	150 x 150	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	See below
NIL	150 x 150	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	See below
NIL	75 x 150	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	
NIL	75 x 150	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	

Remarks (12)
(1) RWY 11/29 CLSD due MAINT every MON BTN 0700-1200. RWY 06/24 available for operations.
(2) When RWY 06/24 is CLSD for MAINT BTN 0700-1200, ACFT will be cautioned on MAINT activities taking place.
(3) RWY AVBL in case of ACFT declared EMERG with 15MIN prior notice.
(4) Airfield CLSD to fixed wing ACFT first MON of the month BTN 0700-1200 due to MAINT at RWY 11/29 and RWY 06/24 intersection. RWY will be made AVBL with 15MIN prior notice in case of ACFT declared EMERG.

FAWB AD 2.13 DECLARED DISTANCES

RWY Designator	*TORA (M)*	*TODA (M)*	*ASDA (M)*	*LDA (M)*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*
11	1828	1978	1828	1828	NIL
29	1828	1978	1828	1828	NIL
06	1267	1342	1267	1267	NIL
24	1267	1342	1267	1267	NIL

FAWB AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	*APCH LGT Type LEN INTST*	*THR LGT colour WBAR*	*VASIS (MEHT) PAPI*	*TDZ LGT LEN*	*RWY Centre Line LGT LEN, spacing, colour, INTST*	*RWY Edge LGT LEN, spacing, colour, INTST*	*RWY End LGT colour and WBAR*	*SWY LGT LEN (M) colour*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*
11	NIL	Green	PAPI Left/ 2.6°	NIL	NIL	1828 M, 60M White Last 600M Yellow	Red	NIL	NIL
29	NIL	Green	PAPI Left/ 2.7°	NIL	NIL	1828 M, 60M White Last 600M Yellow	Red	NIL	NIL
06	NIL	NIL	NIL	NIL	NIL	NIL	NIL	NIL	NIL
24	NIL	NIL	NIL	NIL	NIL	NIL	NIL	NIL	NIL
(1) RWY lights AVBL after 1700 on remote switch FREQ 118.35 MHz. 5 clicks to turn lights on, 3 clicks for intensity. Lights will stay on for 15MIN. (2) PAPI RWY 11/29: Touchdown displaced by + 300M from THR, System to be used with CTN at DIST in excess of 4NM.									

FAWB AD 2.15 OTHER LIGHTING SYSTEMS, SECONDARY POWER SUPPLY

1	*ABN/IBN location, characteristics and hours of operation*	On control TWR roof, 253928.62S 0281255.01E, Colour: Alternate Blue and White rotating, 1HR before sunset and 1 HR after sunrise
2	*LDI location and LGT Anemometer location and LGT*	LDI: NIL Anemometer Location: S of THR 06 and TWY 'F', N of THR 11 and NE of THR 24.
3	*TWY edge and centre line lighting*	Edge: Blue LGT and Reflective markers
4	*Secondary power supply and switch-over time*	Secondary power supply to all lighting, RDO and navaid systems including PAPI, R/T COM and AFTN systems at AD. Switch over-time: 2 SEC
5	*Remarks*	OBST, Floodlights, LGT on main windsock.

FAWB AD 2.16 HELICOPTER LANDING AREA

1	*Coordinates TLOF or THR of FATO Geoid undulation*	Main Helistop on GS APN NE of Main terminal building. Circuit Training: -50 M SW of TWY B2 BTN TWY C2 and RWY 06/24 at grass square. -150 M NE of THR RWY 11 at grass square. -110 M SE of RWY 06/24 at cement square. - 95 SE of THR RWY 06 on TWY parallel to RWY 06/24.
2	*TLOF and/or FATO elevation M/FT*	N/A
3	*TLOF and FATO area dimensions, surface, strength, marking*	TLOF: 18 M X 18 M, cement, 10 M X 10 M, grass, white chalk 200 M X10 M, Asphalt, NIL
4	*True BRG of FATO*	N/A
5	*Declared distance available*	NIL INFO AVBL
6	*APP and FATO lighting*	NIL INFO AVBL

7	*Remarks*	- ATC view of hangars to the W of THR RWY 11near the Secondary (cement) Apron is obstructed. Helicopters to contact ATC prior to lift-off from hangars within area. - Helicopters are to land outside the designated apron area and the hover taxi less than 20 Knots to the landing position within the apron area or at the Fuel Bay. Circuit pattern and ALT * RWY 29, Left hand 4800 FT remain 150 M clear of RWY 29. * RWY 11, Right hand 4800 FT remain 150 M clear of RWY 11. * RWY 06, Right hand 4800 FT remain SE of RWY 11/29 and remain 85 M clear of RWY 06. * RWY 29 with Parachuting at the AD, NE OF THR RWY 11, right hand 4800 FT remaining 150 M clear of RWY 29. * RWY 11, Left hand 4800 FT remain 150 M clear from RWY 11. * RWY 06/24 with parachuting at AD, no Helicopter Circuits or auto rotations allowed. * With RWY 11 in use without parachuting at AD, auto rotations to the S of RWY 11 only allowed from Final APP or Base leg remaining clear of the Airport buildings. * All landings between hangars at pilots own discretion with due regard to the other tenants in close proximity. * All areas to be used for landing to be approved by APM.

FAWB AD 2.17 ATS AIRSPACE

1	*Designation and lateral limits*	Wonderboom Control Zone (CTR) The area bounded by lines drawn as follows: a) From a point at 253214.37S 0281245.45E along a straight line to a point at 253249.53S 0282153.35E; b) Thence clockwise along the arc of a circle, radius 5NM, centred at 253750.00S 0282142.00E, to a point at 254250.06S 0282120.24E; c) Thence along a straight line to a point at 254215.42S 0281225.64E; d) Thence clockwise along the arc of a circle, radius 5NM, centred at 253715.00S 0281238.00E, back to the starting point at 253214.37S 0281245.45E.
2	*Vertical limits*	7600FT ALT
3	*Airspace classification*	C
4	*ATS unit call-sign* *Language*	English
5	*Transition altitude*	8000FT MSL
6	*Remarks*	Except where otherwise authorized, no aircraft is to be operated within this airspace unless two-way radio contact is maintained with ATC.

FAWB AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	*Call sign*	*Frequency*	*Hours of operation*	*Remarks*
1	*2*	*3*	*4*	*5*
APP/TWR	Wonderboom Tower	118.35 MHz transmits and receives	see ATS HOD	NIL INFO AVBL

Service designation	*Call sign*	*Frequency*	*Hours of operation*	*Remarks*
1	*2*	*3*	*4*	*5*
APP/TWR VDF	Wonderboom Tower	118.35 MHz transmits and receives	see ATS HOD	On roof of Control Tower
Ground Movement Control	Wonderboom Ground	120.60 MHz Transmits and receives	see ATS HOD	NIL INFO AVBL

FAWB AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, MAG VAR, Type of supported OPS (for VOR/ILS/ MLS, give declination)	*ID*	*Frequency*	*Hours of operation*	*Position of transmitting antenna coordinates*	*Elevation of DME transmitting antenna*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*
VOR	DPV	112.20 MHz	H24	253921.30S 281312.27E	4080.997 FT	NIL
DME	DPV	CH 59X	H24	253921.44S 0281311.80E	4088.618 FT	NIL

FAWB AD 2.20 LOCAL TRAFFIC REGULATIONS

1) Engine running only to be conducted on Designated Engine running area at Main windsock E of TWY D4. Taxi clearance to be obtained from Ground Movement Control, FREQ 120.60 MHz.
2) No PRKG by any ACFT is allowed on or close to any TWY this includes the taxiways located within the APN and AD MOV area.
3) Pilots taxiing to or FM the ‘B’ or ‘C’ (Main) APN or Fuel bay have to obtain instructions FM ATC on FREQ 120.6 MHz.
4) Pilots taxiing on TWY C2 to EXER CTN BTN TWY B and TWY D, due to HEL circuits PARL to RWY 11/29.
5) No vehicles allowed on the APN without a rotating Amber LGT and permission FM APM
6) No vehicles/persons are allowed entry into manoeuvring area without permission FM ATC.
7) Instructions are only allowed to exit ACFT for the purpose of the student continuing with solo flying within the manoeuvring area. Students are to call for taxi instructions FM ATC before re-entering the manoeuvring area.
8) All students pilots are to advise ATC on first CTC that they are conducting solo student flight training.
9) Unless otherwise advised by ATC, pilots landing on RWY 11/29 may vacate onto RWY 24 and right onto TWY B.
10) Airport services are available daily between the hours 0400-1800. Outside those operational hours as published in the AIP, the airport has zero services available and is unmanned by ANS and RFFS. It is the sole discretion of the pilot in command, and/or owner/operator of an ACFT operated after the termination of the airport services and/or before resumption to ensure that such operations are permissible. The onus rests upon the pilot in command, and/or owner/operator to ensure that the risk mitigation is in place for a safe operation of the aircraft and its occupants. The pilot in command and or owner/operator must comply to the required licensing requirements as approved for the operator.
The pilot in command and or owner/operator must record and report to the aerodrome administrator all movements of aircraft conducted outside the stipulated hours of airport operations in the prescribed form which is made available by the airport. The prescribed form must be collected via email or hard copy from Airport Administration and returned to Airport Administration via email or hard copy.

FAWB AD 2.21 NOISE ABATEMENT PROCEDURES

* According to AIC 20.3.
* See ENR 1.5, Noise Abatement Procedures.
* No low level circuits on SUN.
* No helicopter circuits training before 0900 on SUN and Religious HOL.
* No parachuting before 0900 on SUN and Religious HOL
* All HEL OPS below 4600 FT to be conducted within AD perimeter fence.
* No engines runs allowed: MON - SAT 1700 - 0500 and SUN before 0900 and after 1500.

FAWB AD 2.22 FLIGHT PROCEDURES

General

Circuit procedures:
a) ATC in operation - as advised by ATC.
b) Circuit ALT
Helicopter - 4800 FT, Piston engine - 5100 FT, Turbine engine - 5600 FT
c) Fixed wing circuit: RWY 29 and 24 - Right hand, RWY 06 and 11 - Left hand.
Early turnouts subject to ATC approval.

Procedures for VFR Flights within FAWB CTR:
VFR pilots must obtain an ATC joining clearance at the following reporting points:
a) N (GFA1/FAD 127): 2 NM N of Rooiwal PWR STN,
b) W: OHD Rosslyn industrial area,
c) NW: join W or N, that is: report at Rosslyn or 2 NM N of Rooiwal PWR STN.
d) E: OHD the Cullinan town or Cullinan dam.
e) S W: Crossing the Magaliesberg ridge S of Rosslyn industrial area.
f) S E: 5 NM S E of Mamelodi.g) N E (GFA2/FAD128): 7 NM N E of Roodeplaat dam.
VFR pilots that have not received and acknowledged an ATC CLR cannot enter the FAWB CTR. In the case of an EMERG , joining will be according to ATC CLR and pilot discretion.

Communication Failure:
In the case of RCF, follow the STD published RCF procedures.
NE (GFA2/FAD128): 7 NM N E of Roodeplaat dam.
VFR pilots that have not received and acknowledged an ATC CLR cannot enter the FAWB CTR. In the case of an EMERG, joining will be according to ATC CLR and pilot discretion.
In the case of RCF, follow the STD published RCF procedures.

FAWB AD 2.23 ADDITIONAL INFORMATION

Warning:
Occasional blasting 1.3 NM N of AD. Danger HGT GND - 2000 FT. ACFT in circuit to N should remain N of Railway line and W of Bon Accord Dam as advised by ATC.
* Hazard - Wind shear on THR of all runways due to close proximity of hangars and geographical features to runways and AD. Normally present when wind speed exceeds 15KT
- Buck and Guinea Fowl on AD.

Parachuting:
Drop zone designated as area S of RWY 11/29 and 06/24.
Times:
a) Every SAT and Public HOL during ATS HOD only, from 0700 till sunset.
b) Every SUN and Religious HOL during ATS HOD only, till sunset.
c) Every second WED from 1000 till 1400.

FAWB AD 2.24 CHARTS RELATED TO AN AERODROME

AD	-AD-01
RNAV (GNSS) RWY 29	-RNAV-01
Data Tabulation	-RNAV-01A
VOR RWY 29	-VOR-01