# FAWN

## AD 2.1 AERODROME LOCATION INDICATOR AND NAME

FAWN - CAPE WINELANDS

## AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

| | | |
|---|---|---|
| 1 | *ARP co-ordinates and site at AD* | Ref. Point: 334617S 0184424E |
| 2 | *Direction and distance from city* | 5 NM NE of Durbanville |
| 3 | *Reference elevation/Reference temperature* | ELEV: 399 FT |
| 4 | *Geoid undulation at aerodrome elevation position* | NIL INFO AVBL |
| 5 | *MAG VAR*<br>*annual change* | 24.5°W /2007 |
| 6 | *AD operator, address, telephone, telefax, e-mail, AFS address and, if available, website address* | Authority and Remarks:<br>Cape Winelands Airport Ltd<br>Lichtenburg Road, R312<br>Durbanville<br>Cape Town<br>TEL: +27 21 486 5999<br>FAX: +27 21 447 9120<br>Email: info@capewinelands.aero<br>Website: www.capewinelands.aero |
| 7 | *Types of traffic permitted (IFR / VFR)* | VFR |
| 8 | *Remarks* | NIL |

## AD 2.3 OPERATIONAL HOURS

| | | |
|---|---|---|
| 1 | *AD Operator* | HJ |
| 2 | *Customs and immigration* | NIL |
| 3 | *Health and sanitation* | NIL INFO AVBL |
| 4 | *AIS briefing office* | NIL INFO AVBL |
| 5 | *ATS reporting office (ARO)* | NIL INFO AVBL |
| 6 | *MET briefing office* | NIL INFO AVBL |
| 7 | *ATS* | NIL |
| 8 | *Fuelling* | MON-FRI: 0600 – 1500<br>SAT-SUN: 0600 – 1000<br>Outside HOD: Available on a R150 call out. |
| 9 | *Handling* | NIL INFO AVBL |
| 10 | *Security* | NIL INFO AVBL |
| 11 | *De-icing* | NIL INFO AVBL |
| 12 | *Remarks* | NIL |

## AD 2.4 HANDLING SERVICES AND FACILITIES

| | | |
|---|---|---|
| 1 | *Cargo-handling facilities* | NIL INFO AVBL |
| 2 | *Fuel and Oil types* | AVGAS available. Monthly fuel and landing arrangement to be made with George Lourens at +27 72 184 5587. |
| 3 | *Fuelling facilities and capacity* | 28000 litres |
| 4 | *De-icing facilities* | NIL INFO AVBL |
| 5 | *Hangar space for visiting aircraft* | Hangarage available. |
| 6 | *Repair facilities for visiting aircraft* | Diepkloof AMO - Pieter +27 82 784 7133 |
| 7 | *Remarks* | NIL |

## AD 2.5 PASSENGER FACILITIES

| | | |
|---|---|---|
| 1 | *Hotels* | NIL INFO AVBL |
| 2 | *Restaurants* | NIL INFO AVBL |
| 3 | *Transportation* | NIL INFO AVBL |
| 4 | *Medical facilities* | NIL INFO AVBL |
| 5 | *Bank and Post Office* | NIL INFO AVBL |
| 6 | *Tourist office* | NIL INFO AVBL |
| 7 | *Remarks* | NIL |

## AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

| | | |
|---|---|---|
| 1 | *Aerodrome category for fire fighting* | CAT I |
| 2 | *Rescue equipment* | NIL INFO AVBL |
| 3 | *Capability for removal of disabled aircraft* | NIL INFO AVBL |
| 4 | *Remarks* | NIL |

## AD 2.7 SEASONAL AVAILABILITY - CLEARING

| | | |
|---|---|---|
| 1 | *Types of clearing equipment* | NIL INFO AVBL |
| 2 | *Clearance priorities* | NIL INFO AVBL |
| 3 | *Remarks* | NIL |

## AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

| | | |
|---|---|---|
| 1 | *Designation, surface and strength of aprons* | Concrete.LCN unavailable |
| 2 | *Designation, width, surface and strength of taxiways* | Concrete. LCN unavailable |
| 3 | *ACL location and elevation* | NIL INFO AVBL |
| 4 | *VOR checkpoints* | NIL INFO AVBL |
| 5 | *INS checkpoints* | NIL INFO AVBL |
| 6 | *Remarks* | Visiting aircraft to park in the public apron just SW of the fuel bay at 33.77168582S 18.74264402E |

## AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

| | | |
|---|---|---|
| 1 | *Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands.* | NIL INFO AVBL |
| 2 | *RWY and TWY markings and LGT* | NIL INFO AVBL |
| 3 | *Stop bar* | NIL INFO AVBL |
| 4 | *Remark* | NIL |

## AD 2.10 AERODROME OBSTACLES

| **In Area 2** | | | | | |
|---|---|---|---|---|---|
| *OBST ID/ Designation* | *OBST type* | *OBST position* | *ELEV/HGT* | *Markings/type, colour* | *Remarks* |
| *a* | *b* | *c* | *d* | *e* | *f* |
| NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | NIL |

| **In Area 3** | | | | | |
|---|---|---|---|---|---|
| *OBST ID/ Designation* | *OBST Type* | *OBST position* | *ELEV/HGT* | *Markings/type, colour* | *Remarks* |
| *a* | *b* | *c* | *d* | *e* | *f* |
| NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | NIL |

## AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

| | | |
|---|---|---|
| 1 | *Associated MET office* | NIL INFO AVBL |

| | | |
|---|---|---|
| *2* | *Hours of service*<br>*MET office responsible outside hours* | NIL INFO AVBL |
| *3* | *Office responsible for TAF preparation and periods of validity* | NIL INFO AVBL |
| *4* | *Type of trend forecast and interval of issuance* | NIL INFO AVBL |
| *5* | *Briefing / consultation provide* | NIL INFO AVBL |
| *6* | *Flight documentation / language(s) used* | NIL INFO AVBL |
| *7* | *Charts and other information available for briefing or consultation* | NIL INFO AVBL |
| *8* | *Supplementary equipment available for providing information* | iWeathar station<br>https://iweathar.co.za/display?s_id=799 |
| *9* | *ATS units provided with information* | NIL INFO AVBL |
| *10* | *Additional information (limitation of service, e.t.c.)* | NIL INFO AVBL |

## AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

| *Designations RWY NR* | *TRUE &MAG BRG* | *Dimensions of RWY (M)* | *Strength (PCN) and surface of RWY and SWY* | *THR coordinates RWY end coordinates THR geoid undulation* | *THR elevation and highest elevation of TDZ of precision APP RWY* | *Slope of RWY-SWY* |
|---|---|---|---|---|---|---|
| *1* | *2* | *3* | *4* | *5* | *6* | *7* |
| 05 | 25.18°T/<br>50.70°M | 900 X 20 | Concrete<br>LCN<br>16 | 334631.48S<br>0184415.74E | 400 FT | NIL INFO AVBL |
| 23 | 203.70°T/<br>229.22°M | 900 X 20 | Concrete<br>LCN<br>16 | 334601.11S<br>0184432.47E | 394 FT | NIL INFO AVBL |
| 14 | 117.31°T/<br>142.83°M | 700 x 16 | NIL INFO AVBL | 334614.20S<br>0184417.59E | 400 FT | NIL INFO AVBL |
| 32 | 293.57°T/<br>319.09°M | 700 x 16 | NIL INFO AVBL | 334625.72S<br>0184447.60E | 407 FT | NIL INFO AVBL |
| *SWY dimensions (M)* | *CWY dimensions (M)* | *Strip dimensions (M)* | *RESA dimensions (M)* | *Location (which runway end) and description of arresting system (if any);* | *OFZ* | *Remarks* |
| *8* | *9* | *10* | *11* | *12* | *13* | *14* |
| NIL | 130 X 90 M | NIL INFO AVBL | NIL INFO AVBL | NIL NIL INFO AVBL | NIL INFO AVBL | See below |
| NIL | NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | See below |
| NIL | NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | See below |

| | | | | | | |
|---|---|---|---|---|---|---|
| NIL | NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | See below |
| Remarks:<br>1. All Circuits to be confined within an area 2.5 NM radius of the aerodrome.<br>2. Landing area is on the Western side of cement area marked with white blocks of 3 x 1 M and 100 M apart and all landings and take-off's are to be conducted in the marked area. | | | | | | |

## AD 2.13 DECLARED DISTANCES

| *RWY* | *TORA (M)* | *TODA (M)* | *ASDA (M)* | *LDA (M)* | *Remarks* |
|---|---|---|---|---|---|
| *1* | *2* | *3* | *4* | *5* | *6* |
| 05 | 900 | 1030 | 900 | 900 | NIL |
| 23 | 900 | 900 | 900 | 900 | NIL |
| 14 | 700 | 700 | 700 | 700 | NIL |
| 32 | 700 | 700 | 700 | 700 | NIL |

## AD 2.14 APPROACH AND RUNWAY LIGHTING

| *RWY Designator* | *APCH LGT Type, LEN INTST* | *THR LGT Colour WBAR* | *VASIS (MEHT) PAPI* | *TDZ, LGT LEN* | *RWY Centre Line LGT LEN, spacing, colour, INTST* | *RWY Edge LGT, LEN, spacing, colour, INTST* | *RWY End LGT Colour WBAR* | *SWY LGT LEN (M) colour* | *Remarks* |
|---|---|---|---|---|---|---|---|---|---|
| *1* | *2* | *3* | *4* | *5* | *6* | *7* | *8* | *9* | *10* |
| 05 | NIL | Green, No WBAR | NIL | NIL | NIL | 900M, 80M, White, No WBAR | Red, No WBAR | NIL | See AD 2.15 Remarks |
| 23 | NIL | Green, No WBAR | NIL | NIL | NIL | 900M, 80M, White, No WBAR | Red, No WBAR | NIL | See AD 2.15 Remarks |
| 14 | NIL | NIL | NIL | NIL | NIL | NIL | NIL | NIL | NIL |
| 32 | NIL | NIL | NIL | NIL | NIL | NIL | NIL | NIL | NIL |

## AD 2.15 OTHER LIGHTING SYSTEMS, SECONDARY POWER SUPPLY

| | | |
|---|---|---|
| *1* | *ABN/IBN location, characteristics and hours of operation* | LGT units require MNM 4 HR direct sun for APRX 100 HR OPS. Periodic inspection conducted to verify service life. Not recommended for use in OVC conditions. |
| *2* | *LDI location & LGT*<br>*Anemometer location and LGT* | NIL |

| | | |
|---|---|---|
| *3* | *TWY edge and centre line lighting* | NIL |
| *4* | *Secondary power supply and switch-over time* | NIL |
| *5* | *Remarks* | 1. RWY LGT AVBL with PN.<br>2. Fixed solar powered RWY LGT and REIL.<br>3. RWY LGT and REIL are intended for private use of Airport Operators and not AVBL for general use.<br>4. Usage requires signing of an indemnity obtainable from FAWN office. |

## AD 2.16 HELICOPTER LANDING AREA

| | | |
|---|---|---|
| *1* | *Coordinates TLOF or THR of FATO / Geoid undulation* | NIL INFO AVBL |
| *2* | *TLOF / FATO elevation (m/ft)* | NIL INFO AVBL |
| *3* | *TLOF and FATO area dimensions, surface, strength, marking* | NIL INFO AVBL |
| *4* | *True BRG of FATO* | NIL INFO AVBL |
| *5* | *Declared distance available* | NIL INFO AVBL |
| *6* | *APP and FATO lighting* | NIL INFO AVBL |
| *7* | *Remarks* | No helicopters are to take-off, land, or taxi between the hangars. All helicopter movements are restricted to the main runways, taxiways, or designated public aircraft parking area just SW of the fuel bay at 334618S 0184434E. |

## AD 2.17 ATS AIRSPACE

| | | |
|---|---|---|
| *1* | *Designation and lateral limits* | NIL |
| *2* | *Vertical limits* | NIL |
| *3* | *Airspace classification* | NIL |
| *4* | *ATS unit call sign*<br>*Language(s)* | NIL |
| *5* | *Transition altitude* | NIL |
| *6* | *Remarks* | NIL |

## AD 2.18 ATS COMMUNICATION FACILITIES

| *Service designation* | *Call sign* | *Channel(s)* | *Hours of operation* | *Remarks* |
|---|---|---|---|---|
| *1* | *2* | *3* | *4* | *5* |
| NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | NIL INFO AVBL | NIL |

## AD 2.19 RADIO NAVIGATION AND LANDING AIDS

| *Type of aid, MAG VAR, Type of supported OPS (for VOR/ ILS/MLS, give declination)* | *ID* | *Frequency* | *Hours of operation* | *Position of transmitting antenna coordinates* | *Elevation of DME transmitting antenna* | *Remarks* |
|---|---|---|---|---|---|---|
| *1* | *2* | *3* | *4* | *5* | *6* | *7* |
| NIL | NIL | NIL | NIL | NIL | NIL | NIL |

## AD 2.20 LOCAL AERODROME REGULATIONS

Circuit joining procedures:
- All traffic within 5NM of the airfield must monitor and make regular position reports on frequency 131.10MHz.
- All inbound traffic shall approach the airfield at 2000FT ALT from 5NM.
- A radio call must be made at 5 NM inbound at 2000FT ALT on VHF frequency 131.10 MHz.
- Join overhead at 2000FT ALT, to enter a left-hand pattern for either runway 05/23 or 14/32.
- A further radio call must be made from overhead the airfield at 2000FT ALT to advise traffic of further intentions.
- Descend on the “dead side”, and join on left crosswind (over RWY numbers) to merge with the active circuit on the downwind at 1300FT ALT.
- Standard circuit height for all aircraft 1300FT ALT, except microlight aircraft which shall fly a “low level” circuit at 900FT ALT. Standard radio calls must be made in the circuit.
- Orbits are not permitted in the circuit.
- Aircraft leaving the area must maintain 1500FT ALT until 5NM and call outbound on 131.10MHz. Aircraft with dual-frequency monitoring capability are advised to also listen out on 124.8MHz for inbound traffic.
- Transiting aircraft to avoid overflying the airfield and to maintain 2000FT ALT from 5NM until past the airfield, descending to 1500FT ALT thereafter until outbound at 5NM.
- Aircraft turning right after take-off must remain below 900FT ALT until 3NM before climbing to 1500FT ALT to ensure no conflict with joining traffic.
- Circuit joining procedures herein to be adhered to by all general aviation.

Non-standard operations/procedures may be conducted by FAWN Fixed-Base Operators with the prior consent of the Airport Authority.
Unmanned AD: Frequency 131.10 MHz,
Call-sign: **Winelands Traffic**
Caution: AIAA (Area of Intense Aerial Activity) – maintain a constant lookout for traffic
Banner tow operations taking place, Call-sign: Sky AD FREQ: 131.10 MHz
Crop Spraying Operations
Intensive Flight Training Operations involving multiple aircraft.
Multiple active runways

## AD 2.21 NOISE ABATEMENT PROCEDURES

NIL INFO AVBL

## AD 2.22 FLIGHT PROCEDURES

NIL INFO AVBL

## AD 2.23 ADDITIONAL INFORMATION

NIL

## AD 2.24 CHARTS RELATED TO AN AERODROME

NIL