AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	*Designation, surface and strength of aprons*	Concrete N/A.
2	*Designation, width, surface and strength of taxiways*	TWY Widths: A = 12,2 M B =28,3 M C = 29,4 M
3	*ACL location and elevation*	NIL INFO AVBL
4	*VOR checkpoints*	NIL INFO AVBL
5	*INS checkpoints*	VIP: 335413.75S 0182941.54E C130: 335422.74S 0182932.39E 22 SQN: 335418.46S 0182940.13E SAPS: 335413.13S 0182934.69E
6	*Remarks*	NIL

AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	*Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands.*	NIL INFO AVBL
2	*RWY and TWY markings and LGT*	NIL INFO AVBL
3	*Stop bar*	NIL INFO AVBL
4	*Remark*	Marking aids: All runways - threshold, Touch-down, RWY designator, RWY centreline and Holding points.

AD 2.10 AERODROME OBSTACLES

In Area 2					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	Mast	335434S 0182942E	HGT 150 FT	NIL INFO AVBL	0.45 NM SW of AD.
NIL INFO AVBL	Power lines	NIL INFO AVBL	HGT 83 FT	Red hazard LGT	S & SE of THR RWY 02
- 7 x Apron lighting masts, height 99 FT, erected above dispersal area marked by double red lights. -RENL visible from both directions. -Fence 1.2 M AGL erected along the length of RWY 02/20 N of TWY C and 250 M W of RWY. - Raised lights at THR RWY 20. - ACFT to avoid landing on THR RWY 02/20 due to cracks on the surface.					