20	NIL	NIL	NIL	NIL	NIL
Remarks 12 Circuit Procedures (a) Circuit altitude: Fixed wing aircraft - 1 000 FT Helicopters - 800 FT (b) RWY 02 in use - Left hand circuit RWY 20 in use - Right hand circuit (c) Raised lights at THR RWY 20					

AD 2.13 DECLARED DISTANCES

RWY	*TORA (M)*	*TODA (M)*	*ASDA (M)*	*LDA (M)*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*
02	1585	1585	1585	1585	NIL
20	1585	1585	1585	1585	NIL

AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY	*APCH LGT Type and LEN INST*	*THR LGT Colour WBAR*	*VASIS (MEHT) PAPI*	*TDZ, LGT LEN*	*RWY Centre Line LGT, Spacing, colour INTST*	*RWY Edge LGT, LEN, Spacing, Colour, WBAR*	*RWY End LGT Colour WBAR*	*SWY LGT LEN (m) Colour*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*
02	NIL INFO AVBL	NIL INFO AVBL	RL PAPI (3º)	NIL INFO AVBL	AVBL	AVBL	NIL INFO AVBL	NIL INFO AVBL	Runway Lighting available RWY 02/20
20	NIL INFO AVBL	NIL INFO AVBL	RL PAPI (3º)	NIL INFO AVBL	AVBL	AVBL	NIL INFO AVBL	NIL INFO AVBL	Runway Lighting available RWY 02/20

AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	*ABN/IBN location, characteristics and hours of operation*	NIL INFO AVBL
2	*LDI location & LGT and anemometer location and LGT*	NIL INFO AVBL
3	*TWY edge and centre line lighting*	NIL INFO AVBL
4	*Secondary power supply and switch-over time*	Emergency lighting & secondary supply available / 15 SEC for switch over,
5	*Remarks*	NIL