AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, MAG VAR, Type of supported OPS (for VOR/ILS/ MLS, give declination)	*ID*	*Frequency*	*Hours of operation*	*Position of transmitting antenna coordinates*	*Elevation of DME transmitting antenna*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*
VOR/DME	RBV	113.0 MHz	H24	284426.49S 0320536.91E	93 FT	NIL

AD 2.20 LOCAL AERODROME REGULATIONS

Circuit procedures.
a) Circuit altitude: Piston engined aircraft - 1500 FT AMSL.
Jet engined aircraft - 1500FT AMSL
b) Circuit on all Runways (05/23) to the east unless directed otherwise by ATC.

AD 2.21 NOISE ABATEMENT PROCEDURES

NIL INFO AVBL

AD 2.22 FLIGHT PROCEDURES

Aircraft routing to/from FARB airspace to contact ATC prior to departure/entering controlled airspace. IFR Departures and all helicopters to call ATC for start. All VFR Traffic Operators coastwise to exercise caution and to monitor on all appropriate FREQ GND/1000 FT MSL.

DEEMED SEPARATION BETWEEN VFR AND IFR AIRCRAFT ROUTING
Deemed separation between all VFR aircraft routing/transiting the FARB CTR.
a) Seawards of the coastline within the CTR at 500 FT AGL.
b) West of the N2 highway within the CTR at 1500 FT AGL or below and all IFR traffic established inbound to either RWY 05/23 at 2000 FT ALT or below, or when on departure maintaining RWY track off either RWY 05/23 to 2500 FT ALT prior to commencing the respective turn in the direction of the next fix/point as per Flight plan concerned.

For Radio Communication failure refer AIP ENR 1.5-5.