ENR 2.2 OTHER REGULATED AIRSPACE

1 JOHANNESBURG FIR

1) An active surveillance control (MSSR) service is provided by Bloemfontein Approach Control (ATC) within the Bloemfontein TMA/CTR and Kimberley TMA (at or above 7000FT ALT), where the following is applicable to all aircraft.
2) Aircraft must be equipped with a serviceable mode A & C transponder when operating below and within 5NM (vicinity) of the lateral limits of the Bloemfontein TMA or Kimberley TMA, unless operating within the Special Rules Area (SRA) for non-transponder operations below the Bloemfontein TMA or below the Kimberley TMA as described within the SAAIP, ENR 2.2. para 1.1&1.2.

1.1 BLOEMFONTEIN AREA

1.1.1 RECOMMENDED VFR ROUTES FROM AND TO THE NEW TEMPE AIRFIELD

To enable VFR flights, not on flight plan, to remain clear of the Bloemfontein Control Zone (CTR) and TMA the following routes are to be flown in and out of New Tempe airfield:

NOTE:
All such flights are required to be conducted below the Bloemfontein TMA (i.e. below 6500FT ALT) and to route around and remain clear of the Bloemfontein CTR.
VFR or IFR flights on flight planned flights, departing New Tempe Airfield, are to comply with the routes below until a clearance to enter the Bloemfontein CTR or TMA is obtained from Bloemfontein APP.

a) Flights departing to or approaching from destinations South of Bloemfontein are to route West of the N1 highway and outside of 20NM South of 290602.38S 0261802.31E before setting course for destination.
b) Flights departing to or approaching from destinations North of Bloemfontein are to remain West of the Bloemfontein/ Bultfontein Road and route via the intersection of this road and the Modder River (Soetdoring) before setting course for destination.
c) For destinations East of the intersection mentioned in paragraph b above, aircraft are to route via the intersection (Soetdoring) and North of Brandfort station before setting course for destination.

VFR Routes for aircraft, not landing at New Tempe, to avoid the Bloemfontein CTR.

d) VFR flights wishing to fly abeam and to the South of Bloemfontein, in an Easterly or Westerly direction, are to route South of the Tierpoort Dam.
e) VFR flights wishing to fly abeam and to the North of Bloemfontein, in an Easterly or Westerly direction, are to route Soetdoring then North of Brandfort.

f) VFR flights wishing to fly abeam Bloemfontein in a Northerly or Southerly direction, are to route either East of Brandfort and East of Mockes Dam or route to the West of the Bloemfontein/Bultfontein Road and the N1, until 20NM South of 290602.38S 0261802.31E.

1.1.2 SPECIAL RULES AREA (SRA) FOR NON TRANSPONDER AIRCRAFT FROM AND TO THE NEW TEMPE AIRPORT (FATP)

Aircraft not equipped with a serviceable mode A and C transponder intending to operate from and to New Tempe airport (FATP) can route through and remain within the area bound by the following points and remaining clear of the Bloemfontein CTR:

Lateral boundary:

a) From a point 290528.83S 0261021.31E at the intersection of the R64 and N1 main roads.
b) Then westwards along the R64 road to a point 284252.56S 0254805.40E where this road intercepts the 35NM arc of the Bloemfontein TMA boundary.
c) Then clockwise along the 35NM arc centred at 290602.38S 0261802.31E to a point 283307.56S 0260413.44E where this arc intercepts the Bloemfontein/Bultfontein road.
d) Then southwards along the Bloemfontein /Bultfontein main road to a point 290018.68S 0261226.59E where the Bultfontein /Bloemfontein main road intercepts the Bloemfontein CTR boundary.
e) Then a straight line along the Bloemfontein CTR boundary to a point 290323.61S 0261226.42E where the Bloemfontein CTR boundary intercepts the N1 main road.
f) Then southwards along the N1 main road to the starting point 290528.83S 0261021.31E.

Vertical limit: GND/6000 FT ALT.

1.2 KIMBERLEY AREA

1.2.1 RULES APPLICABLE FOR VFR FLIGHTS OPERATING WITHIN OR BELOW THE FAKM TMA

1) All VFR flights operating on a filed flight plan intending to enter the Kimberley TMA are required to join the TMA via one of the following VFR Geographical points:

Boshoff (283252.7S 0251418.0E)
Perdeberg (285900S 0250500E)
Jacobsdal (290759S 0244602E)
Belmont (292530S 0242230E)

Plooysburg (290222.6S 0241409.0E)
Barkley West (283223.0S 0243156.9E)
Windsorton Road (282001.5S 0244219.8E)

All VFR flights routing in a North/South direction, or vice versa, passing East and South of Kimberley after joining the TMA via aforementioned points are required to follow the routing via Boshoff (283252.7S 0251418.0E) to Perdeberg (285900S 0250500E) to Jacobsdal (290759S 0244602E), or vice versa, thereafter set course as per flight plan.

All VFR flights routing in a North/South direction, or vice versa, passing west of Kimberley, after joining the TMA via afore-mentioned points are required to follow the routing via Barkley West (283223.0S 0243156.9E) to Plooysburg (290222.6S 0241409.0E), or vice versa, thereafter set course as per flight plan.

2) Aircraft routing below the Kimberley TMA intending to route clear of the Kimberley CTR should follow the following VFR routings:

Vertical Requirements: Aircraft to remain VFR below 5500 FT ALT.

Aircraft intending to route East of the Kimberley CTR in a North/South/North direction:
Route via or remain East of the Geographical Route directly between Boshoff (283252.7S 0251418.0E) to Olifantskop (285115.69S 245417.77E) to Jacobsdal (290759S 0244602E), or vice versa.
Aircraft intending to route North of the Kimberley CTR in a East/West/East direction:
Route via or remain North of the Geographical Point of Dronfield (283750S 0244602E) and remain clear of the Kimberley CTR.
Aircraft routing to the West of Kimberley CTR in a North/South/North direction:
Route via or remain West of the Geographical Direct Route from Dronfield (283750S 0244602E), remain West and clear of the CTR to Plooysburg (290222.6S 0241409.0E), or vice versa.
Aircraft routing South of Kimberley CTR in a East/West/East direction:
Route via or remain South of the Geographical Route directly between Jacobsdal (290759S 0244602E) to Ritchie (290218.89S 0243508.07E) to Plooysburg (290222.6S 0241409.0E), or vice versa.

3) These procedures are only applicable during daytime and whilst the Bloemfontein SSR is operating.
4) Any pilot who wishes to gain further information or clarification on these routings can contact Bloemfontein Approach on (051) 503 7201/2/3.

Vertical Limits: GND/FL145

1.2.2 SPECIAL RULES AREA (SRA) FOR NON TRANSPONDER AIRCRAFT FROM AND TO THE JOHN WESTON AIRFIELD

Aircraft not equipped with a serviceable mode A and C transponder intending to operate from and to John Weston airfield can route through and remain within the area bound by the following points and remaining clear of the Kimberley CTR:

Lateral boundary:

a) From a point 284644.44S 0243813.42E at the intersection of the Kimberley CTR boundary and the R357 main road to Douglas; then south-westwards along the R357 main road towards Douglas to a point 285726.72S 0240714.52E 35NM from 284759.81S 0244537.32E;
b) Then clockwise along the arc of a circle radius 35NM centred at 284759.81S 0244537.32E to a point 282232.07S 0241816.93E where this arc intercepts the R31 main road;
c) Then along the R31 main road to a point 284208.65S 0244024.69E where the R31 main road intercepts the Kimberley CTR boundary;
d) Then a straight line along the Kimberley CTR boundary to the starting point 284644.44S 0243813.42E.

Vertical limits: GND/5000 FT ALT

1.3 JOHANNESBURG SRA

1.3.1 SPECIAL RULES AREA

Airspace other than restricted airspace where special (non-standard) rules are applied to promote safety, efficiency and orderliness outside of controlled airspace.

The area below the Johannesburg TMA has been divided into three sectors known as the Eastern, Southern and Western sectors. These sectors each have their own frequency in order to minimize frequency congestion. Aircraft in the Eastern Sector should maintain a listening watch and broadcast regular position reports on frequency 125.4 MHz. Aircraft in the Southern Sector should maintain a listening watch and broadcast regular position reports on frequency 125.6 MHz. Aircraft in the Western Sector should maintain a listening watch and broadcast regular position reports on frequency 125.8 MHz.

The dividing line between the sectors runs as follows:

Name	FREQ	Lateral Limits
Special rules East	125.4 MHz	From a point S253405.629 E0280819.253 on the Wonderboom CTR southwards along the Wonderboom CTR to a point at S254225.411 E0281350.838 on the Wonderboom/Waterkloof CTR. Thence westwards along the Waterkloof CTR to a point at S254259.986 E0280600.359. Thence southwards along the Waterkloof CTR to a point at S255221.904 E0280640.317. Thence southwards along the OR Tambo CTR to a point at S261244.019 E0280420.527 on the OR Tambo CTR/Rand ATZ. Thence southwards along the OR Tambo CTR to a point at S262332.000 E0281139.000. Thence eastwards along the OR Tambo CTR to a point at S262226.965 E0281433.832. Thence southwards along the N3 highway to a point at S264700.833 E0282651.034 on the Johannesburg TMA. Thence Northeastwards along the Johannesburg TMA to a point at S254820 E0284545. Thence Northwestwards along the Waterkloof TMA back to the starting point.

Name	FREQ	Lateral Limits
Special rules West	125.8 MHz	From a point S253405.629 E0280819.253 on the Wonderboom CTR southwards along the Wonderboom CTR to a point at S254225.411 E0281350.838 on the Wonderboom/Waterkloof CTR. Thence westwards along the Waterkloof CTR to a point at S254259.986 E0280600.359. Thence southwards along the Waterkloof CTR to a point at S255221.904 E0280640.317. Thence southwards along the OR Tambo CTR to a point at S261244.019 E0280420.527 on the OR Tambo CTR/Rand ATZ. Thence westwards along the M2 highway to a point at S261244.803 E0280125.648 (M2/M1 intersection). Thence westwards in a direct line to a point north of the Soccer City Stadium at S261352.240 E0275905.430. Thence westwards in a direct line to a point north of the Orlando Power Station cooling towers at S261512.110 E0275536.110. Thence westwards in a direct line to a point at S261544.878 E0275324.306 at the intersection of the Potchefstroom Road and Klipspruit Valley Road. Thence westwards along the Potchefstroom Road to a point at S261740.034 E0275017.927 at the intersection of the Potchefstroom Road and the N12. Thence westwards along the N12 highway to a point at S262427.143 E0273317.290 on the Johannesburg TMA. Thence northwards along the Johannesburg TMA back to the starting point.

Name	FREQ	Lateral Limits
Special rules South	125.6MHz	From a point at S261244.019 E0280420.527 on the OR Tambo CTR/Rand ATZ westwards along the M2 highway to a point at S261244.803 E0280125.648 (M2/ M1 intersection). Thence westwards in a direct line to a point north of the Soccer City Stadium at S261352.240 E0275905.430. Thence westwards in a direct line to a point north of the Orlando Power Station cooling towers at S261512.110 E0275536.110. Thence westwards in a direct line to a point at S261544.878 E0275324.306 at the intersection of the Potchefstroom Road and Klipspruit Valley Road. Thence westwards along the Potchefstroom Road to a point at S261740.034 E0275017.927 at the intersection of the Potchefstroom Road and the N12. Thence westwards along the N12 highway to a point at S262427.143 E0273317.290 on the Johannesburg TMA. Thence southwards along the Johannesburg TMA to a point a S264700.833 E0282651.034 on the Johannesburg TMA. Thence northwards along the N3 highway to a point at S262226.965 E0281433.832 on the OR Tambo CTR. Thence westwards along the OR Tambo CTR to a point at S262332.000 E0281139.000. Thence northwards along the OR Tambo CTR back to the starting point.

1.3.2 RULES APPLICABLE WITHIN THE JOHANNESBURG SPECIAL RULES AREA

The airspace below the lateral boundaries of the Johannesburg and Waterkloof TMAs, excluding promulgated controlled airspace and flying training areas will be declared a special rules area - JOHANNESBURG SPECIAL RULES AREA.

a) Avoid controlled airspace unless otherwise authorised by Air Traffic Control.
b) Comply with the Traffic Information Broadcast by Aircraft (TIBA)
c) Procedures as laid down for the area.
d) Flights must be conducted at an indicated airspeed not exceeding 180 knots.
e) VFR flights operating from or to aerodromes situated within the Johannesburg Special Rules Area must not exceed 7500 FT ALT (FAOR QNH). Pilots wishing to exceed 7500 FT ALT must comply with the normal procedures for obtaining a clearance to enter controlled or advisory airspace.
f) It is recommended that, where possible aircraft have their landing lights switched on.
g) VFR flights on magnetic tracks between 090 DEG M and 269 DEG M included, must operate at 7000 FT ALT (FAOR QNH).
h) VFR flights on magnetic tracks between 270 DEG M and 089 DEG M included, must operate at 7500 FT ALT (FAOR QNH).

i) **All VFR flights, unable to comply with the procedures as laid down in paragraphs g and h must operate at or below 6500 FT ALT (FAOR QNH). All VFR flights are, however, required to comply with Regulation 91.06.32 of the Civil Aviation Regulations, 2011, i.r.o. minimum heights.**

j) **By virtue of the fact that uncontrolled VFR aircraft are to remain below the Johannesburg and Waterkloof TMAs radar separation and information provided to aircraft operating within the Johannesburg and Waterkloof TMAs will only take known identified targets into account.**

k) **For the information of those aircraft operating within the Johannesburg and Waterkloof TMAs, unidentified unknown targets, performing as expected for general aviation within the confines of the Johannesburg Special Rules Area will be deemed to separated from aircraft operating within the aforementioned TMAs by procedures as opposed to radar.**

l) **Pilots operating below the TMAs in the Special Rules Area should therefore ensure that they do not exceed the applicable altitude restrictions as stipulated.**

NOTE: Due to the nature of their operations Traffic Patrol helicopters have been granted dispensation to operate over the Greater Johannesburg area, as and when required, without complying with the recommendations in so far separation below the Johannesburg TMA. Frequent PSN reports will be made by the helicopters involved in the above mentioned operations. Times of operations will normally be between 0430-0800 UTC and 1400 -1530 UTC DLY.

1.3.3 The following procedures for flights in the Wonderboom/Waterkloof environs are to effect separation between civil and military aircraft:

a) **Aircraft flying between Wonderboom Airport and aerodromes East and South-East of Wonderboom must proceed East of Mamelodi township to accomplish better separation from aircraft taking off from Waterkloof. Where a pilot wishes to fly between Mamelodi township and Waterkloof CTR, clearance must be obtained from Air Traffic Control at Waterkloof on frequency 124.1 MHz.**

b) **ACFT operating to/from FABB must do so within the segment of the FAOR CTR between straight lines joining Ergo Slimes Dam/FABB or OR Tambo International at or below 6 000 FT ALT (FAOR QNH).**

c) **Pilots of aircraft equipped with a transponder are advised to obtain a SSR code from Johannesburg Information on first contact.**

1.4 JOHANNESBURG BUFFER ZONE

The Buffer Zone extends from a point on the Rand ATZ, South and East of the Johannesburg CTR to a point on the Waterkloof CTR. The co-ordinates related to this Buffer Zone are as follows:

a) **From a point bound at position S261952.00 E0280817.00 thence a straight line to a point at S262205.00 E0280640.00**

b) **Thence a straight line to a point at S262707.00 E0281035.00**

c) Thence a straight line to a point at S262503.00 E0281625.00
d) Thence a straight line to a point at S261753.00 E0282318.00
e) Thence a straight line to a point at S255800.00 E0282734.00
f) Thence a straight line to a point at S260002.00 E0282344.00
g) Thence a straight line to a point at S261632.00 E0282014.00
h) Thence a straight line to a point at S262232.00 E0281429.00
i) Thence a straight line to a point at S262332.00 E0281139.00
j) Thence a straight line back to the starting point at S261952.00 E0280817.00

All aircraft wishing to enter the Buffer Zone must communicate with Johannesburg Information on 119.5MHz between the hours of 0430 - 1600 UTC and between the hours of 1600 - 0430 UTC must communicate with Johannesburg Area on 126.7MHz

Pilots are advised to communicate with Johannesburg Information on 127.4MHz should they have no reply on 119.5MHz when trying to establish contact with them during their stipulated HOD as mentioned.

The Buffer zone is situated within 3NM of the Johannesburg CTR and its vertical limits are calculated from ground to 7500 feet altitude. It extends from a point on the Rand ATZ, South and East of the Johannesburg CTR to a point on the Waterkloof CTR. Traffic routing outside of the Buffer Zone while flying in the special rules area, and routing from west to east or vica versa, need to identify the following landmarks as visual reference points which includes an approximate distance outlining the boundary extremity of the Buffer Zone in order to remain clear of this airspace.

NOTE - Items 1 and 7 listed below indicate the beginning of the Buffer Zone which borders on the Johannesburg CTR boundary extremity:

1) Intersection the Sybrand van Niekerk Freeway and Kliprivier Drive interchange
2) South of the Kliprivier station
3) S/SE of the R550 and Ergo Slimes Dam
4) S/SE of the R23 / Alberton road interchange
5) East of Kwa-Thema
6) East of the Garsfontein / Pretoria road junction
7) Intersection of the Delmas road (R50) and Pretoria Road (R51)

1.5 Kyalami VFR Route

The Kyalami VFR route was established to address the safety issues within the corridor between the Lanseria CTR and the Waterkloof CTR/Swartkop ATZ that were highlighted through various forums.

Rules applicable within the Johannesburg Special Rules Area, as published in AIP ENR Paragraph 5, are still applicable and must be complied with.

Traffic unable to comply with this procedure must operate at or below 6500FT ALT (FAOR QNH), clear of controlled airspace and in compliance with CAR 91.06.31 i.r.o Minimum Heights.

Northbound Routing

Northbound traffic on magnetic tracks between 270 DEG and 089 DEG must operate at 7500 FT ALT (FAOR QNH) and within 1NM on either side of a track defined by the following route:

From Sandton City Tower (2606.3S 02803.1E) route direct to Kyalami Race Track (2559.6S 02803.5E) then direct to Attridgeville (2547.9S 02803.3E).

Southbound Routing

Southbound traffic on magnetic tracks between 090 DEG and 269 DEG must operate at 7000 FT ALT (FAOR QNH) and within 1NM on either side of a track defined by the following route:

From Attridgeville (2547.9S 02803.3E) route direct to Kyalami Race Track (2559.6S 02803.5E) then direct to Sandton City Tower (2606.3S 02803.1E)

Caution: 1. Pilots are reminded to exercise greater vigilance and accident avoidance techniques due to the increased accuracy of navigation through the use of GPS and increased traffic normally associated with defined routes and landmarks.

1.6 DURBAN SPECIAL RULES AREA

The airspace below the Durban TMA, excluding that part of the Virginia ATZ, the airspace below Durban TMA G and all Restricted Areas (FAR's), Prohibited Areas (FAP's) and Danger Areas (FAD's), is declared as a Special Rules Area and termed as the DURBAN SPECIAL RULES AREA.

This is to promote safety, efficiency and orderliness in the Durban Special Rules Area.

All aircraft operating in the Durban Special Rules Area shall maintain a listening watch and broadcast regular position reports on frequency 124.2 MHz.

By virtue of the fact that uncontrolled VFR aircraft are to remain below the Durban TMA radar separations and information provided to aircraft operating within the Durban TMA, will only take known identified targets into account.

For the information of those aircraft operating within the Durban TMA, unidentified unknown targets, performing as expected for general aviation within the confines of the Durban Special Rules Area will be deemed to be separated from aircraft operating within the Durban TMA, by procedures as opposed to radar.

Pilots operating below the Durban TMA should therefore ensure that they do not exceed the applicable altitude restriction as stipulated on SRA routings and also to remain at least 500 FT below the TMA whilst flying below the Durban TMA.

Pilots are requested to squawk transponder code 2000 at all times with altitude selected. Helicopters to squawk 2600 also with altitude selected.

The following routes will be applicable in the Durban Special Rules Area:

Routes for VFR Aircraft in the Durban Special Rules Area:

Gauteng Area to Virginia:

All VFR traffic is to route via Greytown, clear of the Durban TMA, then to the right of the Alvaston Mast at or below 5000 FT AMSL, then south of the N3 to the Coopers Lighthouse. Cross abeam Pinetown CBD at or below 3000 FT AMSL, cross the N2 at 1500 FT AMSL. Establish communication with Virginia prior to crossing the N2. If no contact, enter into a VFR orbit, at 1500 FT AMSL at Coopers Lighthouse till a joining clearance has been obtained.

Helicopter traffic is to route via the Umgeni River. Establish communication with Virginia prior to crossing the N2. Cross the Inanda Dam wall at or below 2000 FT AMSL, cross the N2 national road at or below 1000 FT AMSL and Umgeni River Mouth at 500 FT AMSL.

Virginia to North Western KwaZulu/Natal and Gauteng Area:

All VFR traffic is to route via the Durban CBD, then west of the Pinetown CBD, then south of the N3, to the right of the Alvaston Mast, then via Greytown. Cross the Durban CBD at or below 1500 FT AMSL, but above 1000 FT AMSL, cross the N2 at or below 1500 FT AMSL to pass west abeam the Pinetown CBD at, or below, 3000 FT AMSL, to the right of the Alvaston Mast at or below 5000 FT AMSL. Remain clear of the Durban TMA.

Helicopter traffic to route via the Umgeni River to the Inanda Dam. Remain in communication with Virginia until crossing the N2. Cross the Umgeni River Mouth at 500 FT AMSL, cross the National Road, N2 at or below 1000 FT AMSL, cross the Inanda Dam wall at or below 2000 FT AMSL.

Northern KwaZulu/Natal to Virginia:

All VFR traffic to route via Blythedale Beach (cross Blythedale Beach below 2000 FT AMSL), then seawards of the coastline (cross Tinley Manor not above 500 FT AMSL), transiting the King Shaka CTR, seawards of the coastline, not above 500 FT AMSL. VFR traffic transiting through the King Shaka CTR are then deemed to be separated from departing and arriving traffic at King Shaka Airport. All transiting traffic is regarded as circuit traffic, thus reduced separation minima can be applied, in the vicinity of the aerodrome.

The clearance shall only be valid during daylight hours, in VMC operations, in communication with ATC and the aircraft shall be Mode C transponder equipped.

Pilots to comply with the Aviation Legislation, as described in General Operating and Flight Rules. Following line features as per CAR 91.06.08.

Virginia to Northern KwaZulu Natal:

All VFR traffic wishing to route seawards of the coastline, transiting the King Shaka CTR, are to remain seawards of the coastline, not above 500FT AMSL. VFR traffic transiting through the King Shaka CTR are then deemed to be separated from departing and arriving traffic at King Shaka Airport. All transiting traffic is regarded as circuit traffic, thus reduced separation minima can be applied, in the vicinity of the aerodrome.

The clearance shall only be valid during daylight hours, in VMC operations, in communication with ATC and the aircraft shall be Mode-C transponder equipped.

Pilots to comply with the Aviation Legislation, as described in General Operating and Flight Rules. Following line features as per CAR 91.06.08.

Pietermaritzburg to Virginia:

All VFR traffic must route to the right of the Alvaston Mast, (cross abeam the Alvaston Mast below 5000FT AMSL), then route direct to the Coopers Lighthouse. Cross abeam Pinetown CBD at or below 3000FT AMSL, cross the N2 at 1500FT AMSL. Establish communication with Virginia prior to crossing the N2. If no contact, enter into a VFR orbit, at 1500FT AMSL at Coopers Lighthouse till a joining clearance has been obtained.

Helicopter traffic is to route via the Umgeni River. Establish communication with Virginia prior to crossing the N2. Cross the Inanda Dam wall at or below 2000FT AMSL, cross the National Road, N2 at or below 1000FT AMSL and Umgeni River Mouth at 500FT AMSL.

Virginia to Pietermaritzburg:

All VFR traffic is to route via the Durban CBD, then west of the Pinetown CBD, then south of the N3, to the right of the Alvaston Mast, then via the Nagle Dam.

Cross the Durban CBD at or below 1500FT AMSL, but above 1000FT AMSL, cross the N2 at or below 1500FT AMSL to pass west abeam the Pinetown CBD at, or below, 3000FT AMSL, to the right of the Alvaston Mast at or below 5000FT. Remain clear of the Durban TMA.

Helicopter traffic to route via the Umgeni River to the Inanda Dam. Remain in communication with Virginia until crossing the N2. Cross the Umgeni River Mouth at 500FT AMSL, cross the N2 national road at or below 1000FT AMSL, cross the Inanda Dam wall at or below 2000FT AMSL.

Virginia to the South:

All VFR traffic to route via the Harbour entrance, then seawards of the coastline.

Cross the Harbour entrance at 1000FT AMSL. Passing Amanzimtoti, climb to requested level, remaining clear of the Durban TMA.

Passing Sezela, change frequency to 124.8MHz and broadcast.

From the South to Virginia:

All VFR traffic is to route seawards of the coastline, via the harbour entrance to Virginia.

Remain clear of the Durban TMA. Passing Sezela, change frequency to 124.2MHz and broadcast.

Cross Scottburgh at 1500FT AMSL. Establish communication with Virginia prior to passing abeam Coopers Lighthouse. If no contact, enter into a VFR orbit, at 1500FT AMSL at Coopers Lighthouse, until a joining clearance has been obtained.

Virginia to FAD56:

All VFR traffic to route direct to the FAD56 at 1500FT AMSL or above, but to remain clear of the Durban TMA.

Traffic without SSR from the North Sector to Virginia

All traffic to route via Ndwedwe, then to the right of the Alvaston Mast, (cross abeam the Alvaston Mast below 5000FT AMSL), then route direct to the Coopers Lighthouse. Cross abeam Pinetown CBD at or below 3000FT AMSL, cross the N2 at 1500FT AMSL. Establish communication with Virginia prior crossing the N2. If no contact, enter into a VFR orbit, at 1500FT AMSL at Coopers Lighthouse till a joining clearance has been obtained.

FAD 56 to Virginia:

Exit the FAD56 via Amanzimtoti, then seawards of the coastline at 1500FT AMSL. Establish communication with Virginia prior to passing abeam Coopers Lighthouse. If no contact, enter into a VFR orbit, at 1500FT AMSL, at Coopers Lighthouse, until a joining clearance has been obtained.

Virginia to and from FAD58:

Helicopter traffic is to route via the Umgeni River. Establish communication with Virginia prior to crossing the N2. Cross the Inanda Dam wall at or below 2000FT AMSL, cross the N2 national road at or below 1000FT AMSL and Umgeni River Mouth at 500FT AMSL.

Note: The area east of the N2 national road, North of Coopers Lighthouse, to the Virginia ATZ boundary, 2NM seawards of the coastline, is regarded as a high density helicopter and general aviation operating area. All VFR traffic entering this area must be in communication and remain on the Virginia frequency 120.6MHz.

VFR traffic is to avoid flying below 1000FT AGL in this area.

Northern KwaZulu/Natal to Margate:

Traffic is to route west of Midmar Dam, clear of the Pietermaritzburg TMA then to Umzimkulu for Margate.

Gauteng Area to Pietermaritzburg:

All traffic to route via the Albert Falls dam then to Pietermaritzburg.

From the West to Pietermaritzburg

All traffic to route via Sweetwaters then to Pietermaritzburg.

From the South-west to Pietermaritzburg:

All traffic to route via Richmond then to Pietermaritzburg.

Richards Bay Area to Pietermaritzburg:

All traffic to route via Nagel dam then to Pietermaritzburg.

1.7 KRUGER SPECIAL RULES AREA (SRA) AND VFR ROUTINGS IN THE SRA AND CTR

The airspace below the Kruger Mpumalanga TMA A, B, C, D, G and portion of F, excluding the airspace below the Kruger Mpumalanga TMA E and that part of the Kruger National Park FAR 78, between ground level and 2500FT ALT, which falls below the Kruger Mpumalanga TMA, is declared as a SRA and termed as the Kruger SRA.
The Kruger SRA shall be defined as follows:

a) From a point on the Kruger Mpumalanga TMA A boundary 250428.11S 0305751.91E clockwise along the arc of a circle, radius 20NM and centered at 252251.70S 0310640.05E to a point 252127.89S 0312841.76E on the Kruger Mpumalanga TMA A boundary.

b) Thence along a straight line to 252354.94S 0313414.96E on the Kruger Mpumalanga TMA A boundary.

c) Thence along a straight line to a point 253024.26S 0312101.29E on the Kruger Mpumalanga TMA A boundary.

d) Thence clockwise along the arc of a circle, radius 15NM and centered at 252251.70S 0310640.05E to a point 253735.50S 0310959.65E on the Kruger Mpumalanga TMA F boundary

e) Thence along a straight line to a point 255250.55S 0310837.81E on the Kruger Mpumalanga TMA F boundary.

f) Thence clockwise along the arc of a circle radius 30NM and centered at 252251.70S 0310640.05E to a point 252123.38S 0303335.50E on the Kruger Mpumalanga TMA D boundary.

g) Thence along a straight line to a point 252150.65S 0304330.71E on the Kruger Mpumalanga TMA B boundary.

h) Thence clockwise along the arc of a circle radius 21NM and centered at 252251.70S 0310640.05E to a point 250332.91S 0305725.57E on the Kruger Mpumalanga TMA B boundary.

i) Thence along a straight line back to the starting point at 250428.11S 0305751.91E on the Kruger Mpumalanga TMA A boundary.

This is to promote safety, efficiency and orderliness in the Kruger Special Rules Area.

All aircraft operating in the Kruger Special Rules Area should maintain a listening watch and broadcast regular position reports on frequency 130.35 MHz.

Pilots operating below the Kruger TMA should therefore ensure that they do not exceed the applicable altitude restriction as stipulated on SRA routings and also to remain below the Kruger TMA.

Pilots are encouraged to squawk 2000, Mode C, at all times.

The following routes will be applicable in the Kruger Special Rules Area:

Routes for VFR aircraft in the Kruger Special Rules Area:

From the North and North-West to Kruger

All VFR traffic is to route via Hazyview, cross Hazyview at 5000 FT ALT, then Da Gama Dam, cross Da Gama Dam at 5000FT ALT, then via White River, cross White River at 4500FT ALT, then to Kruger/Mpumalanga International Airport. All VFR traffic is to remain clear of the Kruger TMA. If no contact or no ATC clearance into the Kruger CTR has been obtained, hold north of White River at 4500FT ALT, till a joining clearance has been obtained.

From Kruger to the North and North-West

All VFR traffic is to route via the White River Sawmill at 4000FT ALT, then west of Legogote, at 4000FT ALT, then via Hazyview, cross Hazyview at 4500FT ALT.

From the North-North-East and North-West to Nelspruit

All VFR traffic is to route via Hazyview at 5000FT ALT, then via Da Gama Dam, cross Da Gama Dam at 5000FT ALT, then via the White River, cross White River at 5000FT ALT, then direct to Nelspruit Airport, cross the National Road (N4) maintaining 4500FT. All VFR traffic is to remain clear of the Kruger TMA/CTR.

From Nelspruit to the North, North-West and North-East

All VFR traffic is to route via the Mbombela stadium, at 4000FT ALT, then via White River Sawmill, at 4000FT ALT, then via Hazyview, cross Hazyview at 4500FT ALT. All VFR traffic is to remain clear of the Kruger TMA/CTR.

From the North-East to Kruger:

All VFR traffic is to route via Amor, at 4500FT ALT, then to FAKN. All VFR traffic is to remain clear of the Kruger TMA. If no contact or no ATC clearance into the Kruger CTR has been obtained, hold east of Amor at 4500FT ALT, till a joining clearance has been obtained.

From Kruger to the North-East

All VFR traffic is to route via Amor, cross Amor at 4000FT ALT, then set course and climb to cruising ALT/Level. All VFR traffic is to remain clear of the Kruger TMA.

From the East and South-East to Kruger

All VFR traffic is to route via the Gorge, at 4500FT ALT, then via the Stadium in Kanyamazane then via the Reservoir East of FAKN, cross the Reservoir East of FAKN at 4500FT ALT. All VFR traffic is to remain clear of the Kruger TMA. If no contact or no ATC clearance into the Kruger CTR has been obtained, hold east of the Gorge at 4500FT ALT, till a joining clearance has been obtained.

From Kruger to the East and South-East

All VFR traffic is to route via the Reservoir East of FAKN, cross the Reservoir East of FAKN at 4000FT ALT, then via the Stadium in Kanyamazane, then via the Gorge, at 4000FT ALT. Passing the Gorge set course and climb to ALT/Level as per flight plan.

From the East and South-East to Nelspruit

All VFR traffic is to route via the Gorge, at 4500FT ALT, then direct to Nelspruit, to remain south of the Regional Road (R104) and National Road (N4) at 4500FT ALT. All VFR traffic is to remain clear of the Kruger TMA. If no contact or no ATC clearance into the Kruger CTR has been obtained, hold east of the Gorge at 4500FT ALT, till a joining clearance has been obtained.

From Nelspruit to the East and South-East

All VFR traffic is to route south of the Regional Road (R104) and the National Road (N4), direct to the Gorge, at 4000FT ALT. Passing the Gorge set course and climb to ALT/Level as per flight plan. The clearance shall only be valid during daylight hours, in VMC operations and in communication with ATC. Special VFR clearance may be issued by ATC, to one aircraft at a time only.

From the West and South-West to Kruger

All VFR traffic is to route via Ngodwana, cross Ngodwana at 8000FT ALT, then direct to Mbombela stadium, then direct to Rockys Drift. Cross the TMA C boundary, at 7000FT ALT, cross TMA A boundary at 5000FT ALT, cross Mbombela stadium at 4500FT ALT. All VFR traffic is to remain clear of the Kruger TMA/CTR. If no contact or no ATC clearance into the Kruger CTR has been obtained, hold west of the Mbombela stadium, at 4500FT ALT, till a joining clearance has been obtained.

From Kruger to the West and South-West

All VFR traffic is to route via Rockys Drift or White River, cross Rockys Drift/White River at 3500FT ALT, then north of the National Road (N4), at 5000FT ALT direct to Elandsriver, cross TMA C at 7000FT ALT, cross Elandsriver below 8000FT ALT, then proceed to Ngodwana. Passing Ngodwana set course as per flight plan. All VFR traffic is to remain clear of the Kruger TMA/CTR.

From the West and South-West to Nelspruit

All VFR traffic is to route via Ngodwana, cross Ngodwana at 8000FT ALT, then direct to Nelspruit. Cross the TMA C boundary, at 7000FT ALT, cross TMA A boundary at 5000FT ALT, enter Nelspruit circuit at 4500FT ALT. All VFR traffic is to remain clear of the Kruger TMA.

From Nelspruit to the West and South-West

All VFR traffic is to route via the Mbombela stadium, at 4000FT ALT, then north of the National Road (N4), at 5000FT ALT direct to Elandsriver, cross TMA C at 7000FT ALT, cross Elandsriver below 8000FT ALT, then proceed to Ngodwana. Passing Ngodwana set course as per flight plan.

Transiting of Kruger CTR West to East

All VFR traffic is to route via Ngodwana, cross Ngodwana at 8000FT ALT, then direct to Mbombela stadium. Cross the TMA C boundary, at 7000FT ALT, cross TMA A boundary at 5000FT ALT, cross Mbombela stadium at 4000FT ALT, then direct to the Gorge. All VFR traffic transiting the Kruger CTR, are to remain south of the Regional Road (R104) and the National Road (N4), at 4000FT ALT. VFR traffic wishing to transit through the Kruger CTR must obtain an ATC clearance. If no contact or no ATC clearance into the Kruger CTR has been obtained, hold west of Mbombela Stadium at 4000FT ALT, till a joining clearance has been obtained.

The clearance shall only be valid during daylight hours, in VMC operations, in communication with ATC. Special VFR clearance may be issued by ATC, to one aircraft at a time only.

Transiting of the Kruger CTR East to West

All VFR traffic is to route via the Gorge, at 4500FT ALT, then to the Mbombela Stadium, remaining south of the Regional Road (R104) and the National Road (N4) at 4500FT ALT till passing Nelspruit Central Business District, then proceed to the Mbombela Stadium, then north of the National Road (N4), at 5000FT ALT, then direct to Elandsriver, cross TMA C at 7000FT ALT, cross Elandsriver below 8000FT ALT, then proceed to Ngodwana. Passing Ngodwana set course as per flight plan. All VFR traffic is to remain clear of the Kruger TMA/CTR. If no contact or no ATC clearance into the Kruger CTR has been obtained, hold east of the Gorge at 4500FT ALT, till a joining clearance has been obtained.

The clearance shall only be valid during daylight hours, in VMC operations and in communication with ATC.

Special VFR clearance may be issued by ATC, to one aircraft at a time only.

Note: All VFR traffic with destinations to airfields below the Kruger TMA and within the Kruger CTR are to comply with the above routings to the nearest point on the route and then to the destination.

Frequency: 130.35 MHz within the Special Rules Area.

1.7.1 VFR ROUTINGS WITHIN THE KRUGER CTR AND THE KRUGER SPECIAL RULES AREA (SRA)

Note: All proposed VFR routes will be for use by day and in VMC only.

Standard VFR Departure Routes, leaving the Kruger CTR

Departing RWY 23

Leaving the Kruger CTR to the West and South-West:

Rockys Drift 23 VFR Departure

After departure runway 23, maintain runway track to 3300FT ALT, then turn right track 320 degrees and climb to 3500FT ALT. At 3500FT ALT, set course and join the SRA VFR route. Report crossing the National Road R40.

Leaving the Kruger CTR to the North-West

Legogote 23 VFR Departure

After departure runway 23, maintain runway track to 3300FT ALT, then turn right track 320 degrees and climb 4000FT ALT. At 4000FT ALT, set course and join the SRA VFR route. Report passing west of Legogote. Remain clear of the Kruger CTR.

Leaving the Kruger CTR to the North East

Amor 23 VFR Departure

After departure runway 23, maintain runway track to 3300FT ALT, then turn left track 140 degrees and climb to 4000FT ALT. At 4000FT ALT turn left set course to Amor. Passing Amor, set course as per flight plan. Report passing Amor.

Leaving the Kruger CTR to the East and South-East

Kanyamazane 23 VFR Departure

After departure runway 23, maintain runway track to 3300FT ALT, then turn left track 140 degrees and climb to 4000FT ALT. At 4000FT ALT set course to Kanyamazane. Passing Kanyamazane, join the SRA VFR route. Report passing Kanyamazane.

Departing RWY 05

Leaving the Kruger CTR to the North-East

Amor 05 VFR Departure

After departure runway 05, maintain runway track to 3300FT ALT, then turn right track 140 degrees, and climb 4000FT ALT, at 4000FT ALT set course to route Amor. Passing Amor, set course as per flight plan. Report passing Amor.

Leaving the Kruger CTR to the South-West

White River 05 VFR Departure

After departure runway 05, maintain runway track to 3300FT ALT, then turn left track 320 degrees and climb to 3500FT ALT. At 3500FT ALT set course and join the SRA VFR route. Report passing White River.

Leaving the Kruger CTR to the North-West

Hazyview 05 VFR Departure

After departure runway 05, maintain runway track to 3300FT ALT, then turn left track 320 degrees and climb 4000FT ALT, at 4000FT ALT proceed west of Legogote and join the VFR route to Hazyview. Report passing abeam Legogote

Leaving the Kruger CTR to the South-East

Kanyamazane 05 VFR Departure

After departure runway 05, maintain runway track to 3300FT ALT, then turn right track 140 degrees and climb to 4000 FT ALT. At 4000FT ALT set course to Kanyamazane. Report passing Kanyamazane.

STANDARD VFR ARRIVAL ROUTES

VFR routes to Kruger Airport, entering the CTR from the West and South West

Rockys Drift 05 or 23 VFR Arrival

VFR aircraft, inbound to Kruger, from the west and south-west, are to remain below the Kruger TMA and route to Rockys Drift via SRA VFR routes 4500FT ALT. From Rockys Drift comply with ATC instructions to join the circuit.

VFR routes to Kruger Airport, entering the CTR from the North West

Hazyview 05 or 23 VFR Arrival

VFR aircraft, inbound to Kruger, from the North West, are to remain below the Kruger TMA and to route via White River. Cross White River at 4500FT ALT. From White River comply with ATC instructions to join the circuit.

VFR routes to Kruger Airport, entering the CTR from the East and South East

Kanyamazane 05 or 23 VFR Arrival Kanyamazane

VFR aircraft, inbound to Kruger, from the east and south east are to remain below the Kruger TMA and route to Kanyamazane via SRA VFR routes. From Kanyamazane, route via the Reservoir East of FAKN. Cross the Kanyamazane at 4500FT ALT. From Kanyamazane comply with ATC instructions to join the circuit.

VFR routes to Kruger Airport, entering the CTR from the North East

Amor 05 or 23 VFR Arrival

VFR aircraft, inbound to Kruger, from the north east, are to remain below the Kruger TMA and route to Amor at 4500FT ALT. From Amor comply with ATC instructions to join the circuit.

Radio failure procedures for VFR flights to and from Kruger into the SRA.

En-route to the Special Rules Area - continue on the Standard VFR departure till clear of the Kruger CTR. Thereafter proceed to FANS and land. After landing contact ATC via telephone.

In the Special Rules Area - remain clear of controlled airspace and proceed to FANS and land. After landing contact ATC via telephone.

Inbound (once cleared inbound by ATC) - continue on the cleared Standard VFR arrival route, join the circuit and position in traffic, land and vacate RWY ASAP.

SIGNIFICANT POINTS:

- Amor - 252135.06S 0311636.18E
- Elandsriver - 252951S 0304154E
- Da Gama Dam - 250901.42S 0310101.84E
- Gorge - 253121.80S 0311302.50E
- Hazyview - 250235.39S 0310742.38E
- Kanyamazane - 252750.60S 0311119.60E
- Legogote - 251419.49S 0310544.22E
- Mbombela stadium - 252738S 0305544E
- Ngodwana - 253438.84S 0303939.30E
- Reservoir East of FAKN - 252338.40S 0311015.10E
- Rockys Drift - 252241.34S 0305908.03E
- White River - 251911S 0305815E

– White River Sawmill - 251941S 0305836E

1.8 MALELANE SPECIAL RULES AREA

A portion of the airspace below the Kruger Mpumalanga TMA F extending eastwards towards the South African and Mozambique International Boundary and southwards along the Matsapha TMA boundary is declared as a Special Rules Area and will be known as the Malelane SRA.

The Malelane SRA shall be defined as follows:

a) From a point on the Kruger Mpumalanga TMA F Boundary at 253735.50S 0310959.65E anti-clockwise around the arc of a circle, radius 15NM and centered at 252251.70S 0310640.05E, to a point at 253024.26S 0312101.29E on the Kruger Mpumalanga TMA F boundary.

b) Thence along a straight line to a point 252354.94S 0313414.96E on the Kruger Mpumalanga TMA F boundary.

c) Thence along a straight line to a point 252616.06S 0313935.39E on the Kruger Mpumalanga TMA F Boundary.

d) Thence along a straight line to a point 252659.36S 0314115.17E on the FAR 78 boundary.

e) Thence along the FAR 78 boundary to a point 252900.00S 0314130.00E on the FAR 78 boundary.

f) Thence along the FAR 78 boundary to a point 252555.96S 0315923.09Eon the South African and Mozambique International Boundary.

g) Thence along the international boundary between South Africa and Mozambique to the following points:

252714.94S 0315858.05E
253033.15S 0315841.57E
253046.11S 0315847.28E
253055.11S 0315859.58E
253109.61S 0315955.62E
253605.81S 0320036.71E
253916.26S 0320024.62E
254120.46S 0315852.99E
255019.44S 0315607.53E

h) Thence along the International boundary between South Africa and Mozambique to a point 255700.89S 0315844.42E on the Eswatini, Mozambique and South African Boundary.

i) Thence along a straight line to a point 255125.37S 0313843.37E on the Matsapha TMA

j) Thence along a straight line to a point 254256.92S 0312529.96E on the Matsapha TMA Boundary.

k) Thence along a straight line to a point 254426.57S 0311851.81E on the Matsapha TMA Boundary.

l) Thence along a straight line to a point 254753.99S 0311607.68E on the Matsapha TMA Boundary.
m) Thence along a straight line to a point 255250.55S 0310837.81E on the Matsapha TMA Boundary.
n) Thence along a straight line to the starting point at 253735.50S 0310959.65E FAKN TMA F boundary.

RULES APPLICABLE WITHIN MALELANE SRA

1. Malelane SRA is established to promote safety, efficiency and orderly operations in the Lowveld areas of Malelane and surrounds as defined.
2. Avoid controlled airspace unless otherwise authorised by ATC.
3. All aircraft operating in the Malelane special rules area shall maintain a listening watch and broadcast regular position reports on frequency 129.35 Mhz.
4. All aircraft outbound from Malelane, must establish contact with FAKN TWR/APP on frequency 119.20 MHz, before airborne.
5. Pilots are requested to squawk transponder code #2000 at all times with altitude selected. Helicopters to squawk #2600 with altitude selected.
6. Pilots to observe SA CARs semi-circular rules and minimum heights requirements within the Malelane SRA.
7. Pilots to ensure to obtain joining clearances from adjacent ATSUs prior to entering respective controlled and information airspaces, i.e., FAKN TWR/APP, FDSK TWR/APP, LASS, and FQMA TWR/APP.
8. Pilots operating in the SRA should ensure that they do not exceed the applicable altitude restrictions as defined.

Vertical limits: GND – FL105
- **Frequency:** 129.35 MHz.

1.9 SABI-SANDS SPECIAL RULES AREA

The portion of airspace from the Kruger Mpumalanga TMA A Northern boundary including the airspace below Kruger Mpumalanga TMA E extending Northwards towards the Hoedspruit Military TMA Boundary, extending eastwards towards the Kruger National Park FAR 78 boundary is declared as a SRA and will be known as the Sabi-Sands SRA. The Sabi-Sands SRA shall be defined as follows:

a) From a point on the Kruger Mpumalanga TMA A boundary 250428.11S0305751.91E along a straight line to a point 250332.91S 0305725.57E on the Kruger Mpumalanga TMA B boundary.
b) Thence along a straight line to 244957.00S 0305434.00E on the Hoedspruit Military TMA Boundary.
c) Thence anti-clockwise along the arc of a circle, radius 30NM and centered at 242049.93S 0310251.39E to a point at 243120.65S 0313342.91E on the FAR 78 boundary.

d) Thence along a straight line to a point at 243600.00S 0313500.00E on the FAR 78 Boundary.
e) Thence along a straight line to a point at 252659.36S 0314115.17E on the FAR 78 Boundary.
f) Thence along a straight line to a point at 252127.89S 0312841.76E on the Kruger Mpumalanga TMA A Boundary.
g) Thence anti-clockwise along the arc of a circle, radius 20NM and centered at 252251.70S 0310640.05E back to the starting point at 250428.11S 0305751.91E on the Kruger Mpumalanga TMA A boundary.

RULES APPLICABLE WITHIN SABI-SANDS SRA

1) Sabi-Sands SRA is established to promote safety, efficiency and orderly operations within the Sabi-Sands and surrounding lowveld areas.
2) Avoid controlled airspace unless otherwise authorised by ATC (Air Traffic Control).
3) All aircraft operating in the Sabi-Sands SRA shall maintain a listening watch and broadcast regular position reports on frequency 128.35 MHz.
4) All outbound aircraft intending to climb above 6000FT ALT, must establish contact with LASS (Lowveld FIS) 119.0 MHz, preferably before airborne or at the latest before passing 5000FT ALT on the climb.
5) Pilots are requested to squawk transponder code #2000 at all times with altitude selected, Helicopters to squawk #2600 with altitude selected.
6) Pilots to observe semi-circular rules and minimum heights requirements of the South African CARs within the Sabi-Sands SRA.
7) Pilots to ensure to obtain joining clearances from adjacent ATSUs prior to entering respective controlled and information airspaces, i.e., FAKN TWR/APP, FAHS TWR/APP and LASS.
8) Pilots operating in the SRA should ensure that they do not exceed the applicable altitude restrictions as stipulated.
9) Pilots to ensure to comply with the National Enviromental Management: Protected Areas Act (NEMPAA) as applicable.

Vertical limits: GND – 6000FT ALT
Frequency: 128.35 MHz

1.10 HOEDSPRUIT SPECIAL RULES AREA

a) Aircraft operating below the Hoedspruit TMA must contact LASS on frequency 119.0 MHz.
b) The airspace below the Hoedspruit TMA, excluding controlled airspace, will be declared a Special Rules Area - HOEDSPRUIT SPECIAL RULES AREA.

1.10.1 Mandatory VFR/IFR Routings in the LASS Area between the Kruger and Hoedspruit TMA's

Mandatory VFR/IFR routings are implemented in the LASS airspace, between the Kruger and Hoedspruit TMA.

This is to promote safety, efficiency and orderliness in this part of the LASS airspace. All aircraft operating in this airspace shall maintain a listening watch and make regular position reports to LASS on frequency 119.0 MHz. Pilots shall squawk 2000, Mode C, at all times. The following routes will be applicable in the airspace described above.

1.10.2 Mandatory routes for VFR Aircraft in the airspace between the Kruger and Hoedspruit TMAs:

a) All traffic below 5500 FT ALT need not comply with the mandatory VFR routes around the Kruger TMA, as the Kruger TMA A lower ALT only commences from 5500 FT.

b) All traffic below 6000 FT ALT need not comply with the mandatory VFR routes around the Hoedspruit TMA, as the Hoedspruit TMA lower ALT only commences from 6000 FT.

c) The areas below the Kruger and Hoedspruit TMAs have been declared Special Rules Areas and aircraft must comply with these rules as published.

d) All VFR traffic, above 5500 FT ALT, routing east bound to destinations east of Lydenburg, are to route via Lydenburg or north of Lydenburg, to Graskop to Mkhuhlu then to destination

e) All VFR traffic west bound, with departure points east of Lydenburg, above 5500 FT ALT, to route via Mkhuhlu, then to Graskop, then to Lydenburg or north of Lydenburg.

All traffic transiting this area, must be in contact with Lowveld or broadcast on the appropriate frequency, outside of the hours of duty of LASS.

1.10.3 Mandatory routes for IFR Aircraft in the airspace between the Kruger and Hoedspruit TMAs:

a) IFR traffic, eastbound, with destinations east of Lydenburg are to route via UNPAX (245054.86S 0310345.22E), before setting course to destination, unless otherwise instructed by Lowveld Information.

b) IFR traffic, westbound, with departure points east of a straight line between VOR HSV and PKV, are to route via UMVET (245555.67S 0310354.18E), unless otherwise instructed by Lowveld Information, before setting course to next fix or destination.

– Lydenburg: 250445.00S 0302532.00E
– Graskop: 245557.94S 0305038.97E
– Mkhuhlu: 245911.69S E311418.10E

1.11 MANDATORY VFR ROUTING FOR UPINGTON AERODROME

Flights from the West of FAUP

Unless otherwise cleared, flights approaching from destinations North or West of point 1 (280958.00S 0211006.00E) and South or West of Point 2 (283820.00S 0212113.00E) to route via UTSOS for downwind for the active runway.

Departing Upington to destinations North or West of point 1 (280958.00S 0211006.00E) and South or West of Point 2 (283820.00S 0212113.00E) to route via UTSOS after departure.

Flights from the East of FAUP

Unless otherwise cleared flights approaching from destinations East of point 1 (280958.00S 0211006.00E) and East of Point 2 (283820.00S 0212113.00E) to route via UVDIK for downwind for the active runway.

Departing Upington to destinations East of point 1 (280958.00S 0211006.00E) and East of Point 2 (283820.00S 0212113.00E) to route via UVDIK after take-off.

VFR Reporting Points

- UTSOS – 282858.00S 0205932.00E
- UVDIK – 281913.00S 0213142.00E

2 CAPE TOWN FIR

2.1 SPECIAL RULES AIRSPACE EAST LONDON

The airspace below the East London TMA, excluding that part of the Port Alfred General Flying Area (FAD192), which falls below the East London TMA, is declared as a Special Rules Area and termed as the EAST LONDON SPECIAL RULES AREA.

This is to promote safety, efficiency and orderliness in the East London Special Rules Area.

All aircraft operating in the East London Special Rules Area should maintain a listening watch and broadcast regular position reports on FREQ 125.2 MHz.

By virtue of the fact that uncontrolled VFR aircraft are to remain below the East London TMA radar separations and information provided to aircraft operating within the East London TMA, will only take known identified targets into account.

For the information of those aircraft operating within the East London TMA, unidentified unknown targets, performing as expected for general aviation within the confines of the East London Special Rules Area will be deemed to be separated from aircraft operating within the East London TMA, by procedures as opposed to radar.

Pilots operating below the East London TMA should therefore ensure that they do not exceed the applicable altitude restriction as stipulated on SRA routings and also to remain at least 500FT below the TMA whilst flying below the East London TMA.

Pilots are encouraged to squawk 2000 at all times.

The following routes will be applicable in the East London Special Rules Area:

Routes for VFR Aircraft in the East London Special Rules Area

From the North to King Phalo

All VFR traffic is to route via the Nahoon Dam, cross Nahoon Dam at 2000 FT AMSL. All VFR traffic is to remain clear of the East London TMA. If no contact or no ATC clearance into the King Phalo CTR has been obtained, hold north of the Nahoon Dam, at 2000 FT AMSL, till a joining clearance has been obtained.

From the North-East to King Phalo

All VFR traffic is to route east of the National Road (N2), at 2000 FT AMSL, via Gonubie, then seawards of the coastline. All VFR traffic is to remain clear of the East London TMA. If no contact or no ATC clearance into the King Phalo CTR has been obtained, hold east of Gonubie, at 2000 FT AMSL, till a joining clearance has been obtained. Pilots to comply with the Aviation Legislation, as described in General Operating and Flight Rules. Following line features as per CAR 91.06.08.

From the East to King Phalo

All VFR traffic is to route via Cinsta, then Gonubie, remain seawards of the coastline at 1500 FT ALT. All VFR traffic is to remain clear of the East London TMA. If no contact or no ATC clearance into the King Phalo CTR has been obtained, hold east of Gonubie at 1500 FT AMSL, till a joining clearance has been obtained.Pilots to comply with the Aviation Legislation, as described in General Operating and Flight Rules. Following line features as per CAR 91.06.08.

From the West to King Phalo

All VFR traffic is to route via Peddie, cross Peddie at 4000 FT AMSL, then Laing Dam, at 2000 FT AMSL, then the Nahoon Dam, at 2000 FT AMSL. All VFR traffic is to remain clear of the East London TMA and King Phalo CTR. If no contact or no ATC clearance into the King Phalo CTR has been obtained, hold west of the Laing Dam, at 2000 FT AMSL, till a joining clearance has been obtained.

From the South-West of King Phalo

All VFR traffic is to route seawards of the coastline via Hamburg, then Kaysers Beach, at 1500 FT AMSL. All VFR traffic is to remain clear of the East London TMA and King Phalo CTR. If no contact or no ATC clearance into the King Phalo CTR has been obtained, hold west of Kaysers Beach, at 1500 FT AMSL, till a joining clearance has been obtained.Pilots to comply with the Aviation Legislation, as described in General Operating and Flight Rules. Following line features as per CAR 91.06.08.

Transiting of King Phalo CTR South-West to North-East

All VFR traffic is to route seawards of the coastline, transiting the King Phalo CTR, are to remain seawards of the coastline, at 1500 FT AMSL. VFR traffic wishing to transit through the King Phalo CTR must obtain an ATC clearance. If no contact or no ATC clearance into the King Phalo CTR has been obtained, hold west of Kaysers Beach, at 1500 FT AMSL, till a joining clearance has been obtained.

The clearance shall only be valid during daylight hours, in VMC operations, in communication with ATC and the aircraft shall be Mode-C transponder equipped.

Pilots to comply with the Aviation Legislation, as described in General Operating and Flight Rules. Following line features as per CAR 91.06.08.

Transiting of the King Phalo CTR North-East to South-West

All VFR traffic is to route seawards of the coastline, transiting the King Phalo CTR, are to remain seawards of the coastline, at 1000 FT AMSL. VFR traffic wishing to transit through the King Phalo CTR must obtain an ATC clearance. If no contact or no ATC clearance into the King Phalo CTR has been obtained, hold east of Gonubie, at 1000 FT AMSL, till a joining clearance has been obtained.

The clearance shall only be valid during daylight hours, in VMC operations, in communication with ATC and the aircraft shall be Mode C transponder equipped. Pilots to comply with the Aviation Legislation, as described in General Operating and Flight Rules. Following line features as per CAR 91.06.08.

Transiting of the East London SRA West to East

All VFR traffic is to route via Peddie, cross Peddie at 4000 FT AMSL, north of the Laing Dam, at 2000 FT AMSL, north of the Nahoon Dam, at 2000 FT AMSL, then via Cintsa at 4000 FT AMSL. All VFR traffic is to remain clear of the East London TMA and King Phalo CTR.

Transiting of the East London SRA West to East

All VFR traffic is to route via Cinsta at 2500 FT AMSL, north of the Nahoon Dam at 2000 FT AMSL, north of the Laing Dam at 2000 FT AMSL, then Peddie at 4000 FT AMSL. All VFR traffic is to remain clear of the East London TMA and King Phalo CTR.
Frequency: 125.200 MHz within the Special Rules Area.

2.2 VFR Routings within the King Phalo CTR and Special Rules Area.

VFR Routes:

Note: All proposed VFR routes will be for use by day and in VMC only.

Standard VFR Departure Routes, leaving the King Phalo CTR

Departing RWY 29

Leaving the King Phalo CTR to the West

KEYSERS BEACH 29 VFR Departure

After departure runway 29, maintain runway track to 1000 FT ALT, then turn left track 200 degrees, passing the coastline, set course for Keyser Beach and maintain 1000FT ALT. At Keyser beach follow the coastline to intercept the SRA VFR route. Report passing Keyser Beach.

Leaving the King Phalo CTR to the East

GONUBIE 29 VFR Departure

After departure runway 29, maintain runway track to 1000 FT ALT, then turn left track 200 degrees passing the coastline, set course for Gonubie, and maintain 1000 FT ALT. At Gonubie intercept the SRA VFR route. Report passing Gonubie.

Leaving the King Phalo CTR to the North West

NAHOON DAM 29 VFR Departure

After departure runway 29, maintain runway track to 1000 FT ALT, then turn right track 020 degrees and climb to 1500 FT ALT. At 1500 FT ALT set course to Nahoon Dam. Passing Nahoon Dam Bay, join the SRA VFR route. Report passing Nahoon Dam.

Leaving the King Phalo CTR to the North East

GOODSHEDS 29 VFR Departure

After departure runway 29, maintain runway track to 1000FT ALT, then turn right track 020 degrees, and climb 1500 FT ALT. At 1500 FT ALT, set course to Nahoon Dam. Crossing the National Road (N2), set course, remaining north of the N2. Report passing abeam Gonubie.

Departing RWY 11

Leaving the King Phalo CTR to the North East

GOODSHEDS 11 VFR Departure

After departure runway 11, maintain runway track to 1000 FT ALT, then turn left track 020 degrees, and climb 1500 FT ALT. Crossing the National Road (N2), set course, remaining north of the N2. Report passing abeam Gonubie.

Leaving the King Phalo CTR to the West

KEYSERS BEACH 11 VFR Departure

After departure runway 11, maintain runway track to 1000 FT ALT, then turn right track 200 degrees and climb to 1000 FT ALT. Crossing the coast line at 1000FT ALT set course for Keyser Beach and maintain 1000 FT ALT. At Keyser beach follow the coastline to intercept the SRA VFR route at Keyser Beach. Report passing Keyser Beach.

Leaving the King Phalo CTR to the East

GONUBIE 11 VFR Departure

After departure runway 11, maintain runway track to 1000 FT ALT, then proceed seawards of the coastline to Gonubie, and maintain 1000 FT ALT. At Gonubie, follow the coastline to intercept the SRA VFR route. Report passing Gonubie.

Leaving the King Phalo CTR to the North West

NAHOON DAM 11 VFR Departure

After departure runway 11, maintain runway track to 1000 FT ALT, then turn left track 020 degrees and climb to 1500 FT ALT. At 1500 FT ALT set course to Nahoon Dam. Passing Nahoon Dam Bay, join the SRA VFR route. Report passing Nahoon Dam.

2.2.1 STANDARD VFR ARRIVAL ROUTES - KING PHALO

VFR routes to King Phalo Airport, entering the CTR from the West:

Hamburg 11 or 29 VFR Arrival

VFR aircraft, inbound to King Phalo, from the west, are to remain below the East London TMA and route to Hamburg, to join the SRA VFR route. Passing Hamburg, follow the coast line feature to Kaysers Beach at 1000 FT ALT. From Kaysers Beach comply with ATC instructions to join the circuit.

VFR routes to King Phalo Airport, entering the CTR from the North and North West

Nahoon Dam 11 or 29 VFR Arrival

VFR aircraft, inbound to King Phalo, from the North West, are to remain below the East London TMA and to route via the SRA VFR route to Nahoon Dam at 1500 FT ALT. From Nahoon Dam comply with ATC instructions to join the circuit.

VFR routes to King Phalo Airport, entering the CTR from the East and North-East:

Gonubie 11 or 29 VFR Arrival

VFR aircraft inbound to King Phalo, from the east and North-East are to remain below the East London TMA and route to Gonubie via SRA VFR routes. From Gonubie, follow the coastline feature at 1500 FT ALT. From Gonubie comply with ATC instructions to join the circuit.

Transiting, seawards of the coastline through the King Phalo CTR

All VFR traffic wishing to route seawards of the coastline, through the King Phalo CTR, are to remain seawards of the coastline, not above 1000 FT ALT, subject to ATC instructions.

All transiting traffic is regarded as circuit traffic, thus reduced separation minima, in the vicinity of the aerodrome.The clearance shall only be valid during daylight hours, in VMC operations, in communication with ATC and the aircraft shall be transponder equipped.Pilots to comply with the Aviation Legislation, as described in General Operating and Flight Rules, Following line features Regulation 91.06.08.

Radio failure procedures for circuit training and for training flights to / from the Special Rules Area

In Circuit:

Remain in circuit and position in traffic, land and vacate RWY in use ASAP. After landing contact ATC via telephone.

Flights to / from the SRA

En-route to the Special Rules Area - continue on the Standard VFR departure till clear of the King Phalo CTR. Thereafter proceed to a suitable airfield and land. After landing contact ATC via telephone.

In the Special Rules Area - remain clear of controlled airspace; proceed to a suitable airfield and land. After landing contact ATC via telephone.

Inbound (once cleared inbound by ATC) - continue on the cleared Standard VFR arrival route, join the circuit and position in traffic, land and vacate RWY ASAP. After landing contact ATC via telephone.

The areas defined as follows have been identified for all general and training flying:

Hamburg Area from a point at:

332100S 0272100E

331700S 0272800E

331000S 0272300E

331600S 0271800E

Cintsa Area from a point at:

325000S 0280700E

324600S 0281500E

323900S 0281200E

324300S 0280400E

SIGNIFICANT POINTS:

BRIDLE DRIFT DAM	325900S 0274500E
CINTSA	325000S 0280700E
GONUBIE	325700S 0280100E
GOODSHEDS	325757S 0275315E
KEYSERS BEACH	331243S 0273630E
LAING DAM	325700S 0273000E
NAHOON DAM	325500S 0274800E
WESLEY	331940S 0271900E

Frequency: 125.200 MHz within the Special Rules Area:

2.3 PORT ELIZABETH SPECIAL RULES AREA

The airspace below the Port Elizabeth TMA, excluding FAD193, will be declared as a Special Rules Area and termed as the "PORT ELIZABETH SPECIAL RULES AREA".

To prevent frequency congestion and to promote safety, efficiency and orderliness in the Port Elizabeth Special Rules Area, a dedicated frequency of 130.350 MHz, for Traffic Information Broadcast by Aircraft (TIBA) has been issued.

All aircraft operating in the Port Elizabeth Special Rules Areas shall maintain a listening watch and broadcast regular position reports on frequency 130.350 MHz.

The Chief Dawid Stuurman CTR is excluded from the Port Elizabeth Special Rules Area.

By virtue of the fact that uncontrolled VFR aircraft are to remain below the Port Elizabeth TMA radar separations and information provided to aircraft operating within the Port Elizabeth TMA, will only take known identified targets into account.

For the information of those aircraft operating within the Port Elizabeth TMA, unidentified unknown targets, performing as expected for general aviation within the confines of the Port Elizabeth Special Rules Area, will be deemed to be separated from aircraft operating within the Port Elizabeth TMA, by procedures as opposed to radar.

Pilots operating below the Port Elizabeth TMA should therefore ensure that they do not exceed the applicable altitude restriction as stipulated on Special Rules Area routings and also to remain at least 500 FT below the TMA whilst flying below the Port Elizabeth TMA.

Pilots are requested to squawk transponder code 2000 at all times with altitude selected. Helicopters to squawk 2600 also with altitude selected.

2.3.1 The following routes will be applicable in the Port Elizabeth Special Rules Area:

From the North:

All VFR traffic, from points of departures north of Chief Dawid Stuurman are to route via Addo, then to Coega River mouth, then to Swartkops River mouth (landside of the coast), then to Chief Dawid Stuurman.

VFR traffic is to cross Addo at or below 2000 FT ALT, Coega River mouth at or below 1500 FT ALT and Swartkops River mouth at 1500 FT ALT. VFR traffic to remain clear of the Port Elizabeth TMA. VFR traffic to contact FAPE APP, on 120.4 MHz, at Addo. If no contact or no ATC clearance into the Chief Dawid Stuurman CTR has been obtained from FAPE APP hold clear of the Chief Dawid Stuurman CTR, till a joining clearance has been obtained.

From Chief Dawid Stuurman to the North:

All VFR traffic, departing Chief Dawid Stuurman and with destinations north of Chief Dawid Stuurman, are to route either via Swartkops River mouth, Coega River mouth then to Addo or, runway dependent, Salt Lake, then to Addo before setting course.

Traffic is to cross Swartkops River mouth or Salt Lake at 1500 FT ALT, Coega River mouth at or below 1500 FT ALT, Addo at or below 2000 FT ALT. VFR traffic to report passing Swartkops River mouth or Salt Lake. VFR traffic wishing to route on an alternate route from Chief Dawid Stuurman, must obtain permission from ATC. VFR traffic to remain clear of the Port Elizabeth TMA.

From the North East:

All VFR traffic, with points of departure north east of Chief Dawid Stuurman, are to route via Nanaga, then to Coega River Mouth, then to the Swartkops River Mouth (landside of the coast), then to Chief Dawid Stuurman.

Traffic is to cross Nanaga at or below 2000 FT ALT, Coega River Mouth at or below 1500 FT ALT, Swartkops River Mouth at 1500 FT ALT. VFR traffic to remain clear of the Port Elizabeth TMA. VFR traffic to contact FAPE APP, on 120.4 MHz, at Nanaga. If no contact or no ATC clearance into the Chief Dawid Stuurman CTR has been obtained from FAPE APP, hold clear of the Chief Dawid Stuurman CTR, till a joining clearance has been obtained.

From Chief Dawid Stuurman to the North East:

All VFR traffic, departing Chief Dawid Stuurman and with destinations north east of Chief Dawid Stuurman, are to route either via Swartkops River mouth or Salt Lake, runway dependent, then seawards of the coast to the Coega River Mouth, then to Nanaga, before setting course. Traffic is to cross Swartkops River Mouth at 1500 FT ALT, Nanaga at or below 2000 FT ALT. VFR traffic to report passing Swartkops River mouth or Salt Lake. VFR traffic to remain clear of the Port Elizabeth TMA.

From the West to Chief Dawid Stuurman:

All VFR traffic, with points of departure west of Chief Dawid Stuurman, are to route via Gamtoos River Mouth, then to the Maitland River Mouth, then along the Kragga Kamma Road to Chief Dawid Stuurman.

Traffic is to cross Gamtoos River Mouth and Maitland River Mouth at or below 1500 FT. VFR traffic to remain clear of the Port Elizabeth TMA. VFR traffic to contact FAPE APP, on 120.4 MHz, at Gamtoos River Mouth. If no contact or no ATC clearance into the Chief Dawid Stuurman CTR has been obtained from FAPE APP, hold clear of the Chief Dawid Stuurman CTR, till a joining clearance has been obtained.

Note: Traffic must broadcast on 122.7 MHz passing the Progress circuit.

From Chief Dawid Stuurman to the West:

All VFR traffic, departing Chief Dawid Stuurman, and with destinations west of Chief Dawid Stuurman, are to route towards the Greenbushes Mast and follow the Kragga Kamma Road to the Maitland River Mouth, then to the Gamtoos River Mouth, before setting course. Traffic is to cross Maitland River Mouth and Gamtoos River Mouth at or below 1500 FT ALT. VFR traffic to report passing abeam Seaview. VFR traffic to remain clear of the Port Elizabeth TMA.

Note: Traffic must broadcast on 122.7 MHz passing the Progress circuit.

From the East to Chief Dawid Stuurman:

All VFR traffic, with points of departure east of Chief Dawid Stuurman, are to route abeam of Bird Island, then coastwise to the Sundays River Mouth, then to the Coega River mouth, then to the Swartkops River mouth (landside of the coast), then to Chief Dawid Stuurman.

Traffic is to cross abeam Bird Island at or below 6000 FT ALT, Sundays River Mouth at or below 1500 FT ALT, Coega River mouth at or below 1500 FT ALT, Swartkops River Mouth at 1500 FT ALT. VFR traffic to remain clear of the Port Elizabeth TMA. VFR traffic to contact FAPE APP, on 120.4 MHz, at Bird Island. If no contact or no ATC clearance into the Chief Dawid Stuurman CTR has been obtained, from FAPE APP, hold clear of the Chief Dawid Stuurman CTR, till a joining clearance has been obtained.

From Chief Dawid Stuurman to the East:

All VFR traffic, departing Chief Dawid Stuurman and with destinations east of Chief Dawid Stuurman, are to route either via Swartkops River mouth or Salt Lake, runway dependent, then seawards of the coast to the Coega River mouth, then to the Sundays River Mouth, then to abeam Bird Island, before setting course.

Traffic is to cross the Swartkops River Mouth at or below 1500 FT ALT, cross Coega River mouth at or below 1500 FT ALT, cross the Sundays River Mouth at or below 1500 FT ALT, cross abeam Bird Island at or below 6000 FT ALT. VFR traffic to report passing Swartkops River mouth or Salt Lake. VFR traffic to remain clear of the Port Elizabeth TMA.

From the General Flying Area:

Ready to return from the General Flying Area, VFR traffic to contact FAPE APP, on 120.4 MHz, overhead the Volkswagen factory, and comply with the Kash 26 or Kash 08 arrival, runway dependent. Traffic must then change frequency to the Special Rules Area frequency 130.350 MHz and broadcast.

VFR traffic is to cross SANTA or Salt Lake at or below 2000 FT ALT. VFR traffic to remain clear of the Port Elizabeth TMA. If no contact or no ATC clearance into the Chief Dawid Stuurman CTR has been obtained, from FAPE APP on 120.4 MHz, remain clear of the Chief Dawid Stuurman CTR, until a joining clearance has been obtained.

From Chief Dawid Stuurman to the General Flying Area:

All VFR traffic, departing Chief Dawid Stuurman to the General Flying Area, are to route either via SANTA or Salt Lake, runway dependent, then to the General Flying Area entry point.

Traffic is to cross SANTA or Salt Lake at 1500 FT ALT, remain at or below 1500 FT ALT till entering the General Flying Area. VFR traffic to broadcast on Special Rules Area frequency 130.350 MHz passing SANTA or Salt Lake. At KwaNobuhle change to General Flying Area frequency 124.2 MHz and broadcast. VFR traffic wishing to route on an alternate route from Chief Dawid Stuurman, must obtain permission from ATC. VFR traffic to remain clear of the Port Elizabeth TMA.

Crossing from West to East:

All VFR traffic, with departure points west of Chief Dawid Stuurman and transiting the Special Rules Area, are to route Gamtoos River Mouth, then to Van Stadens River bridge, then to Despatch, then to Sundays River Mouth or Nanaga before setting course. Traffic is to cross Gamtoos River Mouth at or below 1500 FT ALT, to cross Van Stadens River Mouth at or below 1500 FT ALT, cross Despatch at or below 1500 FT ALT, cross Sundays River Mouth at or below 1500 FT ALT, then to abeam Bird Island, at or below 6000 FT ALT or Nanaga at or below 2000 FT ALT. VFR traffic to remain clear of the Port Elizabeth TMA and the Progress Airfield and broadcast on Special Rules Area frequency 130.350 MHz

Note: Traffic must broadcast on 122.7 MHz passing the Progress circuit.

Crossing from East to West:

All VFR traffic, with departure points north east and east of Chief Dawid Stuurman and transiting the Special Rules Area, to route via Nanaga or abeam Bird Island, then to the Sundays River Mouth, then to Despatch, then to Van Stadens River bridge, then to the Gamtoos River Mouth, before setting course. Traffic is to cross Nanaga at or below 2000 FT ALT or abeam Bird Island at or below 6000 FT ALT, cross Sundays River Mouth at or below 1500 FT ALT, cross Despatch at or below 1500FT ALT, cross Van Stadens River bridge at or below 1500 FT ALT, cross the Gamtoos River Mouth at or below 1500 FT ALT before setting course. VFR traffic to remain clear of the Port Elizabeth TMA and the Progress Airfield and broadcast on Special Rules Area frequency 130.350 MHz.

Note: Traffic must broadcast on 122.7 MHz passing the Progress circuit.

2.3.2 VFR ROUTINGS WITHIN THE CHIEF DAWID STUURMAN CTR AND THE PORT ELIZABETH SPECIAL RULES AREA (SRA)

Note: All proposed VFR routes will be for use by day and in VMC only.

Standard VFR Departure Routes, leaving the Chief Dawid Stuurman CTR:

DEPARTING RWY 26:

Leaving the Chief Dawid Stuurman CTR to the General Flying Area, North-West, North, North East and East:

ALBAN 26 VFR Departure

After departure runway 26, maintain runway track to 1000 FT ALT, then turn right on track 350 degrees and climb to 1500 FT ALT. At 1500 FT ALT, set course for Salt Lake and maintain 1500 FT ALT. At Salt Lake, traffic with destinations in the north-east and east to proceed to the Coega River Mouth, seawards of the coast, to intercept the Special Rules Area VFR route. Traffic to the north area to route via Addo. Traffic destined for the General Flying Area to proceed to the General Flying Area entry point.

Leaving the Chief Dawid Stuurman CTR to the West:

GREENBUSHES 26 VFR Departure

After departure runway 26, maintain runway track to 1000 FT ALT, then turn right track 350 degrees and climb 1500 FT ALT, At 1500 FT ALT proceed direct to Greenbushes Mast. At Kragga Kamma Road set course (left turn) for Maitland River Mouth, routing south of the N2. Report passing abeam Seaview.

DEPARTING RWY 08:

Leaving the Chief Dawid Stuurman CTR to the North-West, North, North East, East and West:

COEGA 08 VFR Departure

After departure runway 08, maintain runway track to 1000FT ALT, then turn left to route seawards of the coast to Swartkops River mouth and climb 1500FT ALT. At Swartkops River mouth set course to Coega River Mouth, remaining seawards of the coast to join the Special Rules Area VFR route for destinations in the North-East and East.

Leaving the Chief Dawid Stuurman CTR to the General Flying Area:

SANTA 08 VFR Departure

After departure runway 08, maintain runway track to 1000 FT ALT, then turn left track 350 degrees and climb to 1500 FT ALT. At 1500 FT ALT, set course for SANTA and maintain 1500 FT ALT. At SANTA route to the General Flying Area entry point.

Leaving the Chief Dawid Stuurman CTR to the West:

GREENBUSHES 08 VFR Departure

After departure runway 08, maintain runway track to 1000FT ALT, then turn left, track 350 degrees and climb 1500 FT ALT, At 1500 FT ALT proceed direct to Greenbushes Mast, at Kragga Kamma Road set course (left turn) for Maitland River Mouth, routing south of the N2 road. Report passing abeam Seaview.

STANDARD VFR ARRIVAL ROUTES:

VFR routes to Chief Dawid Stuurman Airport, entering the CTR from the General Flying Area:

Kash 26 VFR Arrival (Runway 26 in use)

VFR aircraft, inbound to Chief Dawid Stuurman from the General Flying Area, are to remain below the Port Elizabeth TMA and route to SANTA at or below 1500 FT ALT. At SANTA contact FAPE TWR on 118.1 MHz. From SANTA comply with ATC instructions to join the circuit.

Kash 08 VFR Arrival (Runway 08 in use)

VFR aircraft, inbound to Chief Dawid Stuurman from the General Flying Area, are to remain below the Port Elizabeth TMA and route to Salt Lake at or below 1500 FT ALT. At Salt Lake contact FAPE TWR on 118.1 MHz. From Salt Lake comply with ATC instructions to join the circuit.

VFR routes to Chief Dawid Stuurman Airport, entering the CTR from the North, North-East and East:

Spies VFR Arrival

VFR aircraft, inbound to Chief Dawid Stuurman, from the north, north-east and east, are to remain below the Port Elizabeth TMA and route to Swartkops River Mouth via Special Rules Area VFR routes. At Swartkops River mouth contact FAPE TWR on 118.1 MHz. From Swartkops River mouth comply with ATC instructions to join the circuit.

Parsons VFR Arrival

VFR aircraft, inbound to Chief Dawid Stuurman from the west, are to remain below the Port Elizabeth TMA and route towards the Greenbushes Mast via Special Rules Area VFR routes. At Seaview contact FAPE TWR on 118.1 MHz. From Seaview comply with ATC instructions to join the circuit.

Radio failure procedures for circuit training and for training flights to / from the Special Rules Area BY DAY

In Circuit: Remain in circuit and position in traffic, land and vacate RWY in use as soon as possible. After landing contact ATC via telephone.

Flights to / from the Special Rules Area:

En-route to the Special Rules Area - continue on the Standard VFR departure until clear of the Chief Dawid Stuurman CTR. Thereafter set course to destination or to Uitenhage and land. After landing contact ATC via telephone. Do not return to Chief Dawid Stuurman.

In the Special Rules Area - remain clear of controlled airspace, proceed to Uitenhage and land. After landing contact ATC via telephone. Do not proceed to Chief Dawid Stuurman.

Inbound (once cleared inbound by ATC) - continue on the cleared Standard VFR arrival route, join the circuit and position in traffic, land and vacate RWY as soon as possible. After landing contact ATC via telephone.

Radio failure procedures for circuit training and for training flights to / from the Special Rules Area BY NIGHT

In Circuit: Remain in circuit and position in traffic, land and vacate RWY in use as soon as possible. After landing contact ATC via telephone.

Flights to / from the Special Rules Area:

En-route to the Special Rules Area - continue on the Standard VFR departure until clear of the Chief Dawid Stuurman CTR. Thereafter squawk 7600, climb to 2000 FT ALT, route back to overhead the airfield, join the circuit and position in traffic, land and vacate RWY as soon as possible. After landing contact ATC by telephone.

Traffic inbound with a RCF, squawk 7600, climb to 2000 FT ALT, route overhead the airfield, join the circuit and position in traffic, land and vacate RWY in use as soon as possible. After landing contact ATC via telephone.

SIGNIFICANT POINTS:

Addo 333151S 0253726E

Bird Island 335045S 0261700E

Coega 334600S 0253900E

Despatch 334800S 0252800E

Gamtoos River Mouth 335720S 0250100E

Greenbushes Mast 335610.32S 0252627.96E

KwaNobuhle 335100S 0252800E

Nanaga 333620S 0255540E

Salt Lake 335300S 0253300E

SANTA 335342S 0252820E

Sundays River Mouth 334309S 0255104E

Swartkops River Mouth 335157S 0253803E

Van Stadens River Bridge 335433S 0251150E

Maitland River Mouth 335918S 0251741E

Kragga Kamma Road 335810S 0252928E

(Railway crosses the road).

2.4 CAPE TOWN SPECIAL RULES AREA

The airspace below the Cape Town TMA is declared as a Special Rules Area and will be known as the CAPE TOWN SPECIAL RULES AREA. Aircraft operating in the western sector shall operate on frequency 125.8 MHz, in the eastern sector on 124.8 MHz and in the northern sector on 126.8 MHz. Aircraft operating within the special rules area below FACT TMA A must not exceed 2000 FT ALT.

The Special Rules Area shall comprise of three sectors divided as follows:

1) all the airspace below the Cape Town TMA east of a straight line starting from a point 330926S 0182252E to a point 335810.82S 0183618.19E and terminating at a point 344652S 0185000E excluding the Cape Town SRA north area, shall be known as the eastern sector of the Cape Town special rules area.

2) All the airspace below the Cape Town TMA west of a straight line starting from a point 330926S 0182252E to a point 335810.82S 0183618.19E and terminating at a point 344652S 0185000E excluding the Cape Town SRA north area, shall be known as the western sector of the Cape Town special rules area.

3) Northern SRA Sector:

a) From a point 334721.49S 0183840.59E on the FACT CTR boundary Northwards along Adderley Road to a point at 334437.84S 0183814.29E
b) Thence continuing northwards along the Adderley Road to the T-junction with Philadelphia Road at 334123.40S 0183818.54E
c) Thence Westwards along the Philadelphia Road to a point at 334042.96S 0183614.96E on the Philadelphia Road and Old Malmesbury Road intersection.
d) Thence South Westwards along the Old Malmesbury Road to a point at 334237.18S 0183457.98E at the Old Malmesbury Road, Botterberg Road and Van Schoorsdrift Road intersection.
e) Thence South Westwards along the Van Schoorsdrift Road to the Havana Hills entrance along the Van Schoorsdrift Road at 334321.77S 0183411.09E.
f) Thence along a straight line to a point at 334332.56S 0183413.25E.

g) Thence west along a straight line to the N7/M19 (Melkbosstrand Road) interchange at 334331.44S 0183239.93E.
h) Thence west along the M19 (Melkbosstrand Road) to the M19/R27 (Westcoast Road) crossing at 334333.45S 0182720.23E.
i) Thence along the R27 (Westcoast Road) to a point at 334327.93S 0182720.51E.
j) Thence clockwise along the arc of a circle, radius 2.5NM, and centered at 334100.00S 0182650.00E to a point at 333830.09S 0182644.12E on the R27 (Westcoast Road).
k) Thence North Westwards along the R27 (Westcoast Road) to a point at 333321.22S 0182234.92E.
l) Thence Westwards along a straight line to a point at 333400.00S 0181830.00E.
m) Thence Southwards along a straight line to a point at 334759.00S 0182154.00E.
n) Thence South Eastwards along a straight line to a point at 335222.07S 0182737.81E on the Ysterplaat ATZ boundary.
o) Thence clockwise along the arc of a circle radius 2.5NM and centered at 335404.00S 0182951.00E to a point at 335135.57S 0183018.52E on the FACT CTR Boundary.
p) Thence along a straight line to a point at 334930.23S 0182829.97E on the FACT CTR boundary
q) Thence clockwise along the arc of a circle radius 11NM centered at 335810.00S 0183621.00E back to the starting point at 334721.49S 0183840.59E.
Frequency: 126.8MHz

RULES APPLICABLE WITHIN THE CAPE TOWN SPECIAL RULES AREA

- Avoid controlled airspace unless otherwise authorised by Air Traffic Control.
- Comply with the Traffic Information Broadcast by Aircraft (TIBA.)
- The Cape Town Special Rules Area shall exclude all promulgated controlled airspace and FADs, FARs, FAPs.
- Flights must be conducted at an indicated airspeed not exceeding 180 knots.
- It is recommended that where possible aircraft have their landing lights switched on.
- Aircraft operating within the special rules area below FACT TMA A must not exceed 2000FT ALT.

2.5 STANDARD VFR TRAFFIC ROUTES AND OPERATIONS WITHIN CAPE TOWN CTR

1) VFR departures and arrivals and transit routes in the FACT CTR via:
   Kenilworth
   Bottleray hills
   Coastwise

2) AIM:
   To standardize VFR routes within the FACT CTR.

3) BENEFITS:
   Standard VFR routings within the CTR leads to:
   Reduced RT,
   Concise traffic information,

Reduced misunderstanding between pilot and ATC,
Reduced conflict between VFR flights,
Ease of separation between VFR and IFR traffic

4) VFR Routes

- The following VFR routes may be used by FACT Air Traffic Control (ATC).
- Aircraft instructed to follow a particular route should comply with all requirements and reporting points for the specific route.
- ATC will provide traffic information regarding other aircraft following the same route, and known conflicting traffic on other routes, or traffic not following a route. At all times keep a good lookout for known and unknown traffic.
- These routes will not be used exclusively, and shorter or alternate routes may be issued by ATC depending on ATM capacity.
- Before entering and after exiting the CTR aircraft are to broadcast on the relevant unmanned (TIBA) frequencies, comply with the rules of the Special Rules Areas and maintain a good lookout for aircraft exiting, entering or waiting to enter the CTR.
- Helicopters departing from and arriving at FACT may be allocated these routes.
- Helicopter and fixed wing operators are to notify ground control on start-up or taxi of preferred route by stating the associated name.
- All departing and arriving aircraft should keep a good lookout for helicopter circuit training operations being conducted on the threshold of runway 34.
- Aircraft are to report entering and leaving the CTR.
- Establishing contact with ATC must not be considered permission to enter the CTR. Aircraft to remain outside the CTR until a joining clearance is issued by ATC.
- Aircraft may be instructed to remain outside the CTR until ATM capacity is available to accommodate the aircraft into the CTR.
- VFR aircraft should not expect to be given routing to exit or enter the CTR from the North

WHEN RUNWAY 01 IS IN USE

DEPARTURES

1) VFR Departure RWY 01 to the East - Bottelary 01 departure:

- Climb to 1500 FT ALT.
- Route via the University of the Western Cape (335600S 0183800E) then overhead the R300/Voortrekker road interchange (335429S 0184025E).
- Then route North of the Kuilsriver Golf course (335404S 0184239E) then route towards the Devon Valley Golf course (335300S 0184800E) remaining immediately to the North of the Bottelary road (M23) until clear of the CTR.
- The CTR boundary is approximately abeam the Red and White tower on the Bottelary Hills (335533S 0184549E).
- Keep a good lookout for helicopter circuit training operations being conducted on Threshold of RWY 34.

2) VFR Departures RWY 01 to the West - Kenilworth 01 departure

– Climb to 1500 FT ALT.
– Route north of the Guguletu Vlei (335903S 0183245E) direct towards the northern point of Kenilworth Race Course (335922S 0182914E) until clear of the CTR.

ARRIVALS

1) VFR Arrival RWY 01 from the East - Bottelary 01 arrival:

– VFR aircraft wishing to enter the CTR from the East can expect to enter the CTR in the vicinity of the Devon Valley Golf course (335300S 0184800E) at the Bottelary Hills, remaining clear of the CTR.
– Once issued the BOTTELARY 01 ARRIVAL, enter the CTR at 1500 FT ALT South of the Bottelary road (M23).
– The CTR boundary is approximately abeam the Red and White tower on the Bottelary Hills (335533S 0184549E)
– Route South of Kuilsriver Golf course (335428S 0184242E) avoiding high terrain and route overhead Blackheath Industrial (335800S 0184200E).
– Join and report Right Downwind RWY 01 abeam the Threshold of RWY 34.
– Keep a good lookout for helicopter circuit training operations being conducted on Threshold of RWY 34.

2) VFR Arrival RWY 01 from the West - Kenilworth 01 arrival

– VFR aircraft wishing to enter the CTR from the West can expect to enter the CTR in the vicinity of the southern most point of Kenilworth race course (340007S 0182901E), remaining clear of the CTR.
– Once issued the KENILWORTH 01 ARRIVAL, enter the CTR at 1500 FT ALT south of the Guguletu Vlei (335954S 0183239E).
– Route directly towards the airport.
– Join and report Left Downwind RWY 01 abeam the ATC Tower

WHEN RUNWAY 19 IS IN USE

DEPARTURES

1) VFR Departures RWY 19 to the East - Bottelary 19 departure:

– Climb to 1500FT ALT.
– Route overhead Blackheath Industrial (S335800 E0184200) remaining south of Kuilsriver Golf course (S335428 E0184242).
– Route towards the Devon Valley Golf course (S335300 E0184800) remaining to the South of the Bottelary road (M23) until clear of the CTR avoiding high terrain.
– The CTR boundary is approximately abeam the Red and White tower on the Bottelary Hills (S335533 E0184549).

2) VFR Departures RWY 19 to the West - Kenilworth 19 departure:

– Climb to 1500FT ALT.
– Route south of the Guguletu Vlei (S335954 E0183239) direct towards the southern most point of the Kenilworth Race Course (S340007 E0182901) until leaving the CTR.

ARRIVALS

1) VFR Arrival RWY 19 from the East - Bottelary 19 arrival

– VFR aircraft wishing to enter the CTR from the East can expect to enter the CTR in the vicinity of the Devon Valley Golf course (335300S 0184800E), remaining clear of the CTR.
– Once issued the BOTTELARY 19 ARRIVAL, enter the CTR at 1500FT ALT immediately to the North of the Bottelary road (M23).
– The CTR boundary is approximately abeam the Red and White tower on the Bottelary Hills (335533S 0184549E)
– Route South of the Brickfields Quarry (335331S 0184340)E North of Kuilsriver Golf course (335404S 0184239E) and overhead R300/Voortrekker interchange (335429S 0184025E)
– Join and report Left Downwind RWY 19 abeam the Threshold of RWY 34.
– Keep a good lookout for helicopter circuit training operations being conducted on Threshold of RWY 34.

2) VFR Arrival RWY 19 from the West - Kenilworth 19 arrival

– VFR aircraft wishing to enter the CTR from the West can expect to enter the CTR in the vicinity of the northern most point of Kenilworth race course(335922S 0182914E), remaining clear of the CTR.
– Once issued the KENILWORTH 19 ARRIVAL, enter the CTR at 1500FT ALT route directly towards the airport route north of the Guguletu Vlei (335903S 0183245E).
– Join and report Right Downwind RWY 19 abeam the Radar tower. (Radar Tower on the Western side of the runway with the round encasing resembling a giant golf ball)

GENERAL

1) FAD200

– Flights to the FAD200 GFA to expect routing via the Kenilworth VFR routes.
– Upon leaving the CTR, broadcast on the relevant TIBA frequency and complying with the Special Rules Area rules, remain well clear of the CTR, and proceed to the FAD200 remaining below the Cape Town TMA
– Contact FAYP for routing through the FAYP ATZ
– Upon returning from the FAD200, route clear of the CTR to Kenilworth or the Bottelary Hills and request joining from FACT Tower.
– Do not enter the CTR or any other controlled airspace until given joining instructions.

2) COASTWISE ROUTING

– Aircraft wishing to transit the CTR from East to West and vice versa may be routed via the COASTWISE route.
– Routing coastwise below 1000 feet or as directed by ATC between Muizenberg (340520S 0183320E) and Macassar beach (340435S 0184420E) then along the northern boundary of FAP33 until leaving the CTR or vice versa.

3) Cape Peninsula

– Flights wishing to operate around the Cape Peninsula to expect routing via the Kenilworth VFR routes.

– Helicopters routeing between FACT and the V&A Waterfront to expect routing via the Kenilworth VFR route.
– Flights wishing to transit the CTR from West to East or vice versa are to expect routing North of the Tygerberg hills or via the COASTWISE route.
– Upon leaving the CTR, broadcast on the relevant TIBA frequency, remain well clear of the CTR, and comply with rules for operating within the Cape Town Special Rules Area. Do not enter the FAR149, FAR39 and FAR144 unless authorized to do so.
– Upon returning to FACT, expect routing via Kenilworth or Bottelary, and request joining from FACT Tower.
– Do not enter the CTR or any other controlled airspace until given joining instructions.

4) Helicopter operations within the CTR

– All helicopters departing from FACT are to request start on GMC frequency (121.9 MHz). Emergency Medical and emergency flight by SAPS may contact Tower directly (118.1 MHz) stating the nature of their flight to minimise delay.
– Helicopter training is conducted on the threshold of RWY34, during VMC daylight hours only.
– Only one helicopter is accommodated for training at THR34 at a time, on a first come first served basis.
– If THR34 is not available, taxiway D1 may be offered by ATC as an alternate.
– Training circuits are conducted to the east of THR34, at a maximum altitude of 1000 FT, no further north than abeam of THR19, no further south than abeam of THR01.
– No other helicopter training operations will be accommodated within the CTR.
– No helicopter circuit training will be accommodated from the General Aviation area of the airport.
– Helicopter circuit training at night will only be accommodated on RWY 01/19 between TWY C and B3 traffic permitting.
– Helicopter pilots operating in close proximity to IFR traffic are to be conscious of the possibility of their aircraft causing ACAS alerts on board IFR aircraft. Helicopters should not be flown on a trajectory that encroaches on the flight path of the IFR aircraft, but should rather operate on trajectories that will pass well abeam and behind the IFR aircraft.

5) Transponders

– The use of a Mode C transponder is compulsory for operations within the CTR. Unless issued a discreet code by ATC, all fixed wing aircraft must squawk A2000 and rotary wing aircraft must squawk A2600 at all times while operating within the CTR, and the Special Rules Areas.

6) Weather

– In the event of the CTR becoming IMC, VFR and SVFR flight by helicopters and SVFR flight by fixed wing aircraft will only be permitted subject to ATC approval. This will only be granted subject to weather conditions being suitable for safe operations, and subject to any IFR aircraft. As the FAYP ATZ falls within the FACT CTR, the same conditions apply to FAYP ATZ.

2.6 PROCEDURES APPLICABLE TO CONTERMANSKLOOF AIRFIELD

The following information and procedures applies to the airspace box around Contermanskloof airfield located inside the Northern boundary of the FACT CTR.

1) The Location of Contermanskloof airfield and dimensions of the Contermanskloof airspace box are as follows:
   a) Aerodrome reference point: 334804S 0183444E
   b) Vertical Limits: GND/1300 FT ALT
   c) Lateral Limits:
      – From a point 334717.01S 0183415.65E clockwise along the arc of FACT CTR, 11NM radius centered at 335810.82S 0183618.19E to a point 334708.69S 0183620.19E
      – Thence a straight line to a point 334827.00S 0183620.43E,
      – Thence a straight line to a point 334857.52S 0183516.58E,
      – Thence a straight line to a point 334816.91S 0183415.95E,
      – Thence a straight line back to the starting point 334717.01S 0183415.65E.
2) Procedures applicable to aircraft operating to, from and at Contermanskloof Airfield:
   a) Traffic wishing to fly to or from Contermanskloof Airfield, or operate within Contermanskloof Airfield will make necessary arrangement with the owner of this airfield, who will in turn be responsible for activating the Contermanskloof Airfield box.
   b) All aircraft will broadcast on the Special Rules Area East -below the Cape Town TMA frequency 124.8 MHz
   c) No aircraft shall fly without a serviceable mode C transponder.
   d) All aircraft shall squawk #4600.
   e) All Circuits will be flown to the East of the runway.
   f) Exit and entry from and to the box will be from the North and no aircraft shall fly through any other part of the FACT CTR without ATC approval.
   g) The circuit altitude shall be 1000 FT Altitude.
3) Procedures applicable to aircraft operating at FACT:
   a) All aircraft making visual approaches on runway 19 from the East and turning final approach outside 5 NM 335810.82S 0183618.19E must maintain 2500 FT until established on final Approach runway 19.
4) Other Procedures:
   a) Operation at Contermanskloof may only be authorised by ATC when MSSR is operational at FACT.
   b) Traffic in the Contermanskloof airspace box is deemed separated from traffic operating at FACT
   c) The Contermanskloof airspace box will be activated on an ad hoc basis. When the airspace box is activated the airspace will be Class G airspace and will not form part of the FACT CTR. When not activated the airspace box will be part of the FACT CTR and will be Class C airspace.

2.7 GEORGE SPECIAL RULES AREA

The airspace below the George TMA, excluding area below TMA E and that part of the Oudtshoorn ATZ below TMA F, will be declared as a Special Rules Area and termed as the GEORGE SPECIAL RULES AREA.

To prevent frequency congestion and to promote safety, efficiency and orderliness in the George Special Rules Area, the area will be divided into two sectors, to be known as the Western and Eastern Sectors, for Traffic Information Broadcast by Aircraft (TIBA).

The dividing line between the sectors is the line that runs as follows:

The Western Sector between R250 GRV, clockwise to R030 GRV, this includes FAMO.

The Eastern Sector between R030 GRV, clockwise to R250 GRV.

All aircraft operating in the Western Sector of the Special Rules Areas should maintain a listening watch and broadcast regular position reports on frequency 124.2 MHz.

All aircraft operating in the Eastern Sector of the Special Rules Areas should maintain a listening watch and broadcast regular position reports on frequency 124.8 MHz.

The George CTR and FAR150 are excluded from the George Special Rules Area.

By virtue of the fact that uncontrolled VFR aircraft are to remain below the George TMA radar separations and information provided to aircraft operating within the George TMA, will only take known identified targets into account.

For the information of those aircraft operating within the George TMA, unidentified unknown targets, performing as expected for general aviation within the confines of the George Special Rules Area will be deemed to be separated from aircraft operating within the George TMA, by procedures as opposed to radar. Pilots operating below the George TMA should therefore ensure that they do not exceed the applicable altitude restriction as stipulated on SRA routings and also to remain at least 500 FT below the TMA whilst flying below the George TMA. Pilots are requested to squawk transponder code 2000 at all times with altitude selected. Helicopters to squawk 2600 also with altitude selected.

The following routes will be applicable in the George Special Rules Area:

Transiting, seawards of the coastline through the George CTR:

All VFR traffic wishing to route seawards of the coastline, through the George CTR, are to remain seawards of the coast line, not above 1000 FT ALT. VFR traffic, transiting through the George CTR is then deemed to be separated from departing and arriving traffic at George Aerodrome.

All transiting traffic is regarded as circuit traffic, thus reduced separation minima can be applied, in the vicinity of the aerodrome.

The clearance shall only be valid during daylight hours, in VMC operations, in communication with ATC and the aircraft shall be transponder equipped.

Pilots to comply with the Aviation Legislation, as described in General Operating and Flight Rules in Part 91.06.8, regarding following line features.

From the North and North West:

All VFR traffic to route via Oudtshoorn, then to the Robinsons pass, then to Hartenbos, then coastwise to George.

Traffic is to cross Oudtshoorn at or below 6000 FT ALT, Robinsons pass at or below 4000 FT ALT, Hartenbos at or below 1500 FT ALT. VFR traffic to remain clear of the George TMA.

VFR traffic wishing to route via the Outeniqua pass to George, must obtain permission from ATC.

From George to the North and North West:

All VFR traffic, departing George, to route via Hartenbos, then to the Robinsons pass, then to Oudtshoorn before setting course.Traffic is to cross Hartenbos at or below 1500 FT ALT, Robinsons at or pass below 4000 FT ALT, Oudtshoorn at or below 6000 FT ALT. VFR traffic wishing to route via the Outeniqua pass from George, must obtain permission from ATC. VFR traffic to remain clear of the George TMA.

From the North and North East:

All VFR traffic to route via Willowmore, then to Avontuur, then to the Prince Alfred pass, then to Walker point, then coastwise to George.Traffic is to cross Willowmore at semi-circular level, Avontuur at or below 8000 FT ALT, Prince Alfred pass, at or below 6000 FT ALT, Walker point at 1500 FT ALT. VFR traffic to remain clear of the George TMA.

From George to the North and North East:

All VFR traffic departing George, to route via Walker point, then to the Prince Alfred pass, then to Avontuur, then to Willowmore, before setting course.Traffic is to cross Walker point at 1500 FT ALT, Prince Alfred pass at or below 6000 FT ALT, Avontuur, at or below 8000 FT ALT, Willowmore at semi circular level. VFR traffic to remain clear of the George TMA.

From the West to George:

All VFR traffic, to route via Heidelberg then to Hartenbos, then coastwise to George.

Traffic is to cross Heidelberg at semi circular level, cross TMA I boundary at or below 3000 FT ALT, Hartenbos at or below 1500 FT ALT. VFR traffic to remain clear of the George TMA.

From George to the West:

All VFR traffic, departing George, to route via Hartenbos, then to Heidelberg before setting course.Traffic is to cross Hartenbos at or below 1500 FT ALT, remain at or below 3000 FT till TMA I Boundary and cross Heidelberg at semi circular level. VFR traffic to remain clear of the George TMA.

From the East to George:

All VFR traffic, to route via Walker point, then coastwise to George.Traffic is to cross Walker point below 1500 FT ALT. VFR traffic to remain clear of the George TMA.

From George to the East:

All VFR traffic, departing George, to route via Walker point, before setting course.Traffic is to cross Walker point below 1500 FT ALT. VFR traffic to remain clear of the George TMA.

Crossing from West to East:

All VFR traffic to route via Heidelberg, then to Hartenbos, then coastwise, transiting the George CTR, to Knysna, before setting course.

Traffic is to cross Heidelberg at semi circular level, cross TMA I boundary at or below 3000 FT ALT, Hartenbos at or below 1500 FT ALT. Walker point at 1500 FT ALT. An ATC clearance must be obtained to transit the George CTR. VFR traffic to remain clear of the George TMA.

Crossing from East to West:

All VFR traffic to route via Walker point, then coastwise, transiting the George CTR, to Hartenbos, then to Heidelberg, before setting course.

Traffic is to cross Walker point at 1500 FT ALT, Hartenbos below 1500 FT ALT, En route Heidelberg, cross TMA I boundary at or below 3000 FT ALT. Cross Heidelberg at semi circular level. An ATC clearance must be obtained to transit the George CTR. VFR traffic to remain clear of the George TMA.

Heidelberg at semi circular level:

Alternately route: Traffic is to cross Walker point at 1500 FT ALT, Hartenbos below 1500 FT ALT, En route Heidelberg, cross TMA D boundary below 4000 FT ALT and TMA E boundary below 7000 FT ALT and Heidelberg at semi circular level. An ATC clearance must be obtained to transit the George CTR.

Traffic routing eastward along the coastline between Hartenbos and Walker point are to route with the coastline to the left of the aircraft at 1500 FT ALT or below. Except in the George CTR where the aircraft is subject to ATC.

Traffic routing Westward along the coastline between Walker point and Hartenbos are to route with the N2 roadway to the left of the aircraft at 1500 FT ALT or below. Except in the George CTR where the aircraft is subject to ATC.

The area defined as follows has been identified for all general and training flying:

From a point at 335549S 0213232E to a point at 335724S 0220000E.

Thence a straight line to a point at 341751S 0220000E.

Thence a straight line to a point at 342049S 0215608E.

Then clockwise along the 30 NM radius GRV to a point at 341400S 0215027E.

Thence a straight line to a point at 341709S 0213617E

Then clockwise along the 42 NM radius GRV back to the starting point at 335549S 0213232E.

2.8 VFR ROUTINGS WITHIN THE GEORGE CTR AND THE GEORGE SPECIAL RULES AREA (SRA)

Note: All proposed VFR routes will be for use by day and in VMC only.

Standard VFR Departure Routes, leaving the George CTR:

Departing RWY 29:

Leaving the George CTR to the South West:

GLENTANA 29 VFR Departure

After departure runway 29, maintain runway track to 1000FT ALT, then turn left track 200 degrees and climb to 1500 FT ALT. At 1500FT ALT, set course for Glentana Beach and maintain 1500FT ALT. At Glentana beach follow the coastline to intercept SRA, VFR route at Great Brak River. Report passing Great Brak River.

Leaving the George CTR to the North West:

EIGHT BELLS 29 VFR Departure

After departure runway 29, maintain runway track to 1000FT ALT, then turn right track 020 degrees and climb 1900 FT ALT, At 1900 FT ALT proceed direct to Geelhoutboom, at Geelhoutboom set course (left turn) for Eight Bells, on track Eight Bells, when passing Eight Bells set course as required, remaining clear of the George CTR. Report passing north of Wolwedansdam.

Leaving the George CTR to the South East:

HEROLDS BAY 29 VFR Departure

After departure runway 29, maintain runway track to 1000FT ALT, then turn left track 200 degrees and climb to 1500 FT ALT. At 1500 FT ALT turn left set course to Herolds Bay. Passing Herolds Bay, follow the coastline as a line feature to Wilderness and join the SRA VFR route. Report passing Kaaimans River.

Leaving the George CTR to the North East:

FANCOURT 29 VFR Departure

After departure runway 29, maintain runway track to 1000FT ALT, then turn right track 020 degrees and climb 1500 FT ALT, proceed direct to Fancourt and climb 1700 FT ALT, at Fancourt set course (right turn) to route north of the George town, to pass north of the Garden route dam. Once passed the Garden route dam position, set course for Wilderness and join the SRA VFR route. Report passing Garden route dam.

Departing RWY 11

Leaving the George CTR to the North East:

FANCOURT 11 VFR Departure

After departure runway 11, maintain runway track to 1000 FT ALT, then turn left track 020 degrees, proceeding direct to Fancourt and climb 1700 FT ALT, at Fancourt set course (right turn) to route north of the George town, to pass north of the Garden route dam. Once passed the Garden route dam position, set course for Wilderness and join the SRA VFR route. Report passing Garden route dam.

Leaving the George CTR to the South West:

GLENTANA 11 VFR Departure

After departure runway 11, maintain runway track to 1000 FT ALT, then turn right track 200 degrees and climb to 1500 FT ALT. At 1500 FT ALT set course for Glentana Beach and maintain 1500 FT ALT. At Glentana beach follow the coastline to intercept SRA VFR route at Great Brak River. Report passing Great Brak River.

Leaving the George CTR to the North West:

EIGHT BELLS 11 VFR Departure

After departure runway 11, maintain runway track to 1000FT ALT, then turn left track 020 degrees and climb 1900 FT ALT, at 1900 FT ALT proceed direct to Fancourt, at Fancourt set course (left turn) for Eight Bells, passing Eight Bells set course as required, remaining clear of the George CTR. Report passing abeam Wolwedans dam.

Leaving the George CTR to the South East:

HEROLDS BAY 11 VFR Departure

After departure runway 11, maintain runway track to 1000 FT ALT, then turn right track 200 degrees and climb to 1500 FT ALT. At 1500 FT ALT set course to Herolds Bay. Passing Herolds Bay, follow the coastline as a line feature to Wilderness and join the SRA VFR route. Report passing Kaaimans River.

STANDARD VFR ARRIVAL ROUTES:

VFR routes to George Airport, entering the CTR from the West:

HEROLDS BAY 11 or 29 VFR Arrival

VFR aircraft, inbound to George, from the west, are to remain below the George TMA and route to Great Brak River via SRA VFR routes. Passing Great Brak River, follow the coast line feature to Herolds Bay at 1500 FT ALT. From Herolds Bay comply with ATC instructions to join the circuit.

Alternate VFR routes to George Airport, entering the CTR from the West:

EIGHT BELLS 11 or 29 VFR Arrival

VFR aircraft, inbound to George, from the North West, are to remain below the George TMA and to route via Eight Bells (Ruitersbos). Passing Eight Bells, route north of the George CTR to Fancourt at 1500 FT ALT. From Fancourt comply with ATC instructions to join the circuit.

VFR routes to George Airport, entering the CTR from the East:

WILDERNESS 11 or 29 VFR Arrival

VFR aircraft, inbound to George, from the east, are to remain below the George TMA and route to Wilderness via SRA VFR routes. From Wilderness, follow the coast line feature at 1500 FT ALT to Herolds Bay. From Herolds Bay comply with ATC instructions to join the circuit.

Alternate VFR routes to George Airport, entering the CTR from the East:

FANCOURT 11 or 29 VFR Arrival

VFR aircraft, inbound to George, from the east, are to remain below the George TMA and route to Wilderness via SRA VFR routes. From Wilderness, route to a position north of the Garden route dam at 1700 FT ALT. Then route north around the George town to Fancourt. From Fancourt comply with ATC instructions to join the circuit.

Radio failure procedures for circuit training and for training flights to / from the Special Rules Area.

In Circuit: Remain in circuit and position in traffic, land and vacate RWY in use ASAP. After landing contact ATC via telephone.

FLIGHTS TO / FROM THE SRA:

En-route to the Special Rules Area - continue on the Standard VFR departure till clear of the George CTR. Thereafter proceed to FAMO and land. After landing contact ATC via telephone.

In the Special Rules Area - remain clear of controlled airspace, proceed to FAMO or FAPG and land. After landing contact ATC via telephone.

Inbound (once cleared inbound by ATC) - continue on the cleared Standard VFR arrival route, join the circuit and position in traffic, land and vacate RWY ASAP. After landing contact ATC via telephone.

SIGNIFICANT POINTS:

Fancourt 335715S 0222340E

Eight Bells (Ruiterbos) 335640S 0220205E

North of Wolwedansdam 335700S 0221200E

Great Brak River 340300S 0221320E

Glentana 340300S 0221910E

Herolds Bay 340320S 0222335E

North of Garden route dam 335715S 0223100E

Wilderness 335950S 0223500E

Geelhoutboom 335639S 0222056E

3 COMMUNICATION CONTINGENCY MEASURES WITHIN THE FAJO FIR

1) All ACFT operating over the Indian and Atlantic Oceans inside the South African area of responsibility and outside of VHF coverage of the relevant ACC are to communicate with Johannesburg Oceanic.
2) Flights operating west of positions EGSOX (S282331.94 E0344131.38), APLUK (S285213 E0342532), GEVIS (S294137.49 E0335737.56) and ANVED (S310939.47 E0330634.63) will be the responsibility of Johannesburg Area East.
3) Flights operating east of positions, OKTEL (S280753.81 E0150000.00) and UVGOD (S290943.27 E0150000.00) will be the responsibility of Johannesburg Area West.
4) Flights operating east of positions BUXIR (S320000.00 E0150000.00), OKDOG (S330500.00 E0150000.00), ITMEK (S341200.00 E0150000.00) and ITLIK (S351600.00 E0145957.00) will be the responsibility of Cape Town Area West.
5) Part of the Windhoek FIR from ILDIR (S180000.00 E0100000.00) south bound to a position S273000.00 E0100000.00, then eastbound to a position S273000.00 E0150000.00, then northwest bound through position NIGAM (S263356.00 E0143710.00), DULGO (S250000.00 E0135908.00), ANTEP (S240000.00 E0133604.00), NIBEK (S225831.00 E0131254.00), ETUDU (S214000.00 E0124321.18), NEVEP (S202000.00 E0121404.44), IBNEV (S184706.00 E0114005.00) then to a position S173000.00 E0111300.00, then westbound through position DIMIX (S174648.00 E0103000.00) back to starting point ILDIR (S180000.00 E0100000.00), is the responsibility of Johannesburg Oceanic due to limited range of Windhoek ACC frequency 124.7 MHz. All aircraft operating in this airspace must be in contact with Johannesburg Oceanic.
6) In the possible event of the Johannesburg HF system becoming unserviceable, aircraft operating into the Johannesburg Oceanic FIR are to comply with the following:
   - Airborne traffic is required to maintain last assigned flight level until clearing the Johannesburg Oceanic area of responsibility unless a level change has been approved through one of the communication sources listed,
   - Airborne traffic operating within the Oceanic FIR over the Atlantic Ocean should contact:
   - Luanda FIC on FREQ: 8903 kHz, 8960 kHz, 5565 kHz, 3461 & 2878 kHz or
   - Springbok Johannesburg on FREQ; 5532 kHz, 8933 kHz, 11354 kHz, 13330 kHz, 17925 kHz, 21943 kHz for relay purposes to Johannesburg Oceanic.

4 DELEGATION OF ESWATINI UPPER AIRSPACE TO SOUTH AFRICA

The Eswatini CAA has acknowledged that the AFI Region and ATM community in general stands to gain greater benefits from the introduction of the new integrated ICAO CNS/ATM Systems.

To ensure a cost effective, operationally orientated implementation of the integrated ICAO CNS/ATM System in Eswatini, the approach and strategy contained in the AFI Doc 003 was adopted, for use and compliance by the Eswatini CAA.

To achieve the above, the upper Eswatini airspace was delegated to South Africa for management by ATNS.

4.1 PURPOSE

The purpose of this document is to inform users that the Eswatini upper airspace i.e. the Matsapha TMA from FL195 and above will be delegated to South Africa for management by ATNS and controlled by Johannesburg Area Control.The sovereignty of the Eswatini airspace will not be compromised.

Note: Johannesburg Area Control (ACC South East) will only be operational during published hours of duty. Outside these hours of duty Matsapha Approach Control will transfer traffic to Johannesburg Area Control (ACC North East) 134.40 MHz or Johannesburg Area Control (ACC South West) 128.3 MHz.

4.2 AIRSPACE

The airspace delegation definition is as follows: Matsapha TMA

- From a point 255342S 0310947E on the South African/Eswatini border to a point at 254831.57S 0311552.72E,
- Thence along the border to a point at 254435.21S 0311855.22E,
- Thence along the border to a point at 254304.36S 0312453.25E,
- Thence along the border to a point at 255121.00S 0313849.00E,
- Thence along a straight line to a point at 255121.00S 0313849.00E,
- Then Southwards along the Eswatini/Mozambique border to a point at 263851.00S 0320745.00E,
- Thence along a straight line to a point at 272031.00S 0315222.00E,
- Thence along a straight line to a point at 271812.00S 0311004.00E,
- Thence along a straight line to a point at 264918.00S 0304707.00E,
- Thence along a straight line to a point at 255548.00S 0304715.00E,
- Thence along a straight line back to the starting point at 255342S 0310947E.

4.3 CONTACTS

Any questions and assistance should be directed to:

Mr. Martin Cooper
+27 11 928 6436
+27 79 500 8871
martinc@atns.co.za

5 DELEGATION OF ATS WITHIN FAJA FIR TO FYWF ACC/FIS:

5.1 Introduction

The airspace that is part of the FAJA FIR, has been delegated to FYWF ACC/FIS FM 1500FT AGL TO FL195:

5.2 Airspace

The airspace delegation definition is as follows:

Lateral limits: FM a point (273000S 0150000E) along a straight line to a point at (273000S 0195439E). Thence a straight line to a point at (282312S 0195453E). Thence clockwise along the INTL BDRY BTN South Africa and Namibia to a point (283548S 0162042E). Thence a straight line to a point (283548S 0150000E). Thence along a straight line back to the starting point at (273000S 0150000E).
FM 1500FT AGL to FL145 FIS will be provided by FYWF FIS on FREQ 123.8 MHz. This airspace is classified class G. HR of OPS is HJ. Outside these HR Pilots to CTC FYWF FIS on FREQ 124.7 MHz.
FM FL145 to FL195 controlled SER will be provided by FYWF ACC on FREQ 124.7 MHz. This airspace is classified class A. HR of OPS 24 HR.
FM FL200 to FL460 a controlled SER will be provided by FAJA ACC West on FREQ 118.5 MHz. This airspace is classified class A. HR of OPS 24 HR.

6 DELEGATION OF ATS WITHIN THE WINDHOEK FIR TO JOHANNESBURG OCEANIC FIR

6.1 Introduction

ATS within the Windhoek FIR. GND to FL650 has been delegated to Johannesburg Oceanic. ATS will be provided by Johannesburg Oceanic.

6.2 Airspace

The airspace delegation definition is as follows:

From a point 273000S 0150000E, along a straight line to a point at 273000S 0100000E,
Thence along a straight line to a point at 180000S 0100000E,
Thence along a straight line to a point at 173000S 0111300E
Thence along a straight line back to the starting point at 273000S 0150000E.

Hours of Operation:	H24
Frequency:	5565kHz, 6559kHz, 8861kHz, 13315kHz, 17955kHz and 21926kHz
Callsign:	Johannesburg Oceanic

7 TRAFFIC INFORMATION BROADCAST BY AIRCRAFT

The following procedures for aircraft operating outside of controlled airspace, within the boundaries of the RSA have been implemented.

7.1 All aircraft operating at or below 1500FT AGL outside the lateral limits of:-

a) The Johannesburg Special Rules Area
b) The Port Elizabeth Special Rules Area
c) The East London Special Rules Area
d) The Hoedspruit Special Rules Area
e) All promulgated General Flying Areas

should maintain a listening watch and broadcast regular position reports on frequency 124.8 MHz.

Aircraft operating within 5NM of an aerodrome where an ATSU is not in operation and where no specific frequency has been allocated, should make regular position reports relative to the aerodrome on frequency 124.8 MHz. (excluding those aerodromes situated within General Flying Areas. Refer to paragraph 7.4)

7.1.1 Where a specific frequency has been allocated to an aerodrome the position reports, relative to the aerodrome, should be made within 5NM of the aerodrome on the appropriate frequency.

7.1.2 En-route position reports should be made at regular intervals containing information useful for collision avoidance e.g. identification, route position/time, level/ altitude, next position and estimate. These position reports should be made with reference to prominent landmarks and/or navigational facilities.

7.2 Aircraft operating above 1500FT AGL outside the areas mentioned in paragraph 7.1 (a)-(e) should maintain a listening watch and should make regular position reports on the appropriate ATC FIS frequency allocated for that area. In the event that due to location or range, no contact can be established with the appropriate ATSU FIS, a listening watch should be maintained and regular position reports/broadcasts should be made on the frequency allocated for that area.

7.3 General Air-to-Air Aviation Frequency

7.3.1 To avoid the TIBA frequencies from being used for purposes other than essential traffic information broadcasting, the frequency 123.45 MHz is available for pilots to discuss general matters.

7.3.2 Messages should be kept short and a listening watch should be maintained on the appropriate TIBA frequency.

7.4 **Frequency for established General Flying Areas**.

Aircraft operating within designated General Flying Areas that do not have an assigned frequency should use 124.4 MHz

Note: Pilots operating at unmanned aerodromes situated within established General Flying Areas should use frequency 124.4 MHz.

7.5 The following table lists all aerodromes without ATSU's to which specific frequencies have been allocated:

Aerodrome	Frequency
Aggeneys	122.7 MHz
Alexander Bay	118.7 MHz
Arnot	122.2 MHz
Brakpan	122.7 MHz
Brits	124.2 MHz
Cape Winelands	131.10 MHz
Delmas	125.4 MHz
Estcourt	123.4 MHz
Grahamstown	123.5 MHz
Greytown	123.5 MHz
Groblersdal	122.4 MHz
Heidelberg	125.9 MHz
Howick	123.4 MHz
Kitty Hawk	120.65 MHz
Kleinsee	123.5 MHz
Klerksdorp	123.5 MHz
Komati	122.2 MHz
Kriel	122.2 MHz
Kroonstad	122.4 MHz
Krugersdorp	122.0 MHz
Lime Acres	123.5 MHz
Majuba	122.2 MHz
Margate	122.7 MHz
Middelburg (FAMB)	127.950 MHz
New Tempe	131.3 MHz
Orient	123.4 MHz
Oudtshoorn	131.100 MHz
Parys	123.5 MHz
Petit	133.2 MHz
Potchefstroom	123.00 MHz
Progress	122.7 MHz

Aerodrome	Frequency
Pullenshope (Hendrina)	122.2 MHz
Rustenburg	122.4 MHz
Saldanha/Vredenburg	122.7 MHz
Secunda	122.0 MHz
Sishen	123.5 MHz
Skukuza	125.250 MHz
Springs	122.4 MHz
Stellenbosch	119.3 MHz
Syferfontein	122.35 MHz
Tutuka	122.2 MHz
Uitenhage	124.2 MHz
Vanderbijlpark	122.3 MHz
Vereeniging	122.1 MHz
Welkom	118.0 MHz
Witbank	123.5 MHz

Pilots should make the appropriate broadcasts and take all necessary collision avoidance action prior to entering or leaving the area.

8 GABORONE CLIMB AND DESCENT COORDINATION AREA

The dimensions of the delegated South African airspace to Gaborone are as follows:

Gaborone Climb/Descent Coordination Area A
• From a point 244514.76S 0255051.54E along the international boundary between Botswana and South Africa to a point at 244115.69S 0261104.89E
• Thence clockwise along the arc of a circle, radius 20NM and centered at 243551.77S 0254956.84E (VOR GBV) to a point at 245552.18S 0255135.18E.
• Thence along the international boundary between Botswana and South Africa to a point at 245257.74S 0255319.31E.
• Thence along the international boundary between Botswana and South Africa back to the starting point at 244514.76S 0255051.54E.

Vertical Limits: 7000FT – FL200

Frequency: 128.20 MHz

Gaborone Climb/Descent Coordination Area B

• From a point at 244115.69S 0261104.89E along the international boundary between Botswana and South Africa to a point at 243915.24S 0261915.74E
• Thence along a straight line to a point at 245158.12S 0264157.43E
• Thence clockwise along the arc of a circle, radius 50NM and centered at 243551.77S 0254956.84E (VOR GBV) to a point at 251919.63S 0261724.20E
• Thence along a straight line to a point at 250200.85S 0254913.74E
• Thence along the international boundary between Botswana and South Africa to a point at 245552.18S 0255135.18E
• Thence anti-clockwise along the arc of a circle, radius 20NM and centered at 243551.77S 0254956.84E (VOR GBV) back to the starting point at 244115.69S 0261104.89E

Vertical Limits: 9000FT – FL200

Frequency: 128.20 MHz