

Advanced Web Programming

SIB245007 | D-IV Sistem Informasi Bisnis

Meeting 1: Modern Web Architecture and the Laravel Ecosystem

Semester Learning Plan (RPS) & Meeting 1 Materials

Part 1

Course Information

Study Program	D-IV Sistem Informasi Bisnis
Course Code	SIB245007
Course Name	Advanced Web Programming

This course uses **Simple POS**, a real point-of-sale cashier app for small businesses that grows commit by commit, as a running case study across the whole semester.

Semester Learning Plan

Meeting	Topic
1	Modern Web Architecture
2	HTTP & MVC Architecture
3	Frontend & Templating
4	Database Design & Migration
5	ORM & Data Relations
6	Input Validation & Security
7	Authentication & Authorization
8	Midterm
9	Data Processing & Export

Meeting	Topic
10	API Architecture & Design
11	PBL Project Planning
12	PBL Feature Development
13	PBL Integration & Testing
14	PBL Optimization & Deployment
15	PBL Project Finalization
16	PBL Final Exam Preparation
17	Final Exam

Meetings 1–10 build the technical foundation in Laravel; Meetings 11–17 shift it into an independent *Project Based Learning* (PBL) project.

Evaluation Components

Evaluation Basis	Weight
Participatory Activity (Case Method)	0%
Project Outcome (Project Based Learning)	55%
Cognitive – Weekly assignment (increment)	15%
Cognitive – Quiz	0%
Cognitive – Midterm (project progress + presentation)	5%
Cognitive – Final Exam (final project + presentation)	25%
Total	100%

Weekly assignment: incremental (*increment*) implementation of the Simple POS application, submitted as evidence of code and documentation per the rubric.

Part 2

What You'll Learn

1. Comparing **monolith**, **microservices**, and **serverless** architectures to explain why Laravel was chosen as Simple POS's framework
2. Understanding why **Laravel 13** with **SQLite** as a zero-setup database was chosen for Simple POS
3. Recognizing the Laravel project folder structure (`routes/` , `app/Http/Controllers/` , `database/migrations/`) as an embodiment of the **MVC** pattern

This slide covers concepts. Installation steps, project setup, and full hands-on practice are covered separately outside this slide.

What Is Web Architecture?

Web architecture: how an application's layers (interface, business logic, data access) are organized and deployed: as a single unit, or as many separate units.

- Choosing an architecture isn't just a technical decision: it determines how many deploy processes, failure points, and network calls the team has to manage
- A "fancier" architecture isn't automatically better: building a food court for a business that only needs one kitchen just burns effort on connecting plumbing instead of features
- Three styles we'll compare: **monolith**, **microservices**, **serverless**

Monolith

Monolith: An application whose layers (interface, business logic, data access) all run in a single codebase and a single deploy process.

- Adding a feature = adding code to the same project
- Deploying an update = replacing one unit with a new version
- Often mistaken for "messy code"
- A well-structured monolith (e.g. with MVC) stays clean
- Its opposite isn't "modular", it's "**distributed**"

Microservices

Microservices: An architecture that splits an application into independent services, each running and deployed on its own, communicating over a network.

- Each service: different language, different deploy schedule, scales independently
- **The price:** 8 services = 8 deploy processes + 8 failure points + network calls between services
- Worth it for **large teams** running systems at millions-of-users scale
- For Simple POS: the cost far outweighs the benefit

Analogy: Family Restaurant vs. Food Court

The two architectures we just defined, in an everyday analogy:

Family restaurant (monolith)

- One kitchen, one register, one team
- Everybody knows everything
- Busy? Add a stove, not a new branch

Food court (microservices)

- Each stall: its own kitchen, register, recipe
- Independent units
- One empty stall doesn't affect the others

Simple POS is built as a **monolith** (the family restaurant) not out of limitation, but because the scale fits: a shop with one or two cashiers doesn't need ten separate services.


Serverless

Serverless: Code runs as small functions that only execute when triggered by an event, with no server process staying up continuously.

- The name is misleading: the server still exists, it's just not your responsibility
- There's a **cold start** delay when a function hasn't been called in a while
- Billing is per execution, not per hour a server stays on
- Good fit: spiky workloads (e.g. image processing on upload)
- Poor fit: Simple POS, which needs a consistent database connection

Comparing the Three Architectures

Architecture	Deployment	Initial Complexity	Best For
Monolith	Single unit	Low	Simple POS, MVPs, small teams
Microservices	Many independent units	High	Large-scale systems, large teams
Serverless	Function per event	Medium	Sporadic workloads



Monolith



Microservices

Why Laravel?

MVC (Model-View-Controller): the Model owns data, the View owns presentation, the Controller owns the request flow between them.

- One PHP project: routing, authentication, ORM, templating, ready to use
- Compared to plain PHP: consistent MVC structure from the first line of code
- Compared to microservices-first frameworks: stays productive for a team of 1–2 people
- Strong package ecosystem: **Sanctum** (API), **Excel** (import/export), **Cashier** (payments)
- Similar philosophy to Django (Python) & Ruby on Rails: *convention over configuration*

One Entry Point: `public/index.php`

Plain PHP


- URL maps directly to a file
- `/product.php` → runs `product.php`
- Every file is potentially accessible directly via URL

Laravel

- Every request enters through one file: `public/index.php`
- URLs are registered in `routes/web.php`
- Other files (Controller, Model) can't be accessed directly via URL

A single entry point means every request can be processed uniformly before reaching the application code: the foundation of routing, middleware, and centralized authentication.

One Laravel Request, Start to Finish



This flow pattern repeats across every Simple POS feature, from the simple POS page to REST API endpoints, all following the same path.

Setting Up the Project: Why SQLite?

- The database is stored in **a single plain file**
- No separate server process to start and configure
- Migrations can run right in the first minute
- Simple POS runs on SQLite even for classroom demos

Before continuing, make sure these four tools are installed: `php -v` (8.2+), `composer -V`, `node -v`, and `git --version`.

Composer & npm: Dependency Managers

Composer: PHP's dependency manager, reads `composer.json`, downloads packages into `vendor/`, then generates `vendor/autoload.php`.

- Thanks to `autoload.php`, every class is usable right away, no manual `require` / `include` like in plain PHP
- **npm** is its counterpart in the JavaScript world: `package.json` lists packages, `node_modules/` stores them, used by Laravel for Vite & Tailwind
- Both folders (`vendor/`, `node_modules/`) are downloaded output, never committed to Git

`.env` & the Configuration Layer

`.env`: a configuration file that separates credentials and environment settings from source code.

- Configuration read path: `.env` → the `env()` helper → `config/*.php` → the `config()` helper used by application code
- The app key inside it is used to encrypt sessions and cookies
- This separation allows different configuration per environment (local, staging, production) without changing code

The `.env` file stores sensitive data and must never be committed. Laravel's default `.gitignore` already excludes it.

Artisan & Migrations

Artisan: Laravel's built-in CLI for everyday development tasks (migrations, seeding, generating boilerplate): a dev tool, not part of the application served to users.

Migration: a PHP file that defines a database schema change in code, so the schema can be rebuilt consistently on any machine.

- Treat migrations like version control for the schema: a new change means a new migration file, never edit an old migration that's already run elsewhere
- The `--seed` option fills tables with realistic sample data for practice and demos

Laravel's Folder Structure = MVC in Practice

Folder	MVC Role	Contents
routes/web.php	Controller	URL registration
app/Http/Controllers/	Controller	Request-handling classes
database/migrations/	Model	Database schema definitions
resources/views/	View	Blade files (Meeting 3)
vendor/	-	Composer packages, not committed

This structure isn't an accident: it embodies the same MVC pattern as the request-flow diagram earlier.

Summary

- **Monolith** unifies every layer in one codebase and one deploy, a fit for Simple POS's scale; **microservices** splits it apart at a cost that's only worth it for large systems; **serverless** suits sporadic workloads
- Laravel is Simple POS's framework because its structure stays consistent from the start (MVC) and it's productive for small teams; **SQLite** is the database because it's zero-setup: one file, no separate server
- **Composer**/npm manage dependencies; **.env** separates configuration from code; **Artisan & migrations** build the database schema programmatically
- Laravel's folder structure embodies the **MVC** pattern, consistently separating the responsibilities of routing, business logic, and presentation

References & Discussion

Official Laravel documentation · PHP Manual

Full code: `github.com/se-polinema/simple-pos`

Next meeting: HTTP & MVC Architecture