حكومة دبي
GOVERNMENT OF DUBAI

DUBAI
للاقتصاد والسياحة
Economy and Tourism

SALES API INTEGRATION DOCUMENT

Revision History

Version	Date	Author	Comments
1.0	18/01/2023	Tibco	Initial version
1.1	09/06/2023	Muhammad Junaid	Update Sections Seats Endpoint Add Nationality code ZZ – Not Supplied
1.2	09/14/2023	Muhammad Junaid	Updated data type of the following fields “Price, GstRate, priceTypeName”. Added the missing paramter in the Refund Partial Order i.e “TicketIds”. Fixed bugs in the performance availability call response and removed sectionCode, availableSeatCount in the api response.
1.3	10/17/2023	Muhammad Junaid	Clarify the “Area” in the basket offer request.

Approvals

This document requires the following approvals. Signed approval forms are filed in the project files.

Name	Signature	Title	Company	Date of Issue	Version

Distribution

This document has been distributed to:

Name	Title	Company	Date of Issue	Version

1. Introduction 4
2. Endpoints 5
2.1. Sales API 5
2.1.1. Retrieve Token 5
2.1.2 Get Performance Map 7
2.1.3 Get Performance Prices 13
2.1.4 Get Performance Availability 18
2.1.5 Get Section Seats 19
2.1.6 Create Basket 22
2.1.7 Add Items to a Basket 29
2.1.8 Delete an Item from Basket 31
2.1.9 View Basket 32
2.1.10 Delete Basket 35
2.1.11 Purchase Basket 35
2.1.12 Get an Order Details 37
2.1.13 Return an Order 43
2.1.14 Return an Order Partially 44
2.1.15 Add a new Customer 45
2.1.16 Update Customer 47
2.2. Error Messages 50

1. Introduction

The goal of this document is to list and document the eTicketing 2.2 Endpoints developed by TIBCO for the integration with all systems under eTicketing scope.

The format of the request and responses of all the request, are the ones provided by DET in the document “Sales API v2.2 Integration Document.pdf”

This endpoints will be deployed on top of the architecture that is explained in the “DET Architecture document”

2. Endpoints

2.1. Sales API

Every Endpoint should be invoked with the value for the **api_key** at the end of the URI ?api_key=3rcbhsn32xmwvu42bmk2pkak (except for the Retrieve Token API which has its own api_key).

Every Endpoint should be invoked using a **Bearer Token** as Header parameter.

Header Parameter	Type	Description
Token	String	The generated access token

2.1.1. Retrieve Token

For this endpoint there is no need to use any authorization token as per the previous ones.

Method	**Endpoint**
POST	https://et-apiuat.detsandbox.com/adfs/oauth2/token?api_key=8555cns4y3hruga8kbtvaubx

Input Parameters
For this endpoint there are no input parameters required

Input Payload

The payload needs to be sent as json in body

Parameter	**Type**

client_id	String
client_secret	String
scope	String
grant_type	String
resource	String

Body Sample

{
"client_id": "ATEST27",
"client_secret": "DaMqdmKjNYjCUoyVLynX__3y2MU8p-nJArM3_kI7",
"scope": "profile",
"grant_type": "client_credentials",
"resource": "https://et-apiuat.detsandbox.com"
}

Output Parameters

Parameter	Type
access_token	String
token_type	String
expires_in	Integer
scope	String

Response Sample

{

"access_token":
"eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsIng1dCI6ImRtbk9ZMGg5MHBNTjdiZll2X3gxRmwzR2I5MCJ9.eyJhdWQiOiJodHRwczovL215d2ViYXBpMi5jb20iLCJpc3MiOiJodHRwOi8vQURGU1VBVC5kdGNtZG9tYWluLmNvbS9hZGZzL3NlcnZpY2VzL3RydXN0IiwiaWF0IjoxNjg0NDAyODM5LCJleHAiOjE2ODQ0MDY0MzksImFwcHR5cGUiOiJDb25maWRlbnRpYWwiLCJhcHBpZCI6Imh0dHBzOi8vbXlzZXJ2ZXJhcHAyLTE1LmNvbSIsImF1dGhtZXRob2QiOiJodHRwOi8vc2NoZW1hcy5taWNyb3NvZnQuY29tL3dzLzIwMDgvMDYvaWRlbnRpdHkvYXV0aGVudGljYXRpb25tZXRob2QvcGFzc3dvcmQiLCJhdXRoX3RpbWUiOiIyMDIzLTA1LTE4VDA5OjQwOjM5LjE3MloiLCJ2ZXIiOiIxLjAiLCJzY3AiOiJwcm9maWxlIn0.F6xLPw3Mh3YjgOKadfQjm320-zf8_HUpnFA9l1I6BgOB-nMAl4KhADreYPzBEgwpHRl8WWckuU51B3QIwfkCgI2mSjOT5w2YFZVzk9qCWH3thMFgjNE_MtuqJdrd_YTV-0UxqzPmNARtCkVFvOf3VW1w2JErToD9T1KiFxjfyMC30qe_JRjGW201u_yP-2Zumt6GH5AIt1fpPsTwTy7-qBWBg57nycW7sH_QQxQehm_D1uxyrxv2NvwMgDNdhauOknszV2nDexLLU4gSQ7__z-I9BlGSsPDjgfpZ0q50t1IcBXZZRPKwNJX6Qs2jj66GnDO1pKXaUotFdtBCT3RxYQ",
"token_type": "bearer",
"expires_in": 3600,
"scope": "profile"
}

Performances

Product for looking up performance prices, price availability and section seat availability.

2.1.2 Get Performance Map

Method	Endpoint
GET	https://et-apiuat.detsandbox.com/performances/{PerformanceCode}/map

Input Parameters

Parameter	Type
PerformanceCode	String

Response Sample

{
"productId": 48,
"performanceCode": "PVEN31DEC2023",
"name": "TEST SHOW 1",
"startDate": "2023-12-31T22:00:00",
"endDate": "2023-12-31T23:00:00",
"webSaleStartDate": "2023-12-31T22:00:00",
"webSaleEndDate": "2023-12-31T23:00:00",

```
            "showCode": "STES23",
            "venueCode": "فنيوز بي جي",
            "PermitNumber": "22CAP-00000-002KTx5",
            "priceCategories": [
            {
            "id": 82,
            "code": "1",
            "name": "GOLD",
            "maxQtyPerTransaction": 0
            }
            ],
            "sections": [
            {
            "id": 74,
            "code": "SGOLD",
            "name": "Gold",
            "categoryId": 82,
            "categoryCode": "",
            "capacity": 100000,
            "comps": 0,
            "holds": 0,
            "isGA": true
            }
            ],
"ticketPrices": [
            {
            "id": 167,
            "priceTag": "",
            "indexNumber": 0,
            "sheetId": 0,
            "sheetName": "",
            "categoryId": 82,
            "categoryCode": 1,
            "typeId": 88,
            "typeCode": "A",
            "feeId": "0",
            "feeCode": "",
            "faceValue": 0,
            "price": 1000.00,
            "faceValueGst": 0,
            "gst": 0,
            "gstRate": 0.0
            }
            ]
}
```


Output Parameters

Parameter	Type
productId	integer
performanceCode	string
name	string
startDate	string
endDate	string
webSaleStartDate	string
webSaleEndDate	string
showCode	string
venueCode	string
PermitNumber	string
priceCategories	Array of priceCategoriesType
sections	Array of sectionsType
ticketPrices	Array of ticketPricesType
priceTypes	Array of priceTypesType
fees	Array of feesType
code	string
hint	string
message	string
reference	string
httpStatusCode	string

PriceCategoriesType

Type for object pryceCategory

Parameter	Type
id	integer

code	string
name	string
maxQtyPerTransaction	integer

SectionsType

Type for object section

Parameter	Type
id	integer
code	string
name	string
categoryId	string
categoryCode	string
capacity	integer
comps	integer
holds	integer
isGA	boolean

TicketPriceType

Type for object ticketPrice

Parameter	Type
id	integer
priceTag	string
indexNumber	integer
sheetId	integer
sheetName	string
categoryId	integer

categoryCode	integer
typeId	integer
typeCode	string
feeId	string
feeCode	string
faceValue	integer
price	integer
faceValueGst	integer
gst	integer
gstRate	integer

PriceTypesType

Type for priceTypes

Parameter	Type
id	integer
code	string
name	integer
description	integer
admitCount	string
concessionCount	integer
comp	integer
hold	integer
offerCode	string
state	string
isPackage	integer

FeesType

Type for object fee

Parameter	Type
id	integer
sheetId	integer
code	string
name	string
admitCount	string
total	integer
gst	integer
gstRate	double

PackagesType

Type for object package

Parameter	Type
id	integer
name	string
description	string
priceTag	string
productDetails	Array of productDetailsType

ProductDetailsType

Type for object productDetails

Parameter	Type
productId	integer

performanceCode	string
priceId	integer
priceTag	string

2.1.3 Get Performance Prices

Method	Endpoint
GET	https://et-apiuat.detsandbox.com/performances/{PerformanceCode}/prices

Input Parameters

Parameter	Type
PerformanceCode	String

Response Sample


```
{
    "priceCategories": [
    {
    "priceCategoryId": 82,
    "priceCategoryCode": 1,
    "priceCategoryName": "GOLD"
    }
    ],
    "priceTypes": [
    {
    "priceTypeId": 88,
    "priceTypeCode": "A",
    "priceTypeName": "Adult",
    "priceTypeDescription": null,
    "priceSheetId": 0,
    "admitCount": 1,
    "concessionCount": 0,
    "offerCode": null,
    "qualifierCode": null,
    "entitlement": null
    }
    ],
    "basketPrices": [
```

```
        null
        ],
        "offerPrices": [
        {
        "prices": [
        null
        ],
        "feeTypes": [
        {
                "feeType": null,
                "feeTypeName": null,
                "inside": false,
                "feeBucket": null,
                "feesDetailed": [
                {
                "feeId": null,
                "feeSheetId": 0,
                "feeCode": null,
                "feeName": null,
                "feeDescription": null,
                "feeTotal": 0,
                "financeCode": null
                }
                ]
        }
        ]
        }
        ],
        "ticketPrices": [
        {
        "prices": [
        {
                "feeTypes": null,
                "priceCategoryCode": "1",
                "priceCategoryId": 82,
                "priceId": 167,
                "priceNet": 10000,
                "priceSheetId": 0,
                "priceTypeCode": "A",
                "priceTypeId": 88
        }
        ],
        "feeTypes": [
        null
        ]
        }
        ]
}
```


Output Parameters

Parameter	Type
priceCategories	Array of priceCategoriesType
priceTypes	Array of priceTypesType
basketPrices	Array of basketPricesType
offerPrices	Array of offersPriceType
ticketPrices	Array of ticketPricesType
id	integer
performanceCode	string

PriceCategoriesType

Type for object pryceCategory

Parameter	Type
priceCategoryId	integer
priceCategorycode	integer
priceCategoryname	string

PriceTypesType

Type for priceTypes

Parameter	Type
priceTypeId	integer
priceTypeCode	string
priceTypeName	string
priceTypeDescription	string
priceSheetId	integer
admitCount	integer
concessionCount	integer

qualifierCode	string
offerCode	string
entitlement	string

BasketPriceType

Type for object priceType

Parameter	Type
prices	Array of priceType

OffersPriceType

Type for object offerPrice

Parameter	Type
prices	Array of priceType
feesTypes	Array of feesTypesType

FeesTypesType

Type for object feesType

Parameter	Type
feeType	string
feeTypeName	string
inside	boolean
feeBucket	string
feesDetailed	Array of feesDetailedType

FeeDetailedType

Type for object feeDetailed

Parameter	Type
feeId	integer
feeSheetId	integer
feeCode	string
feeName	string
feeDescription	string
feeTotal	integer
financeCode	string

TicketPriceType

Type for object ticketPrice

Parameter	Type
prices	Array of priceType
feeTypes	Array of feeTypesType

PriceType

Type for object price

Parameter	Type
feeTypes	Array of feeTypesType
priceCategoryCode	integer
priceId	integer
priceNet	integer
priceSheetId	integer
priceTypeCode	string
priceTypeId	integer

2.1.4 Get Performance Availability

Method	Endpoint
GET	https://et-apiuat.detsandbox.com/performances/{PerformanceCode}/availabilities

Input Parameters

Parameter	Type
PerformanceCode	String

Response Sample


```
{
	"priceCategories": [
	{
	"priceCategoryId": 82,
	"priceCategoryCode": 1,
	"priceCategoryName": "GOLD",
	"availability": {
	"soldOut": false,
	"statusCode": "Ok"
	}
	}
	]
}
```


Output Parameters

Parameter	Type
priceCategories	Array of priceCategoriesType
performanceCode	string

PriceCategoriesType

Type for object pryceCategory

Parameter	Type
priceCategoryId	integer
priceCategorycode	integer
priceCategoryname	string
availability	availabilityType

AvailabilityType

Type for object availability

Parameter	Type
soldOut	boolean
statusCode	string

2.1.5 Get Section Seats

Method	Endpoint
GET	https://et-apiuat.detsandbox.com/performances/{PerformanceCode}/Sections/{SectionCode}

Input Parameters

Parameter	Type
PerformanceCode	String
SectionCode	string

Response Sample


```
{
        "id": "SSECTIONCC",
        "name": "Section CC",
        "stageDirection": 0,
        "isga": false,
```

```
        "priceCategory": 1,
        "capacity": 50,
        "row": [
        {
        "name": "A",
        "number": 451,
        "seat": [
        {
                "columnPos": 0,
                "rowPos": 0,
                "name": "1",
                "status": 0,
                "isRightAisle": false,
                "isLeftAisle": false,
                "isRightBarrier": false,
                "isLeftBarrier": false,
                "isUnavailable": false,
                "isHidden": false,
                "isObstructedView": false,
                "sectionName": "Section CC",
                "priceCategory": 1,
                "sourcePriceTypeId": null
        }]
         }
   ],
        "isFancyMap": false,
        "additionalInfo": null,
        "mapId": 0,
        "availableSeatCount": 0,
        "bestAvailableArea": ""
}
```


Output Parameters

Parameter	Type
id	string
name	string
stageDirection	integer
isga	boolean
priceCategory	integer
capacity	integer
availableCount	integer

holdCount	integer
row	Array of rowType
isFancyMap	boolean
additionalInfo	string
mapId	integer
availableSeatCount	integer
bestAvailableArea	string

RowType
Type for object row

Parameter	Type
priceCategoryId	integer
priceCategoryName	string
priceCategoryCode	string
name	string
number	integer
seat	Array of seatType

SeatType
Type for object seat

Parameter	Type
columnPos	integer
rowPos	integer
status	integer
name	string
isRightAisle	boolean
isLeftAisle	boolean
isRightBarrier	boolean

isLeftBarrier	boolean
isUnavailable	boolean
isHidden	boolean
isObstructedView	boolean
sectionName	string
priceCategory	integer
sourcePriceTypeId	string

Baskets

Use this API call for baskets creating, deleting, adding more items, removing items, purchasing and basket related details.

2.1.6 Create Basket

Method	Endpoint
POST	https://et-apiuat.detsandbox.com/baskets

Input Parameters

This request has no input parameters.

Input Payload

Parameter	Type
channel	string
seller	string
performanceCode	string
area	string

autoreduce	boolean
holdcode	string
seats	seatType
demand	Array of demandType
fees	Array of feeType

DemandType

Type for object demand

Parameter	Type
pricetypecode	string
quantity	integer
admits	integer
offercode	string
qualifiercode	string
entitlement	string
customer	customerType

FeeType

Type for object fees

Parameter	Type
type	string
code	string

SeatType

Type for object seats

Parameter	Type

section	string
row	string
seats	string
rz_str	string

CustomerType

Type for customer in DemandType

Parameter	Type
firstname	string
lastname	string
nationality	string
email	string
phonenumber	string
addressline1	string
city	string
postcode	string
countrycode	string

Note: Field "*Area*" represents the SectionCode only that can be retrieved from the performance Map api call.

Body Sample


```
{
  "Channel": "5",
  "Seller": "ATEST1",
  "Performancecode": "PVEN31DEC2023",
  "Area": "SS1",
  "autoReduce": false,
  "holdcode": "",
  "Demand": [
            {
            "PriceTypeCode": "A",
            "Quantity": 1,
```

```
            "Admits": 1,
            "offerCode": "",
            "qualifierCode": "",
            "entitlement": "",
            "Customer": {}
            }
 ],
 "seats": {
            "section": "SS1",
            "row": "A",
            "seats": "1-1"
 },
 "Fees": [
            {
            "Type": "5",
            "Code": "W"
            }
 ]
}
```


Output Parameters

Parameter	Type
id	string
originBasketId	string
offers	Array of offerType
fees	Array of feeType
basketID	integer
expiry	string
createDate	string
amount	integer
performanceCode	string
area	string
seller	string
channel	string
autoReduce	boolean

OfferType

Type for object offer

Parameter	Type
id	integer
dateTime	string
inventorySource	inventorySourceType
performanceCode	string
performanceCategoryCode	integer
performanceCategoryId	integer
priceCategory	string
seller	string
channel	string
demand	Array of demandType
seats	Array of seatType
fees	Array of feeType

FeeType

Type for object fees

Parameter	Type
id	integer
sheetId	integer
type	string
code	string
name	string
description	string
total	integer
financeCode	string

DemandType

Type for object demand

Parameter	Type
pricetypecode	string
priceTypeId	integer
priceType	string
quantity	integer
admits	integer
offerCode	string
qualifierCode	string
entitlement	string
prices	Array of priceDemandType

PriceDemandType

Type for object prices in object demand

Parameter	Type
id	integer
sheetId	integer
net	integer
fees	Array of feeDemandType

FeeDemandType

Type for object fees in prices of demand object

Parameter	Type
id	integer
sheetId	integer
type	string
code	string

typeName	string
fname	string
total	integer
bucket	string
inside	boolean
financeCode	string

Response Sample


```
{
        "id": "9002",
        "offers": [
        {
        "id": 11156,
        "dateTime": "2023-03-02T16:59:41.153",
        "inventorySource": {
        "name": "Sql",
        "id": "11156"
        },
        "performanceCode": "PVEN31DEC2023",
        "priceCategoryId": 82,
        "priceCategoryCode": 1,
        "priceCategory": null,
        "seller": "ATEST1",
        "channel": "API",
        "demand": [
        {
                "priceTypeId": 88,
                "priceTypeCode": "A",
                "priceType": null,
                "quantity": 1,
                "admits": 0,
                "offerCode": null,
                "qualifierCode": null,
                "entitlement": null,
                "prices": [
                {
                "id": null,
                "sheetId": 0,
                "net": 10000,
                "fees": [
                null
                ]
                }
                ]
```

```
            }
            ],
            "seats": [
            null
            ],
            "fees": [
            null
            ]
            }
            ],
            "fees": [
            null
            ],
            "expiry": "03/02/2023 17:19:41"
}
```


2.1.7 Add Items to a Basket

Method	Endpoint
POST	https://et-apiuat.detsandbox.com/baskets/{basketId}/offers

Input Parameters

Parameter	Type
basketId	integer

Input Payload

For this endpoint use the same input payload as Create Basket (2.1.5 of this document).

Response Sample


```
{
            "id": "9003",
            "expiry": "03/02/2023 17:50:06",
            "offers": [
            {
            "id": 11157,
            "dateTime": "2023-03-02T17:30:06.857",
            "inventorySource": {
            "name": "Sql",
            "id": "11157"
```

```
},
"performanceCode": "PVEN31DEC2023",
"priceCategoryId": 82,
"priceCategoryCode": 1,
"priceCategory": null,
"seller": "ATEST1",
"channel": "API",
"demand": [
{
        "priceTypeId": 88,
        "priceTypeCode": "A",
        "priceType": null,
        "quantity": 1,
        "admits": 0,
        "offerCode": null,
        "qualifierCode": null,
        "entitlement": null,
        "prices": [
        {
        "id": null,
        "sheetId": 0,
        "net": 10000,
        "fees": [
        null
        ]
        }
        ]
}
],
"seats": [
null
],
"fees": [
null
]
},
{
"id": 11158,
"dateTime": "2023-03-02T17:30:13.693",
"inventorySource": {
"name": "Sql",
"id": "11158"
},
"performanceCode": "PVEN31DEC2023",
"priceCategoryId": 82,
"priceCategoryCode": 1,
"priceCategory": null,
"seller": "ATEST1",
"channel": "API",
"demand": [
```

```
        {
                "priceTypeId": 88,
                "priceTypeCode": "A",
                "priceType": null,
                "quantity": 1,
                "admits": 0,
                "offerCode": null,
                "qualifierCode": null,
                "entitlement": null,
                "prices": [
                {
                "id": null,
                "sheetId": 0,
                "net": 10000,
                "fees": [
                null
                ]
                }
                ]
        }
        ],
        "seats": [
        null
        ],
        "fees": [
        null
        ]
        }
        ],
        "fees": [
        null
        ]
}
```


Output Parameters

The output parameters are the same ad Create Basket (2.1.5 of this document).

2.1.8 Delete an Item from Basket

Method	Endpoint
DELETE	https://et-apiuat.detsandbox.com/baskets/{basketId}/items/{itemId}

Input Parameter

Parameter	Type
basketId	integer
itemId	integer

Response Sample

204 - No Content

Output Parameter

Parameter	Type
statusCode	integer

2.1.9 View Basket

Method	Endpoint
GET	https://et-apiuat.detsandbox.com/baskets/{basketsId}

Input Parameter

Parameter	Type
basketId	integer

Response Sample


```
{
        "id": 9003,
        "offers": [
        {
```

```
"id": 11157,
"dateTime": "2023-03-02T17:30:06.857",
"inventorySource": {
"name": "Sql",
"id": "11157"
},
"performanceCode": "PVEN31DEC2023",
"priceCategoryId": 82,
"priceCategoryCode": 1,
"priceCategory": null,
"seller": "ATEST1",
"channel": "API",
"demand": [
{
        "priceTypeId": 88,
        "priceTypeCode": "A",
        "priceType": null,
        "quantity": 1,
        "admits": 0,
        "offerCode": null,
        "qualifierCode": null,
        "entitlement": null,
        "prices": [
        {
        "id": null,
        "sheetId": 0,
        "net": 10000,
        "fees": [
        null
        ]
        }
        ]
}
],
"seats": [
null
],
"fees": [
null
]
},
{
"id": 11158,
"dateTime": "2023-03-02T17:30:13.693",
"inventorySource": {
"name": "Sql",
"id": "11158"
},
"performanceCode": "PVEN31DEC2023",
"priceCategoryId": 82,
```

```
        "priceCategoryCode": 1,
        "priceCategory": null,
        "seller": "ATEST1",
        "channel": "API",
        "demand": [
        {
                "priceTypeId": 88,
                "priceTypeCode": "A",
                "priceType": null,
                "quantity": 1,
                "admits": 0,
                "offerCode": null,
                "qualifierCode": null,
                "entitlement": null,
                "prices": [
                {
                "id": null,
                "sheetId": 0,
                "net": 10000,
                "fees": [
                null
                ]
                }
                ]
        }
        ],
        "seats": [
        null
        ],
        "fees": [
        null
        ]
        }
        ],
        "fees": [
        null
        ]
}
```


Output Parameters

Parameter	Type
id	integer
originBasketId	string
offers	Array of offerType defined in CreateBasket (2.1.5 of this document)

fees	Array of feeDemandType defined in CreateBasket (2.1.5 of this document)

2.1.10 Delete Basket

Method	Endpoint
DELETE	https://et-apiuat.detsandbox.com/baskets/{basketId}

Input Parameter

Parameter	Type
basketId	integer

Output Parameter

Parameter	Type
statusCode	integer

Response Sample

204 - No Content

2.1.11 Purchase Basket

Method	Endpoint
POST	https://et-apiuat.detsandbox.com/baskets/{basketId}/purchase

Input Parameter

Parameter	Type
basketId	integer

Input Payload

Parameter	Type
customer	customerBasketType
seller	string
payments	Array of paymentType

CustomerBasketType

Type for object customer in purchase basket

Parameter	Type
id	integer
account	integer
afile	string

PaymentType

Type for object payment in purchase basket

Parameter	Type
amount	integer
meansofpayment	string

Body Sample

```
{
  "seller": "ATEST1",
  "customer": {
            "id": 1,
            "account": 0,
            "afile": "tel"
  },
  "payments": [
            {
```

"Amount": 10000,
"meansofpayment": "EXTERNAL"
}
]
}

Output Parameters

Parameter	Type
orderId	string

Response sample

{
"orderId": "9663"
}

Orders

Use for looking up and returning orders.

2.1.12 Get an Order Details

Method	Endpoint
GET	https://et-apiuat.detsandbox.com/orders/{orderId}

Input Parameter

Parameter	Type
orderId	integer

Response Sample

{
"id": "9664",
"dateTime": "2023-03-03T08:58:07.053",

```
"payments": [
{
"id": "9005",
"inventorySource": {
"name": "Sql",
"id": "9005"
}
}
],
"orderLines": [
{
"id": "be834c20-7050-404b-8274-646c92513559",
"dateTime": "2023-03-03T08:58:07.053",
"inventorySource": {
"name": "Sql",
"id": "11160"
},
"orderLineItems": [
{
        "id": "3447",
        "dateTime": "2023-03-03T08:58:07.053",
        "performanceCode": "PVEN31DEC2023",
        "priceCategoryId": 82,
        "priceCategoryCode": 1,
        "priceCategoryName": "GOLD",
        "seller": "ATEST1",
        "channel": "API",
        "priceTypeId": 88,
        "priceTypeCode": "A",
        "priceTypeName": "Adult",
        "offerCode": null,
        "qualifierCode": null,
        "entitlement": null,
        "concession": false,
        "customer": {
        "account": 1,
        "orgCustomerId": null,
        "id": 1
        },
        "price": {
        "id": 167,
        "sheetId": 0,
        "net": 10000,
        "fees": [
        {
        "id": null,
        "sheetId": 0,
        "type": null,
        "code": null,
        "typeName": null,
```

```
                "name": null,
                "total": 0,
                "bucket": null,
                "inside": false,
                "financeCode": null
                }
                ]
                },
                "seat": {
                "section": "SGOLD",
                "row": null,
                "seats": null
                }
        }
        ],
        "fees": [
        {
                "id": null,
                "sheetId": 0,
                "type": null,
                "code": null,
                "total": 0,
                "bucket": null,
                "inside": false,
                "financeCode": null
        }
        ]
        }
        ]
}
```


Output Parameters

Parameter	Type
id	integer
dateTime	string
payments	Array of paymentType
orderLines	Array of orderLineType
fees	Array of feeOrderType

PaymentType

Type for payment in Order

Parameter	Type
id	string
inventorySource	inventorySourceType

FeeOrderType

Type for fee in object Order

Parameter	Type
id	integer
sheetId	integer
type	string
code	string
typeName	string
name	string
total	integer
bucket	string
inside	boolean
financeCode	string

OrderLineType

Type for orderLine in object Order

Parameter	Type
id	string
dateTime	string
inventorySource	inventorySourceType
orderLineItems	Array of orderLineItemType

fees	Array of feesLineType

InventorySourceType
Type for inventorySource in OrderLines of order object

Parameter	Type
name	string
id	string

FeesLineType
Type for Fees in orderLines of object Order

Parameter	Type
id	integer
sheetId	integer
type	string
code	string
feeTypeName	string
feeName	string
total	integer
bucket	string
inside	boolean
financeCode	string

OrderLineItemType
Type for OrderLineTime in orderLines of object Order

Parameter	Type
id	string
dateTime	string
performanceCode	string
priceCategoryId	integer
priceCategoryCode	integer
priceCategoryName	string
seller	string
channel	string
priceTypeId	integer
priceTypeCode	string
priceTypeName	string
offerCode	string
qualifierCode	string
entitlement	string
concession	boolean
barCode	string
customer	customerOrderType
price	priceDemandType defined in CreateBasket (2.1.5 of this document)
seat	seatType defined in CreateBasket (2.1.5 of this document)

CustomerOrderType

Type for customer in OrderLineItem of object Order

Parameter	Type
afile	string
account	integer
ordCustomerId	integer
id	integer

2.1.13 Return an Order

Method	Endpoint
POST	https://et-apiuat.detsandbox.com/orders/{orderId}/reverse

Input Parameter

Parameter	Type
orderId	string

Input Payload

Parameter	Type
seller	string
refunds	Array of refundsType

RefundsType
Type for array refunds

Parameter	Type
amount	string
meansofpayment	string

Request Sample

```
{
	"seller":"ATEST1",
	"refunds": [
	{"amount":"10000",
	"meansofpayment":"EXTERNAL"}
	]
}
```

Output Parameter

Parameter	Type
statusCode	integer

Response Sample

204 - No Content

2.1.14 Return an Order Partially

Method	Endpoint
POST	https://et-apiuat.detsandbox.com/orders/{orderId}/{orderLineItem}

Input Parameter

Parameter	Type
orderId	string
orderLineItem	string

Input Payload

For this endpoint is enough to use the same payload used for Return Order (2.1.10 of this document)

Request Sample #1 (Refund OrderlineItem)

```
{
	"seller":"ATEST1",
	"refunds": [
	{
		"amount":"10000",
		"meansofpayment":"EXTERNAL"}
	]
}
```

Request Sample #2 (Refund Tickets)

```
{
        "seller":"ATEST1",
        "refunds": [
        {
                "TicketIds": [111,112],
                "meansofpayment":"EXTERNAL"}
        ]
}
```


Output Parameter

Parameter	Type
statusCode	integer

Response Sample

204 - No Content

Customers

Use for adding a new customer and editing an existing customer and looking up the customer.

2.1.15 Add a new Customer

Method	Endpoint
POST	https://et-apiuat.detsandbox.com/customers

Input Parameters

For this endpoint there is no need for any input parameter

Input Payload

Parameter	Type
salutation	string

firstname	string
lastname	string
nationality	string
email	string
dateofbirth	string
internationalcode	string
areacode	string
phonenumber	string
addressline1	string
addressline2	string
addressline3	string
city	string
state	string
countrycode	string

Request Sample

{
"salutation":"Mr",
"nationality":"PK",
"firstname":"test",
"lastname":"Junaid",
"dateofbirth":"1974-08-10",
"email":"test11@abc.com",
"addressline1":"Villa",
"addressline2":"e",
"city":"-",
"state":"-",
"countrycode":"AE",
"internationalcode":"+971",
"areacode":"50",
"phonenumber":"1504900"
}

Output Parameters

Parameter	Type
id	integer
account	integer
aFile	string

Response Sample


```
{
	"id": 8941,
	"account": 0,
	"aFile": "tel"
}
```


2.1.16 Update Customer

Method	Endpoint
PUT	https://et-apiuat.detsandbox.com/customers/{customerid}

Input Parameter

Parameter	Type
customerid	integer

Input Payload

The payload for this endpoint is the same used in Add a new customer (2.1.13 of this document)

Output Parameter

Parameter	Type
statusCode	integer

Response Sample

204 - No Content

2.1.17 Delete Customer

Method	Endpoint
DELETE	https://apiqa.detsandbox.com/customers/{customerid}

Input Parameter

Parameter	Type
customerid	integer

Output Parameter

Parameter	Type
statusCode	integer

Response Sample

204 - No Content

2.1.18 Get Customer

Method	Endpoint
GET	https://apiqa.detsandbox.com/customers/{customerid}

Input Parameter

Parameter	Type
customerid	integer

Output Parameter

Parameter	Type
id	integer
afile	string
account	integer
createdDateTime	string
organisationCustomerID	integer
salutation	string
firstName	string
lastName	string
nationality	string
email	string
dateofBirth	string
internationalCode	string
areaCode	string
phoneNumber	string
addressLine1	string
addressLine2	string
addressLine3	string

city	string
state	string
countryCode	string
postCode	string

Response sample


```
{
        "id": 8941,
        "account": null,
        "createdDateTime": "2023-03-03T10:11:20.297",
        "organisationCustomerID": 0,
        "salutation": "Mr",
        "firstName": "test",
        "lastName": "Junaid",
        "nationality": "PK",
        "email": "test11@abc.com",
        "dateOfBirth": "1974-08-10",
        "internationalCode": "+971",
        "areaCode": "50",
        "phoneNumber": "1504900",
        "addressLine1": "Villa",
        "addressLine2": "e",
        "addressLine3": null,
        "city": "-",
        "state": "-",
        "countryCode": "AE"
}
```


2.2. Error Messages

All the errors are handled as explained at point 6 of the document “Sales API v2.2 Integration Document.pdf” provided by DET.

Error Output Parameter

Parameter	Type

code	string
httpStatusCode	integer
message	string
hint	string

Error Response Sample


```
{
        "code": "5001",
        "httpStatusCode": 400,
        "message": "No basket found for the requested basket id.",
        "hint": ""
}
```


2.2.1 Error Messages


```
{
  "InternalErrors": [
    {
      "code": "1",
      "httpStatusCode": 500,
      "message": "An unexpected error occured. Please contact support.",
      "hint": ""
    },
    {
      "code": "2",
      "httpStatusCode": 400,
      "message": "Failed to validate requested record.",
      "hint": ""
    },
    {
      "code": "3",
      "httpStatusCode": 400,
      "message": "Internal db erorr.",
      "hint": ""
    },
    {
      "code": "4",
      "httpStatusCode": 400,
      "message": "Internal service error.",
      "hint": ""
    },
```

```
  {
    "code": "1001",
    "httpStatusCode": 401,
    "message": "Access token expired.",
    "hint": ""
  },
  {
    "code": "1002",
    "httpStatusCode": 401,
    "message": "Access token Not Found.",
    "hint": ""
  },
  {
    "code": "1003",
    "httpStatusCode": 401,
    "message": "Client is not active.",
    "hint": ""
  },
  {
    "code": "1004",
    "httpStatusCode": 401,
    "message": "Client Resource Access Not Found.",
    "hint": ""
  },
  {
    "code": "1005",
    "httpStatusCode": 401,
    "message": "Resource Not Found.",
    "hint": ""
  },
  {
    "code": "1006",
    "httpStatusCode": 401,
    "message": "GrantType Missing",
    "hint": ""
  },
  {
    "code": "1007",
    "httpStatusCode": 401,
    "message": "ClientId Missing",
    "hint": ""
  },
  {
    "code": "1008",
    "httpStatusCode": 401,
    "message": "Client Secret Missing",
    "hint": ""
  },
  {
    "code": "1009",
    "httpStatusCode": 401,
    "message": "Invalid GrantType",
    "hint": ""
  },
  {
    "code": "1010",
```

```
    "httpStatusCode": 401,
    "message": "Client Not Found",
    "hint": ""
  },
  {
    "code": "1011",
    "httpStatusCode": 401,
    "message": "Invalid Client Secret",
    "hint": ""
  },
  {
    "code": "1012",
    "httpStatusCode": 401,
    "message": "Invalid Client Credentials",
    "hint": ""
  },
  {
    "code": "2001",
    "httpStatusCode": 404,
    "message": "Product not found",
    "hint": ""
  },
  {
    "code": "2002",
    "httpStatusCode": 404,
    "message": "Section not found",
    "hint": ""
  },
        {
    "code": "2003",
    "httpStatusCode": 404,
    "message": "Error in PerformanceMAP API",
    "hint": ""
  },
  {
    "code": "3001",
    "httpStatusCode": 404,
    "message": "Customer Not Found",
    "hint": ""
  },
  {
    "code": "3002",
    "httpStatusCode": 404,
    "message": "Customer Mapping Error",
    "hint": ""
  },
  {
    "code": "3003",
    "httpStatusCode": 404,
    "message": "Seller UnAuthorised",
    "hint": ""
  },
  {
    "code": "4001",
    "httpStatusCode": 404,
    "message": "Order amount is missing",
```

```
    "hint": ""
  },
  {
    "code": "4002",
    "httpStatusCode": 404,
    "message": "Order not found",
    "hint": ""
  },
  {
    "code": "4003",
    "httpStatusCode": 404,
    "message": "Order item not found",
    "hint": ""
  },
  {
    "code": "4004",
    "httpStatusCode": 404,
    "message": "Order amout mismatch",
    "hint": ""
  },
  {
    "code": "4005",
    "httpStatusCode": 404,
    "message": "Order item amout mismatch",
    "hint": ""
  },
  {
    "code": "4006",
    "httpStatusCode": 404,
    "message": "Product is not active for refunds",
    "hint": ""
  },
  {
    "code": "5001",
    "httpStatusCode": 404,
    "message": "Basket not found",
    "hint": ""
  },
  {
    "code": "5002",
    "httpStatusCode": 404,
    "message": "Basket validation error",
    "hint": ""
  },
  {
    "code": "5003",
    "httpStatusCode": 404,
    "message": "Basket customer validation error",
    "hint": ""
  },
  {
    "code": "5004",
    "httpStatusCode": 404,
    "message": "Basket mapping error",
    "hint": ""
  },
```

```
    {
      "code": "5005",
      "httpStatusCode": 404,
      "message": "Basket seats no longer available",
      "hint": ""
    },
    {
      "code": "5006",
      "httpStatusCode": 404,
      "message": "Basket section soldout",
      "hint": ""
    },
    {
      "code": "5007",
      "httpStatusCode": 404,
      "message": "Basket price item not found",
      "hint": ""
    },
    {
      "code": "5008",
      "httpStatusCode": 404,
      "message": "Basket price type not found",
      "hint": ""
    },
    {
      "code": "5009",
      "httpStatusCode": 404,
      "message": "Basket section not found",
      "hint": ""
    },
    {
      "code": "5010",
      "httpStatusCode": 404,
      "message": "Basket product not found",
      "hint": ""
    }
  ]
}
```


2.2.2 List of Country Codes


```
{
   "AF":"Afghanistan",
   "AX":"Åand Islands",
   "AL":"Albania",
   "DZ":"Algeria",
   "AS":"American Samoa",
   "AD":"Andorra",
   "AO":"Angola",
   "AI":"Anguilla",
   "AQ":"Antarctica",
   "AG":"Antigua and Barbuda",
```

```
"AR":"Argentina",
"AM":"Armenia",
"AW":"Aruba",
"AU":"Australia",
"AT":"Austria",
"AZ":"Azerbaijan",
"BS":"Bahamas",
"BH":"Bahrain",
"BD":"Bangladesh",
"BB":"Barbados",
"BY":"Belarus",
"BE":"Belgium",
"BZ":"Belize",
"BJ":"Benin",
"BM":"Bermuda",
"BT":"Bhutan",
"BO":"Bolivia",
"BA":"Bosnia and Herzegovina",
"BW":"Botswana",
"BV":"Bouvet Island",
"BR":"Brazil",
"IO":"British Indian Ocean Territory",
"BN":"Brunei Darussalam",
"BG":"Bulgaria",
"BF":"Burkina Faso",
"BI":"Burundi",
"KH":"Cambodia",
"CM":"Cameroon",
"CA":"Canada",
"CV":"Cape Verde",
"KY":"Cayman Islands",
"CF":"Central African Republic",
"TD":"Chad",
"CL":"Chile",
"CN":"China",
"CX":"Christmas Island",
"CC":"Cocos (Keeling) Islands",
"CO":"Colombia",
"KM":"Comoros",
"CG":"Congo",
"CD":"Congo (The Democratic Republic of)",
"CK":"Cook Islands",
"CR":"Costa Rica",
"CI":"Côd'Ivoire",
"HR":"Croatia",
"CU":"Cuba",
"CY":"Cyprus",
"CZ":"Czech Republic",
"DK":"Denmark",
"DJ":"Djibouti",
"DM":"Dominica",
"DO":"Dominican Republic",
"EC":"Ecuador",
"EG":"Egypt",
"SV":"El Salvador",
"GQ":"Equatorial Guinea",
```

```
  "ER":"Eritrea",
  "EE":"Estonia",
  "ET":"Ethiopia",
  "FK":"Falkland Islands (Malvinas)",
  "FO":"Faroe Islands",
  "FJ":"Fiji",
  "FI":"Finland",
  "FR":"France",
  "GF":"French Guiana",
  "PF":"French Polynesia",
  "TF":"French Southern Territories",
  "GA":"Gabon",
  "GM":"Gambia",
  "GE":"Georgia",
  "DE":"Germany",
  "GH":"Ghana",
  "GI":"Gibraltar",
  "GR":"Greece",
  "GL":"Greenland",
  "GD":"Grenada",
  "GP":"Guadeloupe",
  "GU":"Guam",
  "GT":"Guatemala",
  "GG":"Guernsey",
  "GN":"Guinea",
  "GW":"Guinea-Bissau",
  "GY":"Guyana",
  "HT":"Haiti",
  "HM":"Heard Island and McDonald Islands",
  "VA":"Holy See (Vatican City State)",
  "HN":"Honduras",
  "HK":"Hong Kong",
  "HU":"Hungary",
  "IS":"Iceland",
  "IN":"India",
  "ID":"Indonesia",
  "IR":"Iran",
  "IQ":"Iraq",
  "IE":"Ireland",
  "IM":"Isle of Man",
  "IL":"Israel",
  "IT":"Italy",
  "JM":"Jamaica",
  "JP":"Japan",
  "JE":"Jersey",
  "JO":"Jordan",
  "KZ":"Kazakhstan",
  "KE":"Kenya",
  "KI":"Kiribati",
  "KP":"Korea (Democratic Peoples Republic)",
  "KR":"Korea (Republic of)",
  "KW":"Kuwait",
  "KG":"Kyrgystan",
  "LA":"Lao Peoples Democratic Republic",
  "LV":"Latvia",
  "LB":"Lebanon",
```

```
"LS":"Lesotho",
"LR":"Liberia",
"LY":"Libyan Arab Jamahiriya",
"LI":"Liechtenstein",
"LT":"Lithuania",
"LU":"Luxembourg",
"MO":"Macao",
"MK":"Macedonia (The Former Yugoslav Republic of)",
"MG":"Madagascar",
"MW":"Malawi",
"MY":"Malaysia",
"MV":"Maldives",
"ML":"Mali",
"MT":"Malta",
"MH":"Marshall Islands",
"MQ":"Martinique",
"MR":"Mauritania",
"MU":"Mauritius",
"YT":"Mayotte",
"MX":"Mexico",
"FM":"Micronesia (Federated States of)",
"MD":"Moldova (Republic of)",
"MC":"Monaco",
"MN":"Mongolia",
"ME":"Montenegro",
"MS":"Montserrat",
"MA":"Morocco",
"MZ":"Mozambique",
"MM":"Myanmar",
"NA":"Namibia",
"NR":"Nauru",
"NP":"Nepal",
"NL":"Netherlands",
"AN":"Netherlands Antilles",
"NC":"New Caledonia",
"NZ":"New Zealand",
"NI":"Nicaragua",
"NE":"Niger",
"NG":"Nigeria",
"NU":"Niue",
"NF":"Norfolk Island",
"MP":"Northern Mariana Islands",
"NO":"Norway",
"OM":"Oman",
"PK":"Pakistan",
"PW":"Palau",
"PS":"Palestinian Territory Occupied",
"PA":"Panama",
"PG":"Papua New Guinea",
"PY":"Paraguay",
"PE":"Peru",
"PH":"Philippines",
"PN":"Pitcairn",
"PL":"Poland",
"PT":"Portugal",
"PR":"Puerto Rico",
```

```
"QA":"Qatar",
"RE":"Réion",
"RO":"Romania",
"RU":"Russian Federation",
"RW":"Rwanda",
"SH":"Saint Helena",
"KN":"Saint Kitts and Nevis",
"LC":"Saint Lucia",
"PM":"Saint Pierre and Miquelon",
"VC":"Saint Vincent and the Grenadines",
"WS":"Samoa",
"SM":"San Marino",
"ST":"Sao Tome and Principe",
"SA":"Saudi Arabia",
"SN":"Senegal",
"RS":"Serbia",
"SC":"Seychelles",
"SL":"Sierra Leone",
"SG":"Singapore",
"SK":"Slovakia",
"SI":"Slovenia",
"SB":"Solomon Islands",
"SO":"Somalia",
"ZA":"South Africa",
"GS":"South Georgia and the South Sandwich Islands",
"ES":"Spain",
"LK":"Sri Lanka",
"SD":"Sudan",
"SR":"Suriname",
"SJ":"Svalbard and Jan Mayen",
"SZ":"Swaziland",
"SE":"Sweden",
"CH":"Switzerland",
"SY":"Syrian Arab Republic",
"TW":"Taiwan Province of China",
"TJ":"Tajikistan",
"TZ":"Tanzania (United Republic of)",
"TH":"Thailand",
"TL":"Timor-Leste",
"TG":"Togo",
"TK":"Tokelau",
"TO":"Tonga",
"TT":"Trinidad and Tobago",
"TN":"Tunisia",
"TR":"Turkey",
"TM":"Turkmenistan",
"TC":"Turks and Caicos Islands",
"TV":"Tuvalu",
"UG":"Uganda",
"UA":"Ukraine",
"AE":"United Arab Emirates",
"GB":"United Kingdom",
"US":"United States",
"UM":"United States Minor Outlying Islands",
"UY":"Uruguay",
"UZ":"Uzbekistan",
```

```
   "VU":"Vanuatu",
   "VE":"Venezuela",
   "VN":"Viet Nam",
   "VG":"Virgin Islands (British)",
   "VI":"Virgin Islands (U.S.)",
   "WF":"Wallis and Futuna",
   "EH":"Western Sahara",
   "YE":"Yemen",
   "ZM":"Zambia",
   "ZW":"Zimbabwe",
   "ZZ":"Not Supplied",
}
```