(Fine-tuned BERT) Encoder Comparison for Document Classification

Knowledge Processing in Intelligent Systems: Practical Seminar
Knowledge Technology, WTM
Department of Informatics, University of Hamburg

Sabrina Ebert
sabrina.ebert@studium.uni-hamburg.de

Muhammad Hamza
(email)

***Abstract*—Encoder models like BERT are small and cheap compared to large language models and are often used for classifying texts. LoRA makes fine-tuning them cheaper by training only a few small added matrices. It comes with several settings, such as rank, learning rate and which layers it is added to, and it is not clear to us which of them matter most for a small encoder. In this work we fine-tune BERT-base with LoRA for text classification on SST-2 and AG News and measure if and for which settings the classification performance changes, and by how much. We change one setting at a time, run every setting with three seeds and compare accuracy and macro F1 to a frozen BERT baseline. Our working hypothesis is that learning rate and LoRA placement change the performance more than the rank does. If time allows, we also take a first look inside the fine-tuned models with explainable AI methods, e.g. word attributions, to explain the results.**

I. Introduction and Motivation

- encoders small and cheap vs. LLMs
- LoRA: many settings, little guidance

II. Theoretical Background

A. BERT

B. LoRA

C. Related Work

III. Experimental Setup

- Kaggle, SST-2, AG News
- baseline, LoRA study, second dataset
- libraries: transformers, peft, scikit-learn, maybe captum (XAI)
- 3 seeds per setting

IV. Results

V. Discussion and Outlook

Acknowledgments and Use of Tools and AI

We used Claude Code (Anthropic) to set up the LaTeX layout, to suggest some of the references and to draft the abstract from our milestones and improve its grammar and wording. The topic, study design and working hypothesis are our own. We checked all text and references and take full responsibility for the content.

REFERENCES

[1] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of NAACL-HLT*, pages 4171–4186, 2019.

[2] Jesse Dodge, Gabriel Ilharco, Roy Schwartz, Ali Farhadi, Hannaneh Hajishirzi, and Noah Smith. Fine-tuning pretrained language models: Weight initializations, data orders, and early stopping. arXiv:2002.06305, 2020.

[3] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*, 2022.

[4] Richard Socher, Alex Perelygin, Jean Wu, Jason Chuang, Christopher D. Manning, Andrew Ng, and Christopher Potts. Recursive deep models for semantic compositionality over a sentiment treebank. In *Proceedings of EMNLP*, pages 1631–1642, 2013.

[5] Chi Sun, Xipeng Qiu, Yige Xu, and Xuanjing Huang. How to fine-tune BERT for text classification? In *China National Conference on Chinese Computational Linguistics (CCL)*, 2019.

[6] Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R. Bowman. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In *International Conference on Learning Representations (ICLR)*, 2019.

[7] Xiang Zhang, Junbo Zhao, and Yann LeCun. Character-level convolutional networks for text classification. In *Advances in Neural Information Processing Systems*, 2015.

APPENDIX: CODE