

# GXL2GV,GV2GXL

20 December 2002

## NAME

`gxl2gv`, `gv2gxl` - GXL-GV converters

## SYNOPSIS

```
gxl2gv [ -gd? ] [ -ooutfile ] [ files ]  
gv2gxl [ -gd? ] [ -ooutfile ] [ files ]
```

## DESCRIPTION

**gxl2gv** converts between graphs represented in GXL and in the GV language. Unless a conversion type is specified using a flag, **gxl2gv** will deduce the type of conversion from the suffix of the input file, a ".gv" suffix causing a conversion from GV to GXL, and a ".gxl" suffix causing a conversion from GXL to GV. If no suffix is available, e.g. when the input is from a pipe, and no flags are used then **gxl2gv** assumes the type of the input file from its executable name so that **gxl2gv** converts from GXL to GV, and **gv2gxl** converts from GV to GXL.

GXL supports a much richer graph model than GV. **gxl2gv** will attempt to map GXL constructs into the analogous GV construct when this is possible. If not, the GXL information is stored as an attribute. The intention is that applying **gxl2gv|gv2gxl** is semantically equivalent to the identity operator.

## OPTIONS

The following options are supported:

- g** The command name and input file extensions are ignored, the input is taken as a GV file and a GXL file is generated.
- d** The command name and input file extensions are ignored, the input is taken as a GXL file and a GV file is generated.

- ? Prints usage information and exits.
- o *outfile* If specified, the output will be written into the file *outfile*. Otherwise, output is written to standard out.

## OPERANDS

The following operand is supported:

***files*** Names of files containing 1 or more graphs in GXL or GV. If no *files* operand is specified, the standard input will be used.

## RETURN CODES

Both **gxl2gv** and **gv2gxl** return **0** if there were no problems during conversion; and non-zero if any error occurred.

## BUGS

**gxl2gv** will only convert in one direction even if given multiple files with varying suffixes.

The conversion can only handle one graph per GXL file.

There are some GXL constructs which **gxl2gv** cannot handle.

## AUTHORS

Krishnam Pericherla <kp@research.att.com>  
Emden R. Gansner <erg@research.att.com>

## SEE ALSO

dot(1), libgraph(3), libagraph(3), neato(1), twopi(1)