

GC

21 March 2001

NAME

gc - count graph components

SYNOPSIS

gc [**-necCaDUrsv?**] [*files*]

DESCRIPTION

gc is a graph analogue to **wc** in that it prints to standard output the number of nodes, edges, connected components or clusters contained in the input files. It also prints a total count for all graphs if more than one graph is given.

OPTIONS

The following options are supported:

- n** Count nodes.
- e** Count edges.
- c** Count connected components.
- C** Count clusters. By definition, a cluster is a graph or subgraph whose name begins with "cluster".
- a** Count all. Equivalent to **-encC**
- r** Recursively analyze subgraphs.
- s** Print no output. Only exit value is important.
- D** Only analyze directed graphs.
- U** Only analyze undirected graphs.

-v Verbose output.

-? Print usage information.

By default, *gc* returns the number of nodes and edges.

OPERANDS

The following operand is supported:

files Names of files containing 1 or more graphs in dot format. If no *files* operand is specified, the standard input will be used.

EXIT STATUS

The following exit values are returned:

0 Successful completion.

1 The **-U** or **-E** option was used, and a graph of the wrong type was encountered.

AUTHOR

Emden R. Gansner <erg@research.att.com>

SEE ALSO

wc(1), *acyclic*(1), *gvpr*(1), *gvcolor*(1), *ccomps*(1), *sccmap*(1), *tred*(1), *libgraph*(3)