

UNFLATTEN

21 January 2001

NAME

unflatten - adjust directed graphs to improve layout aspect ratio

SYNOPSIS

unflatten [-f?] [-llen] [-c*len*] [-o *outfile*] [*files*]

DESCRIPTION

unflatten is a preprocessor to **dot** that is used to improve the aspect ratio of graphs having many leaves or disconnected nodes. The usual layout for such a graph is generally very wide or tall. **unflatten** inserts invisible edges or adjusts the **minlen** on edges to improve layout compaction.

OPTIONS

The following options are supported:

- l *len*** The minimum length of leaf edges is staggered between 1 and *len* (a small integer).
- f** Enables the staggering of the **-l** option to fanout nodes whose indegree and outdegree are both 1. This helps with structures such as $a \rightarrow \{w\ x\ y\ z\}$ $\rightarrow b$. This option only works if the **-l** flag is set.
- c *len*** Form disconnected nodes into chains of up to *len* nodes.
- o *outfile*** causes the output to be written to the specified file; by default, output is written to **stdout**.
- ?** Prints the usage and exits.

OPERANDS

The following operand is supported:

files Names of files containing 1 or more graphs in dot format. If no *files* operand is specified, the standard input will be used.

AUTHORS

Stephen C. North <north@research.att.com>

Emden R. Gansner <erg@research.att.com>

SEE ALSO

gc(1), dot(1), acyclic(1), gvpr(1), gvcolor(1), ccomps(1), tred(1), libgraph(3)