

Report 'default'

Table Of Contents

Report for ForeignKeys	1
Table(s) of Model "RawEuropeanCarManufacturer"	3
Column(s) of Table "CommonColumnsForTriggerTemplate"	3
Column(s) of Table "Country"	3
Column(s) of Table "Customer"	3
Column(s) of Table "ManufacturerModel"	3
Column(s) of Table "ManufacturerVehicleMake"	3
Column(s) of Table "ManufacturerVehicleStock"	4
Column(s) of Table "MarketingCategory"	4
Column(s) of Table "MarketingInformation"	4
Column(s) of Table "SalesCategoryThreshold"	4
Column(s) of Table "SalesOrderVehicle"	5
Column(s) of Table "SalesOrderVehicleDetail"	5
Column(s) of Table "Staff"	5
Column(s) of Table "sysdiagrams"	5
Column(s) of Table "DbSecurity.UserAuthorization"	5
Column(s) of Table "Customer"	6
Column(s) of Table "Country"	6
Column(s) of Table "ManufacturerVehicleStock"	7
Column(s) of Table "Staff"	7
Column(s) of Table "SalesOrderVehicleDetail"	8
Column(s) of Table "ManufacturerModel"	8
Column(s) of Table "ManufacturerVehicleMake"	8
Column(s) of Table "MarketingCategoryLookupTable"	9
Column(s) of Table "MarketingInformationLookupTable"	9
Column(s) of Table "CategorySalesThresholdLookupTable"	9
Index	

Table(s) of Model "RawEuropeanCarManufacturer"

Column(s) of Table "CommonColumnsForTriggerTemplate"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
Note	CommonColumnsForTriggerTemplate	Note are any notes of the item selected.	false	nvarchar(200)
IsDeleted	CommonColumnsForTriggerTemplate	IsDeleted answers if the item was deleted or not.	false	bit
TransactionNumber	CommonColumnsForTriggerTemplate	TransactionNumber is the transaction number of the tables.	false	int
UserAuthenticatedKey	CommonColumnsForTriggerTemplate	UserAuthenticatedKey is the authenticated key of the user.	false	int
Sys_Start_Time	CommonColumnsForTriggerTemplate	SysStartTime is the start time of the system.	false	Datetime2(7)
Sys_End_Time	CommonColumnsForTriggerTemplate	SysEndTime is the end time of the system.	false	Datetime2(7)

Column(s) of Table "Country"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
CountryId	Country	CountryId is the id of the country.	false	int
CountryISO3	Country	CountryISO3 is the ISO3 code used to identify a country.	false	char(3)
CountryName	Country	CountryName is the name of the country.	false	nvarchar(100)
CountryISO2	Country	CountryISO2 is the ISO2 code used to identify a country.	false	char(2)
SalesRegion	Country	SalesRegion is the region of sale made.	false	nvarchar(20)

Column(s) of Table "Customer"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
CustomerId	Customer	CustomerId is the id of the customer.	false	int
CustomerName	Customer	CustomerName is the name of the customer.	false	nvarchar(100)
CustomerAddress1	Customer	CustomerAddress1 is the first part of the customer's address.	false	nvarchar(50)
CustomerAddress2	Customer	CustomerAddress2 is the continuation part of the customer's address.	false	nvarchar(50)
CustomerTown	Customer	CustomerTown is the town of the customer.	false	nvarchar(50)
CustomerPostalCode	Customer	CustomerPostalCode is the postal code of the customer.	false	nvarchar(10)
CustomerCountry	Customer	CustomerCountry is the country of the customer.	false	char(2)
IsCustomeReseller	Customer	IsCustomerReseller answers if the customer is a reseller or not.	false	bit
IsCustomerCreditRisk	Customer	IsCustomerCreditRisk answers if the customer is at a credit risk or not.	false	bit
CustomerSpendCapacityId	Customer	CustomerSpendCapacityId is an id assigned to customer based on their spending capacity.	false	int

Column(s) of Table "ManufacturerModel"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
ManufacturerModelId	ManufacturerModel	ManufacturerModelId is the model id of the manufacturer.	false	int
ManufacturerModelName	ManufacturerModel	ManufacturerModelName is the model name of the manufacturer.	false	nvarchar(100)
ManufacturerModelVariant	ManufacturerModel	ManufacturerModelVariant is the model variant of the manufacturer.	false	char(3)
ManufacturerVehicleStockId	ManufacturerModel	ManufacturerVehicleStockId is the stock id of the manufacturer vehicle.	true	int

Column(s) of Table "ManufacturerVehicleMake"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
---------------	-------------	----------	-------	--------------------

ManufacturerVehicleMakeId	ManufacturerVehicleMake	ManufacturerVehicleMakeId is the make id for the manufacturer vehicle.	false	int
ManufacturerVehicleMakeName	ManufacturerVehicleMake	ManufacturerVehicleMakeName is the name of the make of manufacturer of the vehicle.	false	nvarchar(100)
ManufacturerVehicleMakeCountry	ManufacturerVehicleMake	ManufacturerVehicleMakeCountry is the country of the make of manufacturer of the vehicle.	false	char(3)
MarketingTypeId	ManufacturerVehicleMake	Create a lookup table with a primary Key MarketingTypeId based upon the [dbo].[MarketingCategory] table. Make sure not to create data anomalies. MarketingTypeId is the id of the marketing type used.	false	int

Column(s) of Table "ManufacturerVehicleStock"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
ManufacturerVehicleStockId	ManufacturerVehicleStock	ManufacturerVehicleStockId is the stock id of the manufacturer vehicle.	false	int
StockId	ManufacturerVehicleStock	StockId is the id of the vehicle in stock.	false	int
StockCode	ManufacturerVehicleStock	StockCode is the code of the vehicle in stock.	false	nvarchar(50)
ModelId	ManufacturerVehicleStock	ModelId is the id of the model of vehicle.	false	int
Cost	ManufacturerVehicleStock	Cost is the price of the vehicle.	false	numeric(18,2)
RepairsCharge	ManufacturerVehicleStock	RepairsCharge is the price of repairs for the vehicle. This has a validation rule of a charge from a number 0 - 9999999999999999 since the data type is numeric(18,2)	false	numeric(18,2)
PartsCharge	ManufacturerVehicleStock	PartsCharge is the price of the parts of the vehicle. This has a validation rule of a charge from a number 0 - 9999999999999999 since the data type is numeric(18,2)	false	numeric(18,2)
DeliveryCharge	ManufacturerVehicleStock	DeliveryCharge is the price of the delivery of the vehicle. This has a validation rule of a charge from a number 0 - 9999999999999999 since the data type is numeric(18,2)	false	numeric(18,2)
IsPremiumRoadHandlingPackage	ManufacturerVehicleStock	IsPremiumRoadHandlingPackage is if the vehicle has the premium road handling package. This has a default value of 1.	false	bit
VehicleColor	ManufacturerVehicleStock	VehicleColor is the color of the vehicle.	false	nvarchar(50)
CustomerComments	ManufacturerVehicleStock	CustomerComments are any comments the customer would like to make on the vehicle.	false	nvarchar(4000)
PurchaseDate	ManufacturerVehicleStock	PurchaseDate is the date at which the vehicle was purchased.	false	date

Column(s) of Table "MarketingCategory"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
MakeName	MarketingCategory	MakeName is the name of the marketing.	false	nvarchar(100)
MarketingType	MarketingCategory	MarketingType is the type of marketing used in the sale.	false	nvarchar(200)

Column(s) of Table "MarketingInformation"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
CustomerId	MarketingInformation	CustomerId is the id of the customer.	true	int
CustomerName	MarketingInformation	CustomerName is the name of the customer.	false	nvarchar(100)
Country	MarketingInformation	Country is the country the customer lives in.	false	char(2)
SpendCapacity	MarketingInformation	SpendCapacity is the amount the customer is willing to spend. Has a validation of greater than 0 because you want the spender to spend more than 0 to whichever value they like.	false	numeric(18,2)

Column(s) of Table "SalesCategoryThreshold"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
---------------	-------------	----------	-------	--------------------

LowerThreshold	SalesCategoryThreshold	LowerThreshold is the minimum parameter of the sale.	false	int
UpperThreshold	SalesCategoryThreshold	UpperThreshold is the maximum parameter of the sale.	false	int
CategoryDescription	SalesCategoryThreshold	CategoryDescription is the description of the sale items.	false	nvarchar(4000)

Column(s) of Table "SalesOrderVehicle"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
SalesOrderVehicleId	SalesOrderVehicle	SalesOrderVehicleId is the vehicle id for the sales order.	false	int
CustomerId	SalesOrderVehicle	CustomerId is the id of the customer.	true	int
StaffId	SalesOrderVehicle	StaffId is the id of the staff member.	true	int
InvoiceNumber	SalesOrderVehicle	InvoiceNumber is the invoice number of the sales order.	false	nchar(8)
TotalSalePrice	SalesOrderVehicle	TotalSalePrice is the total amount of the sale.	false	numeric(18,2)
SaleDate	SalesOrderVehicle	SaleDate is the date at which the sale was made.	false	date
CategoryDescription	SalesOrderVehicle	CategoryDescription is the description of the sale.	false	nvarchar(4000)

Column(s) of Table "SalesOrderVehicleDetail"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
SalesOrderVehicleDetailId	SalesOrderVehicleDetail	SalesOrderVehicleDetailId is the id of the vehicle in the sales order.	false	int
SalesOrderVehicleId	SalesOrderVehicleDetail	SalesOrderVehicleId is the vehicle id of the sale.	false	int
LineItemNumber	SalesOrderVehicleDetail	LineItemNumber is the item number of an item on a sales order.	false	int
StockId	SalesOrderVehicleDetail	StockId is the id of a stock item.	false	int
StockCode	SalesOrderVehicleDetail	StockCode is the code of a stock item.	false	nvarchar(50)
SalePrice	SalesOrderVehicleDetail	SalePrice is the price of the sale item.	false	numeric(18,2)
LineItemDiscount	SalesOrderVehicleDetail	LineItemDiscount is the discount applied to a item in an order.	false	numeric(18,2)
DerivedDiscountedSalePrice	SalesOrderVehicleDetail	DerivedDiscountedSalePrice is the price that is discounted to a sale item.	false	numeric(18,2)

Column(s) of Table "Staff"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
StaffId	Staff	StaffId is the id of the staff member.	false	int
StaffName	Staff	StaffName is the name of the staff member.	false	nvarchar(100)
ManagerID	Staff	ManagerID is the id of the manager member.	false	int
Department	Staff	Department is the section the staff member works in.	false	nvarchar(30)

Column(s) of Table "sysdiagrams"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
Name	sysdiagrams	name is the name of the diagrams.	false	nvarchar(30)
PrincipalId	sysdiagrams	principal_id is the id of the principal of the diagrams.	false	int
DiagramId	sysdiagrams	diagram_id is the id of the diagram.	false	int
Version	sysdiagrams	version is the version of the diagrams.	false	int
Definition	sysdiagrams	definition is the definition of the diagrams.	false	nvarchar(4000)

Column(s) of Table "DbSecurity.UserAuthorization"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
---------------	-------------	----------	-------	--------------------

UserAuthorizationId	DbSecurity.UserAuthorization	UserAuthorizationId is the authorization id of the user.	false	int
ClassTime	DbSecurity.UserAuthorization	ClassTime is the time the class starts.	false	nvarchar(5)
IndividualProject	DbSecurity.UserAuthorization	IndividualProject is the name of the project.	false	nvarchar(30)
GroupMemberLastName	DbSecurity.UserAuthorization	GroupMemberLastName is the last name of the group member.	false	nvarchar(30)
GroupMemberFirstName	DbSecurity.UserAuthorization	GroupMemberFirstName is the first name of the group member.	false	nvarchar(30)
GroupName	DbSecurity.UserAuthorization	GroupName is the name of the group.	false	nvarchar(20)
SysStartTime	DbSecurity.UserAuthorization	SysStartTime is the start time of the system.	false	Datetime2(7)
SysEndTime	DbSecurity.UserAuthorization	SysEndTime is the end time of the system.	false	Datetime2(7)

Column(s) of Table "Customer"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
SysStartTime	Customer	SysStartTime is the start time of the system.	false	Datetime2(7)
SysEndTime	Customer	SysEndTime is the end time of the system.	false	Datetime2(7)
Note	Customer	Note are any notes of the item selected.	false	nvarchar(200)
TransactionNumber	Customer	TransactionNumber is the transaction number of the tables.	false	int
IsDeleted	Customer	IsDeleted answers if the item was deleted or not. This has a default value of 0	false	bit
CustomerName	Customer	CustomerName is the name of the customer.	false	nvarchar(100)
CustomerAddress1	Customer	CustomerAddress1 is the first part of the customer's address.	false	nvarchar(50)
CustomerAddress2	Customer	CustomerAddress2 is the continuation part of the customer's address.	false	nvarchar(50)
CustomerTown	Customer	CustomerTown is the town of the customer.	false	nvarchar(50)
CustomerCountry	Customer	CustomerCountry is the country of the customer.	false	char(2)
IsCustomerReseller	Customer	IsCustomerReseller answers if the customer is a reseller or not. This gets a default value of 1	false	bit
IsCostumerCreditRisk	Customer	IsCustomerCreditRisk answers if the customer is at a credit risk or not. This gets a default value of 1	false	bit
CustomerSpendCapacityId	Customer	CustomerSpendCapacityId is an id assigned to customer based on their spending capacity. This gets a validation rule because the customer can have a spending limit from 0-9999999999999999	false	int
CustomerPostalCode	Customer	CustomerPostalCode is the postal code of the customer.	false	nvarchar(10)
CustomerId	Customer	CustomerId is the id of the customer.	false	int

Column(s) of Table "Country"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
UserAuthenticatedKey	Country	UserAuthenticatedKey is the authenticated key of the user.	false	int
SysStartTime	Country	SysStartTime is the start time of the system.	false	Datetime2(7)
SysEndTime	Country	SysEndTime is the end time of the system.	false	Datetime2(7)
IsDeleted	Country	IsDeleted answers if the item was deleted or not.	false	bit
TransactionNumber	Country	TransactionNumber is the transaction number of the tables.	false	int
Note	Country	Note are any notes of the item selected.	false	nvarchar(200)

CountryISO3	Country	CountryISO3 is the ISO3 code used to identify a country.	false	char(3)
CountryName	Country	CountryName is the name of the country.	false	nvarchar(100)
CountryISO2	Country	CountryISO2 is the ISO2 code used to identify a country.	false	char(2)
SalesRegion	Country	SalesRegion is the region of sale made.	false	nvarchar(20)
CountryId	Country	CountryId is the id of the country.	false	int

Column(s) of Table "ManufacturerVehicleStock"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
StockId	ManufacturerVehicleStock	StockId is the id of the vehicle in stock.	false	int
StockCode	ManufacturerVehicleStock	StockCode is the code of the vehicle in stock.	false	nvarchar(50)
ModelID	ManufacturerVehicleStock	ModelID is the id of the model of vehicle.	false	int
Cost	ManufacturerVehicleStock	Cost is the price of the vehicle.	false	numeric(18,2)
RepairsCharge	ManufacturerVehicleStock	RepairsCharge is the price of repairs for the vehicle. This has a validation rule of a charge from a number 0 - 9999999999999999 since the data type is numeric(18,2)	false	numeric(18,2)
PartsCharge	ManufacturerVehicleStock	PartsCharge is the price of the parts of the vehicle. This has a validation rule of a charge from a number 0 - 9999999999999999 since the data type is numeric(18,2)	false	numeric(18,2)
DeliveryCharge	ManufacturerVehicleStock	DeliveryCharge is the price of the delivery of the vehicle. This has a validation rule of a charge from a number 0 - 9999999999999999 since the data type is numeric(18,2)	false	numeric(18,2)
IsPremiumRoadHandlingPackage	ManufacturerVehicleStock	IsPremiumRoadHandlingPackage is if the vehicle has the premium road handling package. This has a default value of 1.	false	bit
VehicleColor	ManufacturerVehicleStock	VehicleColor is the color of the vehicle.	false	nvarchar(50)
CustomerComments	ManufacturerVehicleStock	CustomerComments are any comments the customer would like to make on the vehicle.	false	nvarchar(4000)
PurchaseDate	ManufacturerVehicleStock	PurchaseDate is the date at which the vehicle was purchased.	false	date
Note	ManufacturerVehicleStock	Note are any notes of the item selected.	false	nvarchar(200)
IsDeleted	ManufacturerVehicleStock	IsDeleted answers if the item was deleted or not.	false	bit
TransactionNumber	ManufacturerVehicleStock	TransactionNumber is the transaction number of the tables.	false	int
UserAuthenticatedKey	ManufacturerVehicleStock	UserAuthenticatedKey is the authenticated key of the user.	false	int
SysStartTime	ManufacturerVehicleStock	SysStartTime is the start time of the system.	false	Datetime2(7)
SysEndTime	ManufacturerVehicleStock	SysEndTime is the end time of the system.	false	Datetime2(7)
ManufacturerVehicleStockId	ManufacturerVehicleStock	ManufacturerVehicleStockId is the stock id of the manufacturer vehicle.	false	int

Column(s) of Table "Staff"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
StaffName	Staff	StaffName is the name of the staff member.	false	nvarchar(100)
ManagerID	Staff	ManagerID is the id of the manager member.	false	int
Department	Staff	Department is the section the staff member works in.	false	nvarchar(30)
StaffId	Staff	StaffId is the id of the staff member.	false	int
Note	Staff	Note are any notes of the item selected.	false	nvarchar(200)

IsDeleted	Staff	IsDeleted answers if the item was deleted or not. We will set is to 0 as a default value.	false	bit
TransactionNumber	Staff	TransactionNumber is the transaction number of the tables.	false	int
UserAuthenticatedKey	Staff	UserAuthenticatedKey is the authenticated key of the user.	false	int
Sys_Start_Time	Staff	SysStartTime is the start time of the system.	false	Datetime2(7)
Sys_End_Time	Staff	SysEndTime is the end time of the system.	false	Datetime2(7)

Column(s) of Table "SalesOrderVehicleDetail"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
SalesOrderVehicleId	SalesOrderVehicleDetail	SalesOrderVehicleId is the vehicle id of the sale.	true	int
LineItemNumber	SalesOrderVehicleDetail	LineItemNumber is the item number of an item on a sales order.	false	int
StockId	SalesOrderVehicleDetail	StockId is the id of a stock item.	false	int
StockCode	SalesOrderVehicleDetail	StockCode is the code of a stock item.	false	nvarchar(50)
SalePrice	SalesOrderVehicleDetail	SalePrice is the price of the sale item.	false	numeric(18,2)
LineItemDiscount	SalesOrderVehicleDetail	LineItemDiscount is the discount applied to a item in an order.	false	numeric(18,2)
DerivedDiscountedSalePrice	SalesOrderVehicleDetail	DerivedDiscountedSalePrice is the price that is discounted to a sale item.	false	CHAR(18)
SalesOrderVehicleDetailId	SalesOrderVehicleDetail	SalesOrderVehicleDetailId is the id of the vehicle in the sales order.	false	int
Note	SalesOrderVehicleDetail	Note are any notes of the item selected.	false	nvarchar(200)
IsDeleted	SalesOrderVehicleDetail	IsDeleted answers if the item was deleted or not.	false	bit
TransactionNumber	SalesOrderVehicleDetail	TransactionNumber is the transaction number of the tables.	false	int
UserAuthenticatedKey	SalesOrderVehicleDetail	UserAuthenticatedKey is the authenticated key of the user.	false	int
Sys_Start_Time	SalesOrderVehicleDetail	SysStartTime is the start time of the system.	false	Datetime2(7)
Sys_End_Time	SalesOrderVehicleDetail	SysEndTime is the end time of the system.	false	Datetime2(7)

Column(s) of Table "ManufacturerModel"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
ManufacturerModelName	ManufacturerModel	ManufacturerModelName is the model name of the manufacturer.	false	nvarchar(100)
ManufacturerModelVariant	ManufacturerModel	ManufacturerModelVariant is the model variant of the manufacturer.	false	char(3)
ManufacturerModelId	ManufacturerModel	ManufacturerModelId is the model id of the manufacturer.	false	int
Note	ManufacturerModel	Note are any notes of the item selected.	false	nvarchar(200)
IsDeleted	ManufacturerModel	IsDeleted answers if the item was deleted or not. This has a default value of 0	false	bit
TransactionNumber	ManufacturerModel	TransactionNumber is the transaction number of the tables.	false	int
UserAuthenticatedKey	ManufacturerModel	UserAuthenticatedKey is the authenticated key of the user.	false	int
SysStartTime	ManufacturerModel	SysStartTime is the start time of the system.	false	Datetime2(7)
SysEndTime	ManufacturerModel	SysEndTime is the end time of the system.	false	Datetime2(7)

Column(s) of Table "ManufacturerVehicleMake"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
ManufacturerVehicleMakeName	ManufacturerVehicleMake	ManufacturerVehicleMakeName is the name of the make of manufacturer of the vehicle.	false	nvarchar(100)
ManufacturerVehicleMakeCountry	ManufacturerVehicleMake	ManufacturerVehicleMakeCountry is the country of the make of manufacturer of the vehicle.	false	char(3)

MarketingTypeld	ManufacturerVehicleMake	Create a lookup table with a primary Key MarketingTypeld based upon the [dbo].[MarketingCategory] table. Make sure not to create data anomalies. MarketingTypeld is the id of the marketing type used.	false	int
ManufacturerVehicleMakeld	ManufacturerVehicleMake	ManufacturerVehicleMakeld is the make if for the manufacturer vehicle.	false	int
Note	ManufacturerVehicleMake	Note are any notes of the item selected.	false	nvarchar(200)
IsDeleted	ManufacturerVehicleMake	IsDeleted answers if the item was deleted or not. This has a default value of 0	false	bit
TransactionNumber	ManufacturerVehicleMake	TransactionNumber is the transaction number of the tables.	false	int
UserAuthenticatedKey	ManufacturerVehicleMake	UserAuthenticatedKey is the authenticated key of the user.	false	int
Sys_Start_Time	ManufacturerVehicleMake	SysStartTime is the start time of the system.	false	Datetime2(7)
Sys_End_Time	ManufacturerVehicleMake	SysEndTime is the end time of the system.	false	Datetime2(7)

Column(s) of Table "MarketingCategoryLookupTable"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
MarketingTypeld	MarketingCategoryLookupTable	MarketingTypeld is the id for the marketing type.	false	nvarchar(200)
MakeName	MarketingCategoryLookupTable	MakeName is the name of the marketing.	false	nvarchar(100)
MarketingType	MarketingCategoryLookupTable	MarketingType is the type of marketing used in the sale.	false	nvarchar(200)

Column(s) of Table "MarketingInformationLookupTable"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
CustomerSpendCapacityId	MarketingInformationLookupTable	CustomerSpendCapacityId is the id for the customer's spend capacity.	false	numeric(18,2)
CustomerName	MarketingInformationLookupTable	CustomerName is the name of the customer.	false	int
Country	MarketingInformationLookupTable	Country is the country the customer lives in.	false	char(2)

Column(s) of Table "CategorySalesThresholdLookupTable"

Physical Name	@Table Name	Comments	Is FK	Physical Data Type
LowerThreshold	CategorySalesThresholdLookupTable	LowerThreshold is the minimum parameter of the sale.	false	int
UpperThreshold	CategorySalesThresholdLookupTable	UpperThreshold is the maximum parameter of the sale.	false	int
CategoryDescription	CategorySalesThresholdLookupTable	CategoryDescription is the description of the sale items.	false	nvarchar(4000)

Index

C

CategoryDescription 6, 10
CategorySalesThresholdLookupTable 10
ClassTime 7
CommonColumnsForTriggerTemplate 4
Cost 5, 8
Country 4, 5, 7, 8, 10
CountryId 4, 8
CountryISO2 4, 8
CountryISO3 4, 8
CountryName 4, 8
Customer 4, 7
CustomerAddress1 4, 7
CustomerAddress2 4, 7
CustomerComments 5, 8
CustomerCountry 4, 7
CustomerId 4, 5, 6, 7
CustomerName 4, 5, 7, 10
CustomerPostalCode 4, 7
CustomerSpendCapacityId 4, 7, 10
CustomerTown 4, 7

D

DbSecurity.UserAuthorization 6, 7
Definition 6
DeliveryCharge 5, 8
Department 6, 8
DerivedDiscountedSalePrice 6, 9
DiagramId 6

G

GroupMemberFirstName 7
GroupMemberLastName 7
GroupName 7

I

IndividualProject 7
InvoiceNumber 6
IsCustomerCreditRisk 7
IsCustomerCreditRisk 4
IsCustomerReseller 4
IsCustomerReseller 7
IsDeleted 4, 7, 8, 9, 10
IsPremiumRoadHandlingPackage 5, 8

L

LineItemDiscount 6, 9
LineItemNumber 6, 9
LowerThreshold 6, 10

M

MakeName 5, 10
ManagerID 6, 8
ManufacturerModel 4, 9
ManufacturerModelId 4, 9
ManufacturerModelName 4, 9
ManufacturerModelVariant 4, 9
ManufacturerVehicleMake 4, 5, 9, 10
ManufacturerVehicleMakeCountry 5, 9
ManufacturerVehicleMakeId 5, 10
ManufacturerVehicleMakeName 5, 9
ManufacturerVehicleStock 5, 8
ManufacturerVehicleStockId 4, 5, 8
MarketingCategory 5
MarketingCategoryLookupTable 10
MarketingInformation 5
MarketingInformationLookupTable 10
MarketingType 5, 10
MarketingTypeId 5, 10

ModelID 5, 8

N

Name 6

Note 4, 7, 8, 9, 10

P

PartsCharge 5, 8

PrincipalId 6

PurchaseDate 5, 8

R

RawEuropeanCarManufacturer 4

RepairsCharge 5, 8

S

SaleDate 6

SalePrice 6, 9

SalesCategoryThreshold 5, 6

SalesOrderVehicle 6

SalesOrderVehicleDetail 6, 9

SalesOrderVehicleDetailId 6, 9

SalesOrderVehicleId 6, 9

SalesRegion 4, 8

SpendCapacity 5

Staff 6, 8, 9

StaffId 6, 8

StaffName 6, 8

StockCode 5, 6, 8, 9

StockId 5, 6, 8, 9

Sys_End_Time 4, 9, 10

Sys_Start_Time 4, 9, 10

S

sysdiagrams 6

S

SysEndTime 7, 8, 9

SysStartTime 7, 8, 9

T

TotalSalePrice 6

TransactionNumber 4, 7, 8, 9, 10

U

UpperThreshold 6, 10

UserAuthenticatedKey 4, 7, 8, 9, 10

UserAuthorizationId 7

V

VehicleColor 5, 8

Version 6