

# Domain model — what nests inside what

One process holds one palace. Everything inside the vault boundary is sealed at rest.

## palace

one per process · master key · data dir

### vault — isolation + crypto boundary

HKDF-derived key · AAD binds vault id

Cross-vault access fails cryptographically, not just logically. One SQLite database, one audit chain.

#### wing person · project · tenant user

search scope

##### room topic · session · ticket

###### drawer one verbatim chunk

content (sealed) · embedding (sealed) · HMAC tag  
meta: content\_date, occurrences, time\_mentions, entities

drawer · drawer · drawer ...

id = hash(wing, room, source, chunk\_index, normalize\_version)  
content is not in the id — re-mine updates, API save appends

##### room "facts"

Distilled fact-drawers — one per distinct triple, written by refine (CLI or /v1).

Each carries an HMAC receipt citing the verbatim drawer it came from.

The room filter alone selects the surface:

**verbatim** · **distilled** · **both**

Sources exclude this room, so refining never re-distills its own output.

### knowledge graph

Receipted triples — subject, predicate, object.  
valid\_from: the note's dating words, else its content\_date.  
triple\_id keyed by a stored secret ⇒ repeats collapse  
grounding: stated / background / unevaluated

### audit chain

Head lives in chain\_meta and advances inside the same transaction as the data it covers.

Manifest anchor lags on purpose:

behind ⇒ crash, fast-forward · ahead ⇒ tamper alarm