

Production Code Draft: ‘0_LiDAR-FAIB-WSVHA-raster-to-raster-production.R’

Cabin-GIS


21/05/2022

Contents

Action	1
Import LiDAR: Load, list and merge chunks	2
CHM-derived covariates: Variable window function	3
CHM-derived covariates: Stem-detection & 95% height	4
DEM-derived covariates: Terrain rasters	5
Species covariates: VRI rasterization	6
Masking: Generate mask layers	6
Masking: Apply masking	8
Tidy: Stack covariates	9
Tidy plot data: Bootstrapped resampling	13
Tidy plot data: Data cleaning & training-test split	14
Exploratory data analysis: Visualize distributions	14
Modelling: Fit, cross-validate and tune models	21

Action


The following markdown report provides a complete run-through and guide of a raster-to-raster workflow to generating Whole Stem Volume (m^3/ha : WSVHA) raster estimates from initial phases of importing LiDAR tiles, to deriving stem-detection map and a 95% canopy height model, to generating and masking DEM-based and species covariates, to fitting and training models with faib.csv data, to finally making spatial predictions using raster stack of covariates. The graphical abstract below is offered as reference guide.



Import LiDAR: Load, list and merge chunks

```
zip_file_vh_quesnel = ("/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/quesnel_region/VegHt.zip")
zip_file_be_quesnel = ("/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/quesnel_region/BareEarth.zip")
zip_dir_vh_quesnel = ("/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/quesnel_region")
zip_dir_be_quesnel = ("/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/quesnel_region")
unzip(zip_file_vh_quesnel, exdir = zip_dir_vh_quesnel, overwrite = TRUE)
unzip(zip_file_be_quesnel, exdir=zip_dir_be_quesnel, overwrite = TRUE)
unzip_dir_vh_quesnel <- paste0("/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/quesnel_region/VegHt")
unzip_dir_be_quesnel <- paste0("/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/quesnel_region/BareEarth")
zip_file_vh_gaspard = ("/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/gaspard_region/VegHt.zip")
zip_file_be_gaspard = ("/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/gaspard_region/BareEarth.zip")
zip_dir_vh_gaspard = ("/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/gaspard_region")
zip_dir_be_gaspard = ("/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/gaspard_region")
unzip(zip_file_vh_gaspard, exdir=zip_dir_vh_gaspard, overwrite = TRUE)
unzip(zip_file_be_gaspard, exdir=zip_dir_be_gaspard, overwrite = TRUE)
unzip_dir_vh_gaspard <- paste0("/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/gaspard_region/VegHt")
unzip_dir_be_gaspard <- paste0("/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/gaspard_region/BareEarth")
filez_vh_quesnel = list.files(unzip_dir_vh_quesnel, full.names = T, all.files = FALSE, pattern = '.tif$')
filez_be_quesnel = list.files(unzip_dir_be_quesnel, full.names = T, all.files = FALSE, pattern = '.tif$')
filez_vh_gaspard = list.files(unzip_dir_vh_gaspard, full.names = T, all.files = FALSE, pattern = '.tif$')
filez_be_gaspard = list.files(unzip_dir_be_gaspard, full.names = T, all.files = FALSE, pattern = '.tif$')
lead_htop_raster_list_quesnel <- lapply(filez_vh_quesnel, raster)
lead_htop_raster_list_gaspard <- lapply(filez_vh_gaspard, raster)
elev_raster_list_quesnel <- lapply(filez_be_quesnel, raster)
elev_raster_list_gaspard <- lapply(filez_be_gaspard, raster)
lead_htop_raster_quesnel = do.call(merge, c(lead_htop_raster_list_quesnel, tolerance = 1))
lead_htop_raster_gaspard = do.call(merge, c(lead_htop_raster_list_gaspard, tolerance = 1))
elev_raster_quesnel = do.call(merge, c(elev_raster_list_quesnel, tolerance = 1))
```


```
elev_raster_gaspard = do.call(merge, c(elev_raster_list_gaspard, tolerance = 1))
writeRaster(lead_htop_raster_quesnel, filename = "/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/quesnel_")
writeRaster(lead_htop_raster_gaspard, filename = "/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/gaspard_")
writeRaster(elev_raster_quesnel, filename = "/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/quesnel_region")
writeRaster(elev_raster_gaspard, filename = "/media/seamus/128GB_WORKD/EFI-TCC/LiDAR_Data/gaspard_region")
```



CHM-derived covariates: Variable window function

```
kernel <- matrix(1,3,3)
wf_quan<-function(x){
  a=0.179-0.1
  b=0.51+0.5
  y<-a*x+b
  return(y)}
wf_plowright<-function(x){
  a=0.05
  b=0.6
  y<-a*x+b
  return(y)}
heights <- seq(0,40,0.5)
window_quan <- wf_quan(heights)
window_plowright <- wf_plowright(heights)
```

```
plot(heights, window_quan, type = "l", ylim = c(0,12), xlab="point elevation (m)", ylab="window diameter (m)")
plot(heights, window_plowright, type = "l", ylim = c(0,12), xlab="point elevation (m)", ylab="window diameter (m)")
```



CHM-derived covariates: Stem-detection & 95% height

```
lead_htop_raster_1m_smoothed_quesnel = focal(lead_htop_rast_quesnel, w = kernel, fun = median, na.rm = TRUE)
lead_htop_raster_1m_smoothed_gaspard = focal(lead_htop_rast_gaspard, w = kernel, fun = median, na.rm = TRUE)
ttops_2m_quan_quesnel <- ForestTools::vwf(lead_htop_raster_1m_smoothed_quesnel, wf_quan, 2)
ttops_2m_quan_gaspard = ForestTools::vwf(CHM = lead_htop_raster_1m_smoothed_gaspard, winFun = wf_quan, 2)
ttops_2m_plowright_quesnel = ForestTools::vwf(CHM = lead_htop_raster_1m_smoothed_quesnel, winFun = wf_plowright, 2)
ttops_2m_plowright_gaspard = ForestTools::vwf(CHM = lead_htop_raster_1m_smoothed_gaspard, winFun = wf_plowright, 2)
writeOGR(ttops_2m_quan_quesnel, "/media/seamus/128GB_WORKD/data/vector/stem_maps", "treetops_quan_quesnel")
writeOGR(ttops_2m_quan_gaspard, "/media/seamus/128GB_WORKD/data/vector/stem_maps", "treetops_quan_gaspard")
writeOGR(ttops_2m_plowright_quesnel, "/media/seamus/128GB_WORKD/data/vector/stem_maps", "treetops_plowright_quesnel")
writeOGR(ttops_2m_plowright_gaspard, "/media/seamus/128GB_WORKD/data/vector/stem_maps", "treetops_plowright_gaspard")

quant95 <- function(x, ...)
  quantile(x, c(0.95), na.rm = TRUE)
custFuns <- list(quant95, max)
names(custFuns) <- c("95thQuantile", "Max")

ttops_2m_quan_quesnel <- readOGR(dsn = "/media/seamus/128GB_WORKD/data/vector/stem_maps/treetops_quan_quesnel")
ttops_2m_quan_gaspard <- readOGR(dsn = "/media/seamus/128GB_WORKD/data/vector/stem_maps/treetops_quan_gaspard")
ttops_2m_Quan_raster_2m1.5m_95th_20cell_quesnel <- ForestTools::sp_summarise(ttops_2m_quan_quesnel, grid = 20, fun = quant95)
ttops_2m_Quan_raster_2m1.5m_95th_20cell_gaspard <- ForestTools::sp_summarise(ttops_2m_quan_gaspard, grid = 20, fun = quant95)
ttops_2m_Quan_raster_2m1.5m_95th_100cell_quesnel <- ForestTools::sp_summarise(ttops_2m_quan_quesnel, grid = 100, fun = quant95)
ttops_2m_Quan_raster_2m1.5m_95th_100cell_gaspard <- ForestTools::sp_summarise(ttops_2m_quan_gaspard, grid = 100, fun = quant95)
lead_htop_95th_raster_20m_quesnel = ttops_2m_Quan_raster_2m1.5m_95th_20cell_quesnel[["height95thQuantile"]]
lead_htop_95th_raster_20m_gaspard = ttops_2m_Quan_raster_2m1.5m_95th_20cell_gaspard[["height95thQuantile"]]
lead_htop_95th_raster_100m_quesnel = ttops_2m_Quan_raster_2m1.5m_95th_100cell_quesnel[["height95thQuantile"]]
lead_htop_95th_raster_100m_gaspard = ttops_2m_Quan_raster_2m1.5m_95th_100cell_gaspard[["height95thQuantile"]]
stemsha_L_raster_20m_quesnel = ttops_2m_Quan_raster_2m1.5m_95th_20cell_quesnel[["TreeCount"]]
stemsha_L_raster_20m_gaspard = ttops_2m_Quan_raster_2m1.5m_95th_20cell_gaspard[["TreeCount"]]
stemsha_L_raster_100m_quesnel = ttops_2m_Quan_raster_2m1.5m_95th_100cell_quesnel[["TreeCount"]]
stemsha_L_raster_100m_gaspard = ttops_2m_Quan_raster_2m1.5m_95th_100cell_gaspard[["TreeCount"]]
raster::writeRaster(lead_htop_95th_raster_20m_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/lead_htop_95th_raster_20m_quesnel.tif")
raster::writeRaster(lead_htop_95th_raster_20m_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/lead_htop_95th_raster_20m_gaspard.tif")
```

```

raster::writeRaster(lead_htop_95th_raster_100m_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/lead_htop_95th_raster_100m_quesnel.tif")
raster::writeRaster(lead_htop_95th_raster_100m_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/lead_htop_95th_raster_100m_gaspard.tif")
raster::writeRaster(stemsha_L_raster_20m_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/stemsha_L_raster_20m_quesnel.tif")
raster::writeRaster(stemsha_L_raster_20m_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/stemsha_L_raster_20m_gaspard.tif")
raster::writeRaster(stemsha_L_raster_100m_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/stemsha_L_raster_100m_quesnel.tif")
raster::writeRaster(stemsha_L_raster_100m_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/stemsha_L_raster_100m_gaspard.tif")

```

DEM-derived covariates: Terrain rasters

```

terra::crs(elev_rast_quesnel) = "epsg:3005"
terra::crs(elev_rast_gaspard) = "epsg:3005"
elev_rast_quesnel = terra::aggregate(elev_rast_quesnel, fact = 100, fun = mean)
elev_rast_gaspard = terra::aggregate(elev_rast_gaspard, fact = 100, fun = mean)
slope_rast_quesnel = terra::terrain(elev_rast_quesnel, v="slope", unit="degrees", neighbors=8)
slope_rast_gaspard = terra::terrain(elev_rast_gaspard, v="slope", unit="degrees", neighbors=8)
aspect_rast_quesnel = terra::terrain(elev_rast_quesnel, v="aspect", unit="degrees", neighbors=8)
aspect_rast_gaspard = terra::terrain(elev_rast_gaspard, v="aspect", unit="degrees", neighbors=8)
asp_cos_rast_quesnel = cos((aspect_rast_quesnel*pi)/180)
asp_cos_rast_gaspard = cos((aspect_rast_gaspard*pi)/180)
asp_sin_rast_quesnel = sin((aspect_rast_quesnel*pi)/180)
asp_sin_rast_gaspard = sin((aspect_rast_gaspard*pi)/180)

lead_htop_rast_quesnel = terra::rast(lead_htop_95th_raster_100m_quesnel)
lead_htop_rast_gaspard = terra::rast(lead_htop_95th_raster_100m_gaspard)
stemsha_L_rast_quesnel = terra::rast(stemsha_L_raster_100m_quesnel)
stemsha_L_rast_gaspard = terra::rast(stemsha_L_raster_100m_gaspard)
terra::crs(lead_htop_rast_gaspard) = "epsg:3005"
terra::crs(lead_htop_rast_quesnel) = "epsg:3005"
terra::crs(stemsha_L_rast_gaspard) = "epsg:3005"
terra::crs(stemsha_L_rast_quesnel) = "epsg:3005"

lead_htop_rast_quesnel = terra::resample(lead_htop_rast_quesnel, elev_rast_quesnel)
lead_htop_rast_gaspard = terra::resample(lead_htop_rast_gaspard, elev_rast_gaspard)
stemsha_L_rast_quesnel = terra::resample(stemsha_L_rast_quesnel, elev_rast_quesnel)
stemsha_L_rast_gaspard = terra::resample(stemsha_L_rast_gaspard, elev_rast_gaspard)
elev_rast_quesnel = terra::mask(elev_rast_quesnel, lead_htop_rast_quesnel)
elev_rast_gaspard = terra::mask(elev_rast_gaspard, lead_htop_rast_gaspard)
slope_rast_quesnel = terra::mask(slope_rast_quesnel, lead_htop_rast_quesnel)
slope_rast_gaspard = terra::mask(slope_rast_gaspard, lead_htop_rast_gaspard)
asp_cos_rast_quesnel = terra::mask(asp_cos_rast_quesnel, lead_htop_rast_quesnel)
asp_cos_rast_gaspard = terra::mask(asp_cos_rast_gaspard, lead_htop_rast_gaspard)
asp_sin_rast_quesnel = terra::mask(asp_sin_rast_quesnel, lead_htop_rast_quesnel)
asp_sin_rast_gaspard = terra::mask(asp_sin_rast_gaspard, lead_htop_rast_gaspard)

writeRaster(elev_rast_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/elev_rast_quesnel.tif")
writeRaster(elev_rast_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/elev_rast_gaspard.tif")
writeRaster(slope_rast_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/slope_rast_quesnel.tif")
writeRaster(slope_rast_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/slope_rast_gaspard.tif")
writeRaster(asp_cos_rast_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/asp_cos_rast_quesnel.tif")
writeRaster(asp_cos_rast_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/asp_cos_rast_gaspard.tif")
writeRaster(asp_sin_rast_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/asp_sin_rast_quesnel.tif")
writeRaster(asp_sin_rast_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/asp_sin_rast_gaspard.tif")

```

```
writeRaster(asp_sin_rast_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covari
```

Species covariates: VRI rasterization

```
lead_htop_sv_quesnel = as.polygons(lead_htop_rast_quesnel)
lead_htop_sv_gaspard = as.polygons(lead_htop_rast_gaspard)
lead_htop_sf_quesnel = sf::st_as_sf(lead_htop_sv_quesnel)
lead_htop_sf_gaspard = sf::st_as_sf(lead_htop_sv_gaspard)
vri_sf = read_sf("/media/seamus/128GB_WORKD/data/vector/vri/vri_bc_2020_rank1.shp")
vri_species = vri_sf[c("SPECIES__1", "SPECIES_CD", "SPECIES_PC")]
vri_species_aoi = dplyr::filter(
  vri_species, SPECIES__1=='PL' | SPECIES__1=='PLI' | SPECIES__1=='FD' | SPECIES__1=='FDI' |
  SPECIES__1=='SB' | SPECIES__1=='SE' | SPECIES__1=='SW' | SPECIES__1=='SX' |
  SPECIES__1=='CW' | SPECIES__1=='HW' | SPECIES__1=='BL' | SPECIES__1=='LW')
vri_species_aoi_gaspard = vri_species_aoi[!(
  vri_species_aoi$SPECIES__1 == 'FD' & vri_species_aoi$SPECIES_PC >= 50 |
  vri_species_aoi$SPECIES__1 == 'FDI' & vri_species_aoi$SPECIES_PC >=50),]
vri_species_aoi_gaspard$SPECIES__1 = dplyr::recode(
  vri_species_aoi_gaspard$SPECIES__1,
  PL = 0, PLI = 0, SB = 1, SE = 1, SW = 1, SX = 1,
  FD = 2, FDI = 2, CW = 3, HW = 4, BL = 5, LW = 6)
vri_species_aoi_gaspard = dplyr::rename(vri_species_aoi_gaspard, species_class = SPECIES__1)
vri_species_aoi_gaspard = vri_species_aoi_gaspard["species_class"]
vri_species_aoi_sf_gaspard = sf::st_as_sf(vri_species_aoi_gaspard)

vri_species_aoi_quesnel = vri_species_aoi
vri_species_aoi_quesnel$SPECIES__1 = dplyr::recode(vri_species_aoi$SPECIES__1, PL = 0, PLI = 0, SB = 1,
vri_species_aoi_quesnel = dplyr::rename(vri_species_aoi_quesnel, species_class = SPECIES__1)
vri_species_aoi_quesnel = vri_species_aoi_quesnel["species_class"]
vri_species_aoi_sf_quesnel = sf::st_as_sf(vri_species_aoi_quesnel)

vri_species_aoi_quesnel = st_intersection(vri_species_aoi_sf_quesnel, st_make_valid(lead_htop_sf_quesnel)
vri_species_aoi_gaspard = st_intersection(vri_species_aoi_sf_gaspard, st_make_valid(lead_htop_sf_gaspard)
species_class_rast_quesnel = terra::rasterize(vect(vri_species_aoi_quesnel), lead_htop_rast_quesnel, fi
species_class_rast_gaspard = terra::rasterize(vect(vri_species_aoi_gaspard), lead_htop_rast_gaspard, fi
species_class_rast_quesnel = terra::resample(species_class_rast_quesnel, lead_htop_rast_quesnel)
species_class_rast_gaspard = terra::resample(species_class_rast_gaspard, lead_htop_rast_gaspard)
species_class_raster_quesnel = raster::raster(species_class_rast_quesnel)
species_class_raster_gaspard = raster::raster(species_class_rast_gaspard)
raster::writeRaster(species_class_raster_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc
raster::writeRaster(species_class_raster_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc
```

Masking: Generate mask layers

```
mask_burn2017 = sf::read_sf("/media/seamus/128GB_WORKD/data/vector/tcc_mask_layers/TCC_Burn_Severity TCC
mask_burn2018 = sf::read_sf("/media/seamus/128GB_WORKD/data/vector/tcc_mask_layers/TCC_Burn_Severity TCC
mask_burn2021 = sf::read_sf("/media/seamus/128GB_WORKD/data/vector/tcc_mask_layers/TCC_Burn_Severity TCC
mask_burn2017 = mask_burn2017["BurnSev"]
mask_burn2018 = mask_burn2018["BurnSev"]
```



```

mask_burn2021 = mask_burn2021["BurnSev"]
mask_burn2017 = dplyr::filter(mask_burn2017, BurnSev == 'High')
mask_burn2018 = dplyr::filter(mask_burn2018, BurnSev == 'High')
mask_burn2021 = dplyr::filter(mask_burn2021, BurnSev == 'High')
mask_burn2017_quesnel = sf::st_intersection(sf::st_make_valid(mask_burn2017), lead_htop_sf_quesnel)
mask_burn2017_gaspard = sf::st_intersection(sf::st_make_valid(mask_burn2017), lead_htop_sf_gaspard)
mask_burn2018_quesnel = sf::st_intersection(sf::st_make_valid(mask_burn2018), lead_htop_sf_quesnel)
mask_burn2018_gaspard = sf::st_intersection(sf::st_make_valid(mask_burn2018), lead_htop_sf_gaspard)
mask_burn2021_quesnel = sf::st_intersection(sf::st_make_valid(mask_burn2021), lead_htop_sf_quesnel)
mask_burn2021_gaspard = sf::st_intersection(sf::st_make_valid(mask_burn2021), lead_htop_sf_gaspard)
masks_df_quesnel = full_join(as_tibble(mask_burn2017_quesnel), as_tibble(mask_burn2018_quesnel), as_tibble(mask_burn2021_quesnel))
masks_df_gaspard = full_join(as_tibble(mask_burn2017_gaspard), as_tibble(mask_burn2018_gaspard), as_tibble(mask_burn2021_gaspard))
masks_sf_quesnel = st_as_sf(masks_df_quesnel) # easier to combine by 'geometry'
masks_sf_gaspard = st_as_sf(masks_df_gaspard) # easier to combine by 'geometry'

mask_clearcut = sf::read_sf("/media/seamus/128GB_WORKD/data/vector/tcc_mask_layers/RSLT_CCRES_CLEAR.shp")
mask_clearcut_quesnel = sf::st_intersection(mask_clearcut, st_make_valid(lead_htop_sf_quesnel))
mask_clearcut_gaspard = sf::st_intersection(mask_clearcut, st_make_valid(lead_htop_sf_gaspard))
masks_df_quesnel = full_join(as_tibble(masks_sf_quesnel), as_tibble(mask_clearcut_quesnel), by = 'geometry')
masks_df_gaspard = full_join(as_tibble(masks_sf_gaspard), as_tibble(mask_clearcut_gaspard), by = 'geometry')
masks_sf_quesnel = st_as_sf(masks_df_quesnel)
masks_sf_gaspard = st_as_sf(masks_df_gaspard)



mask_blocks = sf::read_sf("/media/seamus/128GB_WORKD/data/vector/tcc_mask_layers/TCC_Blocks_Join.shp")
mask_blocks_quesnel = sf::st_intersection(mask_blocks, st_make_valid(lead_htop_sf_quesnel))
mask_blocks_gaspard = sf::st_intersection(mask_blocks, st_make_valid(lead_htop_sf_gaspard))
masks_df_quesnel = full_join(as_tibble(masks_sf_quesnel), as_tibble(mask_blocks_quesnel), by = 'geometry')
masks_df_gaspard = full_join(as_tibble(masks_sf_gaspard), as_tibble(mask_blocks_gaspard), by = 'geometry')
masks_sf_quesnel = st_as_sf(masks_df_quesnel)
masks_sf_gaspard = st_as_sf(masks_df_gaspard)

mask_roads_tcc = sf::read_sf("/media/seamus/128GB_WORKD/data/vector/tcc_mask_layers/TCC_Roads.shp")
mask_roads_tcc = sf::st_zm(mask_roads_tcc)
mask_roads_tcc_quesnel = sf::st_intersection(mask_roads_tcc, st_make_valid(lead_htop_sf_quesnel))
mask_roads_tcc_gaspard = sf::st_intersection(mask_roads_tcc, st_make_valid(lead_htop_sf_gaspard))
mask_roads_tcc_quesnel = sf::st_buffer(mask_roads_tcc_quesnel, dist = 15, nQuadSegs = 5, endCapStyle = 1)
mask_roads_tcc_gaspard = sf::st_buffer(mask_roads_tcc_gaspard, dist = 15, nQuadSegs = 5, endCapStyle = 1)

mask_roads_ften = sf::read_sf("/media/seamus/128GB_WORKD/data/vector/tcc_mask_layers/FTEN_Roads_All.shp")
mask_roads_ften = sf::st_zm(mask_roads_ften)
mask_roads_ften_quesnel = sf::st_intersection(mask_roads_ften, st_make_valid(lead_htop_sf_quesnel))
mask_roads_ften_gaspard = sf::st_intersection(mask_roads_ften, st_make_valid(lead_htop_sf_gaspard))
mask_roads_ften_quesnel = sf::st_buffer(mask_roads_ften_quesnel, dist = 15, nQuadSegs = 5, endCapStyle = 1)
mask_roads_ften_gaspard = sf::st_buffer(mask_roads_ften_gaspard, dist = 15, nQuadSegs = 5, endCapStyle = 1)
masks_df_quesnel = full_join(as_tibble(masks_sf_quesnel), as_tibble(mask_roads_tcc_quesnel), as_tibble(mask_roads_ften_quesnel))
masks_df_gaspard = full_join(as_tibble(masks_sf_gaspard), as_tibble(mask_roads_tcc_gaspard), as_tibble(mask_roads_ften_gaspard))
masks_sf_quesnel = st_as_sf(masks_df_quesnel)
masks_sf_gaspard = st_as_sf(masks_df_gaspard)
masks_rast_quesnel = rasterize(vect(masks_sf_quesnel), lead_htop_rast_quesnel, touches = TRUE)
masks_rast_gaspard = rasterize(vect(masks_sf_gaspard), lead_htop_rast_gaspard, touches = TRUE)
masks_raster_quesnel = raster::raster(masks_rast_quesnel)
masks_raster_gaspard = raster::raster(masks_rast_gaspard)
writeRaster(masks_raster_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/mask/mask_raster_quesnel.tif")
writeRaster(masks_raster_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/mask/mask_raster_gaspard.tif")

```

```
writeRaster(masks_raster_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/mask/mask_raster_gaspard.tif", overwrite = TRUE)
ggplot(masks_sf_gaspard) + geom_sf(aes(fill = 'red'), show.legend = FALSE)
ggplot(masks_sf_quesnel) + geom_sf(aes(fill = 'red'), show.legend = FALSE)
```



Masking: Apply masking

```
elev_rast_quesnel = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/elev_rast_quesnel.tif")
elev_rast_gaspard = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/elev_rast_gaspard.tif")
slope_rast_quesnel = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/slope_rast_quesnel.tif")
slope_rast_gaspard = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/slope_rast_gaspard.tif")
asp_cos_rast_quesnel = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/asp_cos_rast_quesnel.tif")
asp_cos_rast_gaspard = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/asp_cos_rast_gaspard.tif")
asp_sin_rast_quesnel = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/asp_sin_rast_quesnel.tif")
asp_sin_rast_gaspard = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/asp_sin_rast_gaspard.tif")
lead_htop_rast_quesnel = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/lead_htop_rast_quesnel.tif")
lead_htop_rast_gaspard = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/lead_htop_rast_gaspard.tif")
stemsha_L_rast_quesnel = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/stemsha_L_rast_quesnel.tif")
stemsha_L_rast_gaspard = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/stemsha_L_rast_gaspard.tif")
species_class_rast_quesnel = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/species_class_rast_quesnel.tif")
species_class_rast_gaspard = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/unmasked-covariates/species_class_rast_gaspard.tif")
masks_rast_quesnel = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/mask/mask_raster_100m_quesnel.tif")
masks_rast_gaspard = terra::rast("/media/seamus/128GB_WORKD/data/raster/tcc/mask/mask_raster_100m_gaspard.tif")

# masking by stem map
lead_htop_rast_quesnel = terra::resample(lead_htop_rast_quesnel, elev_rast_quesnel)
lead_htop_rast_gaspard = terra::resample(lead_htop_rast_gaspard, elev_rast_gaspard)
stemsha_L_rast_quesnel = terra::resample(stemsha_L_rast_quesnel, elev_rast_quesnel)
stemsha_L_rast_gaspard = terra::resample(stemsha_L_rast_gaspard, elev_rast_gaspard)
elev_rast_quesnel = terra::mask(elev_rast_quesnel, lead_htop_rast_quesnel)
elev_rast_gaspard = terra::mask(elev_rast_gaspard, lead_htop_rast_gaspard)
slope_rast_quesnel = terra::mask(slope_rast_quesnel, lead_htop_rast_quesnel)
slope_rast_gaspard = terra::mask(slope_rast_gaspard, lead_htop_rast_gaspard)
asp_cos_rast_quesnel = terra::mask(asp_cos_rast_quesnel, lead_htop_rast_quesnel)
asp_cos_rast_gaspard = terra::mask(asp_cos_rast_gaspard, lead_htop_rast_gaspard)
asp_sin_rast_quesnel = terra::mask(asp_sin_rast_quesnel, lead_htop_rast_quesnel)
asp_sin_rast_gaspard = terra::mask(asp_sin_rast_gaspard, lead_htop_rast_gaspard)
species_class_rast_quesnel = terra::mask(species_class_rast_quesnel, lead_htop_rast_quesnel)
species_class_rast_gaspard = terra::mask(species_class_rast_gaspard, lead_htop_rast_gaspard)
```



```

# masking by mask
masks_rast_quesnel = terra::resample(masks_rast_quesnel, lead_htop_rast_quesnel)
masks_rast_gaspard = terra::resample(masks_rast_gaspard, lead_htop_rast_gaspard)
masks_rast_quesnel = terra::resample(masks_rast_quesnel, elev_rast_quesnel)
masks_rast_gaspard = terra::resample(masks_rast_gaspard, elev_rast_gaspard)
lead_htop_rast_quesnel = mask(lead_htop_rast_quesnel, masks_rast_quesnel, inverse=TRUE)
lead_htop_rast_gaspard = mask(lead_htop_rast_gaspard, masks_rast_gaspard, inverse=TRUE)
elev_rast_quesnel = mask(elev_rast_quesnel, masks_rast_quesnel, inverse=TRUE)
elev_rast_gaspard = mask(elev_rast_gaspard, masks_rast_gaspard, inverse=TRUE)
slope_rast_quesnel = mask(slope_rast_quesnel, masks_rast_quesnel, inverse=TRUE)
slope_rast_gaspard = mask(slope_rast_gaspard, masks_rast_gaspard, inverse=TRUE)
asp_cos_rast_quesnel = mask(asp_cos_rast_quesnel, masks_rast_quesnel, inverse=TRUE)
asp_cos_rast_gaspard = mask(asp_cos_rast_gaspard, masks_rast_gaspard, inverse=TRUE)
asp_sin_rast_quesnel = mask(asp_sin_rast_quesnel, masks_rast_quesnel, inverse=TRUE)
asp_sin_rast_gaspard = mask(asp_sin_rast_gaspard, masks_rast_gaspard, inverse=TRUE)
stemsha_L_rast_quesnel = mask(stemsha_L_rast_quesnel, masks_rast_quesnel, inverse=TRUE)
stemsha_L_rast_gaspard = mask(stemsha_L_rast_gaspard, masks_rast_gaspard, inverse=TRUE)
species_class_rast_quesnel = mask(species_class_rast_quesnel, masks_rast_quesnel, inverse=TRUE)
species_class_rast_gaspard = mask(species_class_rast_gaspard, masks_rast_gaspard, inverse=TRUE)

# masking by species
lead_htop_rast_quesnel = mask(lead_htop_rast_quesnel, species_class_rast_quesnel, inverse=FALSE)
lead_htop_rast_gaspard = mask(lead_htop_rast_gaspard, species_class_rast_gaspard, inverse=FALSE)
elev_rast_quesnel = mask(elev_rast_quesnel, species_class_rast_quesnel, inverse=FALSE)
elev_rast_gaspard = mask(elev_rast_gaspard, species_class_rast_gaspard, inverse=FALSE)
slope_rast_quesnel = mask(slope_rast_quesnel, species_class_rast_quesnel, inverse=FALSE)
slope_rast_gaspard = mask(slope_rast_gaspard, species_class_rast_gaspard, inverse=FALSE)
asp_cos_rast_quesnel = mask(asp_cos_rast_quesnel, species_class_rast_quesnel, inverse=FALSE)
asp_cos_rast_gaspard = mask(asp_cos_rast_gaspard, species_class_rast_gaspard, inverse=FALSE)
asp_sin_rast_quesnel = mask(asp_sin_rast_quesnel, species_class_rast_quesnel, inverse=FALSE)
asp_sin_rast_gaspard = mask(asp_sin_rast_gaspard, species_class_rast_gaspard, inverse=FALSE)
stemsha_L_rast_quesnel = mask(stemsha_L_rast_quesnel, species_class_rast_quesnel, inverse=FALSE)
stemsha_L_rast_gaspard = mask(stemsha_L_rast_gaspard, species_class_rast_gaspard, inverse=FALSE)

writeRaster(elev_rast_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/")
writeRaster(elev_rast_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/")
writeRaster(slope_rast_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/")
writeRaster(slope_rast_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/")
writeRaster(asp_cos_rast_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/")
writeRaster(asp_cos_rast_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/")
writeRaster(asp_sin_rast_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/")
writeRaster(asp_sin_rast_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/")
writeRaster(species_class_rast_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/")
writeRaster(species_class_rast_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/")
writeRaster(stemsha_L_rast_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/")
writeRaster(stemsha_L_rast_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/")
writeRaster(lead_htop_rast_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/")
writeRaster(lead_htop_rast_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/")

```

Tidy: Stack covariates

```

#tidy names
names(elev_rast_quesnel) = "elev"

```

```

names(slope_rast_quesnel) = "slope"
names(asp_cos_rast_quesnel) = "asp_cos"
names(asp_sin_rast_quesnel) = "asp_sin"
names(species_class_rast_quesnel) = "species_class"
names(stemsha_L_rast_quesnel) = "stemsha_L"
names(lead_htop_rast_quesnel) = "lead_htop"

names(elev_rast_gaspard) = "elev"
names(slope_rast_gaspard) = "slope"
names(asp_cos_rast_gaspard) = "asp_cos"
names(asp_sin_rast_gaspard) = "asp_sin"
names(species_class_rast_gaspard) = "species_class"
names(stemsha_L_rast_gaspard) = "stemsha_L"
names(lead_htop_rast_gaspard) = "lead_htop"

elev_raster_quesnel = raster::raster(elev_rast_quesnel)
slope_raster_quesnel = raster::raster(slope_rast_quesnel)
asp_cos_raster_quesnel = raster::raster(asp_cos_rast_quesnel)
asp_sin_raster_quesnel = raster::raster(asp_sin_rast_quesnel)
species_class_raster_quesnel = raster::raster(species_class_rast_quesnel)
stemsha_L_raster_quesnel = raster::raster(stemsha_L_rast_quesnel)
lead_htop_raster_quesnel = raster::raster(lead_htop_rast_quesnel)

elev_raster_gaspard = raster::raster(elev_rast_gaspard)
slope_raster_gaspard = raster::raster(slope_rast_gaspard)
asp_cos_raster_gaspard = raster::raster(asp_cos_rast_gaspard)
asp_sin_raster_gaspard = raster::raster(asp_sin_rast_gaspard)
species_class_raster_gaspard = raster::raster(species_class_rast_gaspard)
stemsha_L_raster_gaspard = raster::raster(stemsha_L_rast_gaspard)
lead_htop_raster_gaspard = raster::raster(lead_htop_rast_gaspard)

elev_raster_list = list(elev_raster_quesnel, elev_raster_gaspard)
slope_raster_list = list(slope_raster_quesnel, slope_raster_gaspard)
asp_cos_raster_list = list(asp_cos_raster_quesnel, asp_cos_raster_gaspard)
asp_sin_raster_list = list(asp_sin_raster_quesnel, asp_sin_raster_gaspard)
species_class_raster_list = list(species_class_raster_quesnel, species_class_raster_gaspard)
stemsha_L_raster_list = list(stemsha_L_raster_quesnel, stemsha_L_raster_gaspard)
lead_htop_raster_list = list(lead_htop_raster_quesnel, lead_htop_raster_gaspard)

elev_raster = do.call(merge, c(elev_raster_list, tolerance = 1))
slope_raster = do.call(merge, c(slope_raster_list, tolerance = 1))
asp_cos_raster = do.call(merge, c(asp_cos_raster_list, tolerance = 1))
asp_sin_raster = do.call(merge, c(asp_sin_raster_list, tolerance = 1))
species_class_raster = do.call(merge, c(species_class_raster_list, tolerance = 1))
stemsha_L_raster = do.call(merge, c(stemsha_L_raster_list, tolerance = 1))
lead_htop_raster = do.call(merge, c(lead_htop_raster_list, tolerance = 1))

writeRaster(elev_raster, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/elev_r")
writeRaster(slope_raster, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/slope")
writeRaster(asp_cos_raster, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/asp")
writeRaster(asp_sin_raster, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/asp")
writeRaster(species_class_raster, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/species_class")
writeRaster(stemsha_L_raster, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/stemsha_L")

```

```

writeRaster(lead_htop_raster, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/masked-covariates/1

covs_m1_quesnel = raster::stack(
  elev_raster_quesnel,
  slope_raster_quesnel,
  asp_cos_raster_quesnel,
  asp_sin_raster_quesnel,
  species_class_raster_quesnel,
  lead_htop_raster_quesnel,
  stemsha_L_raster_quesnel)

covs_m1_gaspard = raster::stack(
  elev_raster_gaspard,
  slope_raster_gaspard,
  asp_cos_raster_gaspard,
  asp_sin_raster_gaspard,
  species_class_raster_gaspard,
  lead_htop_raster_gaspard,
  stemsha_L_raster_gaspard)

covs_m2_quesnel = raster::stack(
  elev_raster_quesnel,
  slope_raster_quesnel,
  asp_cos_raster_quesnel,
  asp_sin_raster_quesnel,
  species_class_raster_quesnel,
  lead_htop_raster_quesnel)


covs_m2_gaspard = raster::stack(
  elev_raster_gaspard,
  slope_raster_gaspard,
  asp_cos_raster_gaspard,
  asp_sin_raster_gaspard,
  species_class_raster_gaspard,
  lead_htop_raster_gaspard)

covs_m2 = raster::stack(
  elev_raster,
  slope_raster,
  asp_cos_raster,
  asp_sin_raster,
  lead_htop_raster,
  species_class_raster)


covs_m1 = raster::stack(
  elev_raster,
  slope_raster,
  asp_cos_raster,
  asp_sin_raster,
  lead_htop_raster,
  species_class_raster,
  stemsha_L_raster)

```

```
rasterVis::levelplot(covs_m1_gaspard)
```




```
rasterVis::levelplot(covs_m1_quesnel)
```



Tidy plot data: Bootstrapped resampling

```
## # A tibble: 691 x 8
##   elev slope  asp_cos asp_sin lead_htop species_class stemsha_L wsvha_L
##   <int> <int>    <dbl>  <dbl>    <dbl>        <dbl>    <dbl>    <dbl>
## 1   793    15 -1.84e-16  -1      23.0          1    770.    303.
## 2   793    15 -1.84e-16  -1      26.0          1    700.    384.
## 3   661     4  3.09e- 1   0.951    23.6          2    817.    338.
## 4   788     5  1.74e- 1   0.985    27.8          2    883.    507.
## 5   903     2  6.98e- 2  -0.998    18.3          1    315.    113.
## 6   903     2  6.98e- 2  -0.998    21.1          1    522.    184.
## 7   903     2  6.98e- 2  -0.998    24.4          1    660.    272.
## 8   903     2  6.98e- 2  -0.998    25.8          1    650.    356.
## 9   903     2  6.98e- 2  -0.998    26.0          2    414.    219.
## 10  825    10 -3.42e- 1  -0.940    18.3          2    335.    126.
## # ... with 681 more rows
```



Tidy plot data: Data cleaning & training-test split

```
faib_psp$elev = as.numeric(faib_psp$elev)
faib_psp$slope = as.numeric(faib_psp$slope)
faib_psp$asp_cos = as.numeric(faib_psp$asp_cos)
faib_psp$asp_sin = as.numeric(faib_psp$asp_sin)
faib_psp$lead_htop = as.numeric(faib_psp$lead_htop)
faib_psp$species_class = as.numeric(faib_psp$species_class)
faib_psp$stemsha_L = as.numeric(faib_psp$stemsha_L)
faib_psp$wsvha_L = as.numeric(faib_psp$wsvha_L)

faib_psp$elev[faib_psp$elev <= 0] = NA
faib_psp$slope[faib_psp$slope <= 0] = NA
faib_psp$lead_htop[faib_psp$lead_htop < 2] = NA
faib_psp$stemsha_L[faib_psp$stemsha_L <= 0] = NA
faib_psp$wsvha_L[faib_psp$wsvha_L <= 0] = NA

faib_vri_true_m1_df = faib_psp[c("elev", "slope", "asp_cos", "asp_sin", "lead_htop", "species_class", "stemsha_L", "wsvha_L"), ]
faib_vri_true_m2_df = faib_psp[c("elev", "slope", "asp_cos", "asp_sin", "lead_htop", "species_class", "stemsha_L", "wsvha_L"), ]
faib_vri_true_m1_df = na.omit(faib_vri_true_m1_df)
faib_vri_true_m2_df = na.omit(faib_vri_true_m2_df)

n <- nrow(faib_vri_true_m1_df)
frac <- 0.8
ix <- sample(n, frac * n)
train_m1 = faib_vri_true_m1_df[ix,]
test_m1 = faib_vri_true_m1_df[-ix,]
train_m2 = faib_vri_true_m2_df[ix,]
test_m2 = faib_vri_true_m2_df[-ix,]

X_train_m1=train_m1[,-8]
X_test_m1=test_m1[,-8]
y_train_m1=train_m1[,8]
y_test_m1=test_m1[,8]

X_train_m2=train_m2[,-7]
X_test_m2=test_m2[,-7]
y_train_m2=train_m2[,7]
y_test_m2=test_m2[,7]

X_m1 = faib_vri_true_m1_df[,-8]
y_m1 = faib_vri_true_m1_df[,8]
X_m2 = faib_vri_true_m2_df[,-7]
y_m2 = faib_vri_true_m2_df[,7]
```

Exploratory data analysis: Visualize distributions


```
truehist(faib_vri_true_m1_df$elev, main="DEM (faib)", maxpixels=22000000)
hist(elev_raster, main="DEM (all sites)", maxpixels=22000000)
hist(elev_raster_gaspard, main="DEM (Gaspard)", maxpixels=22000000)
hist(elev_raster_quesnel, main="DEM (Quesnel)", maxpixels=22000000)
```




```

truehist(faib_vri_true_m1_df$slope, main="Slope (faib)", maxpixels=2200000)
hist(slope_raster, main="Slope (all sites)", maxpixels=2200000)
hist(slope_raster_gaspard, main="Slope (Gaspard)", maxpixels=2200000)
hist(slope_raster_quesnel, main="Slope (Quesnel)", maxpixels=2200000)
truehist(faib_vri_true_m1_df$asp_cos, main="Northness (faib)", maxpixels=2200000)
hist(asp_cos_raster, main="Northness (all sites)", maxpixels=2200000)
hist(asp_cos_raster_gaspard, main="Northness (Gaspard)", maxpixels=2200000)
hist(asp_cos_raster_quesnel, main="Northness (Quesnel)", maxpixels=2200000)
truehist(faib_vri_true_m1_df$asp_cos, main="Eastness (faib)", maxpixels=2200000)
hist(asp_cos_raster, main="Eastness (all sites)", maxpixels=2200000)
hist(asp_cos_raster_gaspard, main="Eastness (Gaspard)", maxpixels=2200000)
hist(asp_cos_raster_quesnel, main="Eastness (Quesnel)", maxpixels=2200000)
truehist(faib_vri_true_m1_df$stemsha_L, main="Stems/ha (faib)", maxpixels=2200000)
hist(stemsha_L_raster, main="Stems/ha (all sites)", maxpixels=2200000)
hist(stemsha_L_raster_gaspard, main="Stems/ha (Gaspard)", maxpixels=2200000)
hist(stemsha_L_raster_quesnel, main="Stems/ha (Quesnel)", maxpixels=2200000)
faib_vri_true_m1_df$species_class = as.numeric(faib_vri_true_m1_df$species_class)
truehist(faib_vri_true_m1_df$species_class, main="Lead Species (faib)", maxpixels=2200000)
hist(species_class_raster, main="Lead Species (all sites)", maxpixels=2200000)
hist(species_class_raster_gaspard, main="Lead Species (Gaspard)", maxpixels=2200000)
hist(species_class_raster_quesnel, main="Lead Species (Quesnel)", maxpixels=2200000)
truehist(faib_vri_true_m1_df$lead_htop, main="CHM 95th% (faib)", maxpixels=2200000)
hist(lead_htop_raster, main="CHM 95th% (all sites)", maxpixels=2200000)
hist(lead_htop_raster_gaspard, main="CHM 95th% (Gaspard)", maxpixels=2200000)
hist(lead_htop_raster_quesnel, main="CHM 95th% (Quesnel)", maxpixels=2200000)

```





Exploratory data analysis: Visualize trends in variance

```
elev_wsvha_lm = lm(wsvha_L ~ elev, data = faib_vri_true_m1_df)
slope_wsvha_lm = lm(wsvha_L ~ slope, data = faib_vri_true_m1_df)
asp_cos_wsvha_lm = lm(wsvha_L ~ asp_cos, data = faib_vri_true_m1_df)
asp_sin_wsvha_lm = lm(wsvha_L ~ asp_sin, data = faib_vri_true_m1_df)
lead_htop_wsvha_lm = lm(wsvha_L ~ lead_htop, data = faib_vri_true_m1_df)
species_class_wsvha_lm = lm(wsvha_L ~ species_class, data = faib_vri_true_m1_df)
stemsha_L_wsvha_lm = lm(wsvha_L ~ stemsha_L, data = faib_vri_true_m1_df)

summary(elev_wsvha_lm)
```

```
##
## Call:
## lm(formula = wsvha_L ~ elev, data = faib_vri_true_m1_df)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -217.13  -111.13   -47.98    72.19   624.56
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept) 351.20563   37.89240   9.268  < 2e-16 ***
## elev        -0.17006    0.03742  -4.545 6.58e-06 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 153.9 on 633 degrees of freedom
## Multiple R-squared:  0.0316, Adjusted R-squared:  0.03007
## F-statistic: 20.66 on 1 and 633 DF, p-value: 6.584e-06
```

```

truehist(faib_vri_true_m1_df$elev)
truehist(elev_wsvha_lm$residuals)
plot(wsvha_L ~ elev, data = faib_vri_true_m1_df,
     main="Linear function showing negative correlation:\nR^2=0.011, ==-0.0954, p<0.0000",
     col="blue", pch=20, cex=0.5, cex.main=0.6, cex.lab=0.8, cex.axis=0.8, adj=1,
     ylab = "wsvha_L (m3/ha)", xlab = "DEM")
abline(elev_wsvha_lm, col = "red")
plot(elev_wsvha_lm, which=1,
     main="Residuals showing increasing trend\n clustering at larger fitted values",
     col="blue", pch=20, cex=0.5, cex.main=0.6, cex.lab=0.5, cex.axis=0.5, adj=1) # Residuals vs Fitted
summary(slope_wsvha_lm)

```

```

##
## Call:
## lm(formula = wsvha_L ~ slope, data = faib_vri_true_m1_df)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -183.60 -115.29  -47.90   74.18  619.15
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  185.5195     9.1698  20.232  <2e-16 ***
## slope        -0.4469     0.7050  -0.634    0.526
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 156.3 on 633 degrees of freedom
## Multiple R-squared:  0.0006344, Adjusted R-squared:  -0.0009444
## F-statistic: 0.4018 on 1 and 633 DF,  p-value: 0.5264

```

```

truehist(faib_vri_true_m1_df$slope)
truehist(slope_wsvha_lm$residuals)
plot(wsvha_L ~ slope, data = faib_vri_true_m1_df,
     main="Linear function showing negative correlation:\nR^2=0.0013, ==-0.5171: p=0.0009",
     col="blue", pch=20, cex=0.5, cex.main=0.6, cex.lab=0.8, cex.axis=0.8, adj=1,
     ylab = "wsvha_L (m3/ha)", xlab = "slope")
abline(slope_wsvha_lm, col = "red")
plot(slope_wsvha_lm, which=1,
     main="Residuals showing increasing trend of\nnegative errors near larger fitted values",
     col="blue", pch=20, cex=0.5, cex.main=0.6, cex.lab=0.5, cex.axis=0.5, adj=1)
summary(asp_cos_wsvha_lm)

```

```

##
## Call:
## lm(formula = wsvha_L ~ asp_cos, data = faib_vri_true_m1_df)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -193.04 -117.03  -46.78   75.16  606.31
##
## Coefficients:

```

```
##           Estimate Std. Error t value Pr(>|t|)
## (Intercept) 181.491      6.199  29.276  <2e-16 ***
## asp_cos      12.635      9.010   1.402   0.161
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 156.2 on 633 degrees of freedom
## Multiple R-squared:  0.003097, Adjusted R-squared:  0.001522
## F-statistic: 1.966 on 1 and 633 DF, p-value: 0.1613
```

```
truehist(faib_vri_true_m1_df$asp_cos)
truehist(asp_cos_wsvha_lm$residuals)
plot(wsvha_L ~ asp_cos, data = faib_vri_true_m1_df,
     main="Linear function showing positive correlation:\nR^2=0.005, =15.197, p<0.000",
     col="blue", pch=20, cex=0.5, cex.main=0.6, cex.lab=0.8, cex.axis=0.8, adj=1,
     ylab = "wsvha_L (m3/ha)", xlab = "asp_cos")
abline(asp_cos_wsvha_lm, col = "red")
plot(asp_cos_wsvha_lm, which=1,
     main="Residuals showing almost constant variance",
     col="blue", pch=20, cex=0.5, cex.main=0.6, cex.lab=0.5, cex.axis=0.5, adj=1)
summary(asp_sin_wsvha_lm)
```

```
##
## Call:
## lm(formula = wsvha_L ~ asp_sin, data = faib_vri_true_m1_df)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -180.68 -114.56  -48.57   74.30  618.14
##
## Coefficients:
##           Estimate Std. Error t value Pr(>|t|)
## (Intercept) 181.071      6.268  28.887  <2e-16 ***
## asp_sin       1.658      8.638   0.192   0.848
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 156.4 on 633 degrees of freedom
## Multiple R-squared:  5.818e-05, Adjusted R-squared:  -0.001522
## F-statistic: 0.03683 on 1 and 633 DF, p-value: 0.8479
```

```
truehist(faib_vri_true_m1_df$asp_sin)
truehist(asp_sin_wsvha_lm$residuals)
plot(wsvha_L ~ asp_sin, data = faib_vri_true_m1_df,
     main="Linear function showing positive correlation:\nR^2=0.005, =15.197, p<0.000",
     col="blue", pch=20, cex=0.5, cex.main=0.6, cex.lab=0.8, cex.axis=0.8, adj=1,
     ylab = "wsvha_L (m3/ha)", xlab = "asp_sin")
abline(asp_sin_wsvha_lm, col = "red")
plot(asp_sin_wsvha_lm, which=1,
     main="Residuals showing almost constant variance",
     col="blue", pch=20, cex=0.5, cex.main=0.6, cex.lab=0.5, cex.axis=0.5, adj=1)
summary(lead_htop_wsvha_lm)
```

```
##
## Call:
## lm(formula = wsvha_L ~ lead_htop, data = faib_vri_true_m1_df)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -237.481  -41.807   -4.616   45.469  287.232
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept) -233.8917     9.1330  -25.61  <2e-16 ***
## lead_htop    21.1705     0.4419   47.91  <2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 72.72 on 633 degrees of freedom
## Multiple R-squared:  0.7838, Adjusted R-squared:  0.7835
## F-statistic: 2295 on 1 and 633 DF,  p-value: < 2.2e-16
```

```
truehist(faib_vri_true_m1_df$lead_htop)
truehist(lead_htop_wsvha_lm$residuals)
plot(wsvha_L ~ lead_htop, data = faib_vri_true_m1_df,
     main="Linear function shows positive correlation:\n R^2=0.6508, =20.6829, p<0.0000",
     col="blue", pch=20, cex=0.5, cex.main=0.6, cex.lab=0.8, cex.axis=0.8, adj=1,
     ylab = "wsvha_L (m3/ha)", xlab = "lead_htop")
abline(lead_htop_wsvha_lm, col = "red")
plot(lead_htop_wsvha_lm, which=1,
     main="Residuals showing non-constant variance with\n increasing trends at smallest and largest fit",
     col="blue", pch=20, cex=0.5, cex.main=0.6, cex.lab=0.5, cex.axis=0.5, adj=1)
summary(stemsha_L_wsvha_lm)
```

```
##
## Call:
## lm(formula = wsvha_L ~ stemsha_L, data = faib_vri_true_m1_df)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -194.29  -88.39  -40.98   52.69  599.97
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)  21.79199    14.02008   1.554   0.121
## stemsha_L    0.29974     0.02419  12.392  <2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 140.3 on 633 degrees of freedom
## Multiple R-squared:  0.1952, Adjusted R-squared:  0.194
## F-statistic: 153.6 on 1 and 633 DF,  p-value: < 2.2e-16
```

```
truehist(faib_vri_true_m1_df$stemsha_L)
truehist(stemsha_L_wsvha_lm$residuals)
plot(wsvha_L ~ stemsha_L, data = faib_vri_true_m1_df,
```

```

    main="No significant relationship with response variable:\nR^2=0.0001, =-0.0008, p<0.4743",
    col="blue", pch=20, cex=0.5, cex.main=0.6, cex.lab=0.5, cex.axis=0.5, adj=1,
    ylab = "wsvha_L (m3/ha)", xlab = "stemsha_L")
abline(stemsha_L_wsvha_lm, col = "red")
plot(stemsha_L_wsvha_lm, which=1,
     main="Residuals showing non-constant variance with negative\nand positive errors clusters at large",
     col="blue", pch=20, cex=0.5, cex.main=0.6, cex.lab=0.5, cex.axis=0.5, adj=1)
wsvha_L_lm = lm(wsvha_L ~ ., data = faib_vri_true_m1_df)
truehist(faib_vri_true_m1_df$wsvha_L)
truehist(wsvha_L_lm$residuals)
plot(wsvha_L_lm$residuals,
     main="",
     col="blue", pch=20, cex=0.8, cex.main=0.8, cex.lab=0.8, cex.axis=0.8, adj=1,
     ylab = "wsvha_L (m3/ha)", xlab = "predictors")
abline(wsvha_L_lm, col="red")
summary(species_class_wsvha_lm)

```

```





##
## Call:
## lm(formula = wsvha_L ~ species_class, data = faib_vri_true_m1_df)
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -275.02 -108.63  -41.67   76.84  581.18
##
## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)    117.692     12.580   9.356 < 2e-16 ***
## species_class     33.627       5.836   5.762 1.3e-08 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 152.5 on 633 degrees of freedom
## Multiple R-squared:  0.04983,    Adjusted R-squared:  0.04833
## F-statistic: 33.2 on 1 and 633 DF,  p-value: 1.301e-08


```

```

faib_vri_true_m1_df$species_class = as.numeric(faib_vri_true_m1_df$species_class)
truehist(faib_vri_true_m1_df$species_class)
truehist(species_class_wsvha_lm$residuals)
plot(species_class_wsvha_lm, which=1,
     main="Residuals showing decreasing trend with True-fir group:\nR^2=0.0025, =6.584, p<0.000",
     col="blue", pch=20, cex=0.5, cex.main=0.6, cex.lab=0.5, cex.axis=0.5, adj=1)
car::residualPlots(elev_wsvha_lm, terms= ~ 1 | species_class, cex=0.1, pch=19) # plot vs. yhat grouping

```





Modelling: Fit, cross-validate and tune models

```

tuneResult_rf_m2_full <- tune.randomForest(
  X_m2, y_m2,
  mtry = c(2:10), ntree = 50,
  tunecontrol = tune.control(sampling = "cross", cross = 10),
  preProcess = c("BoxCox", "center", "scale"))

tuneResult_rf_m1_full <- tune.randomForest(
  X_m1, y_m1,
  mtry = c(2:10), ntree = 50,
  tunecontrol = tune.control(sampling = "cross", cross = 10),
  preProcess = c("BoxCox", "center", "scale"))

tunedModel_rf_m2_full <- tuneResult_rf_m2_full$best.model
tunedModel_rf_m1_full <- tuneResult_rf_m1_full$best.model
print(summary(tunedModel_rf_m2_full))
print(summary(tunedModel_rf_m1_full))
tunedModel_rf_m2_full
tunedModel_rf_m1_full
save(tunedModel_rf_m2_full, file = "/media/seamus/128GB_WORKD/data/models/tcc-wsvha/wsvha_model2_rndmFor")
save(tunedModel_rf_m1_full, file = "/media/seamus/128GB_WORKD/data/models/tcc-wsvha/wsvha_model1_rndmFor")
tunedModel_rf_m2 = predict(tunedModel_rf_m2_full, X_m2, y_m2, type = "response")
tunedModel_rf_m1 = predict(tunedModel_rf_m1_full, X_m1, y_m1, type = "response")
tuneResult_rf_m2_train <- tune.randomForest(X_train_m2, y_train_m2, mtry = c(2:10), ntree = 50,
  tunecontrol = tune.control(sampling = "cross", cross = 10), preProcess = c("BoxCox", "center", "scale"))
tuneResult_rf_m1_train <- tune.randomForest(X_train_m1, y_train_m1, mtry = c(2:10), ntree = 50,
  tunecontrol = tune.control(sampling = "cross", cross = 10), preProcess = c("BoxCox", "center", "scale"))
tunedModel_rf_m2_train <- tuneResult_rf_m2_train$best.model
tunedModel_rf_m1_train <- tuneResult_rf_m1_train$best.model
tunedModel_rf_m2_test = predict(tunedModel_rf_m2_train, X_test_m2, y_test_m2, type="response")
tunedModel_rf_m1_test = predict(tunedModel_rf_m1_train, X_test_m1, y_test_m1, type="response")
tunedModel_rf_m2_full_MAE = MAE(tunedModel_rf_m2, y_m2)
tunedModel_rf_m2_full_RMSE = RMSE(tunedModel_rf_m2, y_m2)
tunedModel_rf_m1_full_MAE = MAE(tunedModel_rf_m1, y_m2)
tunedModel_rf_m1_full_RMSE = RMSE(tunedModel_rf_m1, y_m2)
tunedModel_rf_m2_test_MAE = MAE(tunedModel_rf_m2_test, y_test_m2)
tunedModel_rf_m2_test_RMSE = RMSE(tunedModel_rf_m2_test, y_test_m2)
tunedModel_rf_m1_test_MAE = MAE(tunedModel_rf_m1_test, y_test_m2)
tunedModel_rf_m1_test_RMSE = RMSE(tunedModel_rf_m1_test, y_test_m2)

R2(tunedModel_rf_m2, y_m2)
MAE(tunedModel_rf_m2, y_m2)
RMSE(tunedModel_rf_m2, y_m2)
MAE(tunedModel_rf_m2_test, y_test_m2)
RMSE(tunedModel_rf_m2_test, y_test_m2)
tunedModel_rf_m2_full_RMSE/tunedModel_rf_m2_test_RMSE
R2(tunedModel_rf_m1, y_m1)
MAE(tunedModel_rf_m1, y_m1)
RMSE(tunedModel_rf_m1, y_m1)
MAE(tunedModel_rf_m1_test, y_test_m1)
RMSE(tunedModel_rf_m1_test, y_test_m1)
tunedModel_rf_m1_full_RMSE/tunedModel_rf_m1_test_RMSE





tuneResult_rf_m2_full$performances

```

```

tuneResult_rf_m1_full$performances
tunedModel_rf_m2_to_raster <- predict(covs_m2, tunedModel_rf_m2_full)
tunedModel_rf_m1_to_raster <- predict(covs_m1, tunedModel_rf_m1_full)
tunedModel_rf_m2_to_raster_gaspard <- predict(covs_m2_gaspard, tunedModel_rf_m2_full)
tunedModel_rf_m1_to_raster_gaspard <- predict(covs_m1_gaspard, tunedModel_rf_m1_full)
tunedModel_rf_m2_to_raster_quesnel <- predict(covs_m2_quesnel, tunedModel_rf_m2_full)
tunedModel_rf_m1_to_raster_quesnel <- predict(covs_m1_quesnel, tunedModel_rf_m1_full)
writeRaster(tunedModel_rf_m2_to_raster, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/wsvha/wsvl")
writeRaster(tunedModel_rf_m1_to_raster, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/wsvha/wsvl")
writeRaster(tunedModel_rf_m2_to_raster_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/wsvha/wsvl")
writeRaster(tunedModel_rf_m1_to_raster_gaspard, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/wsvha/wsvl")
writeRaster(tunedModel_rf_m2_to_raster_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/wsvha/wsvl")
writeRaster(tunedModel_rf_m1_to_raster_quesnel, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/wsvha/wsvl")

```



```

tuneResult_svm_m2_full <- tune(
  svm, X_m2, y_m2,
  ranges = list(cost = c(1,5,7,15,20), gamma = 2^(-1:1)),
  tunecontrol = tune.control(cross = 10),
  preProcess = c("BoxCox", "center", "scale"))

tuneResult_svm_m1_full <- tune(
  svm, X_m1, y_m1,
  ranges = list(cost = c(1,5,7,15,20), gamma = 2^(-1:1)),
  tunecontrol = tune.control(cross = 10),
  preProcess = c("BoxCox", "center", "scale"))

```

```

tunedModel_svm_m2_full <- tuneResult_svm_m2_full$best.model
tunedModel_svm_m1_full <- tuneResult_svm_m1_full$best.model
print(summary(tunedModel_svm_m2_full))
print(summary(tunedModel_svm_m1_full))
save(tunedModel_svm_m2_full, file = "/media/seamus/128GB_WORKD/data/models/tcc-wsvha/wsvha_model2_svmRac
save(tunedModel_svm_m1_full, file = "/media/seamus/128GB_WORKD/data/models/tcc-wsvha/wsvha_model1_svmRac
tunedModel_svm_m2 = predict(tunedModel_svm_m2_full, data=faib_vri_true_m2_df)
tunedModel_svm_m1 = predict(tunedModel_svm_m1_full, data=faib_vri_true_m1_df)

tunedModel_rf_m2_full <- tuneResult_rf_m2_full$best.model
tunedModel_rf_m1_full <- tuneResult_rf_m1_full$best.model
print(summary(tunedModel_rf_m2_full))
print(summary(tunedModel_rf_m1_full))
tunedModel_rf_m2_full
tunedModel_rf_m1_full
save(tunedModel_rf_m2_full, file = "/media/seamus/128GB_WORKD/data/models/tcc-wsvha/wsvha_model2_rndmFor
save(tunedModel_rf_m1_full, file = "/media/seamus/128GB_WORKD/data/models/tcc-wsvha/wsvha_model1_rndmFor
tunedModel_rf_m2 = predict(tunedModel_rf_m2_full, X_m2, y_m2, type = "response")
tunedModel_rf_m1 = predict(tunedModel_rf_m1_full, X_m1, y_m1, type = "response")
tuneResult_rf_m2_train <- tune.randomForest(X_train_m2, y_train_m2, mtry = c(2:10), ntree = 50,
  tunecontrol = tune.control(sampling = "cross", cross = 10), preProcess = c("BoxCox", "center", "scale"))
tuneResult_rf_m1_train <- tune.randomForest(X_train_m1, y_train_m1, mtry = c(2:10), ntree = 50,
  tunecontrol = tune.control(sampling = "cross", cross = 10), preProcess = c("BoxCox", "center", "scale"))
tunedModel_rf_m2_train <- tuneResult_rf_m2_train$best.model
tunedModel_rf_m1_train <- tuneResult_rf_m1_train$best.model
tunedModel_rf_m2_test = predict(tunedModel_rf_m2_train, X_test_m2, y_test_m2, type="response")
tunedModel_rf_m1_test = predict(tunedModel_rf_m1_train, X_test_m1, y_test_m1, type="response")
tunedModel_rf_m2_full_MAE = MAE(tunedModel_rf_m2, y_m2)
tunedModel_rf_m2_full_RMSE = RMSE(tunedModel_rf_m2, y_m2)
tunedModel_rf_m1_full_MAE = MAE(tunedModel_rf_m1, y_m2)
tunedModel_rf_m1_full_RMSE = RMSE(tunedModel_rf_m1, y_m2)
tunedModel_rf_m2_test_MAE = MAE(tunedModel_rf_m2_test, y_test_m2)
tunedModel_rf_m2_test_RMSE = RMSE(tunedModel_rf_m2_test, y_test_m2)
tunedModel_rf_m1_test_MAE = MAE(tunedModel_rf_m1_test, y_test_m2)
tunedModel_rf_m1_test_RMSE = RMSE(tunedModel_rf_m1_test, y_test_m2)

R2(tunedModel_rf_m2, y_m2)
MAE(tunedModel_rf_m2, y_m2)
RMSE(tunedModel_rf_m2, y_m2)
MAE(tunedModel_rf_m2_test, y_test_m2)
RMSE(tunedModel_rf_m2_test, y_test_m2)
tunedModel_rf_m2_full_RMSE/tunedModel_rf_m2_test_RMSE
R2(tunedModel_rf_m1, y_m1)
MAE(tunedModel_rf_m1, y_m1)
RMSE(tunedModel_rf_m1, y_m1)
MAE(tunedModel_rf_m1_test, y_test_m1)
RMSE(tunedModel_rf_m1_test, y_test_m1)
tunedModel_rf_m1_full_RMSE/tunedModel_rf_m1_test_RMSE

tuneResult_rf_m2_full$performances
tuneResult_rf_m1_full$performances
tunedModel_rf_m2_to_raster <- predict(covs_m2, tunedModel_rf_m2_full)

```

```
tunedModel_rf_m1_to_raster <- predict(covs_m1, tunedModel_rf_m1_full)
writeRaster(tunedModel_rf_m2_to_raster, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/wsvha/wsvl")
writeRaster(tunedModel_rf_m1_to_raster, filename = "/media/seamus/128GB_WORKD/data/raster/tcc/wsvha/wsvl")
```