

## CS61B Lecture #36

### Today:

- A Brief Side Trip: Enumeration types.
- *DSIJ*, Chapter 10, *HFJ*, pp. 489-516.
  - Threads
  - Communication between threads
  - Synchronization
  - Mailboxes

## Side Trip into Java: Enumeration Types

- Problem: Need a type to represent something that has a few discrete values.
- In the purest form, the only necessary operations are `==` the only property of a value of the type is that it differs from others.
- In older versions of Java, used named integer constants:

```
interface Pieces {  
    int BLACK_PIECE = 0,    // Fields in interfaces are static  
        BLACK_KING = 1,  
        WHITE_PIECE = 2,  
        WHITE_KING = 3,  
        EMPTY = 4;  
}
```

- C and C++ provide *enumeration types* as a shorthand, with syntax like this:

```
enum Piece { BLACK_PIECE, BLACK_KING, WHITE_PIECE, WHITE_KING, ... }
```

- But since all these values are basically **ints**, accidents can happen

## Enum Types in Java

- New version of Java allows syntax like that of C or C++, but with more guarantees:

```
public enum Piece {  
    BLACK_PIECE, BLACK_KING, WHITE_PIECE, WHITE_KING, EMPTY  
}
```

- Defines Piece as a new reference type, a special kind of class.
- The names BLACK\_PIECE, etc., are static, final *enumeration constants* (or *enumerals*) of type PIECE.
- They are automatically initialized, and are the only values of the enumeration type that exist (illegal to use **new** to create a new value.)
- Can safely use ==, and also switch statements:

```
boolean isKing(Piece p) {  
    switch (p) {  
        case BLACK_KING: case WHITE_KING: return true;  
        default: return false;  
    }  
}
```

## Making Enumerals Available Elsewhere

- Enumerals like `BLACK_PIECE` are static members of a class, not methods.
- Therefore, unlike *C* or *C++*, their declarations are not automatically visible outside the enumeration class definition.
- So, in other classes, must write `Piece.BLACK_PIECE`, which is a bit annoying.
- However, with version 1.5, Java has *static imports*: to import static definitions of class `checkers.Piece` (including enumerals), write

```
import static checkers.Piece.*;
```

among the import clauses.

- Alas, cannot use this for enum classes in the anonymous package.

## Operations on Enum Types

- Order of declaration of enumeration constants significant: `Piece.BLACK_KING.ordinal()` gives the position (numbering from 0) of an enumeration value. `Piece.BLACK_KING.ordinal()` is 1.
- The array `Piece.values()` gives all the possible values of the type `Piece`. Thus, you can write:

```
for (Piece p : Piece.values())  
    System.out.printf("Piece value #%d is %s%n", p.ordinal(), p.name());
```

- The static function `Piece.valueOf()` converts a `String` into a type `Piece`. So `Piece.valueOf("EMPTY") == EMPTY`.

## Fancy Enum Types

- Enums are classes. You can define all the extra fields, methods, constructors you want.
- Constructors are used only in creating enumeration constants. Constructor arguments follow the constant name:

```
enum Piece {  
    BLACK_PIECE(BLACK, false, "b"), BLACK_KING(BLACK, true, "E"  
    WHITE_PIECE(WHITE, false, "w"), WHITE_KING(WHITE, true, "W"  
    EMPTY(null, false, " ");  
  
    private final Side color;  
    private final boolean isKing;  
    private final String textName;  
  
    Piece(Side color, boolean isKing, String textName) {  
        this.color = color; this.isKing = isKing; this.textName  
    }  
  
    Side color() { return color; }  
    boolean isKing() { return isKing; }  
    String textName() { return textName; }  
}
```

## Threads

- So far, all our programs consist of single sequence of instructions.
- Each such sequence is called a *thread* (for “thread of control”).
- Java supports programs containing *multiple* threads, which (virtually) run concurrently.
- Actually, on a uniprocessor, only one thread at a time actually runs, while others wait, but this is largely invisible.
- To allow program access to threads, Java provides the type `Thread` in `java.lang`. Each `Thread` contains information about, and controls, one thread.
- Simultaneous access to data from two threads can cause corruption. Java also provides constructs for controlled communication, allowing threads to *lock* objects, to *wait* to be notified of events, and to *interrupt* other threads.

## But Why?

- Typical Java programs always have  $> 1$  thread: besides the main program, others clean up garbage objects, receive signals, update the display, other stuff.
- When programs deal with asynchronous events, it is sometimes convenient to organize into subprograms, one for each independent sequence of events.
- Threads allow us to insulate one such subprogram from another.
- GUIs often organized like this: application is doing some computation or I/O, another thread waits for mouse clicks (like a waiter), another pays attention to updating the screen as needed.
- Large servers like search engines may be organized this way with one thread per request.
- And, of course, sometimes we do have a real multiprocessor.



## Java Mechanics

- To specify the actions “walking” and “chewing gum”:

```
class Chewer1 implements Runnable {  
    public void run()  
        { while (true) ChewGum(); }  
}  
class Walker1 implements Runnable {  
    public void run()  
        { while (true) Walk(); }  
}
```

```
// Walk and chew gum  
Thread clomp  
    = new Thread(new  
Chewer1());  
Thread clomp  
    = new Thread(new  
Walker1());  
clomp.start(); clomp.st
```

- Concise Alternative (uses fact that Thread implements Runnable)

```
class Chewer2 extends Thread {  
    public void run()  
        { while (true) ChewGum(); }  
}  
class Walker2 extends Thread {  
    public void run()  
        { while (true) Walk(); }  
}
```

```
Thread clomp = new Chewer2();  
clomp = new Walker2();  
clomp.start();  
clomp.start();
```

## Avoiding Interference

- When one thread has data for another, one must wait for the other to be ready.
- Likewise, if two threads use the same data structure, generally only one should modify it at a time; other must wait.
- E.g., what would happen if two threads simultaneously insert an item into a linked list at the same point in the list?
- A: Both could conceivably execute

```
p.next = new ListCell(x, p.next);
```

with the same values of `p` and `p.next`; one insertion is lost.

- Can arrange for only one thread at a time to execute a method on a particular object with either of the following equivalent definitions

```
void f(...) {  
    synchronized (this) {  
        body of f  
    }  
}
```

```
synchronized void f(...)  
{  
    body of f  
}
```

## Communicating the Hard Way

- Communicating data is tricky: the faster party must wait slower.
- Obvious approaches for sending data from thread to thread work:

```
class DataExchanger {  
    Object value = null;  
    Object receive() {  
        Object r; r = null;  
        while (r == null)  
            { r = value; }  
        value = null;  
        return r;  
    }  
    void deposit(Object data) {  
        while (value != null) { }  
        value = data;  
    }  
}
```

```
DataExchanger exchanger  
    = new DataExchanger()  
-----  
  
// thread1 sends to thr  
exchanger.deposit("Hell  
-----  
  
// thread2 receives from  
msg = (String) exchange
```

- **BAD:** One thread can monopolize machine while waiting; two executing deposit or receive simultaneously cause chaos.

## Primitive Java Facilities

- `wait` method on `Object` makes thread wait (not using process) until notified by `notifyAll`, unlocking the `Object` while it waits
- Example, `ucb.util.mailbox` has something like this (simplified)

```
interface Mailbox {
    void deposit(Object msg) throws InterruptedException;
    Object receive() throws InterruptedException;
}


class QueuedMailbox implements Mailbox {
    private List<Object> queue = new LinkedList<Object>();

    public synchronized void deposit(Object msg) {
        queue.add(msg);
        this.notifyAll(); // Wake any waiting receivers
    }

    public synchronized Object receive() throws InterruptedException {
        while (queue.isEmpty()) wait();
        return queue.remove(0);
    }
}
```

## Message-Passing Style

- Use of Java primitives very error-prone. Wait until CS162.
- Mailboxes are higher-level, and allow the following programming structure:



- Where each Player is a thread that looks like this:

```
while (! gameOver()) {  
    if (myMove())  
        outBox.deposit(computeMyMove(lastMove));  
    else  
        lastMove = inBox.receive();  
}
```

## More Concurrency

- Previous example can be done other ways, but mechanism flexible.
- E.g., suppose you want to think during opponent's move:

```
while (!gameOver()) {  
    if (myMove())  
        outBox.deposit(computeMyMove(lastMove));  
    else {  
        do {  
            thinkAheadALittle();  
            lastMove = inBox.receiveIfPossible();  
        } while (lastMove == null);  
    }  
}
```

- receiveIfPossible (written receive(0) in our actual package) wait; returns null if no message yet, perhaps like this:

```
public synchronized Object receiveIfPossible()  
    throws InterruptedException {  
    if (queue.isEmpty())  
        return null;  
    return queue.remove(0);  
}
```

## Coroutines

- A *coroutine* is a kind of synchronous thread that explicitly hands off control to other coroutines so that only one executes at a time, like Python generators. Can get similar effect with three mailboxes.
- Example: recursive inorder tree iterator:

```
class TreeIterator extends Thread {
    Tree root; Mailbox r;
    TreeIterator(Tree T, Mailbox r) {
        this.root = T; this.dest = r;
    }
    public void run() {
        traverse(root);
        r.deposit(End marker);
    }
    void traverse(Tree t) {
        if (t == null) return;
        traverse(t.left);
        r.deposit(t.label);
        traverse(t.right);
    }
}
```

```
void treeProcessor(Tree T) {
    Mailbox m = new QueuedMailbox();
    new TreeIterator(T, m).start();
    while (true) {
        Object x = m.receive();
        if (x is end marker)
            break;
        do something with x;
    }
}
```

## Use In GUIs

- Java runtime library uses a special thread that does not wait for *events* like mouse clicks, pressed keys, mouse movement, etc.
- You can designate an object of your choice as a *listener*, which means that Java's event thread calls a method of that object whenever an event occurs.
- As a result, your program can do work while the GUI continues to respond to buttons, menus, etc.
- Another special thread does all the drawing. You don't have to be aware when this takes place; just ask that the thread wake up whenever you change something.



## Highlights of a GUI Component

```
/** A widget that draws multi-colored lines indicated by mouse
class Lines extends JComponent implements MouseListener {
    private List<Point> lines = new ArrayList<Point>();

    Lines() { // Main thread calls this to create one
        setPreferredSize(new Dimension(400, 400));
        addMouseListener(this);
    }
    public synchronized void paintComponent(Graphics g) { // Paint
        g.setColor(Color.white);    g.fillRect(0, 0, 400, 400);
        int x, y;    x = y = 200;
        Color c = Color.black;
        for (Point p : lines)
            g.setColor(c); c = chooseNextColor(c);
            g.drawLine(x, y, p.x, p.y); x = p.x; y = p.y;
        }
    }
    public synchronized void mouseClicked(MouseEvent e) // Event
    { lines.add(new Point(e.getX(), e.getY())); repaint(); }
    ...
}
```

# Interrupts

- An *interrupt* is an event that disrupts the normal flow of control in a program.
- In many systems, interrupts can be totally *asynchronous*, occurring at arbitrary points in a program, the Java developers considered this unwise; arranged that interrupts would occur only at control points.
- In Java programs, one thread can interrupt another to indicate that something unusual needs attention:

```
otherThread.interrupt();
```

- But `otherThread` does not receive the interrupt until it waits in methods `wait`, `sleep` (wait for a period of time), `join` (wait for thread to terminate), and mailbox `deposit` and `receive`.
- Interrupt causes these methods to throw `InterruptedException`, so typical use is like this:

```
try {  
    msg = inBox.receive();  
} catch (InterruptedException e) { HandleEmergency(); }
```

## Remote Mailboxes (A Side Excursion)

- RMI: Remote Method Interface allows one program to reference objects in another program.
- We use it to allow mailboxes in one program be received & deposited into in another.
- To use this, you define an *interface* to the remote object:


```
import java.rmi.*;
interface Mailbox extends Remote {
    void deposit(Object msg)
        throws InterruptedException, RemoteException;
    Object receive()
        throws InterruptedException, RemoteException;
    ...
}
```

- On machine that actually will contain the object, you define

```
class QueuedMailbox ... implements Mailbox {
    Same implementation as before, roughly
}
```

## Remote Objects Under the Hood

```
// On machine #1:           // On Machine #2:
Mailbox outBox              Mailbox inBox
    = new QueuedMailbox();    = get outBox from machine #1
```



- Because Mailbox is an interface, hides fact that on Machine #1 doesn't actually have direct access to it.
- Requests for method calls are relayed by I/O to machine that has the real object.
- Any argument or return type OK if it also implements RemoteObject can be *serialized*—turned into stream of bytes and back, primitive types and String.
- Because I/O involved, expect failures, hence every method call can throw RemoteException (subtype of IOException).