

Recreation

What is the sum of the coefficients of

$$(1 - 3x + 3x^2)^{743}(1 + 3x - 3x^2)^{744}$$

after expanding and collecting terms?

Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 1

CS61B Lecture #5: Arrays

- An array is a structured container whose components are
 - **length**, a fixed integer.
 - a sequence of **length** simple containers of the same type, numbered from 0.
 - (.length field usually implicit in diagrams.)
- Arrays are anonymous, like other structured containers.
- Always referred to with pointers.
- For array pointed to by A,
 - Length is A.length
 - Numbered component i is A[i] (i is the *index*)
 - Important feature: index can be *any integer expression*.


Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 2

A Few Samples

Java

Results



```
int[] x, y, z;
String[] a;
x = new int[3];
y = x;
a = new String[3];
x[1] = 2;
y[1] = 3;
a[1] = "Hello";
```

Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 4

Example: Accumulate Values

Problem: Sum up the elements of array A.

```
static int sum(int[] A) {
    int N;
    N = 0;
    for (int i = 0; i < A.length; i += 1)
        N += A[i];
    return N;
}
```

// For the hard-core: could have written

```
int N, i;
for (i=0, N=0; i<A.length; N += A[i], i += 1)
    { } // or just ;
```


// But please don't: it's obscure.

Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 5

Example: Insert into an Array

Problem: Want a call like insert(A, 2, "gnu") to convert (destructively)



/** Insert X at location K in ARR, moving items K, K+1, ... to locations K+1, K+2, The last item in ARR is lost. */

```
static void insert (String[] arr, int k, String x) {
    for (int i = arr.length-1; i > k; i -= 1) // Why backwards?
        arr[i] = arr[i-1];
```

/* Alternative to this loop:

System.arraycopy(arr, k, arr, k+1, arr.length-k-1);*/

arr[k] = x;

}

Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 6

(Aside) Java Shortcut

- **Useful tip:** Can write just `'arraycopy'` by including at the top of the source file:

```
import static java.lang.System.arraycopy;
```

- This means "define the simple name `arraycopy` to be the equivalent of `java.lang.System.arraycopy` in the current source file."

- Can do the same for out so that you can write

```
out.println(...);
```

in place of

```
System.out.println(...);
```

- Finally, a declaration like

```
import static java.lang.Math.*;
```

means "take all the (public) static definitions in `java.lang.Math` and make them available in this source file by their simple names (the name after the last dot)."


- Useful for functions like `sin`, `sqrt`, etc.

Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 7

Growing an Array

Problem: Suppose that we want to change the description above, so that `A = insert2(A, 2, "gnu")` does *not* shove "skunk" off the end, but instead "grows" the array.



```
/** Return array, r, where r.length = ARR.length+1; r[0..K-1]
 * the same as ARR[0..K-1], r[K] = x, r[K+1..] same as ARR[K..] */
static String[] insert2(String[] arr, int k, String x) {
    String[] result = new String[arr.length + 1];
    arraycopy(arr, 0, result, 0, k);
    arraycopy(arr, k, result, k+1, arr.length-k);
    result[k] = x;
    return result;
}
```


Why do we need a different return type from `insert2`???

Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 8

Example: Merging

Problem: Given two sorted arrays of ints, A and B, produce their *merge*: a sorted array containing all items from A and B.



Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 9

Example: Merging Program

Problem: Given two sorted arrays of ints, A and B, produce their *merge*: a sorted array containing all from A and B.

Remark: In order to solve this recursively, it is useful to *generalize* the original function to allow merging *portions* of the arrays.

```
/** Assuming A and B are sorted, returns their merge. */
public static int[] merge(int[] A, int[] B) {
    return mergeTo(A, 0, B, 0);
}

/** The merge of A[L0..] and B[L1..] assuming A and B sorted. */
static int[] mergeTo(int[] A, int L0, int[] B, int L1) {
    int N = A.length - L0 + B.length - L1; int[] C = new int[N];
    if (L0 >= A.length) arraycopy(B, L1, C, 0, N);
    else if (L1 >= B.length) arraycopy(A, L0, C, 0, N);
    else if (A[L0] <= B[L1]) {
        C[0] = A[L0]; arraycopy(mergeTo(A, L0+1, B, L1), 0, C, 1, N-1);
    } else {
        C[0] = B[L1]; arraycopy(mergeTo(A, L0, B, L1+1), 0, C, 1, N-1);
    }
    return C;
}
```

What is wrong with this implementation?

Last modified: Mon Sep 9 14:29:19 2019


CS61B: Lecture #5 10

A Tail-Recursive Strategy

```
public static int[] merge(int[] A, int[] B) {
    return mergeTo(A, 0, B, 0, new int[A.length+B.length], 0);
}
```

```
/** Merge A[L0..] and B[L1..] into C[K..], assuming A and B sorted. */
static int[] mergeTo(int[] A, int L0, int[] B, int L1, int[] C, int k){
    ...
}
```

This last method merges *part* of A with part of B into part of C. For example, consider a possible call `mergeTo(A, 3, B, 1, C, 2)`



Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 11

A Tail-Recursive Solution

```
public static int[] merge(int[] A, int[] B) {
    return mergeTo(A, 0, B, 0, new int[A.length+B.length], 0);
}
```

```
/** Merge A[L0..] and B[L1..] into C[K..], assuming A and B sorted. */
static int[] mergeTo(int[] A, int L0, int[] B, int L1, int[] C, int k){
    if (??) {
        return C;
    } else if (??) {
        C[k] = A[L0];
        return mergeTo(A, ??, B, ??, C, ??)
    } else {
        C[k] = B[L1];
        return mergeTo(A, ??, B, ??, C, ??)
    }
}
```

Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 12

A Tail-Recursive Solution

```
public static int[] merge(int[] A, int[] B) {
    return mergeTo(A, 0, B, 0, new int[A.length+B.length], 0);
}

/** Merge A[L0..] and B[L1..] into C[K..], assuming A and B sorted. */
static int[] mergeTo(int[] A, int L0, int[] B, int L1, int[] C, int k){
    if (L0 >= A.length && L1 >= B.length) {
        return C;
    } else if (??) {
        C[k] = A[L0];
        return mergeTo(A, ??, B, ??, C, ??)
    } else {
        C[k] = B[L1];
        return mergeTo(A, ??, B, ??, C, ??)
    }
}
```

Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 13

A Tail-Recursive Solution

```
public static int[] merge(int[] A, int[] B) {
    return mergeTo(A, 0, B, 0, new int[A.length+B.length], 0);
}

/** Merge A[L0..] and B[L1..] into C[K..], assuming A and B sorted. */
static int[] mergeTo(int[] A, int L0, int[] B, int L1, int[] C, int k){
    if (L0 >= A.length && L1 >= B.length) {
        return C;
    } else if (L1 >= B.length || (L0 < A.length && A[L0] <= B[L1])) {
        C[k] = A[L0];
        return mergeTo(A, ??, B, ??, C, ??)
    } else {
        C[k] = B[L1];
        return mergeTo(A, ??, B, ??, C, ??)
    }
}
```

Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 14

A Tail-Recursive Solution

```
public static int[] merge(int[] A, int[] B) {
    return mergeTo(A, 0, B, 0, new int[A.length+B.length], 0);
}

/** Merge A[L0..] and B[L1..] into C[K..], assuming A and B sorted. */
static int[] mergeTo(int[] A, int L0, int[] B, int L1, int[] C, int k){
    if (L0 >= A.length && L1 >= B.length) {
        return C;
    } else if (L1 >= B.length || (L0 < A.length && A[L0] <= B[L1])) {
        C[k] = A[L0];
        return mergeTo(A, L0 + 1, B, L1, C, k + 1);
    } else {
        C[k] = B[L1];
        return mergeTo(A, ??, B, ??, C, ??)
    }
}
```

Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 15

A Tail-Recursive Solution

```
public static int[] merge(int[] A, int[] B) {
    return mergeTo(A, 0, B, 0, new int[A.length+B.length], 0);
}

/** Merge A[L0..] and B[L1..] into C[K..], assuming A and B sorted. */
static int[] mergeTo(int[] A, int L0, int[] B, int L1, int[] C, int k){
    if (L0 >= A.length && L1 >= B.length) {
        return C;
    } else if (L1 >= B.length || (L0 < A.length && A[L0] <= B[L1])) {
        C[k] = A[L0];
        return mergeTo(A, L0 + 1, B, L1, C, k + 1);
    } else {
        C[k] = B[L1];
        return mergeTo(A, L0, B, L1 + 1, C, k + 1);
    }
}
```

Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 16

Iterative Solution

In general, we don't use either of the previous approaches in languages like C and Java. Array manipulation is most often iterative:

```
public static int[] merge(int[] A, int[] B) {
    int[] C = new int[A.length + B.length];
    // mergeTo(A, 0, B, 0, C, 0)
    int L0, L1, k;
    L0 = L1 = k = 0;

    while (??) {
        if (L1 >= B.length || (L0 < A.length && A[L0] <= B[L1])) {
            C[k] = A[L0];
            ??
        } else {
            C[k] = B[L1];
            ??
        }
    }
    return C;
}
```

Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 17

Iterative Solution

In general, we don't use either of the previous approaches in languages like C and Java. Array manipulation is most often iterative:

```
public static int[] merge(int[] A, int[] B) {
    int[] C = new int[A.length + B.length];
    // mergeTo(A, 0, B, 0, C, 0)
    int L0, L1, k;
    L0 = L1 = k = 0;

    while (L0 < A.length || L1 < B.length) {
        if (L1 >= B.length || (L0 < A.length && A[L0] <= B[L1])) {
            C[k] = A[L0];
            ??
        } else {
            C[k] = B[L1];
            ??
        }
    }
    return C;
}
```

Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 18

Iterative Solution

In general, we don't use either of the previous approaches in languages like C and Java. Array manipulation is most often iterative:

```
public static int[] merge(int[] A, int[] B) {
    int[] C = new int[A.length + B.length];
    // mergeTo(A, 0, B, 0, C, 0)
    int L0, L1, k;
    L0 = L1 = k = 0;

    while (L0 < A.length || L1 < B.length) {
        if (L1 >= B.length || (L0 < A.length && A[L0] <= B[L1])) {
            C[k] = A[L0];
            L0 += 1; k += 1;
        } else {
            C[k] = B[L1];
            L1 += 1; k += 1;
        }
    }
    return C;
}
```

Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 19

Iterative Solution II

The same, with a for loop:

```
public static int[] merge(int[] A, int[] B) {
    int[] C = new int[A.length + B.length];
    int L0, L1;
    L0 = L1 = 0;
    for (int k = 0; k < C.length; k += 1) {
        if (L1 >= B.length || (L0 < A.length && A[L0] <= B[L1])) {
            C[k] = A[L0]; L0 += 1;
        } else {
            C[k] = B[L1]; L1 += 1;
        }
    }
    return C;
}
```

Invariant (true after `int k = 0`):

$0 \leq L0 < A.length \wedge 0 \leq L1 < B.length \wedge C.length = A.length + B.length \wedge k = L0 + L1$
 $\wedge C[0 : k]$ is a permutation of $A[0:L0] + B[0:L1]$
 $\wedge C[0 : k], A, B$ are sorted.


Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 20

Alternative Solution: Removing k

Using previous invariant that $k=L0+L1$ simplifies things:

```
public static int[] merge(int[] A, int[] B) {
    int[] C = new int[A.length + B.length];
    int L0, L1; L0 = L1 = 0;
    while (L0 + L1 < C.length) {
        if (L1 >= B.length || (L0 < A.length && A[L0] < B[L1])) {
            C[L0 + L1] = A[L0]; L0 += 1;
        } else {
            C[L0 + L1] = B[L1]; L1 += 1;
        }
    }
    return C;
}
```



Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 21

Multidimensional Arrays

What about two- or higher-dimensional layouts, such as

$$A = \begin{bmatrix} 2 & 3 & 4 & 5 \\ 4 & 9 & 16 & 25 \\ 8 & 27 & 64 & 125 \end{bmatrix} ?$$


Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 22

Multidimensional Arrays in Java

These are not primitive in Java, but we can build them as **arrays of arrays**:

```
int[][] A = new int[3][];
A[0] = new int[] {2, 3, 4, 5};
A[1] = new int[] {4, 9, 16, 25};
A[2] = new int[] {8, 27, 64, 125};
// or
int[][] A;
A = new int[][] { {2, 3, 4, 5},
                  {4, 9, 16, 25},
                  {8, 27, 64, 125} };
// or
int[][] A = { {2, 3, 4, 5},
              {4, 9, 16, 25},
              {8, 27, 64, 125} };
// or
int[][] A = new A[3][4];
for (int i = 0; i < 3; i += 1)
    for (int j = 0; j < 4; j += 1)
        A[i][j] = (int) Math.pow(j + 2, i + 1);
```




Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 23

Exotic Multidimensional Arrays

- Since every element of an array is independent, there is no single "width" in general:

```
int[][] A = new int[5][];
A[0] = new int[] {};
A[1] = new int[] {0, 1};
A[2] = new int[] {2, 3, 4, 5};
A[3] = new int[] {6, 7, 8};
A[4] = new int[] {9};
```



- What does this print?

```
int[][] ZERO = new int[3][];
ZERO[0] = ZERO[1] = ZERO[2] =
    new int[] {0, 0, 0};
ZERO[0][1] = 1;
System.out.println(ZERO[2][1]);
```


Last modified: Mon Sep 9 14:29:19 2019

CS61B: Lecture #5 24

Exotic Multidimensional Arrays

- Since every element of an array is independent, there is no single "width" in general:

```
int[] [] A = new int[5] [];  
A[0] = new int[] {};  
A[1] = new int[] {0, 1};  
A[2] = new int[] {2, 3, 4, 5};  
A[3] = new int[] {6, 7, 8};  
A[4] = new int[] {9};
```



- What does this print?

```
int[] [] ZERO = new int[3] [];  
ZERO[0] = ZERO[1] = ZERO[2] =  
    new int[] {0, 0, 0};  
ZERO[0][1] = 1;  
System.out.println(ZERO[2][1]);
```

