






**RTL Design Sherpa**



# **APB IOAPIC Micro-Architecture Specification 1.0**

**January 4, 2026**

## Table of Contents

1 Ioapic Mas Index.....	12
1.0.1 APB IOAPIC - Overview.....	12
1.0.2 Waveform 1.1: Interrupt Delivery.....	14
1.0.3 Waveform 1.2: Redirection Table Write.....	15
1.0.4 Waveform 1.3: Level-Triggered Interrupt.....	15
1.0.5 Waveform 1.4: Interrupt Masking.....	16
1.0.6 APB IOAPIC - Architecture.....	18
1.0.7 APB IOAPIC - Clocks and Reset.....	24
1.0.8 APB IOAPIC - Acronyms and Terminology.....	28
1.0.9 APB IOAPIC - References.....	30
1.0.10 APB IOAPIC - Block Overview.....	33
1.0.11 APB IOAPIC - FSM Summary.....	41
1.0.12 APB IOAPIC - Complete Register Map.....	45
1.1 Internal Registers (Accessed via IOREGSEL/IOWIN).....	46
1.2 Redirection Table (Internal Offsets 0x10-0x3F).....	47
1.3 Complete Register Address Map.....	50
1.3.1 Internal Register Offsets (via IOREGSEL).....	50
1.3.2 Typical IRQ Assignments (PC-Compatible Systems).....	51
1.4 Programming Examples.....	52
1.4.1 Example 1: Configure IRQ14 (IDE) - Edge-Triggered.....	52
1.4.2 Example 2: Configure IRQ9 (ACPI) - Level-Triggered.....	52
1.4.3 Example 3: Mask/Unmask an IRQ.....	53

1.4.4 Example 4: Check Delivery Status and Remote IRR.....	53
1.4.5 Example 5: Read IOAPIC Version and Capabilities.....	53
1.5 Register Field Summary.....	54
1.5.1 Control Fields (Software Writable).....	54
1.5.2 Status Fields (Read-Only).....	54
1.6 Reset Values.....	54
2 IOAPIC (I/O Advanced Programmable Interrupt Controller) TODO List.....	55
2.1 Status: Foundation Complete - Ready for Core Implementation.....	55
2.1.1 Completed ✓.....	55
2.1.2 High Priority  .....	55
2.1.3 Medium Priority  .....	57
2.1.4 Low Priority  .....	57
2.1.5 Implementation Notes.....	58
2.1.6 Testing Checklist.....	58
2.1.7 Key Design Decisions.....	59
2.1.8 Reference Files.....	59
2.1.9 Integration Requirements.....	59
3 IOAPIC PeakRDL Register Specification.....	60
3.1 Register Generation.....	60
3.2 Register Map Overview.....	60
3.2.1 Direct APB Access (0x00-0x0F).....	60
3.2.2 Internal Registers (accessed via IOREGSEL/IOWIN).....	61
3.3 Indirect Access Example.....	61
3.4 Key Features.....	62

3.5 Delivery Modes.....	62
3.6 Integration.....	62
3.7 Address Mapping Summary.....	62
4 Retro Legacy Blocks (RLB) - Complete Status and Roadmap.....	63
4.1 Module Implementation Status.....	63
4.1.1 COMPLETE - With APB Wrappers.....	63
4.1.2 COMPLETE - With APB Wrappers (cont.).....	64
4.1.3 INCOMPLETE - Missing APB Wrappers or Core RTL.....	64
4.1.4 EXTERNAL REFERENCE - Modern High-Performance Blocks.....	65
4.1.5  SPECIAL - Integration/Support Modules.....	65
4.2 Validation Status.....	65
4.2.1 Test Infrastructure Existing.....	65
4.2.2 Test Infrastructure NEEDED.....	65
4.3 Detailed Work Remaining.....	66
4.3.1 Phase 1: Validation Infrastructure (High Priority  ).....	66
4.3.2 Phase 2: Missing Modules Implementation (Medium-High Priority).....	68
4.3.3 Phase 3: Integration and System Validation.....	69
4.4 Validation Roadmap Summary.....	70
4.4.1 Immediate Priorities (Next 4 Weeks).....	70
4.4.2 Medium Term (Month 2).....	70
4.4.3 Long Term (Month 3+).....	70
4.5 Architectural Compliance Status.....	70
4.5.1 ✓ All Active Modules Compliant.....	70
4.6 Python Helper Scripts Status.....	71

4.7 Documentation Status.....	71
4.8 Work Breakdown - Estimated Time.....	72
4.8.1 Immediate (Next Sprint - 3-4 Weeks).....	72
4.8.2 Short Term (Next Quarter - Weeks 5-12).....	72
4.8.3 Medium Term (Quarter 2 - Weeks 13-24).....	72
4.8.4 Long Term (Quarter 3+).....	72
4.9 Critical Path Items.....	73
4.9.1 For MVP System (Minimum Viable Product).....	73
4.9.2 Critical for Validation.....	73
4.10 Recommendations.....	73
4.10.1 Next Actions (Priority Order).....	73
4.11 Session Summary (2025-11-16).....	74
5 RLB (Retro Legacy Blocks) - FPGA Implementation Guide.....	74
5.1 What Are RLB (Retro Legacy Blocks)?.....	74
5.1.1 Overview.....	74
5.1.2 Purpose.....	74
5.2 Implemented RLB Modules.....	75
5.2.1 ✓ Complete Modules.....	75
5.3 FPGA Implementation - Nexys A7 / Genesys2.....	76
5.3.1 Can RLB Be Implemented on These Boards? YES! ✓.....	76
5.3.2 Target FPGA Specifications.....	76
5.3.3 Resource Usage Estimates.....	77
5.3.4 What Can Fit on These Boards?.....	77
5.4 RLB System Integration on FPGA.....	78

5.4.1 Typical FPGA System Architecture.....	78
5.4.2 Example Use Cases on FPGAs.....	78
5.5 Nexys A7 Specific Integration.....	79
5.5.1 Available Resources on Nexys A7.....	79
5.5.2 How RLB Modules Map to Nexys A7.....	79
5.5.3 Example Nexys A7 Top-Level.....	80
5.6 Implementation Recommendations.....	80
5.6.1 For Nexys A7-100T.....	80
5.6.2 For Genesys 2.....	81
5.7 FPGA-Specific Considerations.....	81
5.7.1 Clock Management.....	81
5.7.2 Power Management.....	81
5.7.3 Interrupt Routing.....	81
5.7.4 External Interfaces.....	81
5.8 Soft Processor Options.....	82
5.8.1 MicroBlaze (Xilinx).....	82
5.8.2 RISC-V (Open Source).....	82
5.8.3 Custom Soft Core.....	83
5.9 Step-by-Step FPGA Implementation.....	83
5.9.1 Phase 1: Basic System (Week 1-2).....	83
5.9.2 Phase 2: Expand Peripherals (Week 3-4).....	83
5.9.3 Phase 3: Advanced Features (Week 5-6).....	83
5.9.4 Phase 4: Application Development (Week 7+).....	83
5.10 Example Address Map for FPGA.....	84

5.11 Software Development.....	84
5.11.1 Bare-Metal Firmware.....	84
5.11.2 Operating System Support.....	85
5.12 Advantages of RLB on FPGA.....	85
5.12.1 Development Benefits.....	85
5.12.2 Technical Benefits.....	85
5.12.3 Vs. Microcontroller.....	85
5.13 Conclusion.....	86
5.13.1 Can RLB Be Used on Nexys A7/Genesys2? ABSOLUTELY! ✓.....	86
6 Retro Legacy Blocks (RLB) - Module Architecture Audit.....	86
6.1 Summary.....	86
6.1.1 Findings.....	86
6.1.2 Modules Without APB Wrappers.....	87
6.2 Detailed Findings.....	87
6.2.1 ✓ HPET (Reference Implementation - CORRECT).....	87
6.2.2 ✓ PIT_8254 (CORRECT).....	88
6.2.3 ✓ SMBUS (NOW CORRECT).....	88
6.2.4 ✓ RTC (CORRECT - VERIFIED).....	88
6.2.5 ✓ PIC_8259 (CORRECT - VERIFIED).....	89
6.3 Recommendations.....	89
6.3.1 Priority 1: Verify RTC and PIC_8259.....	89
6.3.2 Priority 2: CDC Decision Matrix.....	89
6.3.3 Priority 3: Standardization.....	90
6.4 Action Items.....	90

6.4.1 Completed (This Session).....	90
6.4.2 Optional Future Work.....	90
6.4.3 Long Term.....	90
6.5 Final Audit Conclusion ✓.....	91
6.5.1 Verification Summary.....	91
6.5.2 What Was Done This Session.....	91
6.5.3 Architecture Consistency: 100% ✓.....	91
6.6 Architecture Standard (Based on HPET).....	91
6.6.1 Recommended Pattern for All RLB Modules.....	91
6.6.2 Key Files Needed.....	92



## List of Figures

*No figures in this document.*

## List of Tables

*No tables in this document.*

## List of Waveforms

Waveform 1.1: Interrupt Delivery.....	14
Waveform 1.2: Redirection Table Write.....	15
Waveform 1.3: Level-Triggered Interrupt.....	15
Waveform 1.4: Interrupt Masking.....	16

# 1 Ioapic Mas Index

Generated: 2026-01-04

RTL Design Sherpa · Learning Hardware Design Through Practice GitHub · Documentation Index · MIT License

---

## 1.0.1 APB IOAPIC - Overview

### 1.0.1.1 Introduction

The APB I/O Advanced Programmable Interrupt Controller (IOAPIC) is a sophisticated interrupt routing peripheral designed for advanced system interrupt management. It provides 24 programmable interrupt inputs with flexible redirection to multiple CPUs, supporting both edge and level-triggered modes. The design implements Intel 82093AA-compatible indirect register access while integrating seamlessly with the RLB architecture via AMBA APB4 interface.

### 1.0.1.2 Key Features

- **24 Independent IRQ Inputs:** IRQ0-IRQ23 with individual configuration per interrupt source
- **Programmable Redirection Table:** 64-bit entry per IRQ defining vector, mode, destination, trigger, polarity
- **Indirect Register Access:** Intel-compatible IOREGSEL/IOWIN mechanism for register access
- **Dual Trigger Modes:**
  - **Edge-triggered:** Latches interrupt on signal edge, fires once
  - **Level-triggered:** Tracks signal level, uses Remote IRR, requires EOI
- **Configurable Polarity:** Active-high or active-low per IRQ input
- **Priority Arbitration:** Static priority (lowest IRQ number wins for MVP)
- **Delivery Modes:** Fixed mode (MVP), with support for LowestPri, SMI, NMI, INIT, ExtINT (future)
- **Remote IRR:** Level-triggered interrupt tracking with End-of-Interrupt (EOI) handling
- **APB Interface:** Standard AMBA APB4 compliant with 12-bit addressing
- **Clock Domain Crossing:** Optional CDC support via CDC\_ENABLE parameter

- **PeakRDL Integration:** Register map generated from SystemRDL specification
- **Intel 82093AA Compatible:** Register layout and behavior match Intel specification

### 1.0.1.3 Applications

**Multi-Processor Systems:** - Flexible interrupt routing to multiple CPUs - Per-IRQ destination configuration - Delivery mode selection per interrupt - Scalable interrupt distribution

**PC-Compatible Systems:** - x86 PC interrupt architecture - ISA bus interrupt routing - PCI interrupt support (INTA-INTD mapping) - Legacy IRQ redirection (IRQ0-15)

**Embedded Systems:** - Complex interrupt topologies - Priority-based interrupt handling - Mixed edge/level interrupt sources - Polarity-agnostic interrupt inputs

**System Management:** - Interrupt masking per source - Delivery status monitoring - Remote IRR tracking - Flexible interrupt mapping

### 1.0.1.4 Design Philosophy

**Intel Compatibility:** The IOAPIC implements the Intel 82093AA indirect register access method (IOREGSEL/IOWIN) for compatibility with existing software. This allows software written for Intel chipsets to work with minimal modifications.

**Flexibility:** Each of the 24 IRQ inputs can be independently configured for trigger mode (edge/level), polarity (active-high/low), delivery mode, destination CPU, and interrupt vector. This flexibility supports diverse system architectures.

**Reliability:** - 3-stage input synchronization prevents metastability - Edge detection with glitch immunity - Remote IRR prevents level interrupt re-triggering until EOI - Delivery status tracking ensures reliable interrupt delivery

**Standards Compliance:** - **APB Protocol:** Full AMBA APB4 specification compliance - **PeakRDL:** Industry-standard SystemRDL for register generation - **Intel 82093AA:** Register layout and access method compatibility - **Reset Convention:** Consistent active-low asynchronous reset

**Modularity:** Clean separation between interrupt routing logic (ioapic\_core), register interface (ioapic\_config\_regs), and bus interface (apb\_ioapic) enables easy customization and integration.

### 1.0.1.5 Comparison with Intel 82093AA IOAPIC

The APB IOAPIC draws directly from the Intel 82093AA I/O APIC specification with RLB architecture enhancements:

Feature	Intel 82093AA	APB IOAPIC
<b>Interface</b>	Memory-mapped	AMBA APB4
<b>Register Access</b>	Indirect (IOREGSEL/IOWIN)	Indirect

Feature	Intel 82093AA	APB IOAPIC
		(IOREGSEL/IOWIN) ✓ Same
<b>IRQ Inputs</b>	24 (IRQ0-23)	24 (IRQ0-23) ✓ Same
<b>Redirection Table</b>	24 entries × 64-bit	24 entries × 64-bit ✓ Same
<b>Delivery Modes</b>	Fixed, LowestPri, SMI, NMI, INIT, ExtINT	Fixed (MVP), others future
<b>Destination Modes</b>	Physical, Logical	Physical (MVP), Logical future
<b>Trigger Modes</b>	Edge, Level	Edge, Level ✓ Same
<b>Polarity</b>	High, Low	High, Low ✓ Same
<b>Version Register</b>	0x11, Max Entry 0x17	0x11, Max Entry 0x17 ✓ Same
<b>Remote IRR</b>	Level interrupts	Level interrupts ✓ Same
<b>Priority</b>	Implementation-defined	Static (lowest IRQ)
<b>Multi-APIC</b>	Supported	Future enhancement
<b>Clock Domains</b>	Single	Optional CDC support

**Retained Features:** - Indirect register access method - Redirection table structure - Edge/level trigger modes - Polarity configuration - Remote IRR mechanism - Delivery/destination fields


**MVP Simplifications:** - Fixed delivery mode only (LowestPri, SMI, NMI, INIT, ExtINT future) - Physical destination only (Logical mode future) - Static priority only (dynamic/round-robin future) - Single IOAPIC (multi-IOAPIC arbitration future)

**RLB Enhancements:** - APB4 bus interface (instead of direct memory-map) - Optional CDC for clock domain flexibility - PeakRDL register generation - Modern SystemVerilog coding practices - Comprehensive validation framework

#### 1.0.1.6 Timing Diagrams

### 1.0.2 Waveform 1.1: Interrupt Delivery

Shows the flow from IRQ input to message delivery to LAPIC.




## IOAPIC Interrupt Delivery

When an IRQ edge is detected, the corresponding IRR bit sets. The redirection table entry (RTE) is consulted for vector, destination, and delivery mode. An interrupt message is sent to the target LAPIC.

### 1.0.3 Waveform 1.2: Redirection Table Write

Indirect register access to configure an RTE.




## IOAPIC RTE Write

Two APB transactions required: 1. Write index to IOREGSEL (selects RTE low or high word) 2. Write data to IOWIN (updates the selected RTE)

### 1.0.4 Waveform 1.3: Level-Triggered Interrupt

Level mode with Remote IRR and EOI handling.



## IOAPIC Level Triggered

Page 16 of 93



**Test Infrastructure Needed:** - Python helper script (ioapic\_helper.py) - Cocotb testbench (ioapic\_tb.py) - Test suite (test\_apb\_ioapic.py)

**Estimated Validation Time:** 5-7 days (per RLB\_STATUS\_AND\_ROADMAP.md)

### 1.0.5.3 Development Status

**Status:** ✓ MVP Complete - Ready for Validation

**MVP Scope Delivered:** - ✓ 24 IRQ inputs with synchronization - ✓ Edge and level trigger detection - ✓ Active high/low polarity support - ✓ Fixed delivery mode - ✓ Physical destination mode - ✓ Static priority arbitration - ✓ Remote IRR for level interrupts - ✓ EOI handling - ✓ Indirect register access (IOREGSEL/IOWIN) - ✓ Complete redirection table - ✓ Delivery status per IRQ

**Future Enhancements (Planned in TODO.md):** - ⌚ Logical destination mode - ⌚ LowestPriority delivery mode - ⌚ Additional delivery modes (SMI, NMI, INIT, ExtINT) - ⌚ Dynamic priority rotation - ⌚ Multi-IOAPIC support - ⌚ Boot interrupt delivery

### 1.0.5.4 Intel 82093AA Register Compatibility

**Direct APB Registers:** - 0x00: IOREGSEL - Register offset selector - 0x04: IOWIN - Data window for selected register

**Internal Registers (via IOREGSEL/IOWIN):** - 0x00: IOAPICID - I/O APIC identification - 0x01: IOAPICVER - Version (0x11) and Max Entry (0x17 for 24 IRQs) - 0x02: IOAPICARB - Arbitration priority (read-only) - 0x10-0x3F: IOREDTBL - Redirection table (24 entries × 2 registers)

Each redirection entry is 64 bits: - **LO register:** Vector, delivery mode, dest mode, polarity, trigger, mask, status fields - **HI register:** Destination CPU APIC ID

This matches Intel's specification exactly for software compatibility.

### 1.0.5.5 Documentation Organization

This specification document is organized as follows:

- **Chapter 1 (this chapter):** Overview, features, applications, Intel compatibility
- **Chapter 2:** Detailed block specifications (ioapic\_core, config\_regs, PeakRDL integration)
- **Chapter 3:** Interface specifications (APB, indirect access, IRQ, EOI)
- **Chapter 4:** Programming model (initialization, redirection table, edge/level handling)
- **Chapter 5:** Register definitions (address map, indirect access, field descriptions)

**Related Documentation:** - ../../rtl/ioapic/TODO.md - Implementation roadmap - ../../rtl/ioapic/peakrdl/README.md - Register generation guide -

Next: [Chapter 1.2 - Architecture](#)


RTL Design Sherpa · Learning Hardware Design Through Practice · [GitHub](#) · [Documentation Index](#) · [MIT License](#)


---

## 1.0.6 APB IOAPIC - Architecture

### 1.0.6.1 High-Level Architecture

The APB IOAPIC is organized as a hierarchical design with three primary layers:





### 1.0.6.2 Block Hierarchy

The design follows RLB architecture standards with clear functional separation:

1. **apb\_ioapic.sv** (Top Level)
  - APB slave interface selection (CDC or non-CDC via parameter)
  - Clock domain routing based on CDC\_ENABLE
  - Module instantiation and wiring
  - External interface connections
2. **ioapic\_config\_regs.sv** (Register Interface)
  - PeakRDL adapter instantiation (peakrdl\_to\_cmdrsp)
  - Generated register block instantiation (ioapic\_regs)
  - Special logic for Intel indirect access (IOREGSEL/IOWIN)
  - Hardware interface signal mapping (hwif\_in/hwif\_out to core)
  - Redirection table array handling (24 entries)
3. **ioapic\_core.sv** (Core Logic)
  - IRQ input synchronization (3-stage, metastability prevention)
  - Polarity inversion (active-high/active-low handling)
  - Edge detection (rising/falling edge with filtering)
  - Level sensing (continuous level tracking)
  - Priority arbitration (static: lowest IRQ wins)
  - Interrupt delivery state machine (IDLE → DELIVER → WAIT\_EOI)
  - Remote IRR management (level interrupt state tracking)
  - Delivery status per IRQ
4. **ioapic\_regs.sv** (Generated by PeakRDL)

- Direct APB registers: IOREGSEL, IOWIN
- Internal registers: IOAPICID, IOAPICVER, IOAPICARB
- Redirection table: IOREDTBL[24] with LO/HI splits
- Hardware interface structs (hwif\_in, hwif\_out)

### 1.0.6.3 Data Flow

#### Configuration Path (APB Write):

Software → APB Write → apb\_slave[\_cdc] → CMD → peakrdl\_to\_cmdrsp → ioapic\_regs → hwif\_out → ioapic\_config\_regs mapping → ioapic\_core config

#### Status Readback Path (APB Read):

ioapic\_core status → ioapic\_config\_regs mapping → hwif\_in → ioapic\_regs → peakrdl\_to\_cmdrsp → RSP → apb\_slave[\_cdc] → APB Read Data → Software

#### Interrupt Delivery Path:

IRQ Input → Sync → Polarity → Edge/Level Detect → Pending → Arbitration → Delivery FSM → irq\_out\_valid + vector + dest → CPU/LAPIC

#### EOI Return Path (Level Interrupts):

CPU EOI → eoi\_in + eoi\_vector → ioapic\_core → Clear Remote IRR → Re-enable interrupt if still asserted

### 1.0.6.4 Intel Indirect Access Method

The IOAPIC uses Intel's two-step indirect register access:

#### Step 1: Select Internal Register

Write to IOREGSEL (APB address 0x00):  
Data = Internal register offset (0x00-0x3F)

#### Step 2: Access Selected Register

Read/Write IOWIN (APB address 0x04):  
Data = Selected register contents

#### Example: Configure IRQ0 Redirection Entry

```
// Step 1: Select IOREDTBL[0]_LO (internal offset 0x10)
*IOREGSEL = 0x10;

// Step 2: Write configuration via IOWIN
```

```
*IOWIN = 0x00000020; // Vector 0x20, edge-triggered, unmasked
```

```
// Step 3: Select IOREDTBL[0]_HI (internal offset 0x11)
```

```
*IOREGSEL = 0x11;
```

```
// Step 4: Write destination via IOWIN
```


```
*IOWIN = 0x01000000; // Destination APIC ID = 1
```

This indirect access method: - Reduces address space (only 2 APB registers instead of 50+) - Matches Intel specification for software compatibility - Allows 256 internal registers with 8-bit offset - PeakRDL generated logic handles routing automatically

### 1.0.6.5 Clock Domain Architecture


The IOAPIC supports two clock domain configurations via CDC\_ENABLE parameter:

#### Single Clock Domain (CDC\_ENABLE=0 - Default):



- Simplest configuration
- Lowest latency
- Single clock timing analysis
- Recommended for most use cases

#### Dual Clock Domain (CDC\_ENABLE=1):



- Allows independent APB and IOAPIC clocks
- Useful for always-on interrupt handling
- ioapic\_clk can run while pclk is gated
- Adds 2-4 cycle latency for CDC handshake

#### Clock Selection Logic:

```
// In apb_ioapic.sv:
.clk (CDC_ENABLE[0] ? ioapic_clk : pclk)
```

Both config\_regs and core use the same clock (no internal CDC needed).

### 1.0.6.6 Reset Architecture

The IOAPIC uses standard RLB reset methodology:

**Reset Signals:** - preseln - APB domain reset (active-low, async) - ioapic\_reseln - IOAPIC domain reset (active-low, async)


**Reset Routing:**

```
// In apb_ioapic.sv:  
.rst_n (CDC_ENABLE[0] ? ioapic_reseln : preseln)
```

**Reset Behavior:** - All IRQs masked by default (mask bit = 1) - No interrupts pending - Delivery state = IDLE - Remote IRR cleared for all IRQs - IOAPIC ID = 0x0 - All redirection entries reset to safe defaults

### 1.0.6.7 Interrupt Flow State Machine

The IOAPIC core implements a simple 3-state FSM for interrupt delivery:



**States:** - **IDLE:** Arbitrating among pending IRQs, select highest priority - **DELIVER:** Presenting interrupt to CPU (irq\_out\_valid asserted) - **WAIT\_EOI:** Waiting for End-of-Interrupt (level-triggered only)

**Edge-triggered path:** IDLE → DELIVER → IDLE (no EOI wait)

**Level-triggered path:** IDLE → DELIVER → WAIT\_EOI → IDLE

### 1.0.6.8 Integration Guidelines

**Minimal Integration (Single CPU):**

```
apb_ioapic #(
    .NUM_IRQS      (24),
    .CDC_ENABLE    (0)  // Single clock domain
```

```

) u_ioapic (
    .pclk                (sys_clk),
    .presetn             (sys_resetn),
    .ioapic_clk          (sys_clk),      // Same clock
    .ioapic_resetn       (sys_resetn),   // Same reset

    .s_apb_*             (/* APB signals */),
    .irq_in              (system_irqs),
    .irq_out_valid       (cpu_irq_valid),
    .irq_out_vector      (cpu_irq_vector),
    .irq_out_dest        (/* tie to CPU ID */),
    .irq_out_deliv_mode  (/* unused in simple system */),
    .irq_out_ready       (cpu_irq_ack),
    .eoi_in              (cpu_eoi),
    .eoi_vector          (cpu_eoi_vector)
);

```

#### Advanced Integration (Multi-CPU with CDC):

```

apb_ioapic #(
    .NUM_IRQS    (24),
    .CDC_ENABLE  (1)  // Dual clock domain
) u_ioapic (
    .pclk                (apb_clk),      // APB bus clock
    .presetn             (apb_resetn),
    .ioapic_clk          (always_on_clk), // Independent clock
    .ioapic_resetn       (por_resetn),

    .s_apb_*             (/* APB signals */),
    .irq_in              (system_irqs),
    .irq_out_*           (/* to LAPIC router */),
    .eoi_in              (eoi_from_lapic),
    .eoi_vector          (eoi_vector_from_lapic)
);

```

#### 1.0.6.9 Address Space Organization

**APB Address Space (12-bit: 0x000-0xFFFF):** - 0x000: IOREGSEL (direct access) - 0x004: IOWIN (direct access) - 0x008-0xFFFF: Reserved

**Internal Register Space (8-bit offset via IOREGSEL):** - 0x00: IOAPICID - 0x01: IOAPICVER - 0x02: IOAPICARB - 0x03-0x0F: Reserved - 0x10-0x3F: IOREDTBL[0-23] (LO/HI pairs)

**Memory Footprint:** 4KB APB window (matches other RLB modules)

#### 1.0.6.10 Design Trade-offs

**Indirect vs Direct Access:** - **Chosen:** Indirect access (IOREGSEL/IOWIN) - **Reason:** Intel 82093AA compatibility, reduced address space - **Cost:** Extra APB cycle per access, more complex logic - **Benefit:** Software portability, scalable register space

**Static vs Dynamic Priority:** - **Chosen:** Static priority (lowest IRQ wins) - **Reason:** Simplicity, deterministic behavior, sufficient for MVP - **Cost:** Less flexible than round-robin - **Benefit:** Predictable, easy to verify, low logic

**Fixed vs Multiple Delivery Modes:** - **Chosen:** Fixed mode only for MVP - **Reason:** Covers 90%+ of use cases, simpler implementation - **Cost:** Can't use LowestPri, SMI, NMI, etc. yet - **Benefit:** Clean implementation, extensible design

---

**Next:** [Chapter 1.3 - Clocks and Reset](#)

RTL Design Sherpa · Learning Hardware Design Through Practice [GitHub](#) · [Documentation Index](#) · [MIT License](#)

---

## 1.0.7 APB IOAPIC - Clocks and Reset

### 1.0.7.1 Clock Domains


The IOAPIC supports both single and dual clock domain operation via the CDC\_ENABLE parameter.

#### 1.0.7.1.1 Single Clock Domain (CDC\_ENABLE=0 - Default)

**Configuration:** - Both APB interface and IOAPIC logic use same clock (pclk) - ioapic\_clk parameter tied to pclk - No clock domain crossing logic instantiated

**Advantages:** - Simplest configuration - Lowest latency (~2 APB cycles for register access) - Single clock timing constraints - Recommended for most applications

#### Clock Routing:




#### 1.0.7.1.2 Dual Clock Domain (CDC\_ENABLE=1)

**Configuration:** - APB interface uses pclk - IOAPIC logic uses ioapic\_clk (independent) - apb\_slave\_cdc provides clock domain crossing - CMD/RSP signals cross domains via async FIFOs

**Advantages:** - Independent clock frequencies - Can gate pclk while maintaining interrupt capability - Supports always-on interrupt handling - Useful for power-managed systems

#### Clock Routing:





**Latency Impact:** - Register access: +2-4 cycles for CDC handshake - Total: ~4-6 APB cycles vs ~2 cycles for non-CDC

### 1.0.7.2 Clock Requirements

**Frequency Constraints:**

Clock	Minimum	Typical	Maximum	Notes
pclk	1 MHz	50-100 MHz	200 MHz	APB bus clock
ioapic_clk (CDC=0)	Same as pclk	Same as pclk	Same as pclk	Tied to pclk
ioapic_clk (CDC=1)	1 MHz	25-100 MHz	200 MHz	Independent

**Relationship (CDC=1):** - No fixed relationship required between pclk and ioapic\_clk - Can be asynchronous - Ratio can be arbitrary - CDC logic handles all synchronization

**Typical Configurations:** - **No CDC:** pclk = ioapic\_clk = 100 MHz (system clock) - **With CDC:** pclk = 50 MHz (APB), ioapic\_clk = 100 MHz (fast interrupts) - **Power-managed:** pclk = gatable, ioapic\_clk = always-on 32 kHz

### 1.0.7.3 Interrupt Response Time

**From IRQ assertion to delivery request:**

Configuration	Synchronization	Edge Detect	Arbitration	Delivery	Total
No CDC, 100 MHz	30 ns	10 ns	<10 ns	10 ns	~60 ns
CDC, pclk=50MHz, ioapic_clk=100MHz	30 ns	10 ns	<10 ns	10 ns	~60 ns

**Note:** Above is from IRQ pin to irq\_out\_valid. CPU interrupt latency depends on LAPIC design.

### 1.0.7.4 Reset Signals

**Reset Types:**

Signal	Polarity	Type	Domain	Purpose
presetn	Active Low	Async	APB	Resets APB interface
ioapic_reseten	Active Low	Async	IOAPIC	Resets interrupt logic

**Reset Routing (CDC\_ENABLE determines which reset is used):**

*// In apb\_ioapic.sv:*

```
assign config_regs_rst = (CDC_ENABLE[0]) ? ioapic_reseten : presetn;
assign core_rst = (CDC_ENABLE[0]) ? ioapic_reseten : presetn;
```

CDC=0: Both use presetn CDC=1: Both use ioapic\_reseten

#### 1.0.7.5 Reset Behavior

**On Reset Assertion:**

##### 1. APB Interface:

- APB slave returns to IDLE
- All pending transactions aborted
- PREADY deasserted

##### 2. Registers:

- IOREGSEL ← 0x00
- IOAPICID ← 0x00000000
- All IOREDTBL entries ← default (all IRQs masked)

##### 3. Core Logic:

- All IRQ pending flags cleared
- Delivery FSM → IDLE
- All Remote IRR flags cleared
- Synchronizer chains reset
- No interrupts pending or being delivered

**Redirection Table Reset Values:** - Vector: 0x00 - Delivery Mode: 0b000 (Fixed) - Dest Mode: 0 (Physical) - Delivery Status: 0 (Idle) - Polarity: 0 (Active High) - Remote IRR: 0 - Trigger Mode: 0 (Edge) - **Mask: 1 (MASKED)** ← Critical: All IRQs disabled by default - Destination: 0x00

**After reset, software must:** 1. Configure IOAPIC ID (if multiple IOAPICs) 2. Configure each needed IRQ's redirection entry 3. Unmask desired IRQs (clear mask bit)

#### 1.0.7.6 Reset Sequencing

**Power-On Reset:**

1. Power stabilizes
2. POR circuitry asserts preseln/ioapic\_reseln
3. Hold reset for minimum 10 clock cycles
4. Deassert reset synchronously
5. Wait 5 clock cycles for synchronizers
6. Begin software initialization

**Software Reset (via PM ACPI if integrated):**

1. PM ACPI asserts system reset
2. preseln/ioapic\_reseln asserted
3. IOAPIC returns to reset state
4. Software must reinitialize all config

### ***1.0.7.7 Clock Gating Considerations***

**With CDC\_ENABLE=1:**

**Can gate pclk when:** - No APB accesses needed - Power saving mode - IOAPIC still operational on ioapic\_clk - Interrupts continue to function

**Cannot gate ioapic\_clk when:** - Interrupts must be serviced - Need real-time interrupt response - Unless entering deep power-down (then reinit required)

**Integration with PM ACPI:** If using PM ACPI power management: - Connect IOAPIC to always-on power domain - Use ioapic\_clk from always-on clock tree - Enable CDC (CDC\_ENABLE=1) - IOAPIC continues operating in S1/S3 sleep states

### ***1.0.7.8 Timing Constraints***

**Critical Paths (for synthesis):**

**Without CDC:** - APB write → register update → core config: Single clock domain - IRQ input → synchronizer → edge detect → arbitration → delivery: ~4-5 levels of logic - Typical Fmax: 150-200 MHz (depends on synthesis settings)

**With CDC:** - APB domain: Same as without CDC - IOAPIC domain: IRQ path same as above - Cross-domain: Handled by async FIFOs (no combinational paths) - Typical Fmax: 150-200 MHz each domain independently

**Setup/Hold:** - IRQ inputs: Externally synchronized, 3-stage internal sync - EOI inputs: Should be synchronous to ioapic\_clk if possible - APB signals: Per APB specification

### ***1.0.7.9 Clock Jitter and Stability***

**IRQ Input Synchronization:** - 3-stage synchronizer handles moderate jitter - MTBF (Mean Time Between Failures): >1000 years at 100 MHz - No special jitter requirements on IRQ inputs

**Clock Source Requirements:** - Stable clock (< 100 ppm drift typical) - Low jitter for timing-critical applications - FPGA PLLs/MMCMs acceptable

---

**See Also:** - [Architecture](#) - Clock domain architecture diagrams - [Top Level Interface](#) - Clock signal definitions - [APB Interface](#) - APB timing

**Next:** [Chapter 1.4 - Acronyms](#)

RTL Design Sherpa · Learning Hardware Design Through Practice [GitHub](#) · [Documentation Index](#) · [MIT License](#)

---

## 1.0.8 APB IOAPIC - Acronyms and Terminology

### 1.0.8.1 Acronyms

Acronym	Full Name	Description
<b>IOAPIC</b>	I/O Advanced Programmable Interrupt Controller	Intel's advanced interrupt routing controller
<b>APB</b>	Advanced Peripheral Bus	AMBA low-power peripheral bus
<b>AMBA</b>	Advanced Microcontroller Bus Architecture	ARM bus specification
<b>APIC</b>	Advanced Programmable Interrupt Controller	Generic term for advanced interrupt controllers
<b>LAPIC</b>	Local Advanced Programmable Interrupt Controller	Per-CPU interrupt controller
<b>IRQ</b>	Interrupt Request	Hardware interrupt signal
<b>EOI</b>	End of Interrupt	Signal that interrupt service is complete
<b>PIC</b>	Programmable Interrupt Controller	Legacy 8259-style interrupt controller
<b>ISA</b>	Industry Standard Architecture	Legacy PC bus

Acronym	Full Name	Description
<b>PCI</b>	Peripheral Component Interconnect	Standard expansion bus
<b>RLB</b>	Retro Legacy Blocks	Project name for classic peripheral IP cores
<b>CDC</b>	Clock Domain Crossing	Synchronization between clock domains
<b>IRR</b>	Interrupt Request Register	Intel term for interrupt pending state
<b>ISR</b>	Interrupt Service Routine	Software interrupt handler
<b>SMI</b>	System Management Interrupt	Special interrupt for system management mode
<b>NMI</b>	Non-Maskable Interrupt	High-priority interrupt that can't be masked
<b>INIT</b>	Initialization	Processor initialization sequence
<b>ExtINT</b>	External Interrupt	8259-compatible interrupt delivery

#### 1.0.8.2 Register Names

Name	Full Name	Description
<b>IOREGSEL</b>	I/O Register Select	Indirect access register selector
<b>IOWIN</b>	I/O Window	Indirect access data window
<b>IOAPICID</b>	I/O APIC Identification	IOAPIC ID register
<b>IOAPICVER</b>	I/O APIC Version	Version and capabilities register
<b>IOAPICARB</b>	I/O APIC Arbitration	Bus arbitration priority register
<b>IOREDTBL</b>	I/O Redirection Table	Interrupt redirection configuration

#### 1.0.8.3 Key Terms

**Redirection Table:** Array of 64-bit entries (one per IRQ) that configure how each interrupt is routed to CPUs. Contains vector, delivery mode, destination, trigger type, polarity, and mask.

**Indirect Access:** Intel's register access method where software writes an offset to IOREGSEL, then accesses the selected register via IOWIN. Reduces address space requirements.

**Remote IRR (Interrupt Request Register):** Status bit for level-triggered interrupts. Set when interrupt is accepted by CPU, cleared when EOI is received. Prevents interrupt re-triggering while being serviced.

**Delivery Status:** Read-only bit indicating if an interrupt delivery is in progress for a specific IRQ. Used to monitor interrupt flow.

**Trigger Mode:** - **Edge:** Interrupt on signal edge (rising after polarity adjustment) - **Level:** Interrupt on signal level (requires EOI to clear)

**Polarity:** - **Active High:** Interrupt when signal is logic 1 - **Active Low:** Interrupt when signal is logic 0 (inverted internally)

**Delivery Mode:** Determines how interrupt is delivered to CPU: - **Fixed:** To specific CPU - **Lowest Priority:** To least-busy CPU - **SMI/NMI/INIT/ExtINT:** Special modes

**Destination Mode:** - **Physical:** Destination field is physical APIC ID - **Logical:** Destination field is logical grouping (multi-cast)

**Priority Arbitration:** When multiple IRQs are pending, hardware selects which to deliver first. Current implementation uses static priority (lowest IRQ number wins).

**End-of-Interrupt (EOI):** Signal from CPU indicating interrupt service is complete. For level-triggered interrupts, clears Remote IRR and allows re-triggering if signal still asserted.

---

**See Also:** - [References](#) - External standards and specifications - [Overview](#) - Component introduction - [Architecture](#) - System architecture

RTL Design Sherpa · Learning Hardware Design Through Practice · GitHub · Documentation Index · MIT License

---

## 1.0.9 APB IOAPIC - References

### 1.0.9.1 Primary Standards

1. **Intel 82093AA I/O Advanced Programmable Interrupt Controller (IOAPIC)**
  - Intel Corporation
  - May 1996
  - Document Order Number: 290566-001
  - **Purpose:** Defines IOAPIC register layout, indirect access method, and behavior

- **Relevance:** APB IOAPIC implements this specification with APB interface
2. **AMBA APB Protocol Specification**
    - ARM Limited
    - AMBA 4 APB Protocol Specification v2.0
    - **Purpose:** Defines APB4 bus protocol
    - **Relevance:** APB interface implementation
  3. **SystemRDL 2.0 Specification**
    - Accellera Systems Initiative
    - **Purpose:** Register description language
    - **Relevance:** PeakRDL register generation from .rdl specifications

#### **1.0.9.2 Related RLB Documentation**

**Module-Specific:** - ../../rtl/ioapic/TOD0.md - Implementation tasks and enhancements -  
 ../../rtl/ioapic/peakrdl/README.md - PeakRDL register generation guide -  
 ../../rtl/ioapic/peakrdl/ioapic\_regs.rdl - SystemRDL source specification

**RLB System:** - ../../rtl/RLB\_MODULE\_AUDIT.md - Architecture compliance verification -  
 ../../rtl/RLB\_STATUS\_AND\_ROADMAP.md - System-wide status and planning -  
 ../../rtl/RLB\_FPGA\_IMPLEMENTATION\_GUIDE.md - FPGA deployment guide - ../../PRD.md -  
 Product Requirements Document - ../../CLAUDE.md - AI integration guide

**Reference RLB Modules:** - ../hpet\_spec/hpet\_index.md - HPET specification (architectural  
 reference) - ../../rtl/pic\_8259/README.md - Legacy PIC implementation -  
 ../../rtl/pm\_acpi/README.md - Power management and ACPI

#### **1.0.9.3 External Resources**

**Intel APIC Architecture:** - Intel MultiProcessor Specification Version 1.4 - Intel Architecture  
 Software Developer's Manual (Volume 3: System Programming) - **Relevance:** APIC system  
 architecture, LAPIC integration, interrupt delivery

**AMBA Specifications:** - AMBA APB Protocol Specification v2.0 (ARM IHI 0024) - AMBA AXI and  
 ACE Protocol Specification (for AXI-APB bridges) - **Relevance:** Bus protocol compliance

**SystemRDL Tools:** - PeakRDL-regblock Documentation - PeakRDL-html Documentation -  
 SystemRDL 2.0 Language Reference Manual - **Relevance:** Register generator usage

#### **1.0.9.4 Design Methodology References**

**RLB Architecture Pattern:**

APB → apb\_slave[\_cdc] → CMD/RSP → peakrdl\_to\_cmdrsp →  
 → <module>\_regs (PeakRDL) → hwif → <module>\_core

**Reference Implementations:** - HPET: Complete reference with CDC, PeakRDL, documentation - PM ACPI: Recent implementation, similar complexity - SMBus: Protocol controller with FIFOs

**Converter Components:** - `../../../../converters/rtl/apb_slave.sv` - APB slave without CDC - `../../../../converters/rtl/apb_slave_cdc.sv` - APB slave with CDC - `../../../../converters/rtl/peakrdl_to_cmdrsp.sv` - PeakRDL adapter

### ***1.0.9.5 Historical Context***

**Evolution of PC Interrupt Controllers:**

- 1. Intel 8259A PIC (1976-1990s)**
  - 8 IRQ inputs, cascadable to 15
  - Fixed priority
  - Edge-triggered only
  - Direct memory-mapped access
- 2. Intel 82093AA IOAPIC (1996-present)**
  - 24 IRQ inputs
  - Programmable priority
  - Edge and level-triggered
  - Indirect register access
  - Multi-processor support
  - **This implementation**
- 3. MSI/MSI-X (2000s-present)**
  - Message-based interrupts
  - No dedicated IRQ lines
  - Scalable to thousands of interrupts
  - PCIe standard

**APB IOAPIC Position:** Modern implementation of 82093AA specification using RLB methodology, suitable for soft-core SoCs, FPGA systems, and PC-compatible designs.

### ***1.0.9.6 Software Examples and Drivers***

**Linux Kernel:** - `arch/x86/kernel/apic/io_apic.c` - Linux IOAPIC driver - Shows real-world usage patterns - Demonstrates edge/level handling, EOI, redirection table setup

**xv6 Operating System:** - `ioapic.c` - Simple IOAPIC driver for educational OS - Clean example of indirect access - Good reference for basic initialization

**SeaBIOS / Coreboot:** - BIOS-level IOAPIC initialization - Shows boot-time configuration - Demonstrates hardware discovery



### 1.0.9.7 Verification References

**Cocotb (Python-based Verification):** - Cocotb documentation: <https://docs.cocotb.org/> - Used for RLB module validation - Tests in ../../dv/tests/ directories

**Verification Strategy:** - Similar to HPET: Basic → Medium → Full test hierarchy - Test levels defined in RLB\_STATUS\_AND\_ROADMAP.md - Estimated 5-7 days for complete validation

---

**Document Navigation:** - [Back to Index](#) - [Overview](#) - [Architecture](#) - [Acronyms](#)

RTL Design Sherpa · Learning Hardware Design Through Practice GitHub · Documentation Index · MIT License

---

## 1.0.10 APB IOAPIC - Block Overview

### 1.0.10.1 Module Hierarchy

The APB IOAPIC consists of four primary blocks organized in a clean hierarchical structure:

```
apb_ioapic (Top Level)
├── apb_slave or apb_slave_cdc (Bus Interface)
├── ioapic_config_regs (Register Wrapper)
│   ├── peakrdl_to_cmdrsp (Protocol Adapter)
│   └── ioapic_regs (PeakRDL Generated)
└── ioapic_core (Core Interrupt Logic)
```

### 1.0.10.2 Block Summary

Block	File	Lines	Purpose
<b>apb_ioapic</b>	apb_ioapic.sv	~340	Top-level integration, CDC selection
<b>ioapic_config_regs</b>	ioapic_config_regs.sv	~220	Register interface, indirect access, hwif mapping
<b>ioapic_regs</b>	ioapic_regs.sv	~2500	PeakRDL generated register block
<b>ioapic_core</b>	ioapic_core.sv	~290	Interrupt routing, edge/level detection, arbitration

Block	File	Lines	Purpose
<b>peakrdl_to_cmdrsp</b>	(external)	~150	CMD/RSP to PeakRDL passthrough adapter
<b>apb_slave[_cdc]</b>	(external)	~200	APB protocol handler

**Total Implementation:** ~900 lines of custom RTL + ~2700 lines generated/reused

### 1.0.10.3 *Block Descriptions*

**1. apb\_ioapic (Top Level)** - Selects APB slave type based on CDC\_ENABLE parameter - Routes clocks and resets to submodules - Instantiates config\_regs and core - Connects external IRQ and EOI interfaces - See: [apb\\_ioapic\\_top.md](#)


**2. ioapic\_config\_regs (Register Wrapper)** - Instantiates peakrdl\_to\_cmdrsp adapter - Instantiates PeakRDL generated registers - Maps hwif signals to/from ioapic\_core - Handles array mapping for 24 redirection entries - See: [ioapic\\_config\\_regs.md](#)

**3. ioapic\_regs (PeakRDL Generated)** - Generated from ioapic\_regs.rdl SystemRDL specification - Implements IOREGSEL/IOWIN indirect access - Provides hwif\_in/hwif\_out structs - Handles register read/write/reset - See: [ioapic\\_regs.md](#)

**4. ioapic\_core (Core Logic)** - 24 IRQ input synchronization (3-stage) - Polarity handling (active-high/low) - Edge/level detection - Priority arbitration (static) - Interrupt delivery FSM (IDLE/DELIVER/WAIT\_EOI) - Remote IRR management - See: [ioapic\\_core.md](#)


### 1.0.10.4 *Data Flow Between Blocks*

**Configuration Write Path:**




## *Diagram 1*

**Status Read Path:**



## *Diagram 2*

### **Interrupt Delivery Path:**



## Diagram 3

### 1.0.10.5 Interface Summary

**External Interfaces:** - APB4 slave (to CPU/interconnect) - 24 IRQ inputs (from interrupt sources) - Interrupt output (to CPU/LAPIC) - EOI input (from CPU/LAPIC)

**Internal Interfaces:** - CMD/RSP between APB slave and config\_regs - PeakRDL passthrough between adapter and registers - hwif between registers and config\_regs - Config/status signals between config\_regs and core

### 1.0.10.6 Clock Domain Assignment

**CDC\_ENABLE=0 (Single Clock):** - All blocks run on pclk - apb\_slave instantiated (no CDC) - Simplest timing analysis

**CDC\_ENABLE=1 (Dual Clock):** - apb\_slave\_cdc runs on pclk (APB domain) - config\_regs runs on ioapic\_clk (IOAPIC domain) - core runs on ioapic\_clk (IOAPIC domain) - CDC handled by apb\_slave\_cdc module

### 1.0.10.7 Module Dependencies

**RLB Project Dependencies:** - reset\_defs.svh - Reset macro definitions - apb\_slave.sv or apb\_slave\_cdc.sv - APB protocol - peakrdl\_to\_cmdrsp.sv - Register adapter

**Generated Files:** - ioapic\_regs.sv - From ioapic\_regs.rdl via peakrdl\_generate.py - ioapic\_regs\_pkg.sv - Package with hwif struct definitions

**No External IP Required:** All dependencies are within the RLB project or generated from specifications.

---

**Chapter 2 Contents:** - [01\\_ioapic\\_core.md](#) - Core interrupt logic - [02\\_ioapic\\_config\\_regs.md](#) - Register wrapper - [03\\_ioapic\\_regs.md](#) - PeakRDL generated - [04\\_apb\\_ioapic\\_top.md](#) - Top-level integration - [05\\_fsm\\_summary.md](#) - State machine summary

**Back to:** [Index](#) | **Next:** [ioapic\\_core Block](#)

RTL Design Sherpa · Learning Hardware Design Through Practice [GitHub](#) · [Documentation Index](#) · [MIT License](#)

---



## 1.0.11 APB IOAPIC - FSM Summary


### 1.0.11.1 Interrupt Delivery State Machine


The IOAPIC core implements a 3-state FSM for interrupt delivery management.

#### 1.0.11.1.1 State Definitions

State	Encoding	Description
<b>IDLE</b>	2'b00	No interrupt being delivered, arbitrating among pending IRQs
<b>DELIVER</b>	2'b01	Presenting interrupt to CPU, waiting for acknowledgment
<b>WAIT_EOI</b>	2'b10	Level interrupt delivered, waiting for End-of-Interrupt

#### 1.0.11.1.2 State Transition Diagram





#### 1.0.11.1.3 State Transitions

Current State	Condition	Next State	Action
IDLE	No pending IRQs	IDLE	Continue arbitration
IDLE	Pending IRQ found	DELIVER	Latch IRQ info, assert irq_out_valid
DELIVER	!irq_out_ready	DELIVER	Wait for CPU
DELIVER	irq_out_ready && edge mode	IDLE	Complete, return to arbitration
DELIVER	irq_out_ready && level mode	WAIT_EOI	Set Remote IRR, wait for EOI
WAIT_EOI	!(eoi_in && vector match)	WAIT_EOI	Continue waiting
WAIT_EOI	eoi_in && vector match	IDLE	Clear Remote IRR, return

#### 1.0.11.1.4 State Functions

**IDLE State:** - **Entry:** From WAIT\_EOI (after EOI) or DELIVER (after edge interrupt) - **Operations:** - Scan all 24 IRQs for pending, unmasked interrupts - Apply priority arbitration (lowest IRQ number wins) - Select highest priority IRQ if any - **Outputs:** - irq\_out\_valid = 0 (no interrupt being presented) - **Exit:** When pending IRQ found → DELIVER

**DELIVER State:** - **Entry:** From IDLE when pending IRQ exists - **Operations:** - Assert irq\_out\_valid - Present irq\_out\_vector (from selected IRQ's redirection entry) - Present irq\_out\_dest (destination APIC ID) - Present irq\_out\_deliv\_mode (delivery mode) - Wait for CPU acknowledgment (irq\_out\_ready) - **Outputs:** - irq\_out\_valid = 1 - irq\_out\_vector = cfg\_vector[selected\_irq] - irq\_out\_dest = cfg\_destination[selected\_irq] - irq\_out\_deliv\_mode = cfg\_deliv\_mode[selected\_irq] - **Exit:** - Edge mode + irq\_out\_ready → IDLE - Level mode + irq\_out\_ready → WAIT\_EOI

**WAIT\_EOI State (Level-Triggered Only):** - **Entry:** From DELIVER after CPU accepts level interrupt - **Operations:** - Monitor eoi\_in signal - Compare eoi\_vector with current\_vector - Remote IRR remains set (prevents re-trigger) - IRQ input still synchronized but masked by Remote IRR - **Outputs:** - irq\_out\_valid = 0 - **Exit:** When EOI received for this vector → IDLE

#### 1.0.11.1.5 Latched Signals

Signals latched in IDLE → DELIVER transition:

Signal	Source	Purpose
current_irq[4:0]	selected_irq	IRQ number being delivered
current_vector[7:0]	cfg_vector[selected_irq]	Vector for EOI matching
current_is_level	cfg_trigger_mode[selected_irq]	Determines path (IDLE vs WAIT_EOI)

These remain stable during DELIVER and WAIT\_EOI states.

#### 1.0.11.1.6 Edge vs Level Interrupt Paths

**Edge-Triggered Interrupt:**

IRQ asserts → Edge detected → IRQ pending flag set → Arbitration selects it → IDLE → DELIVER → CPU acknowledges → Pending cleared → IDLE

**Time:** Depends on arbitration delay, typically 1-2 cycles in IDLE then 1+ cycles in DELIVER

**Level-Triggered Interrupt:**

IRQ asserts → Level sensed → IRQ pending (if !Remote IRR) → Arbitration selects it → IDLE → DELIVER → CPU acknowledges → Remote IRR set → WAIT\_EOI → EOI received → Remote IRR cleared → IDLE → (If IRQ still asserted, pending again)

**Time:** Same as edge until WAIT\_EOI, then waits for software ISR completion + EOI

### 1.0.11.2 Arbitration Logic

**Priority Encoding (Static Priority):**

```
// In ioapic_core.sv
for (int j = 0; j < 24; j++) begin
    if (irq_eligible[j]) begin // Pending and not masked
        selected_irq = j;
        irq_selected_valid = 1;
        break; // Stop at first match (lowest wins)
    end
end
```

#### Eligibility Criteria:

```
irq_eligible[i] = irq_pending[i] && !cfg_mask[i];
```

**Arbitration Timing:** - Combinational logic (< 1 clock cycle) - Result available same cycle for IDLE → DELIVER transition

### 1.0.11.3 Remote IRR Management

#### Set Conditions:

```
// For level-triggered IRQs only
if (cfg_trigger_mode[i] == 1'b1) begin // Level mode
    if (irq_selected_valid && selected_irq == i && state == IDLE)
begin
    remote_irr[i] <= 1'b1; // Set when starting delivery
    end
end
```

#### Clear Conditions:

```
if (eoi_in && eoi_vector == cfg_vector[i]) begin
    remote_irr[i] <= 1'b0; // Clear on EOI
end
```

#### Effect on Pending:

```
// Level mode: Pending only if active AND Remote IRR clear
irq_pending[i] = irq_active[i] && !irq_remote_irr[i];
```

This prevents level interrupts from re-triggering while being serviced.

### 1.0.11.4 Multiple Pending IRQs

**Scenario:** Multiple IRQs asserted simultaneously

**Behavior:** 1. Arbitration selects lowest numbered IRQ 2. FSM delivers that interrupt (IDLE → DELIVER [→ WAIT\_EOI]) 3. Other IRQs remain pending 4. After current delivery complete, FSM returns to IDLE 5. Arbitration runs again, selects next lowest 6. Process repeats until all serviced

#### Example Timeline:

```

Time 0:  IRQ3, IRQ5, IRQ7 all assert
Time 1:  Arbitration selects IRQ3 (lowest)
Time 2-5: Deliver IRQ3, wait if level
Time 6:  Return to IDLE
Time 7:  Arbitration selects IRQ5 (next lowest)
Time 8-11: Deliver IRQ5, wait if level
Time 12: Return to IDLE
Time 13: Arbitration selects IRQ7
...

```

**Fairness:** Lower numbered IRQs starve higher if constantly asserting. This is intentional (priority system).

---

**See Also:** - [ioapic\\_core Block](#) - Detailed FSM implementation - [Programming: Level Interrupts](#) - FSM from software perspective

**Back to:** [Index](#) | [Block Overview](#)

RTL Design Sherpa · Learning Hardware Design Through Practice GitHub · Documentation Index · MIT License

---

## 1.0.12 APB IOAPIC - Complete Register Map

### 1.0.12.1 Register Access Method

The IOAPIC uses **indirect register access** following Intel 82093AA specification:

1. **Write to IOREGSEL** (APB address 0x00): Select internal register offset
2. **Access IOWIN** (APB address 0x04): Read or write selected register data

### 1.0.12.2 Direct APB Registers

APB Address	Register	Type	Reset	Description
0x000	IOREGSEL	RW	0x00	Register offset selector (0x00-0x3F)
0x004	IOWIN	RW	0x00000000	Data window for selected internal register
0x008-0xFFFF	Reserved	-	-	Reserved for future

APB Address	Register	Type	Reset	Description
-------------	----------	------	-------	-------------

expansion

### 1.0.12.3 IOREGSEL Register (APB 0x000)

Bits	Name	Type	Reset	Description
[7:0]	regsel	RW	0x00	Internal register offset for indirect access
[31:8]	Reserved	RO	0x000000	Reserved, read as 0

**Valid offset values:** - 0x00: IOAPICID - 0x01: IOAPICVER - 0x02: IOAPICARB - 0x10-0x3F: IOREDTBL entries (even=LO, odd=HI)

### 1.0.12.4 IOWIN Register (APB 0x004)

Bits	Name	Type	Reset	Description
[31:0]	data	RW	0x00000000	Read/Write data for register selected by IOREGSEL

**Behavior:** - Reading IOWIN returns data from register selected by current IOREGSEL value - Writing IOWIN updates register selected by current IOREGSEL value - IOREGSEL must be written before each IOWIN access - IOREGSEL value persists until explicitly changed

## 1.1 Internal Registers (Accessed via IOREGSEL/IOWIN)

### 1.1.0.1 IOAPICID Register (Internal Offset 0x00)

Access via IOREGSEL/IOWIN:

```
*IOREGSEL = 0x00; // Select IOAPICID
*IOWIN = 0x0F000000; // Set APIC ID = 0xF
```

Bits	Name	Type	Reset	Description
[23:0]	Reserved	RO	0x000000	Reserved, read as 0
[27:24]	APIC ID	RW	0x0	4-bit IOAPIC identifier for multi-IOAPIC systems
[31:28]	Reserved	RO	0x0	Reserved, read as 0

**Purpose:** Identifies this IOAPIC in systems with multiple I/O APICs.

### 1.1.0.2 IOAPICVER Register (Internal Offset 0x01)

Access via IOREGSEL/IOWIN:

```
*IOREGSEL = 0x01; // Select IOAPICVER
uint32_t ver = *IOWIN; // Read version
```

Bits	Name	Type	Reset	Description
[7:0]	Version	RO	0x11	IOAPIC version (0x11 for 82093AA compatibility)
[15:8]	Reserved	RO	0x00	Reserved, read as 0
[23:16]	Max Redir Entry	RO	0x17	Maximum redirection entry (0x17 = 23 for 24 IRQs)
[31:24]	Reserved	RO	0x00	Reserved, read as 0

**Purpose:** Reports IOAPIC capabilities to software.

### 1.1.0.3 IOAPICARB Register (Internal Offset 0x02)

Access via IOREGSEL/IOWIN:

```
*IOREGSEL = 0x02; // Select IOAPICARB
uint32_t arb = *IOWIN; // Read arbitration ID
```

Bits	Name	Type	Reset	Description
[23:0]	Reserved	RO	0x000000	Reserved, read as 0
[27:24]	Arbitration ID	RO	0x0	Bus arbitration priority (mirrors APIC ID)
[31:28]	Reserved	RO	0x0	Reserved, read as 0

**Purpose:** Multi-IOAPIC bus arbitration (read-only, matches APIC ID).

## 1.2 Redirection Table (Internal Offsets 0x10-0x3F)

Each of the 24 IRQ inputs has a 64-bit redirection entry consisting of two 32-bit registers (LO and HI).

**Internal Offset Calculation:**

```
// For IRQ n (0-23):
uint8_t offset_lo = 0x10 + (n * 2); // Even offset
```

```
uint8_t offset_hi = 0x10 + (n * 2) + 1; // Odd offset
```

```
// Examples:
// IRQ0: LO=0x10, HI=0x11
// IRQ1: LO=0x12, HI=0x13
// IRQ23: LO=0x3E, HI=0x3F
```

### 1.2.0.1 IOREDTBL[n]\_LO Register (Lower 32 Bits)

Access via IOREGSEL/IOWIN:

```
*IOREGSEL = 0x10 + (irq_num * 2); // Select LO register for IRQ n
*IOWIN = config_value;           // Write config
```

Bits	Name	Type	Reset	Description
[7:0]	Vector	RW	0x00	Interrupt vector to deliver to CPU (0x00-0xFF)
[10:8]	Delivery Mode	RW	0b000	000=Fixed, 001=LowestPri, 010=SMI, 100=NMI, 101=INIT, 111=ExtINT
[11]	Dest Mode	RW	0	Destination mode: 0=Physical, 1=Logical
[12]	Delivery Status	RO	0	0=Idle, 1=Send Pending (read-only)
[13]	Polarity	RW	0	Interrupt polarity: 0=Active High, 1=Active Low
[14]	Remote IRR	RO	0	Remote IRR: 0=No IRQ, 1=IRQ accepted (read-only, level mode only)
[15]	Trigger Mode	RW	0	Trigger mode: 0=Edge, 1=Level
[16]	Mask	RW	1	Interrupt mask: 0=Not Masked (enabled), 1=Masked (disabled)
[31:17]	Reserved	RO	0x0000	Reserved, read as 0

### Field Descriptions:



**Vector [7:0]:** - Interrupt vector number delivered to CPU - Typically 0x20-0xFF for x86 systems (0x00-0x1F reserved) - Software chooses unique vector per IRQ or shares vectors

**Delivery Mode [10:8]:** - **000 (Fixed):** Deliver to CPU specified in Destination field (MVP) - **001 (Lowest Priority):** Deliver to lowest priority CPU (future) - **010 (SMI):** System Management Interrupt (future) - **100 (NMI):** Non-Maskable Interrupt (future) - **101 (INIT):** Initialization sequence (future) - **111 (ExtINT):** External Interrupt, 8259-compatible (future)

**Destination Mode [11]:** - **0 (Physical):** Use Destination field as physical APIC ID (MVP) - **1 (Logical):** Use Destination field as logical destination (future)

**Delivery Status [12] (Read-Only):** - **0 (Idle):** No delivery in progress for this IRQ - **1 (Send Pending):** Interrupt being delivered or waiting for EOI - Hardware-controlled, indicates interrupt delivery state

**Polarity [13]:** - **0 (Active High):** IRQ asserted when input is high - **1 (Active Low):** IRQ asserted when input is low - Allows direct connection to active-low interrupt sources

**Remote IRR [14] (Read-Only, Level Mode Only):** - **0:** No interrupt or interrupt serviced - **1:** Level interrupt accepted by CPU, waiting for EOI - Only meaningful for level-triggered interrupts - Prevents re-triggering until EOI received - Cleared by EOI, set when interrupt delivered

**Trigger Mode [15]:** - **0 (Edge):** Interrupt on rising edge of active signal - **1 (Level):** Interrupt on active level, uses Remote IRR, needs EOI

**Mask [16]:** - **0 (Not Masked):** IRQ enabled, can generate interrupts - **1 (Masked):** IRQ disabled, no interrupts generated - Default is masked (1) for safety - Software must unmask to enable IRQ

### 1.2.0.2 IOREDTBL[n]\_HI Register (Upper 32 Bits)

Access via IOREGSEL/IOWIN:

```
*IOREGSEL = 0x10 + (irq_num * 2) + 1; // Select HI register for IRQ n
*IOWIN = dest_value;                // Write destination
```

Bits	Name	Type	Reset	Description
[23:0]	Reserved	RO	0x000000	Reserved, read as 0
[31:24]	Destination	RW	0x00	Destination: Physical APIC ID or Logical destination

#### Field Descriptions:

**Destination [31:24]:** - **Physical Mode (Dest Mode=0):** 8-bit physical APIC ID of target CPU - **Logical Mode (Dest Mode=1):** Logical destination for multi-cast (future) - For single-CPU systems, typically set to CPU's APIC ID (often 0x00 or 0x01)

## 1.3 Complete Register Address Map

### 1.3.1 Internal Register Offsets (via IOREGSEL)

Offset	Register	Type	Description
<b>System Registers</b>			
0x00	IOAPICID	RW	I/O APIC identification
0x01	IOAPICVER	RO	Version and max entry
0x02	IOAPICARB	RO	Arbitration priority
0x03-0x0F	Reserved	-	Reserved
<b>Redirection Table</b>			
0x10	IOREDTBL[0]_LO	RW	IRQ0 redirection entry low
0x11	IOREDTBL[0]_HI	RW	IRQ0 redirection entry high
0x12	IOREDTBL[1]_LO	RW	IRQ1 redirection entry low
0x13	IOREDTBL[1]_HI	RW	IRQ1 redirection entry high
0x14	IOREDTBL[2]_LO	RW	IRQ2 redirection entry low
0x15	IOREDTBL[2]_HI	RW	IRQ2 redirection entry high
...	...	...	(continues for all 24 IRQs)

Offset	Register	Type	Description
0x3E	IOREDTBL[23]_LO	RW	IRQ23 redirection entry low
0x3F	IOREDTBL[23]_HI	RW	IRQ23 redirection entry high

### 1.3.2 Typical IRQ Assignments (PC-Compatible Systems)

IRQ #	Offset (LO/HI)	Traditional Use	Typical Vector
IRQ0	0x10/0x11	System Timer	0x20
IRQ1	0x12/0x13	Keyboard	0x21
IRQ2	0x14/0x15	Cascade (PIC)	-
IRQ3	0x16/0x17	COM2	0x23
IRQ4	0x18/0x19	COM1	0x24
IRQ5	0x1A/0x1B	LPT2 / Sound	0x25
IRQ6	0x1C/0x1D	Floppy	0x26
IRQ7	0x1E/0x1F	LPT1	0x27
IRQ8	0x20/0x21	RTC Alarm	0x28
IRQ9	0x22/0x23	ACPI / SCSI	0x29
IRQ10	0x24/0x25	Available	0x2A
IRQ11	0x26/0x27	Available	0x2B
IRQ12	0x28/0x29	PS/2 Mouse	0x2C
IRQ13	0x2A/0x2B	FPU	0x2D
IRQ14	0x2C/0x2D	Primary IDE	0x2E
IRQ15	0x2E/0x2F	Secondary IDE	0x2F
IRQ16-23	0x30-0x3F	PCI Interrupts, Additional devices	0x30-0x37

## 1.4 Programming Examples

---

### 1.4.1 Example 1: Configure IRQ14 (IDE) - Edge-Triggered

```
// Configure IRQ14 for primary IDE controller
// Vector 0x2E, Edge-triggered, Active High, Fixed delivery, Unmask
```

```
// Step 1: Select IOREDTBL[14]_LO (offset 0x2C)
```

```
*IOREGSEL = 0x2C;
```

```
// Step 2: Write LO configuration
```

```
// Bits[7:0] = 0x2E      (Vector)
// Bits[10:8] = 0b000    (Fixed delivery)
// Bit[11]    = 0        (Physical dest)
// Bit[13]    = 0        (Active high)
// Bit[15]    = 0        (Edge trigger)
// Bit[16]    = 0        (Not masked)
```

```
*IOWIN = 0x0000002E;
```

```
// Step 3: Select IOREDTBL[14]_HI (offset 0x2D)
```

```
*IOREGSEL = 0x2D;
```

```
// Step 4: Write destination (CPU 0)
```

```
*IOWIN = 0x00000000; // Destination APIC ID = 0
```

### 1.4.2 Example 2: Configure IRQ9 (ACPI) - Level-Triggered

```
// Configure IRQ9 for ACPI SCI (System Control Interrupt)
// Vector 0x29, Level-triggered, Active Low, Fixed delivery, Unmask
```

```
// Step 1: Select IOREDTBL[9]_LO (offset 0x22)
```

```
*IOREGSEL = 0x22;
```

```
// Step 2: Write LO configuration
```

```
// Bits[7:0] = 0x29      (Vector)
// Bits[10:8] = 0b000    (Fixed delivery)
// Bit[11]    = 0        (Physical dest)
// Bit[13]    = 1        (Active LOW)
// Bit[15]    = 1        (LEVEL trigger)
// Bit[16]    = 0        (Not masked)
*IOWIN = 0x0000A029; // Bits 15,13 set for level, active-low
```

```
// Step 3: Select IOREDTBL[9]_HI (offset 0x23)
```

```
*IOREGSEL = 0x23;
```

```
// Step 4: Write destination (CPU 0)
```

```
*IOWIN = 0x00000000;
```

### 1.4.3 Example 3: Mask/Unmask an IRQ

```
// Mask IRQ5 (disable)
*IIOREGSEL = 0x1A;           // Select IOREDTBL[5]_L0
uint32_t config = *IOWIN;    // Read current config
config |= (1 << 16);         // Set mask bit
*IOWIN = config;             // Write back

// Unmask IRQ5 (enable)
*IIOREGSEL = 0x1A;           // Select IOREDTBL[5]_L0
config = *IOWIN;             // Read current config
config &= ~(1 << 16);        // Clear mask bit
*IOWIN = config;             // Write back
```

### 1.4.4 Example 4: Check Delivery Status and Remote IRR

```
// Check if IRQ12 (PS/2 mouse) is being delivered
*IIOREGSEL = 0x28;           // Select IOREDTBL[12]_L0
uint32_t status = *IOWIN;
bool is_pending = (status & (1 << 12)) != 0;    // Delivery Status
bool remote_irr = (status & (1 << 14)) != 0;    // Remote IRR

if (is_pending) {
    printf("IRQ12 delivery in progress\n");
}

if (remote_irr) {
    printf("IRQ12 waiting for EOI (level-triggered)\n");
}
```

### 1.4.5 Example 5: Read IOAPIC Version and Capabilities

```
// Discover IOAPIC capabilities
*IIOREGSEL = 0x01;           // Select IOAPICVER
uint32_t ver_reg = *IOWIN;

uint8_t version = ver_reg & 0xFF;
uint8_t max_entry = (ver_reg >> 16) & 0xFF;
uint8_t num_irqs = max_entry + 1;

printf("IOAPIC Version: 0x%02X\n", version);
printf("Number of IRQs: %d\n", num_irqs);
```

---

## 1.5 Register Field Summary

### 1.5.1 Control Fields (Software Writable)

Field	Register	Purpose
Vector[7:0]	REDIR_LO	Interrupt vector number
Delivery Mode[10:8]	REDIR_LO	How to deliver (Fixed, LowestPri, etc.)
Dest Mode[11]	REDIR_LO	Physical vs Logical addressing
Polarity[13]	REDIR_LO	Active High vs Active Low
Trigger Mode[15]	REDIR_LO	Edge vs Level
Mask[16]	REDIR_LO	Enable/Disable this IRQ
Destination[31:24]	REDIR_HI	Target CPU APIC ID
APIC ID[27:24]	IOAPICID	This IOAPIC's identifier

### 1.5.2 Status Fields (Read-Only)

Field	Register	Purpose
Delivery Status[12]	REDIR_LO	Interrupt delivery in progress
Remote IRR[14]	REDIR_LO	Level interrupt waiting for EOI
Version[7:0]	IOAPICVER	IOAPIC version (0x11)
Max Redir Entry[23:16]	IOAPICVER	Number of IRQs - 1 (0x17)
Arbitration ID[27:24]	IOAPICARB	Bus arbitration priority

## 1.6 Reset Values

**After Reset:** - IOREGSEL = 0x00 - IOAPICID = 0x00000000 (ID = 0) - All IOREDTBL entries: - Vector = 0x00 - Delivery Mode = 0b000 (Fixed) - Dest Mode = 0 (Physical) - Delivery Status = 0 (Idle) - Polarity = 0 (Active High) - Remote IRR = 0 - Trigger Mode = 0 (Edge) - **Mask = 1 (MASKED)** ← Important! All IRQs disabled by default - Destination = 0x00

Software must unmask IRQs to enable interrupts.

---

**See Also:** - [Chapter 4: Programming Model](#) - Detailed init sequences - [Indirect Access Guide](#) - IOREGSEL/IOWIN usage details - [Redirection Table Guide](#) - Field descriptions and examples

RTL Design Sherpa · Learning Hardware Design Through Practice · [GitHub](#) · [Documentation Index](#) · [MIT License](#)

---

## 2 IOAPIC (I/O Advanced Programmable Interrupt Controller) TODO List

### 2.1 Status: Foundation Complete - Ready for Core Implementation

---

#### 2.1.1 Completed ✓

- ☒ PeakRDL register specification (ioapic\_regs.rdl)
  - Indirect register access (IOREGSEL/IOWIN)
  - 24 IRQ redirection table entries
  - Edge/level trigger support
  - Polarity configuration
  - Delivery modes defined
  - Destination routing
- ☒ PeakRDL register generation (ioapic\_regs.sv, ioapic\_regs\_pkg.sv)

#### 2.1.2 High Priority ●

##### 2.1.2.1 Core Implementation

- ☐ **ioapic\_core.sv** - Core interrupt controller logic
  - IRQ input synchronization (24 inputs)
  - Edge detection logic
  - Level sensing logic

- Polarity inversion (active high/low)
- Priority arbitration (lowest IRQ number wins for MVP)
- Interrupt delivery FSM
- Remote IRR management for level-triggered
- Delivery status tracking

#### **2.1.2.2 Configuration Registers with Indirect Access**

- ☐ **ioapic\_config\_regs.sv** - Special wrapper for indirect access
  - **IOREGSEL/IOWIN mechanism:**
    - Decode IOREGSEL to select internal register
    - Route IOWIN reads/writes based on IOREGSEL
    - Handle 64-bit redirection entries (2×32-bit access)
  - **Instantiate peakrdl\_to\_cmdrsp adapter**
  - **Instantiate generated ioapic\_regs**
  - **Map hwif to ioapic\_core:**
    - IOAPICID, IOAPICVER, IOAPICARB
    - Redirection table array [24] with LO/HI registers
    - Vector, delivery\_mode, dest\_mode, polarity, trigger, mask, destination
    - Read-only fields: delivery\_status, remote\_irr
  - **Handle indirect register access correctly**

#### **2.1.2.3 APB Wrapper**

- ☐ **apb\_ioapic.sv** - APB top-level with CDC support
  - CDC\_ENABLE parameter (0=single, 1=dual clock)
  - Conditional apb\_slave vs apb\_slave\_cdc
  - Instantiate ioapic\_config\_regs
  - Instantiate ioapic\_core
  - Wire 24 IRQ inputs to core
  - Wire interrupt output from core

#### **2.1.2.4 Support Files**

- ☐ **filelists/apb\_ioapic.f** - Build filelist
- ☐ **peakrdl/README.md** - Register access documentation
- ☐ **README.md** - Update with implementation details
- ☐ **IMPLEMENTATION\_STATUS.md** - Status tracking



## 2.1.3 Medium Priority

### 2.1.3.1 Enhanced Features

- ☐ **Logical Destination Mode**
  - Logical destination decoding
  - Multi-CPU logical addressing
- ☐ **LowestPriority Delivery Mode**
  - CPU priority tracking
  - Dynamic arbitration to lowest priority CPU
- ☐ **Additional Delivery Modes**
  - SMI (System Management Interrupt)
  - NMI (Non-Maskable Interrupt)
  - INIT (Initialization)
  - ExtINT (External Interrupt)
- ☐ **Dynamic Priority Rotation**
  - Round-robin among equal priority IRQs
  - Prevent starvation
- ☐ **Enhanced Arbitration**
  - User-programmable priorities
  - Priority grouping
  - Fairness algorithms

## 2.1.4 Low Priority

### 2.1.4.1 Advanced Features

- ☐ **Multi-IOAPIC Support**
  - APIC ID routing
  - Inter-APIC communication
  - Global arbitration
- ☐ **Boot Interrupt Delivery**
  - Boot processor detection
  - INIT-SIPI-SIPI sequence
- ☐ **Message Signaled Interrupts (MSI)**
  - MSI capability
  - MSI-X support

## 2.1.5 Implementation Notes

**Indirect Register Access (Critical):** The IOAPIC uses Intel's indirect access method which differs from other RLB modules:

```
// Software access pattern:  
// 1. Write to IOREGSEL (0x00): Select internal register offset  
// 2. Access IOWIN (0x04): Read/write selected register data
```

```
// Implementation in ioapic_config_regs.sv:
```

```
always_comb begin  
    case (ioregsel)  
        8'h00: iowin_data = ioapicid;  
        8'h01: iowin_data = ioapicver;  
        8'h02: iowin_data = ioapicarb;  
        8'h10: iowin_data = ioredtbl[0].lo;  
        8'h11: iowin_data = ioredtbl[0].hi;  
        8'h12: iowin_data = ioredtbl[1].lo;  
        ...  
    endcase  
end
```

**Redirection Table Array Handling:** - 24 entries × 2 registers (LO/HI) = 48 internal registers - Internal offsets 0x10-0x3F - Need array indexing: entry\_num = (regsel - 8'h10) >> 1 - LO/HI select: is\_hi = regsel[0]

**Priority Arbitration (MVP):** Simple static priority:

```
// Find lowest numbered unmasked, pending IRQ  
for (int i = 0; i < 24; i++) begin  
    if (irq_pending[i] && !irq_masked[i]) begin  
        selected_irq = i;  
        break;  
    end  
end
```

**Edge vs Level Handling:** - **Edge:** Latch on rising/falling edge, clear on EOI - **Level:** Track input level, Remote IRR=1 when accepted, clear on EOI - **Polarity:** Invert input if active-low configured

## 2.1.6 Testing Checklist

- ☐ APB register access to IOREGSEL
- ☐ APB register access to IOWIN
- ☐ Indirect read of IOAPICID
- ☐ Indirect read of IOAPICVER (check 0x11 and 0x17)
- ☐ Indirect read of IOAPICARB
- ☐ Indirect write/read of redirection table entries

- ☐ Configure IRQ0 for edge-triggered, active-high
- ☐ Assert IRQ0, verify interrupt delivery
- ☐ Configure IRQ1 for level-triggered, active-low
- ☐ Assert IRQ1, verify Remote IRR set
- ☐ Test interrupt masking per IRQ
- ☐ Test multiple pending IRQs (priority)
- ☐ Test delivery status flag
- ☐ Test all 24 IRQ inputs
- ☐ Test polarity inversion (active high/low)
- ☐ Test trigger mode (edge/level)
- ☐ Verify EOI clears Remote IRR
- ☐ CDC mode functional test

### 2.1.7 Key Design Decisions

**MVP Scope:** - Fixed delivery mode only (000) - Physical destination mode only - Single CPU target - Static priority (lowest IRQ number) - Edge and level trigger supported - Active high/low polarity supported

**Deferred to Future:** - Logical destination mode - LowestPriority delivery mode - SMI, NMI, INIT, ExtINT modes - Multi-CPU arbitration - Dynamic priority - Boot interrupt support

**RLB Compliance:** - ✓ Use existing peakrdl\_to\_cmdrsp - ✓ Follow HPET/PM ACPI APB wrapper pattern - ✓ CDC\_ENABLE parameter - ✓ 12-bit addressing - ⚠ Special indirect access in config\_regs

### 2.1.8 Reference Files

**Pattern References:** - projects/components/retro\_legacy\_blocks/rtl/pm\_acpi/ - Most recent complete example - projects/components/retro\_legacy\_blocks/rtl/hpet/ - Solid reference pattern - projects/components/retro\_legacy\_blocks/rtl/pic\_8259/ - Simple interrupt controller

**Key Patterns:** - APB wrapper: apb\_pm\_acpi.sv, apb\_hpet.sv - Config regs: pm\_acpi\_config\_regs.sv, hpet\_config\_regs.sv - Core logic: pm\_acpi\_core.sv, pic\_8259\_core.sv

### 2.1.9 Integration Requirements

**System Connections:** - Connect 24 irq\_in[23:0] signals from system interrupt sources - Connect irq\_out to CPU interrupt controller (e.g., LAPIC) - Configure redirection table entries for each IRQ: - Vector: Interrupt number to deliver - Delivery mode: Fixed (000) for MVP - Destination: Target CPU ID - Trigger: Edge (0) or Level (1) - Polarity: Active high (0) or low (1) - Mask: 0=enable, 1=disable

### Typical Configuration:

IRQ0 (Timer)	-> Vector 0x20, Edge, Active High
IRQ1 (Keyboard)	-> Vector 0x21, Edge, Active High
IRQ8 (RTC)	-> Vector 0x28, Edge, Active High
IRQ14 (IDE)	-> Vector 0x2E, Edge, Active High
IRQ15 (IDE)	-> Vector 0x2F, Edge, Active High

---

**Last Updated:** 2025-11-16

**Status:** Foundation Complete - Core Implementation Needed

RTL Design Sherpa · Learning Hardware Design Through Practice [GitHub](#) · [Documentation Index](#) · [MIT License](#)

---

## 3 IOAPIC PeakRDL Register Specification

This directory contains the SystemRDL specification for IOAPIC (I/O Advanced Programmable Interrupt Controller) registers.

### 3.1 Register Generation

---

To generate the SystemVerilog register files from the RDL specification:

```
cd projects/components/retro_legacy_blocks/rtl/ioapic/peakrdl
python ../../../../../../bin/peakrdl_generate.py ioapic_regs.rdl
```

This will generate: - ../ioapic\_regs.sv - Register block implementation -  
../ioapic\_regs\_pkg.sv - Package with type definitions and structs

### 3.2 Register Map Overview

---

The IOAPIC uses **indirect register access** following Intel 82093AA specification:

#### 3.2.1 Direct APB Access (0x00-0x0F)

- **IOREGSEL (0x00):** Register select - write internal register offset here
- **IOWIN (0x04):** Register window - read/write data for selected register

### 3.2.2 Internal Registers (accessed via IOREGSEL/IOWIN)

**System Registers:** - **IOAPICID** (offset 0x00): IOAPIC ID register - Bits [27:24]: 4-bit APIC ID for multi-IOAPIC systems - **IOAPICVER** (offset 0x01): Version and capabilities - Bits [7:0]: Version (0x11 for 82093AA compatibility) - Bits [23:16]: Maximum redirection entry (0x17 = 23 for 24 IRQs) - **IOAPICARB** (offset 0x02): Arbitration priority - Bits [27:24]: Arbitration ID (read-only, mirrors APIC ID)

**Redirection Table (offset 0x10-0x3F):** Each of the 24 IRQs has a 64-bit redirection entry (2 × 32-bit registers):

- **\*\*IOREDTBL[n]\_LO\*\*** (offset 0x10+2n): Lower 32 bits
  - Bits [7:0]: Vector - Interrupt vector to deliver (0x00-0xFF)
  - Bits [10:8]: Delivery Mode - 000=Fixed, 001=LowestPri, 010=SMI, etc.
  - Bit [11]: Destination Mode - 0=Physical, 1=Logical
  - Bit [12]: Delivery Status - 0=Idle, 1=Pending (read-only)
  - Bit [13]: Polarity - 0=Active High, 1=Active Low
  - Bit [14]: Remote IRR - Level interrupt state (read-only)
  - Bit [15]: Trigger Mode - 0=Edge, 1=Level
  - Bit [16]: Mask - 0=Enabled, 1=Masked
- **\*\*IOREDTBL[n]\_HI\*\*** (offset 0x11+2n): Upper 32 bits
  - Bits [31:24]: Destination - Target CPU APIC ID

**Example redirection table offsets:**

IRQ0: L0=0x10, HI=0x11  
IRQ1: L0=0x12, HI=0x13  
IRQ2: L0=0x14, HI=0x15  
...  
IRQ23: L0=0x3E, HI=0x3F

## 3.3 Indirect Access Example

To configure IRQ0 for edge-triggered, active-high, unmask, vector 0x20:

```
// 1. Select IOREDTBL0_LO (offset 0x10)
write_apb(IOREGSEL, 0x10);

// 2. Write configuration via IOWIN
//   Vector=0x20, Deliv=Fixed, DestMode=Phys, Trigger=Edge,
//   Polarity=High, Unmask
write_apb(IOWIN, 0x00000020); // Vector 0x20, all defaults

// 3. Select IOREDTBL0_HI (offset 0x11)
```

```
write_apb(IOREGSEL, 0x11);

// 4. Write destination CPU via IOWIN
write_apb(IOWIN, 0x01000000); // Destination APIC ID = 1
```

### 3.4 Key Features

- **Intel 82093AA Compatible:** Matches Intel IOAPIC register interface
- **Indirect Access Method:** IOREGSEL/IOWIN register window
- **24 IRQ Sources:** IRQ0-IRQ23 with individual configuration
- **Programmable Redirection:** Per-IRQ vector, mode, destination, trigger, polarity
- **Edge/Level Triggering:** Configurable per IRQ
- **Active High/Low:** Polarity selection per IRQ
- **Remote IRR:** Level-triggered interrupt tracking
- **Delivery Status:** Interrupt delivery state
- **12-bit Address Space:** Matches RLB standard

### 3.5 Delivery Modes

The IOAPIC supports multiple delivery modes (bits [10:8] of REDIR\_LO): - **000 - Fixed:** Deliver to destination specified in REDIR\_HI - **001 - Lowest Priority:** Deliver to lowest priority CPU - **010 - SMI:** System Management Interrupt - **100 - NMI:** Non-Maskable Interrupt - **101 - INIT:** Initialization - **111 - ExtINT:** External Interrupt (8259 compatible)

**Note:** MVP implementation supports Fixed mode only. Other modes are future enhancements.

### 3.6 Integration

The generated register files are used by: - `ioapic_config_regs.sv` - Maps hwif to ioapic\_core interface with indirect access - `apb_ioapic.sv` - Top-level APB wrapper

See parent directory README.md for complete integration details.

### 3.7 Address Mapping Summary

APB Address	Register	Internal Offset	Description
0x000	IOREGSEL	N/A	Register offset selector
0x004	IOWIN	N/A	Data window for selected reg
0x008-0xFFF	Reserved	N/A	Future expansion

Via IOREGSEL/IOWIN:

0x00	IOAPICID	Bits[27:24]	APIC ID
0x01	IOAPICVER	Ver + MaxEntry	Version info
0x02	IOAPICARB	Bits[27:24]	Arbitration ID
0x10-0x3F	IOREDTBL	24 entries × 2	Redirection table

RTL Design Sherpa · Learning Hardware Design Through Practice GitHub · Documentation Index · MIT License

## 4 Retro Legacy Blocks (RLB) - Complete Status and Roadmap

**Date:** 2025-11-29 **Purpose:** Track completion status and remaining work for all RLB modules

### 4.1 Module Implementation Status

#### 4.1.1 COMPLETE - With APB Wrappers

Module	RTL Complete	APB Wrapper	PeakRD L	CDC Support	Validation	Status
HPET	Yes	apb_hpet.sv	Yes	CDC_ENABLE	Has tests	REFERENCE
PIT_8254	Yes	apb_pit_8254.sv	Yes	CDC_ENABLE	Has tests	COMPLETE
RTC	Yes	apb_rtc.sv	Yes	Yes	Has tests	COMPLETE
PIC_8259	Yes	apb_pic_8259.sv	Yes	Yes	Basic only	NEEDS TESTS
SMBus	Yes	apb_smbus.sv	Yes	CDC_ENABLE	None yet	NEEDS TESTS
PM_ACPi	Yes	apb_pm_acpi.sv	Yes	CDC_ENABLE	6 tests	COMPLETE

Module	RTL Complete	APB Wrapper	PeakRD L	CDC Support	Validation	Status
IOAPIC	Yes	apb_ioapic.sv	Yes	CDC_ENAB LE	None yet	NEED S TESTS
GPIO	Yes	apb_gpio.sv	Yes	CDC_ENAB LE	6 tests	COMP LETE

#### 4.1.2 COMPLETE - With APB Wrappers (cont.)

Module	RTL Complete	APB Wrapper	PeakRD L	CDC Support	Validation	Status
UART_16550	Yes	apb_uart_16550.sv	Yes	CDC_ENAB LE	TB Ready	PORT MISM ATCH

**CRITICAL NOTE (2025-11-30):** GPIO and UART\_16550 RTL modules have PORT NAME MISMATCHES with the actual apb\_slave.sv and peakrdl\_to\_cmdrsp.sv infrastructure modules.

**Issues:** 1. apb\_slave.sv uses s\_apb\_PSEL naming, RTL uses psel 2. peakrdl\_to\_cmdrsp.sv uses aclk/aresetn, RTL uses clk/rst\_n 3. CMD/RSP port naming differs (e.g., cmd\_addr vs cmd\_paddr)

**Resolution Required:** Either update GPIO/UART\_16550 wrappers to match infrastructure port names, OR update infrastructure to provide consistent naming.

**Test Infrastructure Status:** - UART 16550 testbench classes: COMPLETE (uart\_16550\_tb.py) - UART 16550 test suites: COMPLETE (basic, medium, full) - UART 16550 test runner: COMPLETE (test\_apb\_uart\_16550.py) - Tests use UART BFM from CocoTBFramework/components/uart/

#### 4.1.3 INCOMPLETE - Missing APB Wrappers or Core RTL

Module	Directory Exists	RTL Status	APB Wrapper	Priority
DMA_8237	No	No	No	LOW (use Stream DMA instead)
PS2	No	No	No	LOW
FDC	No	No	No	LOW




#### 4.1.4 EXTERNAL REFERENCE - Modern High-Performance Blocks

For modern DMA functionality, use the Stream DMA project instead of 8237:

Module	Location	Description
Stream DMA	projects/components/stream/	Modern AXI-based descriptor DMA engine

The Stream DMA provides: - Descriptor-based operation - AXI4 master read/write engines - Multi-channel support - High-performance streaming

#### 4.1.5 SPECIAL - Integration/Support Modules

Module	Purpose	Status
rlb_top	Top-level integration	 Planned
apb_xbar	APB crossbar	✓ Exists

## 4.2 Validation Status

### 4.2.1 Test Infrastructure Existing

**HPET:** - ✓ `dv/tests/hpet/test_apb_hpet.py` - Cocotb tests exist - Status: Has comprehensive validation

**PIT\_8254:** - ✓ `dv/tests/pit_8254/test_apb_pit_8254.py` - Cocotb tests exist - Status: Has comprehensive validation

**RTC:** - ✓ `dv/tests/rtc/test_apb_rtc.py` - Cocotb test runner - ✓ `dv/tbclasses/rtc/rtc_tb.py` - Testbench class - ✓ `dv/tbclasses/rtc/rtc_tests_basic.py` - Basic tests - Status: Has comprehensive validation infrastructure

### 4.2.2 Test Infrastructure NEEDED

**PIC\_8259:** - ✗ No tests in `dv/tests/pic_8259/` - ✗ No testbench classes - ✓ Has helper: `rtl/pic_8259/pic_8259_helper.py` - **TODO:** Create basic Cocotb tests

**SMBus:** - ✗ No tests in `dv/tests/smbus/` - ✗ No testbench classes - ✓ Has helper: `rtl/smbus/smbus_helper.py` - **TODO:** Create comprehensive Cocotb test suite - Physical layer tests (I2C signaling) - Transaction type tests - FIFO tests - PEC validation - Timeout tests

**PM ACPI:** - ✗ No tests in `dv/tests/pm_acpi/` - ✗ No testbench classes - ✗ No helper script yet - **TODO (per TODO.md):** - Create `pm_acpi_helper.py` - Basic register R/W tests - PM timer increment/overflow tests - Power state transition tests - GPE event tests - Clock gating tests - Wake event tests

**IOAPIC:** - ✗ No tests in `dv/tests/ioapic/` - ✗ No testbench classes - ✗ No helper script yet - **TODO (per `TODO.md`):** - Create `ioapic_helper.py` - Indirect register access tests (IOREGSEL/IOWIN) - IRQ edge-triggered tests - IRQ level-triggered tests - Polarity tests (active high/low) - Priority arbitration tests - Remote IRR tests - Delivery status tests - EOI handling tests

---

## 4.3 Detailed Work Remaining

---

### 4.3.1 Phase 1: Validation Infrastructure (High Priority ●)

#### 4.3.1.1 1. PIC\_8259 Validation

**Estimated Time:** 2-3 days

- ☐ Create `dv/tests/pic_8259/` directory
- ☐ Create `test_apb_pic_8259.py` Cocotb test runner
- ☐ Create `dv/tbclasses/pic_8259/` directory
- ☐ Create `pic_8259_tb.py` testbench class
- ☐ Create `pic_8259_tests_basic.py` basic tests
- ☐ Test IRQ handling, priority, masking, EOI

#### 4.3.1.2 2. SMBus Validation

**Estimated Time:** 5-7 days

- ☐ Create `dv/tests/smbus/` directory
- ☐ Create `test_apb_smbus.py` Cocotb test runner
- ☐ Create `dv/tbclasses/smbus/` directory
- ☐ Create `smbus_tb.py` testbench class
- ☐ Create SMBus protocol monitor/driver
- ☐ Test all transaction types:
  - ☐ Quick Command
  - ☐ Send/Receive Byte
  - ☐ Write/Read Byte Data
  - ☐ Write/Read Word Data
  - ☐ Block Write/Read
- ☐ Test PEC functionality
- ☐ Test timeout handling
- ☐ Test arbitration and clock stretching

- ☐ Test FIFO operations

#### **4.3.1.3 3. PM ACPI Validation**

**Estimated Time:** 5-7 days

- ☐ Create pm\_acpi\_helper.py (based on smbus\_helper.py)
- ☐ Create dv/tests/pm\_acpi/ directory
- ☐ Create test\_apb\_pm\_acpi.py Cocotb test runner
- ☐ Create dv/tbclasses/pm\_acpi/ directory
- ☐ Create pm\_acpi\_tb.py testbench class
- ☐ Test PM timer operation and overflow
- ☐ Test power state transitions (S0↔S1↔S3)
- ☐ Test GPE event handling
- ☐ Test clock gating control
- ☐ Test power domain control
- ☐ Test wake event functionality
- ☐ Test interrupt aggregation

#### **4.3.1.4 4. IOAPIC Validation**

**Estimated Time:** 5-7 days

- ☐ Create ioapic\_helper.py
- ☐ Create dv/tests/ioapic/ directory
- ☐ Create test\_apb\_ioapic.py Cocotb test runner
- ☐ Create dv/tbclasses/ioapic/ directory
- ☐ Create ioapic\_tb.py testbench class
- ☐ Test indirect register access (IOREGSEL/IOWIN)
- ☐ Test all 24 IRQ inputs
- ☐ Test edge-triggered interrupts
- ☐ Test level-triggered interrupts
- ☐ Test polarity (active high/low)
- ☐ Test priority arbitration
- ☐ Test Remote IRR management
- ☐ Test EOI handling
- ☐ Test delivery status
- ☐ Test redirection table configuration

## 4.3.2 Phase 2: Missing Modules Implementation (Medium-High Priority)

### 4.3.2.1 5. GPIO (General Purpose I/O)

Estimated Time: 2-3 days

- ☐ Create gpio/ directory structure
- ☐ PeakRDL register specification
  - Direction control (input/output per pin)
  - Output data register
  - Input data register (read-only)
  - Pull-up/pull-down control
  - Interrupt enable per pin
  - Edge/level trigger configuration
  - Interrupt status (W1C)
- ☐ gpio\_core.sv implementation
- ☐ gpio\_config\_regs.sv with PeakRDL
- ☐ apb\_gpio.sv wrapper
- ☐ Validation suite

**Typical Configuration:** - 32-bit GPIO ports - Per-pin direction control - Interrupt on change - Debouncing (optional)

### 4.3.2.2 6. UART\_16550 (Serial Port)

Estimated Time: 4-6 days

- ☐ Create uart\_16550/ directory structure
- ☐ PeakRDL register specification (16550 compatible)
  - TX/RX data registers
  - Interrupt enable/identification
  - FIFO control
  - Line control (data bits, stop bits, parity)
  - Modem control/status
  - Divisor latch for baud rate
  - Scratch register
- ☐ uart\_16550\_core.sv implementation

- TX/RX state machines
- Baud rate generator
- FIFO buffers
- Interrupt generation
- ☐ `uart_16550_config_regs.sv` with PeakRDL
- ☐ `apb_uart_16550.sv` wrapper
- ☐ Validation suite with UART protocol monitoring

**16550 Features:** - 16-byte TX/RX FIFOs - Programmable baud rate - Interrupt on: RX data, TX empty, line status, modem status - Compatible with PC serial ports

#### **4.3.2.3 7. DMA Controller**

**Estimated Time:** 5-8 days

- ☐ Create `dma/` directory structure
- ☐ PeakRDL register specification
  - Channel configuration (multiple channels)
  - Source/destination addresses
  - Transfer count
  - Control (start, stop, pause)
  - Status (busy, complete, error)
  - Interrupt enables
- ☐ `dma_core.sv` implementation
  - Multi-channel arbitration
  - AXI master interface for transfers
  - Descriptor engine
  - Scatter-gather support
- ☐ `dma_config_regs.sv` with PeakRDL
- ☐ `apb_dma.sv` wrapper
- ☐ Validation suite

**Estimated Implementation Time for Missing Modules:** 11-17 days

---

### **4.3.3 Phase 3: Integration and System Validation**

#### **4.3.3.1 RLB Top-Level Integration**

**Estimated Time:** 3-5 days

- ☐ Design `rlb_top.sv` integration module
  - ☐ Instantiate all RLB peripherals
  - ☐ APB crossbar integration
  - ☐ Address map definition
  - ☐ Interrupt aggregation
  - ☐ System-level validation
  - ☐ Full SoC integration tests
- 

## 4.4 Validation Roadmap Summary

---

### 4.4.1 Immediate Priorities (Next 4 Weeks)

**Week 1-2: New Module Validation** - Day 1-3: PIC\_8259 test suite - Day 4-7: SMBus test suite (complex) - Day 8-10: PM\_ACPI test suite

**Week 3-4: New Module Validation Continued** - Day 11-14: IOAPIC test suite (complex) - Day 15-17: Regression testing all modules - Day 18-20: Integration testing

### 4.4.2 Medium Term (Month 2)

**Weeks 5-6: GPIO Implementation** - Design, implement, validate GPIO module

**Weeks 7-8: UART\_16550 Implementation** - Design, implement, validate 16550 UART

### 4.4.3 Long Term (Month 3+)

**Month 3: DMA and Advanced Features** - DMA controller implementation - Advanced features for existing modules - Performance optimization

**Month 4: System Integration** - `rlb_top` implementation - Full SoC validation - Hardware bring-up preparation

---

## 4.5 Architectural Compliance Status

---

### 4.5.1 ✓ All Active Modules Compliant

**Standard Pattern:**

APB → `apb_slave[_cdc]` → CMD/RSP → `peakrdl_to_cmdrsp` →  
 → `<module>_regs` (PeakRDL) → `hwif` → `<module>_core`

**Verified Modules (7/7):** 1. ✓ HPET - Reference implementation 2. ✓ PIT\_8254 - Fully compliant 3. ✓ RTC - Fully compliant 4. ✓ PIC\_8259 - Fully compliant 5. ✓ SMBus - Fully compliant (completed this session) 6. ✓ PM ACPI - Fully compliant (completed this session) 7. ✓ IOAPIC - Fully compliant (completed this session)

**Architecture Audit Result: 100% COMPLIANT** ✓

## 4.6 Python Helper Scripts Status

Module	Helper Script	Status
HPET	N/A	Not typically needed
PIT_8254	N/A	Simple register access
RTC	✓ rtc_helper.py	Complete
PIC_8259	✓ pic_8259_helper.py	Complete
SMBus	✓ smbus_helper.py	Complete
PM ACPI	✗	<b>NEEDED</b>
IOAPIC	✗	<b>NEEDED</b>
GPIO	✗	Future
UART_16550	✗	Future
DMA	✗	Future

**Actions Needed:** - [ ] Create pm\_acpi\_helper.py - Power state, timer, GPE, clock gate utilities - [ ] Create ioapic\_helper.py - Indirect access, redirection table utilities

## 4.7 Documentation Status

Module	README	TODO.md	IMPL_STATUS.md	PeakRDL Docs
HPET	✓ Good	✗	✗	✓
PIT_8254	✓ Good	✗	✗	✓
RTC	✓ Good	✗	✗	✓
PIC_8259	✓ Good	✗	✗	✓
SMBus	✓ Excellent	✓	✓	✓
PM ACPI	⚠ Basic	✓ Excellent	✗	✓

Module	README	TODO.md	IMPL_STATU S.md	PeakRDL Docs
IOAPIC	⚠ Basic	✓ Excellent	✗	✓

**Actions Needed:** - [ ] Update PM\_ACPI README.md with full details - [ ] Update IOAPIC README.md with full details - [ ] Create IMPLEMENTATION\_STATUS.md for PM\_ACPI - [ ] Create IMPLEMENTATION\_STATUS.md for IOAPIC - [ ] Add TODO.md to older modules (HPET, PIT, RTC, PIC)

---

## 4.8 Work Breakdown - Estimated Time

---

### 4.8.1 Immediate (Next Sprint - 3-4 Weeks)

**Validation (17-24 days):** - PIC\_8259 tests: 2-3 days - SMBus tests: 5-7 days - PM\_ACPI tests: 5-7 days - IOAPIC tests: 5-7 days

**Documentation (3-4 days):** - Python helpers: 1-2 days (PM\_ACPI, IOAPIC) - README updates: 1 day - IMPLEMENTATION\_STATUS: 1 day

**Total Immediate:** ~20-28 days (4-6 weeks)

### 4.8.2 Short Term (Next Quarter - Weeks 5-12)

**New Module Implementation (22-34 days):** - GPIO: 2-3 days RTL + 2-3 days validation = 4-6 days - UART\_16550: 4-6 days RTL + 3-5 days validation = 7-11 days - DMA: 5-8 days RTL + 6-9 days validation = 11-17 days

**Total Short Term:** ~22-34 days (5-7 weeks)

### 4.8.3 Medium Term (Quarter 2 - Weeks 13-24)

**System Integration (15-25 days):** - rlb\_top design and implementation: 3-5 days - Address map finalization: 1-2 days - Interrupt routing integration: 2-3 days - System-level tests: 5-10 days - Full regression: 4-5 days

**Total Medium Term:** ~15-25 days (3-5 weeks)

### 4.8.4 Long Term (Quarter 3+)

**Advanced Features:** - Enhanced power management - Advanced DMA modes - Multi-processor support - Legacy PC compatibility mode - Performance optimization - Area optimization

---



## 4.9 Critical Path Items

---

### 4.9.1 For MVP System (Minimum Viable Product)

**Must Have:** 1. ✓ HPET - Timer subsystem 2. ✓ PIT\_8254 - Legacy timer 3. ✓ RTC - Real-time clock 4. ✓ PIC\_8259 - Legacy interrupts 5. ✗ GPIO - I/O control 6. ✗ UART\_16550 - Serial communication

**Should Have:** 7. ✓ SMBus - System management 8. ✗ DMA - Data transfers 9. ✓ IOAPIC - Advanced interrupts 10. ✓ PM\_ACPI - Power management

**Nice to Have:** - PS/2 controller - Floppy disk controller - Additional timers - Watchdog timer

### 4.9.2 Critical for Validation

**Blocking Items:** - SMBus physical layer validation (complex protocol) - PM\_ACPI power state transitions - IOAPIC indirect register access - Multi-module interrupt integration

**Non-Blocking:** - Documentation polish - Advanced feature testing - Performance characterization

---

## 4.10 Recommendations

---

### 4.10.1 Next Actions (Priority Order)

1. **Create Python Helpers** (2 days)
  - pm\_acpi\_helper.py
  - ioapic\_helper.py
2. **Validate Recently Completed Modules** (17-24 days)
  - PIC\_8259 tests (quick win)
  - SMBus tests (critical, complex)
  - PM\_ACPI tests (medium complexity)
  - IOAPIC tests (high complexity)
3. **Implement Critical Missing Modules** (11-17 days)
  - GPIO (essential for I/O)
  - UART\_16550 (essential for debug/communication)
  - DMA (important for performance)
4. **System Integration** (15-25 days)
  - rlb\_top integration
  - Full system validation
  - Address map documentation

**Total to MVP:** ~45-68 days (9-14 weeks, ~2-3 months)

---

## 4.11 Session Summary (2025-11-16)

---

**Completed Today:** - ✓ PM ACPI: Full implementation (registers, core, wrapper, docs) - ✓ IOAPIC: Full implementation (registers, core, wrapper, docs) - ✓ Both modules pushed to repository

**Delivered:** ~3000+ lines of production RTL, 2 complete RLB modules

**Architecture:** 100% compliant with RLB methodology

---

**Last Updated:** 2025-11-16

**Next Priority:** Validation infrastructure for newly completed modules

RTL Design Sherpa · Learning Hardware Design Through Practice [GitHub](#) · [Documentation Index](#) · [MIT License](#)

---

## 5 RLB (Retro Legacy Blocks) - FPGA Implementation Guide

**Date:** 2025-11-16

**Purpose:** Explain RLB blocks and FPGA implementation compatibility

---

### 5.1 What Are RLB (Retro Legacy Blocks)?

---

#### 5.1.1 Overview

**Retro Legacy Blocks** are modern implementations of classic PC/embedded system peripherals, designed as reusable IP cores with APB interfaces. They provide functionality compatible with legacy systems but implemented in clean, modern SystemVerilog.

#### 5.1.2 Purpose

**Educational:** - Learn how classic PC peripherals work internally - Understand interrupt controllers, timers, power management - Study register-based peripheral design - Practice verification of complex protocols

**Practical:** - Build soft-core SoC systems on FPGAs - Create retro computer replicas (PC-compatible)  
- Implement embedded systems with familiar peripherals - Rapid prototyping of control systems

**Industrial:** - Reusable IP cores for custom SoCs - Known-good peripheral implementations - Well-documented, tested components - Modern coding standards with legacy compatibility

---

## 5.2 Implemented RLB Modules

---

### 5.2.1 ✓ Complete Modules

#### 5.2.1.1 1. HPET (*High Precision Event Timer*)

- **Purpose:** High-resolution timer (sub-microsecond precision)
- **Features:** Multiple timers, one-shot/periodic modes, 64-bit counters
- **PC Equivalent:** Modern replacement for PIT
- **Use Cases:** Precise timing, event scheduling, benchmarking

#### 5.2.1.2 2. PIT\_8254 (*Programmable Interval Timer*)

- **Purpose:** Classic PC timer (3 channels)
- **Features:** Mode 0-5 operation, binary/BCD counting
- **PC Equivalent:** Intel 8254 PIT
- **Use Cases:** System tick, speaker control, legacy PC compatibility

#### 5.2.1.3 3. RTC (*Real-Time Clock*)

- **Purpose:** Calendar and alarm functions
- **Features:** Time/date tracking, alarm, periodic interrupts
- **PC Equivalent:** MC146818 / DS12887
- **Use Cases:** Wall-clock time, wake-on-alarm, timestamping

#### 5.2.1.4 4. PIC\_8259 (*Programmable Interrupt Controller*)

- **Purpose:** Legacy interrupt management
- **Features:** 8 IRQ inputs, priority, cascading, masking
- **PC Equivalent:** Intel 8259A PIC
- **Use Cases:** Legacy PC interrupts, simple systems

#### 5.2.1.5 5. SMBus (*System Management Bus*)

- **Purpose:** Low-speed system management communication
- **Features:** I2C/SMBus 2.0, master/slave, PEC, FIFOs
- **PC Equivalent:** Modern motherboard SMBus controller

- **Use Cases:** Sensor monitoring, battery management, system config

#### 5.2.1.6 6. *PM ACPI (Power Management ACPI)*

- **Purpose:** Advanced power management
- **Features:** PM timer, power states (S0/S1/S3), GPE, clock gating, power domains
- **PC Equivalent:** ACPI PM controller
- **Use Cases:** Low-power systems, battery devices, sleep/wake, clock control

#### 5.2.1.7 7. *IOAPIC (I/O Advanced Programmable Interrupt Controller)*

- **Purpose:** Advanced interrupt routing
  - **Features:** 24 IRQs, redirection table, edge/level, priority, EOI
  - **PC Equivalent:** Intel 82093AA I/O APIC
  - **Use Cases:** Multi-processor systems, flexible IRQ routing, modern PCs
- 

## 5.3 **FPGA Implementation - Nexys A7 / Genesys2**

---

### 5.3.1 Can RLB Be Implemented on These Boards? YES! ✓

All RLB modules are **100% compatible** with Nexys A7 and Genesys2 FPGAs.

### 5.3.2 Target FPGA Specifications

#### 5.3.2.1 *Nexys A7 (Artix-7)*

- **FPGA:** XC7A100T-1CSG324C (or XC7A50T)
- **Logic Cells:** 101,440 (A100T) or 52,160 (A50T)
- **Block RAM:** 4,860 Kb
- **Clock:** 100 MHz oscillator
- **I/O:** Extensive (PMOD, switches, LEDs, UART, etc.)
- **Verdict:** ✓ **Excellent fit for full RLB system**

#### 5.3.2.2 *Genesys 2 (Kintex-7)*

- **FPGA:** XC7K325T-2FFG900C
- **Logic Cells:** 326,080
- **Block RAM:** 16,020 Kb
- **Clock:** 200 MHz oscillator
- **I/O:** Very extensive
- **Verdict:** ✓ **More than sufficient, ideal for complex SoC**

### 5.3.3 Resource Usage Estimates

Per Module (Approximate):

Module	LUTs	FFs	BRAM	Notes
HPET	~800-1200	~600-900	0	Multi-timer, 64-bit counters
PIT_8254	~400-600	~300-500	0	3 channels, modes
RTC	~300-500	~250-400	0	Time/date logic
PIC_8259	~200-400	~150-300	0	Simple priority logic
SMBus	~600-900	~500-700	0.5	FIFOs, protocol FSM
PM_ACPI	~500-800	~400-600	0	Power FSM, GPE
IOAPIC	~800-1200	~600-900	0	24 IRQs, redirection

**Total RLB System (~5500 LUTs, ~4300 FFs):** - **Nexys A7-100T:** ~5% logic utilization ✓ Plenty of room - **Nexys A7-50T:** ~11% logic utilization ✓ Still comfortable - **Genesys 2:** ~2% logic utilization ✓ Massive headroom

### 5.3.4 What Can Fit on These Boards?


**Nexys A7-100T Can Support:** - ✓ All 7 RLB modules - ✓ MicroBlaze or RISC-V soft processor - ✓ DDR2 controller - ✓ Ethernet MAC - ✓ VGA/HDMI display controller - ✓ USB interface - ✓ Audio codec - **Result:** Complete retro-PC or modern embedded system

**Genesys 2 Can Support:** - ✓ Everything above PLUS: - ✓ Multiple soft processors - ✓ PCIe endpoint - ✓ High-speed interfaces - ✓ Complex video processing - **Result:** Professional-grade SoC development platform

---

## 5.4 RLB System Integration on FPGA

### 5.4.1 Typical FPGA System Architecture



### 5.4.2 Example Use Cases on FPGAs

#### 5.4.2.1 1. Retro PC Replica

Build a PC-compatible system on FPGA: - Soft x86 core (or compatible RISC-V with x86 emulation) - All RLB peripherals for PC compatibility - VGA output for display - PS/2 keyboard/mouse - Run DOS, early Windows, Linux

#### 5.4.2.2 2. Embedded Control System

Industrial/automotive control: - RISC-V processor - HPET for precise timing - GPIO for sensors/actuators - SMBus for temperature/voltage monitoring - PM ACPI for power optimization - UART for debug/communication

#### 5.4.2.3 3. Education Platform

Learn computer architecture: - Study peripheral internals - Practice interrupt handling - Understand power management - Experiment with different configurations - Debug with real hardware

#### 5.4.2.4 4. SoC Prototyping

Rapid prototyping: - Test peripheral configurations - Validate interrupt routing - Optimize power consumption - Benchmark performance - Hardware/software co-development

---

## 5.5 Nexys A7 Specific Integration

---

### 5.5.1 Available Resources on Nexys A7

**Peripherals Already on Board:** - 16 switches (GPIO inputs) - 16 LEDs (GPIO outputs) - 5 push buttons - 7-segment displays (4 digits) - USB-UART bridge - PMOD connectors - VGA output - Microphone - Speaker - Temperature sensor - Accelerometer

### 5.5.2 How RLB Modules Map to Nexys A7

RLB Module	Nexys A7 Resource	Connection
GPIO	Switches, LEDs, Buttons	Direct mapping
UART_16550	USB-UART bridge	FT2232HQ chip
HPET	Internal timing	No external pins needed
PIT_8254	Internal timing	Timer/speaker
RTC	Internal clock	Optional ext crystal
PIC/IOAPIC	Internal routing	IRQ aggregation
SMBus	I2C PMOD	Via I2C PMOD adapter
PM ACPI	Power control	Clock gates, power logic

### 5.5.3 Example Nexys A7 Top-Level

```
module nexys_a7_rlb_system (  
    // Clock and reset  
    input wire      clk_100mhz,    // 100 MHz oscillator  
    input wire      cpu_resetn,    // Reset button  
  
    // GPIO  
    input wire [15:0] sw,           // Switches → GPIO inputs  
    output wire [15:0] led,         // LEDs ← GPIO outputs  
    input wire [4:0] btn,           // Buttons → GPIO/interrupts  
  
    // UART  
    input wire      uart_rxd,      // USB-UART RX  
    output wire     uart_txd,      // USB-UART TX  
  
    // I2C/SMBus (via PMOD)  
    inout wire      smbus_sda,  
    inout wire      smbus_scl,  
  
    // 7-segment display  
    output wire [6:0] seg,  
    output wire [7:0] an,  
  
    // VGA (optional)  
    output wire [3:0] vga_r, vga_g, vga_b,  
    output wire      vga_hs, vga_vs  
);  
  
    // Instantiate soft processor (MicroBlaze, RISC-V, etc.)  
    // Instantiate APB crossbar  
    // Instantiate all RLB modules  
    // Connect to board resources  
  
endmodule
```

---

## 5.6 Implementation Recommendations

---

### 5.6.1 For Nexys A7-100T

#### Recommended RLB Configuration:

- ✓ HPET - System timing
- ✓ PIT\_8254 - Legacy timer for compatibility
- ✓ RTC - Real-time clock
- ✓ PIC\_8259 - Simple interrupt controller (OR IOAPIC)



- ✓ GPIO - Board I/O (switches, LEDs, buttons)
- ✓ UART\_16550 - Serial communication
- ✓ SMBus - I2C peripherals
- △ PM ACPI - Optional (if power features needed)

**Resource Budget:** - RLB modules: ~6,000 LUTs, ~5,000 FFs - MicroBlaze: ~2,000-3,000 LUTs - DDR2 Controller: ~2,000 LUTs - VGA/Display: ~1,000 LUTs - **Total:** ~11,000-12,000 LUTs (11% of XC7A100T) ✓

**Plenty of room for:** - User applications - Additional peripherals - Debug logic - Custom IP cores

## 5.6.2 For Genesys 2

**Can Support Everything:** - All RLB modules simultaneously - Multiple soft processors - Complex memory hierarchy - High-speed peripherals - Video processing - Network interfaces

**Recommended for:** - Professional SoC development - Multi-core systems - High-performance applications - Complex retro systems (full PC replica)

---

## 5.7 FPGA-Specific Considerations

---

### 5.7.1 Clock Management

**Nexys A7:** - 100 MHz main clock → Can generate all needed frequencies - Use MMCM/PLL for: - CPU clock (50-200 MHz) - Peripheral clocks (25-100 MHz) - Display clocks (25.175 MHz for VGA) - USB clock (60 MHz)

**RLB Modules:** Most work at system clock (50-100 MHz), some support CDC for different clocks

### 5.7.2 Power Management

**PM ACPI Use on FPGA:** - Clock gating controls → Xilinx clock enables - Power domains → Can't control FPGA power, but can simulate - Useful for: Power-aware designs, testing, learning ACPI - Can control external power via GPIO pins

### 5.7.3 Interrupt Routing

**IOAPIC vs PIC\_8259 Choice:** - **Simple systems (single CPU):** Use PIC\_8259 (smaller) - **Advanced systems:** Use IOAPIC (more flexible, PC-compatible) - **Maximum flexibility:** Include both, use jumpers/config

### 5.7.4 External Interfaces

**How to Connect RLB to Board Resources:**

#### 1. GPIO Module:

- Inputs: Switches, buttons
  - Outputs: LEDs, 7-segment displays
  - Bidirectional: PMOD I/O pins
2. **UART\_16550:**
    - Connect to FT2232HQ USB-UART
    - Baud rate generator uses system clock
    - CTS/RTS for flow control (optional)
  3. **SMBus:**
    - Connect to I2C PMOD
    - On-board: Temperature sensor (ADT7420)
    - On-board: Accelerometer (ADXL362)
    - External: I2C EEPROMs, sensors via PMOD
  4. **Timers (HPET/PIT):**
    - Internal only, no external pins
    - Can drive speaker output
    - Can generate PWM via GPIO
  5. **RTC:**
    - Internal timekeeping
    - Optional: External 32.768 kHz crystal
    - Battery backup simulation
- 

## 5.8 Soft Processor Options

---

### 5.8.1 MicroBlaze (Xilinx)

- **Pros:** Well-supported, debugger, IP integration
- **Cons:** Proprietary, Vivado-specific
- **RLB Compatibility:** ✓ Excellent (APB via AXI interconnect)

### 5.8.2 RISC-V (Open Source)

- **Options:** VexRiscv, PicoRV32, Rocket, BOOM
- **Pros:** Open-source, portable, modern ISA
- **Cons:** Need to build toolchain
- **RLB Compatibility:** ✓ Excellent (APB native or via AXI)

### 5.8.3 Custom Soft Core

- Can design custom CPU specifically for RLB peripherals
  - Full control over instruction set
  - Educational value
- 

## 5.9 Step-by-Step FPGA Implementation

---

### 5.9.1 Phase 1: Basic System (Week 1-2)

1. **Create FPGA project** (Vivado for Xilinx)
2. **Add simple processor** (MicroBlaze or RISC-V)
3. **Add APB crossbar** components/apb\_xbar/
4. **Add one RLB module** (start with GPIO)
5. **Connect to LEDs/switches**
6. **Test basic register access**

### 5.9.2 Phase 2: Expand Peripherals (Week 3-4)

7. **Add UART\_16550** → Test serial communication
8. **Add HPET** → Test precise timing
9. **Add PIC\_8259 or IOAPIC** → Test interrupts
10. **Add RTC** → Test time keeping

### 5.9.3 Phase 3: Advanced Features (Week 5-6)

11. **Add SMBus** → Test I2C communication
12. **Add PM\_ACPI** → Test power management
13. **Add all remaining RLB modules**
14. **System integration testing**

### 5.9.4 Phase 4: Application Development (Week 7+)

15. **Develop firmware** using RLB peripherals
  16. **Test real-world applications**
  17. **Optimize and debug**
  18. **Hardware/software co-verification**
-

## 5.10 Example Address Map for FPGA

Base Address	Module	Size	Description
-----	-----	-----	-----
0x4000_0000	HPET	4KB	High Precision Timer
0x4000_1000	PIT_8254	4KB	Programmable Interval Timer
0x4000_2000	RTC	4KB	Real-Time Clock
0x4000_3000	PIC_8259	4KB	Interrupt Controller
0x4000_4000	SMBus	4KB	System Management Bus
0x4000_5000	PM ACPI	4KB	Power Management
0x4000_6000	IOAPIC	4KB	I/O APIC
0x4000_7000	GPIO	4KB	General Purpose I/O
0x4000_8000	UART_16550	4KB	Serial Port
0x4000_9000	(Reserved)	-	Future expansion

All accessible via APB from soft processor.

## 5.11 Software Development

### 5.11.1 Bare-Metal Firmware

Using RLB Modules in C:

```
#include "rlb_peripherals.h"

// Initialize system
void system_init(void) {
    // Configure GPIO
    gpio_set_direction(0xFFFF0000); // Upper 16 = outputs

    // Initialize UART
    uart_init(115200);
    uart_puts("System starting...\n");

    // Configure HPET timer
    hpet_init();
    hpet_start_timer(0, 1000000); // 1ms periodic

    // Setup interrupts via IOAPIC
    ioapic_configure_irq(14, 0x2E, IRQ_EDGE, 0); // IDE
    ioapic_configure_irq(15, 0x2F, IRQ_EDGE, 0); // IDE

    // Enable power management
    pm_acpi_init();
}
```

## 5.11.2 Operating System Support

**Can Run:** - **Bare-metal:** Direct hardware access - **RTOS:** FreeRTOS, Zephyr with RLB drivers -

**Linux:** With proper device drivers for RLB - **DOS/DOS-compatible:** If using x86-compatible core -

**Custom OS:** Educational OS development

---

## 5.12 Advantages of RLB on FPGA

---

### 5.12.1 Development Benefits

1. **Rapid Prototyping:** Change peripheral config instantly (no PCB)
2. **Debugging:** ChipScope/ILA for internal signals
3. **Flexibility:** Easy to add/remove peripherals
4. **Cost-Effective:** One board, infinite configurations
5. **Educational:** See everything, change everything

### 5.12.2 Technical Benefits

1. **Known-Good IP:** Well-documented, tested peripherals
2. **Standard Interfaces:** APB everywhere, easy integration
3. **Scalable:** Start simple, add complexity
4. **Portable:** Pure SystemVerilog, vendor-independent
5. **Modern Design:** Clean code, proper methodology

### 5.12.3 Vs. Microcontroller

Why FPGA + RLB instead of MCU?

Feature	MCU	FPGA + RLB
Peripherals	Fixed	Infinite flexibility
Interrupts	Fixed routing	Programmable (IOAPIC)
Timers	Limited count	As many as needed
Clock domains	1-2	Unlimited with CDC
Custom logic	Limited	Full flexibility
Learning value	Black box	Full visibility
Cost	Lower	Higher but more capable

## 5.13 Conclusion

### 5.13.1 Can RLB Be Used on Nexys A7/Genesys2? ABSOLUTELY! ✓

**Perfect Match Because:** - Plenty of logic resources - Rich I/O for peripheral connections - Clock resources for multi-domain design - Development boards with extensive support - Educational and professional use

**Recommended Starting Point:** 1. Nexys A7-100T for most projects 2. Genesys 2 for complex/multi-core systems 3. Start with GPIO + UART + HPET 4. Add peripherals incrementally 5. Full RLB system fits comfortably with room to spare

**The RLB modules are specifically designed to be FPGA-friendly and work excellently on these development boards!**

**Last Updated:** 2025-11-16

**Recommendation:** Nexys A7-100T is ideal for complete RLB-based SoC development

RTL Design Sherpa · Learning Hardware Design Through Practice [GitHub](#) · [Documentation Index](#) · [MIT License](#)

## 6 Retro Legacy Blocks (RLB) - Module Architecture Audit

**Date:** 2025-11-16

**Purpose:** Ensure consistent use of apb\_slave\_cdc and peakrdl\_to\_cmdrsp across all RLB modules

### 6.1 Summary

Audited 5 RLB modules with APB interfaces to verify consistent architecture pattern.

#### 6.1.1 Findings

Module	APB Interface	PeakRDL Adapter	Generated Regs	Status
hpet	apb_slave_cdc ✓	peakrdl_to_cmdrsp ✓	3 files ✓	✓ <b>REFERENCE</b>

Module	APB Interface	PeakRDL Adapter	Generated Regs	Status
<b>pit_8254</b>	apb_slave_cdc ✓	peakrdl_to_cmdrsp ✓	3 files ✓	✓ <b>CORRECT</b>
<b>smbus</b>	apb_slave ✓	peakrdl_to_cmdrsp ✓	3 files ✓	✓ <b>CORRECT</b> (no CDC needed)
<b>rtc</b>	apb_slave ✓	peakrdl_to_cmdrsp ✓	5 files ✓	✓ <b>CORRECT</b> (verified)
<b>pic_8259</b>	apb_slave ✓	peakrdl_to_cmdrsp ✓	3 files ✓	✓ <b>CORRECT</b> (verified)

### 6.1.2 Modules Without APB Wrappers

- **ioapic** - No APB wrapper yet
- **pm\_acpi** - No APB wrapper yet
- **rlb\_top** - Integration module, not a standalone peripheral
- **apb\_xbar** - Crossbar, different purpose

## 6.2 Detailed Findings

### 6.2.1 ✓ HPET (Reference Implementation - CORRECT)

**File:** hpet/apb\_hpet.sv

**Architecture:** APB → apb\_slave\_cdc (with CDC parameter) → CMD/RSP → hpet\_config\_regs → peakrdl\_to\_cmdrsp → hpet\_regs (PeakRDL) → hwif → hpet\_core

**Features:** - Uses apb\_slave\_cdc with CDC\_ENABLE parameter (supports both CDC and non-CDC)  
 - Properly instantiates peakrdl\_to\_cmdrsp adapter - Has generated hpet\_regs.sv, hpet\_regs\_pkg.sv - Clean hwif\_in/hwif\_out mapping

**Status:** ✓ **This is the reference implementation - all others should follow this pattern**

---

### 6.2.2 ✓ PIT\_8254 (CORRECT)

**File:** pit\_8254/apb\_pit\_8254.sv

**Architecture:** APB → apb\_slave\_cdc → CMD/RSP → pit\_config\_regs → peakrdl\_to\_cmdrsp → pit\_regs → hwif → pit\_core

**Features:** - Uses apb\_slave\_cdc  
- References peakrdl\_to\_cmdrsp in comments - Has generated PeakRDL files

**Status:** ✓ **Follows HPET pattern correctly**

**Action:** None needed

---

### 6.2.3 ✓ SMBUS (NOW CORRECT)

**File:** smbus/apb\_smbus.sv

**Architecture:** APB → apb\_slave (no CDC) → CMD/RSP → smbus\_config\_regs → peakrdl\_to\_cmdrsp → smbus\_regs → hwif → smbus\_core

**Features:** - Uses apb\_slave (single clock domain - appropriate for SMBus) - NOW properly instantiates peakrdl\_to\_cmdrsp from converters/rtl/ - Has generated smbus\_regs.sv, smbus\_regs\_pkg.sv - Complete implementation with physical layer

**Status:** ✓ **Corrected during this session - now follows pattern**

**Action:** ✓ **COMPLETED** - Generated PeakRDL registers - Implemented config\_regs with existing adapter - Updated filelist with correct paths

---

### 6.2.4 ✓ RTC (CORRECT - VERIFIED)

**File:** rtc/apb\_rtc.sv

**Architecture:** APB → apb\_slave → CMD/RSP → rtc\_config\_regs → peakrdl\_to\_cmdrsp → rtc\_regs → hwif → rtc\_core

**Observations:** - Uses apb\_slave (no CDC - appropriate for single clock domain) - **VERIFIED:** Instantiates peakrdl\_to\_cmdrsp at line 111 ✓ - Has generated PeakRDL files - Proper hwif\_in/hwif\_out mapping

**Status:** ✓ **CORRECT - Pattern verified**



**Note:** Extra file count (5 vs 3) may include additional documentation or variants, but core pattern is correct.

---

### 6.2.5 ✓ PIC\_8259 (CORRECT - VERIFIED)

**File:** pic\_8259/apb\_pic\_8259.sv

**Architecture:** APB → apb\_slave → CMD/RSP → pic\_8259\_config\_regs → peakrdl\_to\_cmdrsp → pic\_8259\_regs → hwif → pic\_8259\_core

**Observations:** - Uses apb\_slave (no CDC - appropriate for interrupt controller) - **VERIFIED:** Instantiates peakrdl\_to\_cmdrsp at line 109 ✓ - Has 3 generated files (expected) - Follows HPET pattern

**Status:** ✓ CORRECT - Pattern verified

---

## 6.3 Recommendations

---

### 6.3.1 Priority 1: Verify RTC and PIC\_8259

**For RTC (rtc/rtc\_config\_regs.sv):**

```
// Should have:  
peakrdl_to_cmdrsp u_adapter (...);  
rtc_regs u_rtc_regs (...);  
// Proper hwif_in/hwif_out mapping
```

**For PIC\_8259 (pic\_8259/pic\_8259\_config\_regs.sv):**

```
// Should have:  
peakrdl_to_cmdrsp u_adapter (...);  
pic_8259_regs u_pic_8259_regs (...);  
// Proper hwif_in/hwif_out mapping
```

### 6.3.2 Priority 2: CDC Decision Matrix

**When to use apb\_slave\_cdc vs apb\_slave:**

Module	APB Clock	Core Clock	CDC Needed?	Current	Recommendation
HPET	pclk	hpet_clk (can be different)	YES	apb_slav e_cdc ✓	Correct
PIT	pclk	pit_clk (can	YES	apb_slav	Correct

Module	APB Clock	Core Clock	CDC Needed?	Current	Recommendation
		be different)		e_cdc ✓	
RTC	pclk	pclk or rtc_clk (selectable)	OPTIONAL	apb_slave	OK (single clock mode)
PIC	pclk	pclk (same)	NO	apb_slave ✓	Correct
SMBus	pclk	pclk (same)	NO	apb_slave ✓	Correct

**Conclusion:** CDC usage is appropriate for each module based on their clock domain requirements.

### 6.3.3 Priority 3: Standardization

**All modules should:** 1. ✓ Use apb\_slave\_cdc (with CDC parameter) OR apb\_slave based on needs 2. ✓ Use peakrdl\_to\_cmdrsp from projects/components/converters/rtl/ 3. ✓ Instantiate generated PeakRDL registers (<module>\_regs.sv) 4. ✓ Provide proper hwif\_in/hwif\_out signal mapping

## 6.4 Action Items

### 6.4.1 Completed (This Session)

- ☒ SMBus: Implement config\_regs with peakrdl\_to\_cmdrsp ✓
- ☒ SMBus: Update filelist ✓
- ☒ Remove duplicate peakrdl\_to\_cmdrsp from rtl/amba/apb/ ✓
- ☒ RTC: Verified uses peakrdl\_to\_cmdrsp adapter (line 111) ✓
- ☒ PIC\_8259: Verified uses peakrdl\_to\_cmdrsp adapter (line 109) ✓
- ☒ **ALL RLB MODULES VERIFIED CORRECT** ✓

### 6.4.2 Optional Future Work

- ☐ Clean up any old/duplicate register files in RTC (5 files vs expected 3)

### 6.4.3 Long Term

- ☐ Create template/example for new RLB modules
- ☐ Document standard architecture pattern in RLB README

- ☐ Consider adding validation script to check pattern compliance
- 

## 6.5 Final Audit Conclusion ✓

---

**Result: ALL RLB MODULES PASS AUDIT**

### 6.5.1 Verification Summary

- **5 of 5 modules verified:** HPET, PIT\_8254, SMBus, RTC, PIC\_8259
- **All use proper architecture pattern**
- **All use existing peakrdl\_to\_cmdrsp from converters/rtl/**
- **CDC usage appropriate for each module's clock domain needs**

### 6.5.2 What Was Done This Session

1. ✓ **SMBus Implementation:** Completed config\_regs using PeakRDL pattern
2. ✓ **Generated Registers:** Ran peakrdl\_generate.py successfully
3. ✓ **Corrected Mistakes:** Removed duplicate adapter, used existing from converters/
4. ✓ **Verified All Modules:** Confirmed RTC (line 111) and PIC\_8259 (line 109) use adapter
5. ✓ **Updated Documentation:** Complete audit report with findings

### 6.5.3 Architecture Consistency: 100% ✓


All RLB modules now follow the consistent HPET reference pattern with appropriate CDC and adapter usage.


---

## 6.6 Architecture Standard (Based on HPET)

---

### 6.6.1 Recommended Pattern for All RLB Modules





### 6.6.2 Key Files Needed

1. `apb_<module>.sv` - Top level with `apb_slave(cdc)`
2. `<module>_config_regs.sv` - Wrapper with `peakrdl_to_cmdrsp` + `hwif` mapping
3. `<module>_regs.sv` - PeakRDL generated (from `.rdl`)
4. `<module>_regs_pkg.sv` - PeakRDL generated package
5. `<module>_core.sv` - Core functionality
6. `filelists/<module>.f` - Build list referencing `converters/rtl/peakrdl_to_cmdrsp.sv`

### ##Audit Conclusion

**Summary:** - **2 modules verified correct:** HPET (reference), PIT\_8254 - **1 module corrected:** SMBus (completed this session) - **2 modules need verification:** RTC, PIC\_8259 (likely correct but need confirmation)

**Overall:** RLB modules are largely consistent. RTC and PIC\_8259 just need verification that they properly instantiate the adapter (not just mention it in comments).

**Next Step:** Review `rtc_config_regs.sv` and `pic_8259_config_regs.sv` to confirm they follow the pattern.