

✓ Congratulations! You passed!

[Next Item](#)



1. What is the "cache" used for in our implementation of forward propagation and backward propagation?

1 / 1
point



We use it to pass variables computed during forward propagation to the corresponding backward propagation step. It contains useful values for backward propagation to compute derivatives.

Correct

Correct, the "cache" records values from the forward propagation units and sends it to the backward propagation units because it is needed to compute the chain rule derivatives.



It is used to cache the intermediate values of the cost function during training.



We use it to pass variables computed during backward propagation to the corresponding forward propagation step. It contains useful values for forward propagation to compute activations.



It is used to keep track of the hyperparameters that we are searching over, to speed up computation.



2. Among the following, which ones are "hyperparameters"? (Check all that apply.)

1 / 1
point



learning rate α

Correct



weight matrices $W^{[l]}$

Un-selected is correct



size of the hidden layers $n^{[l]}$

Correct



activation values $a^{[l]}$

Un-selected is correct



number of layers L in the neural network

Correct



bias vectors $b^{[l]}$

Un-selected is correct



number of iterations

Correct



3. Which of the following statements is true?

1 / 1
point



The deeper layers of a neural network are typically computing more complex features of the input than the earlier layers.

Correct



The earlier layers of a neural network are typically computing more complex features of the input than the deeper layers.



4. Vectorization allows you to compute forward propagation in an L -layer neural network without an explicit for-loop (or any other explicit iterative loop) over the layers $l=1, 2, \dots, L$. True/False?

1 / 1
point



True



False

Correct

Forward propagation propagates the input through the layers, although for shallow networks we may just write all the lines ($a^{[2]} = g^{[2]}(z^{[2]})$, $z^{[2]} = W^{[2]}a^{[1]} + b^{[2]}$, ...). In a deeper network, we cannot avoid a for loop iterating over the layers: ($a^{[l]} = g^{[l]}(z^{[l]})$, $z^{[l]} = W^{[l]}a^{[l-1]} + b^{[l]}$, ...).



5. Assume we store the values for $n^{[l]}$ in an array called layers, as follows: `layer_dims = [n_x, 4, 3, 2, 1]`. So layer 1 has four hidden units, layer 2 has 3 hidden units and so on. Which of the following for-loops will allow you to initialize the parameters for the model?

1 / 1
point



```
1 * for(i in range(1, len(layer_dims)/2)):  
2   parameter['W' + str(i)] = np.random.randn(layers[i], layers[i-1]) * 0.01  
3   parameter['b' + str(i)] = np.random.randn(layers[i], 1) * 0.01
```



```
1 * for(i in range(1, len(layer_dims)/2)):  
2   parameter['W' + str(i)] = np.random.randn(layers[i], layers[i-1]) * 0.01  
3   parameter['b' + str(i)] = np.random.randn(layers[i-1], 1) * 0.01
```



```
1 * for(i in range(1, len(layer_dims))):  
2   parameter['W' + str(i)] = np.random.randn(layers[i-1], layers[i]) * 0.01  
3   parameter['b' + str(i)] = np.random.randn(layers[i], 1) * 0.01
```



```
1 * for(i in range(1, len(layer_dims))):  
2   parameter['W' + str(i)] = np.random.randn(layers[i], layers[i-1]) * 0.01  
3   parameter['b' + str(i)] = np.random.randn(layers[i], 1) * 0.01
```


Correct



Consider the following neural network

6. Consider the following neural network.

1 / 1
point



How many layers does this network have?

- The number of layers L is 4. The number of hidden layers is 3.

Correct

Yes. As seen in lecture, the number of layers is counted as the number of hidden layers + 1. The input and output layers are not counted as hidden layers.

- The number of layers L is 3. The number of hidden layers is 3.
- The number of layers L is 4. The number of hidden layers is 4.
- The number of layers L is 5. The number of hidden layers is 4.

✓

1 / 1
point

7. During forward propagation, in the forward function for a layer l you need to know what is the activation function in a layer (Sigmoid, tanh, ReLU, etc.). During backpropagation, the corresponding backward function also needs to know what is the activation function for layer l , since the gradient depends on it. True/False?

- True

Correct

Yes, as you've seen in the week 3 each activation has a different derivative. Thus, during backpropagation you need to know which activation was used in the forward propagation to be able to compute the correct derivative.

- False

✓

1 / 1
point

8. There are certain functions with the following properties:

(i) To compute the function using a shallow network circuit, you will need a large network (where we measure size by the number of logic gates in the network), but (ii) To compute it using a deep network circuit, you need only an exponentially smaller network. True/False?

- True


Correct


- False

✓

1 / 1
point

9. Consider the following 2 hidden layer neural network:





Which of the following statements are True? (Check all that apply).

$W^{[1]}$ will have shape (4, 4)

Correct

Yes. More generally, the shape of $W^{[l]}$ is $(n^{[l]}, n^{[l-1]})$.

$b^{[1]}$ will have shape (4, 1)

Correct

Yes. More generally, the shape of $b^{[l]}$ is $(n^{[l]}, 1)$.

$W^{[1]}$ will have shape (3, 4)

Un-selected is correct

$b^{[1]}$ will have shape (3, 1)

Un-selected is correct

$W^{[2]}$ will have shape (3, 4)

Correct

Yes. More generally, the shape of $W^{[l]}$ is $(n^{[l]}, n^{[l-1]})$.

$b^{[2]}$ will have shape (1, 1)

Un-selected is correct

$W^{[2]}$ will have shape (3, 1)

Un-selected is correct

$b^{[2]}$ will have shape (3, 1)

Correct

Yes. More generally, the shape of $b^{[l]}$ is $(n^{[l]}, 1)$.

$W^{[3]}$ will have shape (3, 1)

Un-selected is correct

$b^{[3]}$ will have shape (1, 1)

Correct

Yes. More generally, the shape of $b^{[l]}$ is $(n^{[l]}, 1)$.

$W^{[3]}$ will have shape (1, 3)

Correct

Yes. More generally, the shape of $W^{[l]}$ is $(n^{[l]}, n^{[l-1]})$.

$b^{[3]}$ will have shape (3, 1)

Un-selected is correct



10. Whereas the previous question used a specific network, in the general case what is the dimension of $W^{[l]}$, the weight matrix associated with layer l ?

1 / 1
point

- $W^{[l]}$ has shape $(n^{[l]}, n^{[l+1]})$
- $W^{[l]}$ has shape $(n^{[l-1]}, n^{[l]})$
- $W^{[l]}$ has shape $(n^{[l+1]}, n^{[l]})$
- $W^{[l]}$ has shape $(n^{[l]}, n^{[l-1]})$

Correct

True

