

# A6\_Exercises

Kwon do yun

2021-01-25

## 차 례

implementation basic (P. 4) . . . . .	2
implementation for (P. 5) . . . . .	2
implementation time (P. 9) . . . . .	2
Convergence trajectory . . . . .	3

### implementation basic (P. 4)

```
import numpy as np
np.random.seed(1234)
MC_N = 10**3
x = np.random.uniform(0,1,MC_N)*2-1
y = np.random.uniform(0,1,MC_N)*2-1
t = np.sqrt(x**2+y**2)
pi_hat = 4*sum(t<=1)/MC_N
print(pi_hat)
```

```
## 3.06
```

### implementation for (P. 5)

```
import numpy as np
np.random.seed(1234)
MC_N = 10**6
count = 0
for MC_i in range(MC_N):
    x_i = np.random.uniform(0, 1) * 2 - 1
    y_i = np.random.uniform(0, 1) * 2 - 1
    t_i = np.sqrt(x_i**2+y_i**2)
    if t_i <=1:
        count = count+1
pi_hat = 4*count/MC_N
print(pi_hat)
```

```
## 3.140204
```

### implementation time (P. 9)

```
import numpy as np
from time import time
np.random.seed(1234)
beg_time = time()
old_est = 0
n = 1
MC_N = 10**6
while True:
    x_i = np.random.uniform(0, 1) * 2 - 1
```

```

y_i = np.random.uniform(0, 1) * 2 - 1
t_i = np.sqrt(x_i**2+y_i**2)
A_n = 4*(t_i<=1)
new_est = ((n-1)/n)*old_est + (1/n)*A_n
if(n>MC_N):
    break
n = n+1
old_est = new_est
end_time = time()
print(new_est)

```

```
## 3.1402048597951002
```

```
print('Time difference of ',end_time-beg_time, 'secs')
```

```
## Time difference of 7.615655899047852 secs
```

## Convergence trajectory

```

import numpy as np
import matplotlib.pyplot as plt
np.random.seed(1234)
old_est = 0
n = 1
MC_N = 10**6
results = np.repeat(0,MC_N+1).astype('float')
while True:
    x_i = np.random.uniform(0, 1) * 2 - 1
    y_i = np.random.uniform(0, 1) * 2 - 1
    t_i = np.sqrt(x_i**2+y_i**2)
    A_n = 4*(t_i<=1)
    new_est = ((n-1)/n)*old_est + (1/n)*A_n
    results[n] = new_est
    if(n>=MC_N):
        break
    n = n+1
    old_est = new_est

```

```


plt.plot(results[1:21],marker='o')
plt.xlabel('Index')

```

```
plt.ylabel('results[0:20]')
plt.xticks([5,10,15,20])
```

```
## ([<matplotlib.axis.XTick object at 0x0000000020F22710>, <matplotlib.axis.XTick object at 0x00000000276D2D68>]
```


```
plt.show()
```



```
plt.plot(results[1001:1021],marker='o')
plt.xlabel('Index')
plt.ylabel('results[1000:1020]')
plt.xticks([5,10,15,20])
```

```
## ([<matplotlib.axis.XTick object at 0x0000000027932668>, <matplotlib.axis.XTick object at 0x000000002784D358>]
```


```
plt.show()
```



```
plt.plot(results[100000:100021],marker='o')
plt.xlabel('Index')
plt.ylabel('results[100000:100020]')
plt.xticks([5,10,15,20])
```

```
## ([<matplotlib.axis.XTick object at 0x0000000027AA7A58>, <matplotlib.axis.XTick object at 0x0000000027AA75F8>]
```

```
plt.show()
```



"A6\_Exercises"