

-K1237-5 #12 FASTENER INTO FULL HEIGHT RIB STIFFENER

(TYPICAL BOTH SIDES)

CAULK WELL WITH K1115P

INSTALLING CLIP.

K1115P CAULK

SILL PANEL

VOGT POWER INTERNATIONAL

V17494-BEXD-5066-02

06-Aug-2016

K1237-5 #12 FASTENERS-THRU PANEL RIB INTO RIB

STIFFENER 0 1'-0" C/C (TYP. BOTH SIDES)

CAULK, BOTH SIDES BEFORE

FULL HEIGHT RIB STIFFENER

(IF APPLICABLE)

PANEL

1). WALL OPENING KITS FOR CUSTOMER SUPPLIED ACCESSORIES

MUST BE FIELD LOCATED, CUT AND FLASHED UNLESS PRIOR

ARRANGEMENTS ARE MADE WITH PARKLINE. FOR FACTORY

CUTTING OF THESE OPENINGS, THE EXACT LOCATION AND

2). FOR NON STANDARD WIDTH WALL OPENING KITS STOCK

FINISHED OPENING SIZES MUST BE PROVIDED TO PARKLINE.

LENGTH PANEL CONNECTORS, 'Z' FLASHING FILLER AND SILL CAPS MUST BE FIELD CUT TO FIT OPENING.

3). ON WALL OPENING KITS WIDER THAN 4'-0" THE 1099A TOP

FILLER WILL NEED TO BE SPLICED AND/OR CUT USING

WALL PANEL

FIELD CUT PANEL RIB AS REQUIRED

(SEE NOTE #2)

End Enclosure-Basic Wall Opening Kit Details

STOCK LENGTH FILLERS.

SILL PANEL

NOTES: