

Visual Trajectory Prediction via 3D Agent Queries


Junru Gu^{1*} Chenxu Hu^{1*} Tianyuan Zhang^{2,3} Xuanyao Chen^{2,4}
 Yilun Wang⁵ Yue Wang⁶ Hang Zhao^{1,2†}

¹IIS, Tsinghua University ²Shanghai Qi Zhi Institute


³CMU ⁴Fudan University ⁵Li Auto ⁶MIT

<https://tsinghua-mars-lab.github.io/ViP3D/>

nuScenes



Traditional Perception and Prediction Pipeline



- Perceive agents and predict their behaviors.
- Separate modules
 - Lost useful information
 - Error accumulation


End-to-end models

LiDAR-based: IntenNet / FaF / PnPNet

Drawbacks:

- (1) no rich information from cameras
- (2) convolutional feature map, suffering from non-differentiable operations (ex: NMS in detection, object association in tracking)

Visual Trajectory Prediction via 3D Agent Queries



- Vision-based, fully differentiable
- Interpretable and High performance

nuScenes

Related Work: Trajectory Prediction


- GNNs
- Transformers
- Modeling [uncertainty](#) using latent variables
- [Goal-based](#) methods: predicting the intention first
 - Predict trajectory conditioning on these goals.

[End-to-End](#) Perception and Prediction

- Jointly optimizing detection, tracking, and prediction
- FaF, IntentNet, PnPNet
- Rely on [BEV](#) feature maps or heatmaps, leading to unavoidable non-differentiable operation

Tracked agent queries

Feature Pyramid Networks, FPN



3DETR: An End-to-End Transformer Model for 3D Object Detection

DETR3D: 3D Object Detection from Multi-view Images via 3D-to-2D Queries

Yue Wang

Massachusetts Institute of Technology
yuewang@csail.mit.edu

Vitor Guizilini*

Toyota Research Institute
vitor.guizilini@tri.global

Tianyuan Zhang*

Carnegie Mellon University
tianyuaz@andrew.cmu.edu

Yilun Wang

Li Auto
yilunw@cs.stanford.edu

Hang Zhao ¶

Tsinghua University
hangzhao@mail.tsinghua.edu.cn

Justin Solomon ¶

Massachusetts Institute of Technology
jsolomon@mit.edu

<https://github.com/WangYueFt/detr3d>

