

Example 03

What's your favorite food?

☐ Pizza ☐ Hamburgers ☐ Twinkies ☒ All of the Above ☐ I don't eat food, I'm a robot.

This example shows how to get the value of a radio button in a radio button group.

```
<h3>Example 03</h3>
<form action="#">
  <h2>What's your favorite food?</h2>
  <p>
    <input id="RBPizza" name="RGFood" type="radio" value ="Pizza"/>Pizza
    <input id="RBHamburgers" name="RGFood" type="radio" value="Hamburgers" />Hamburgers
    <input id="RBTwinkies" name="RGFood" type="radio" value="Twinkies" />Twinkies
    <input id="RBAAll" name="RGFood" type="radio" checked="checked"
      value="All of the Above"/>All of the Above
    <input id="RBRobot" name="RGFood" type="radio" value="You're a stinkin' robot."/>I
    don't eat food, I'm a robot.
  </p>
  <div id="DivMessage"></div>
  <input id="BtnFoodType" type="button" value="Get Food Type" onclick="GetFoodChoice();" />
  <input id="BtnReset" type="reset" value="Clear" onclick="ClearDiv('DivMessage');" />
</form>
```

```
<script type="text/javascript">

function GetFoodChoice() {
var myDiv = document.getElementById('DivMessage');
var message;
if (document.getElementById('RBPizza').checked)
    message = document.getElementById('RBPizza').value;
else if (document.getElementById('RBHamburgers').checked)
    message = document.getElementById('RBHamburgers').value;
else if (document.getElementById('RBTwinkies').checked)
    message = document.getElementById('RBTwinkies').value;
else if (document.getElementById('RBAAll').checked)
    message = document.getElementById('RBAAll').value;
else if (document.getElementById('RBRobot').checked)
    message = document.getElementById('RBRobot').value;
myDiv.innerHTML = message;
}

function ClearDiv(thisDiv) {
    var myDiv = document.getElementById(thisDiv);
    myDiv.innerHTML = "";
}

</script>
```