

I. 計算題(50 points) (所有題目必須有計算過程,否則不予計分)

-

3. (15 pts) As shown in Fig. 3, there are continuous charge distribution between line segment AB , CD , with density λ , and between the arc BC with density $-\lambda$. Apply the Coulomb's law to determine the direction and the magnitude of the electric field at point P on the z -axis. (Details of the calculation need to be presented in your answer)
4. (15 pts) A sphere of radius a located at $\vec{R}_0 = (0, 0, 3a)$ (Fig. 4) with charge density $\rho_s(\vec{r}') = \rho_0 \left(\frac{r'}{a} \right)^{3/2}$ where ρ_0 is a constant and r' is the distance to the center of the sphere. An infinite wide slab of thickness $2a$ with uniform volume charge density ρ_E is placed between $z = 0$ and $2a$.
- (a) (3 pts) What is the total charge Q in the sphere? (write your answers in terms of a and ρ_0 .)
- (b) (12 pts) Use Gauss's Law (you need to draw the Gaussian surfaces in your calculation to get full credits) find the electric fields (magnitude and direction) in the following cases
- (i) $\vec{r} = (0, 0, z)$, for $z > 4a$, $2a < z < 4a$, and $0 < z < 2a$. (ii) $\vec{r} = (2a, 0, 3a)$.

II. 選擇題 (51 points)

1. (5pts) As shown in Fig. 5, a point charge Q ($Q > 0$) is located at the origin, and an electric dipole \vec{p} is placed on the z -axis, with its dipole moment pointing in the $+z$ -direction. If the dipole \vec{p} is released to be free to move, which of the following statements is correct regarding the motion of the dipole soon after being released?




Fig. 5

- (A) The dipole will only rotate
- (B) The dipole will only drift in the $+z$ -direction.
- (C) The dipole will only drift in the $-z$ direction.
- (D) The dipole will rotate and drift in the $+z$ -direction.
- (E) The dipole will rotate and drift in the $-z$ -direction.

2. (5pts) As shown in Fig. 6, two positive point charges Q are placed on y-z plane with coordinates as indicated. A negative charge $-q$ located at $(x,0,0)$ is allowed to travel on the x-axis only. For the case that $x \ll a$, the total force acting on $-q$ can be expressed as $F_{total} \approx s \cdot kQq \cdot x/a^3$, which of the following is correct?




Fig. 6

- (A) $s \leq -4$ (B) $-4 < s \leq -2$ (C) $-2 < s \leq 0$ (D) $0 < s \leq 2$
 (E) $2 < s \leq 4$ (F) $4 < s$

3. (5 pts) There are three large plates with charge density σ_1 , σ_2 and σ_3 respectively. The potential is shown in Fig. 7. What is the ratio of the surface charge density $x = \sigma_3 / (\sigma_1 + \sigma_2)$ if an dielectric material ($\kappa = 4$) filled between $x=0$ and $x=2$?




Fig. 7


- (A) $x \leq -6$ (B) $-6 < x \leq -5$ (C) $-5 < x \leq -4$ (D) $-4 < x \leq -3$
 (E) $-3 < x \leq -2$ (F) $-2 < x \leq -1$ (G) $-1 < x \leq +1$
 (H) $+1 < x \leq +2$ (I) $+2 < x < +3$ (J) $+3 < x < +4$
 (K) $+4 < x < +5$ (L) $+5 < x < +6$ (M) $+6 < x$

4. (5 pts) Same as question 3, now we connect plates 1 and 2 by a wire. After the equilibrium reaches, what is the ratio of the surface charge density $x = \sigma_{2,new} / \sigma_3$? (use the same data of the multiple choices in question 3.)

5. (5 pts) A parallel plate capacitor is connected with a battery and allowed to charge up. Now a slab of dielectric material is placed between the plates of the capacitor while the capacitor is still connected to the battery. After this is done one would find out

- (A) The energy stored in the capacitor decreases. (B) The voltage across the capacitor increases.
 (C) The charge on the capacitor increases. (D) The charge on the capacitor does not change.

6. (5 pts) A closed cubic imaginary Gaussian surface is shown in Fig. 8. The surfaces of the cubic are labeled as S_R (right), S_L (left), S_{1-4} (top, front, bottom and back). A negative point charge, $-Q$, is located on the axis through the center of the right Gaussian surface (S_R) with a distance a . The electric flux through surfaces S_L and S_R is Φ_A . The electric flux through surfaces $S_1+S_2+S_3+S_4$ is Φ_B . Which statement below is correct?



- (A) $\Phi_A > 0, \Phi_B > 0, \Phi_A + \Phi_B = 0$ (B) $\Phi_A > 0, \Phi_B < 0, \Phi_A + \Phi_B = 0$ (C) $\Phi_A < 0, \Phi_B > 0, \Phi_A + \Phi_B = 0$
- (D) $\Phi_A < 0, \Phi_B < 0, \Phi_A + \Phi_B = 0$ (E) $\Phi_A > 0, \Phi_B > 0, \Phi_A + \Phi_B \neq 0$ (F) $\Phi_A > 0, \Phi_B < 0, \Phi_A + \Phi_B \neq 0$
- (J) $\Phi_A < 0, \Phi_B > 0, \Phi_A + \Phi_B \neq 0$ (K) $\Phi_A < 0, \Phi_B < 0, \Phi_A + \Phi_B \neq 0$

Multiple Choice Questions:


1	2	3	4	5	6	7	8	9	10
C	C	I	G	C	B	L	C	B	D
11	12	13							
H	F	F							

1. (10 pts). Two cylindrical shells consist of two shells have radii a , $4a$, and length L (Fig. 1 without the shaded area). The most inner shell ($r = a$) carries total charge Q and the outer shell ($r = 4a$) carries total charge $-Q$. Ignoring the end effects and express your answers in terms of the total charge Q , a , L , and/or any other constant.)

(a) (7 pts) Draw the Guassian surfaces and calculate the electric fields (both the direction and magnitude) and electric potential in the region $a \leq r < 4a$. (Assume $V(4a) = 0$.)

(b) (3 pts) Find out the capacitance of this cylinder ?

(a)



Choose surface S as the Gaussian surface.

$$\oint \vec{E} \cdot d\vec{A} = \frac{q_{in}}{\epsilon_0} \quad (1)$$

$$\Rightarrow E 2\pi r l = \frac{\lambda l}{\epsilon_0}$$

where $\lambda = \frac{Q}{L}$

$$\Rightarrow \vec{E} = \frac{\lambda}{2\pi\epsilon_0 r} \hat{r} \quad (2)$$

$$V(r) - V(4a) = - \int_r^{4a} \vec{E} \cdot d\vec{l} \quad (1)$$

$$V(r) = - \int_{4a}^r \frac{\lambda}{2\pi\epsilon_0 r} dr + V(4a)$$

$$= - \frac{\lambda}{2\pi\epsilon_0} \ln\left(\frac{r}{4a}\right) \quad (2)$$

(b)

$$C = \frac{Q}{|\Delta V|} \quad (1)$$

$$C = \frac{Q}{|V(4a) - V(a)|} = \frac{Q}{\frac{Q/L}{2\pi\epsilon_0} \ln 4}$$


$$= \frac{2\pi\epsilon L}{\ln 4} = \frac{\pi\epsilon L}{\ln 2} \quad (2)$$

2. (10 pts) 1. The capacitance of a parallel plate capacitor is C_0 with surface charge density σ_0 . Now a slab of dielectric material with dielectric constant K ($K = 5$) is inserted a distance xL into the space between the square parallel plates, as shown in Fig.2.

(A) (4 pts) Now we want the capacitor to be $3C_0$, how much distance xL should the material be inserted in?

(B) (6 pts) What is surface charge σ_1 , σ_2 and σ_{ind} in terms of σ_0 .

(a)



$$C = \frac{(1-x)L}{L} C_0 + K \frac{xL}{L} C_0 \quad (2)$$

$$3C_0 = (1-x)C_0 + 5 \cdot xC_0$$

$$x = \frac{1}{2} \quad (2)$$

(b)

The total electric field on the right:

$$(1) E_2 = E_{20} - E_{ind} \Rightarrow E_2 = \frac{\sigma_2}{\epsilon_0} - \frac{\sigma_{ind}}{\epsilon_0}$$

The property of dielectric material:

$$(1) E_2 = \frac{E_{20}}{K} \Rightarrow \frac{\sigma_2}{K} = \sigma_2 - \sigma_{ind}$$

$$\Rightarrow \sigma_{ind} = \sigma_2 \left(1 - \frac{1}{K} \right) = \frac{4}{5} \sigma_2$$

The voltage on the right and the left are the same.

$$(1) E_1 = E_2 = \frac{E_{20}}{K} \Rightarrow \sigma_2 = K \sigma_1$$

The total charge is unchanged in this case.


$$\sigma_0 \cdot A = \sigma_1 \cdot (1-x) \cdot A + \sigma_2 \cdot x \cdot A \quad (1)$$

$$\sigma_0 = (1-x)\sigma_1 + xK\sigma_1 = 3\sigma_1$$

$$\Rightarrow \sigma_1 = \frac{\sigma_0}{3}, \quad \sigma_2 = \frac{5\sigma_0}{3}, \quad \sigma_{ind} = \frac{4\sigma_0}{3} \quad (2)$$

$$\text{or } \sigma_1 = \frac{\sigma_0}{1+4x}, \quad \sigma_2 = \frac{5\sigma_0}{1+4x}, \quad \sigma_{ind} = \frac{4\sigma_0}{1+4x}$$

3.



For the field from segment AB,

$$dq = \lambda dx$$

$$d\vec{E} = \frac{k\lambda dx(-x, 0, z)}{\sqrt{x^2 + z^2}^3} \quad (2)$$

$$\vec{E}_{AB} = \int_{-2R}^{-R} \frac{k\lambda dx(-x, 0, z)}{\sqrt{x^2 + z^2}^3},$$

define $u \equiv x^2 + z^2$

$$\begin{aligned} E_{AB,x} &= \int_{-2R}^{-R} \frac{-k\lambda x dx}{\sqrt{x^2 + z^2}^3} = -\frac{k\lambda}{2} \int_{4R^2+z^2}^{R^2+z^2} \frac{du}{\sqrt{u}^3} \\ &= -\frac{k\lambda}{2} (-2) \left(\frac{1}{\sqrt{u}} \right) \Big|_{4R^2+z^2}^{R^2+z^2} \\ &= \frac{k\lambda}{\sqrt{R^2 + z^2}} - \frac{k\lambda}{\sqrt{4R^2 + z^2}} \quad (1) \end{aligned}$$

$$\begin{aligned} E_{AB,z} &= \int_{-2R}^{-R} \frac{k\lambda z dx}{\sqrt{x^2 + z^2}^3} \\ &= k\lambda z \int_{-2R}^{-R} \frac{dx}{\sqrt{x^2 + z^2}^3} \end{aligned}$$

define $x \equiv z \tan \theta$

$$\begin{aligned} E_{AB,z} &= k\lambda z \int_{\tan^{-1}(-2R/z)}^{\tan^{-1}(-R/z)} \frac{z \sec^2 \theta d\theta}{z^3 \sec^3 \theta} \\ &= \frac{k\lambda}{z} \int_{\tan^{-1}(-2R/z)}^{\tan^{-1}(-R/z)} \cos \theta d\theta \\ &= \frac{k\lambda}{z} (\sin \theta) \Big|_{\tan^{-1}(-2R/z)}^{\tan^{-1}(-R/z)} \\ &= \frac{k\lambda}{z} \left(\frac{-R}{\sqrt{R^2 + z^2}} + \frac{2R}{\sqrt{4R^2 + z^2}} \right) \\ &= \frac{k\lambda}{z} \left(\frac{2R}{\sqrt{4R^2 + z^2}} - \frac{R}{\sqrt{R^2 + z^2}} \right) \quad (1) \end{aligned}$$

For the field from segment CD,

$$dq = \lambda dy$$

$$d\vec{E} = \frac{k\lambda dy(0, -y, z)}{\sqrt{x^2 + z^2}^3} \quad (1)$$

$$\vec{E}_{CD} = \int_R^{2R} \frac{k\lambda dx(0, -y, z)}{\sqrt{y^2 + z^2}^3},$$

$$\vec{E}_{CD,y} = \int_R^{2R} \frac{-k\lambda y dx}{\sqrt{y^2 + z^2}^3},$$

define $u \equiv y^2 + z^2$

$$\begin{aligned} E_{CD,y} &= -\frac{k\lambda}{2} \int_{R^2+z^2}^{2R^2+z^2} \frac{du}{\sqrt{u}^3} \\ &= -\frac{k\lambda}{2} (-2) \left(\frac{1}{\sqrt{u}} \right) \Big|_{R^2+z^2}^{4R^2+z^2} \\ &= \frac{k\lambda}{\sqrt{4R^2 + z^2}} - \frac{k\lambda}{\sqrt{R^2 + z^2}} \end{aligned}$$

$$E_{CD,z} = \int_R^{2R} \frac{k\lambda z dx}{\sqrt{x^2 + z^2}^3} \quad (1)$$

define $x \equiv z \tan \theta$

$$\begin{aligned} E_{CD,z} &= k\lambda z \int_{\tan^{-1}(R/z)}^{\tan^{-1}(2R/z)} \frac{z \sec^2 \theta d\theta}{z^3 \sec^3 \theta} \\ &= \frac{k\lambda}{z} \int_{\tan^{-1}(R/z)}^{\tan^{-1}(2R/z)} \cos \theta d\theta \\ &= \frac{k\lambda}{z} (\sin \theta) \Big|_{\tan^{-1}(R/z)}^{\tan^{-1}(2R/z)} \\ &= \frac{k\lambda}{z} \left(\frac{2R}{\sqrt{4R^2 + z^2}} - \frac{R}{\sqrt{R^2 + z^2}} \right) \quad (1) \end{aligned}$$

Solution 1




Fig. x

For the field from segment CB,

According to the angle ϕ defined in the figure,

$$dq = -\lambda R d\phi$$

$$d\vec{E} = \frac{-k\lambda R d\phi (R \sin \phi, -R \cos \phi, z)}{\sqrt{z^2 + R^2}^3} \quad (2)$$

$$\vec{E}_{CB} = \int_0^{\pi/2} \frac{-k\lambda R d\phi (R \sin \phi, -R \cos \phi, z)}{\sqrt{z^2 + R^2}^3}$$

$$\begin{aligned} E_{CB,x} &= \int_0^{\pi/2} \frac{-k\lambda R^2 \sin \phi d\phi}{\sqrt{z^2 + R^2}^3} \\ &= \frac{-k\lambda R^2}{\sqrt{z^2 + R^2}^3} \int_0^{\pi/2} \sin \phi d\phi \\ &= \frac{-k\lambda R^2}{\sqrt{z^2 + R^2}^3} (-\cos \phi \Big|_0^{\pi/2}) = \frac{-k\lambda R^2}{\sqrt{z^2 + R^2}^3} \quad (1) \end{aligned}$$

$$\begin{aligned} E_{CB,y} &= \int_0^{\pi/2} \frac{k\lambda R^2 \cos \phi d\phi}{\sqrt{z^2 + R^2}^3} \\ &= \frac{k\lambda R^2}{\sqrt{z^2 + R^2}^3} \int_0^{\pi/2} \cos \phi d\phi \\ &= \frac{k\lambda R^2}{\sqrt{z^2 + R^2}^3} \sin \phi \Big|_0^{\pi/2} \\ &= \frac{k\lambda R^2}{\sqrt{z^2 + R^2}^3} \quad (1) \end{aligned}$$

$$\begin{aligned} E_{CB,z} &= \int_0^{\pi/2} \frac{-k\lambda R z d\phi}{\sqrt{z^2 + R^2}^3} \\ &= \frac{-k\lambda R z}{\sqrt{z^2 + R^2}^3} \int_0^{\pi/2} d\phi \\ &= \frac{-k\lambda \pi R z}{2\sqrt{z^2 + R^2}^3} \quad (1) \end{aligned}$$


$$\vec{E} = \vec{E}_{AB} + \vec{E}_{CD} + \vec{E}_{CB}$$

$$E_x = \frac{k\lambda}{\sqrt{R^2 + z^2}} - \frac{k\lambda}{\sqrt{4R^2 + z^2}} - \frac{k\lambda R^2}{\sqrt{z^2 + R^2}^3} \quad (1)$$

$$E_y = \frac{k\lambda}{\sqrt{4R^2 + z^2}} - \frac{k\lambda}{\sqrt{R^2 + z^2}} + \frac{k\lambda R^2}{\sqrt{z^2 + R^2}^3} \quad (1)$$

$$E_z = \frac{2k\lambda}{z} \left(\frac{2R}{\sqrt{4R^2 + z^2}} - \frac{R}{\sqrt{R^2 + z^2}} \right) - \frac{k\lambda \pi R z}{2\sqrt{z^2 + R^2}^3} \quad (1)$$

Solution 2



For the field from segment CB,

According to the angle ϕ defined in the figure,

$$dq = -\lambda R d\phi$$

$$d\vec{E} = \frac{-k\lambda R d\phi (R \cos \phi, -R \sin \phi, z)}{\sqrt{z^2 + R^2}^3}$$

$$\vec{E}_{CB} = \int_0^{\pi/2} \frac{-k\lambda R d\phi (R \cos \phi, -R \sin \phi, z)}{\sqrt{z^2 + R^2}^3}$$

$$\begin{aligned} E_{CB,x} &= \int_0^{\pi/2} \frac{-k\lambda R^2 \cos \phi d\phi}{\sqrt{z^2 + R^2}^3} \\ &= \frac{-k\lambda R^2}{\sqrt{z^2 + R^2}^3} \int_0^{\pi/2} \cos \phi d\phi \\ &= \frac{-k\lambda R^2}{\sqrt{z^2 + R^2}^3} (\sin \phi|_0^{\pi/2}) = \frac{-k\lambda R^2}{\sqrt{z^2 + R^2}^3} \end{aligned}$$

$$\begin{aligned} E_{CB,y} &= \int_0^{\pi/2} \frac{k\lambda R^2 \sin \phi d\phi}{\sqrt{z^2 + R^2}^3} \\ &= \frac{k\lambda R^2}{\sqrt{z^2 + R^2}^3} \int_0^{\pi/2} \sin \phi d\phi \\ &= \frac{k\lambda R^2}{\sqrt{z^2 + R^2}^3} (-\cos \phi|_0^{\pi/2}) \\ &= \frac{k\lambda R^2}{\sqrt{z^2 + R^2}^3} \end{aligned}$$

$$\begin{aligned} E_{CB,z} &= \int_0^{\pi/2} \frac{-k\lambda R z d\phi}{\sqrt{z^2 + R^2}^3} \\ &= \frac{-k\lambda R z}{\sqrt{z^2 + R^2}^3} \int_0^{\pi/2} d\phi \\ &= \frac{-k\lambda \pi R z}{2\sqrt{z^2 + R^2}^3} \end{aligned}$$

3 pts

Problem 4


1 pts

1 pts

12 pts

(a) $Q = \int \rho(\vec{r}') d^3 r' = \int \rho_0 \frac{r'^{3/2}}{a^{3/2}} 4\pi r'^2 dr' = \frac{4\pi\rho_0}{a^{3/2}} \int_0^a r'^{7/2} dr' = \frac{8\pi}{9} \rho_0 a^3$ 1 pts

(b)



2 pts

(i) $z > 4a$, use Gaussian surfaces S_2 (for slab) and S_3 (for sphere)

$$\oiint_{S_3} \vec{E} \cdot d\vec{A} = \oiint (E(r') \hat{r}') \cdot \hat{r}' dA' = 4\pi r'^2 E = \frac{Q_{in}}{\epsilon_0} = \frac{8\pi}{9\epsilon_0} \rho_0 a^3$$

2 pts

$$\rightarrow \vec{E}_{sphere}(0,0,z) = \frac{Q_{in}}{4\pi\epsilon_0} \frac{1}{r'^2} \hat{r}' = \frac{2\rho_0 a^3}{9\epsilon_0} \frac{\vec{r} - \vec{R}_0}{|\vec{r} - \vec{R}_0|^3} = \frac{2\rho_0 a^3}{9\epsilon_0} \frac{\hat{z}}{(z-3a)^2}$$

$$\oiint_{S_2} \vec{E} \cdot d\vec{A} = \oiint (E(z) \hat{z}) \cdot d\vec{A} = 2EA = \frac{\rho_E 2aA}{\epsilon_0} \rightarrow \vec{E}_{slab}(0,0,z) = \frac{\rho_E a}{\epsilon_0} \hat{z}$$

1 pts

$$\rightarrow \vec{E}(0,0,z) = \vec{E}_{slab} + \vec{E}_{sphere} = \left[\frac{\rho_E a}{\epsilon_0} + \frac{2\rho_0 a^3}{9\epsilon_0} \frac{1}{(z-3a)^2} \right] \hat{z}$$

(ii) $2a < z < 4a$, use Gaussian surfaces S_2 (for slab) and S_4 (for sphere)

$$\oiint_{S_4} \vec{E} \cdot d\vec{A} = 4\pi r'^2 E = \frac{Q_{in}}{\epsilon_0} = \frac{\rho_0}{\epsilon_0} \int_0^{r'} \frac{r'^{3/2}}{a^{3/2}} 4\pi r'^2 dr' = \frac{8\pi\rho_0}{9\epsilon_0} \frac{r'^{9/2}}{a^{3/2}}$$

$$\rightarrow \vec{E}_{sphere}(0,0,z) = \frac{2\rho_0}{9\epsilon_0} \frac{r'^{5/2}}{a^{3/2}} \hat{r}' = \frac{2\rho_0}{9\epsilon_0} \frac{|\vec{r} - \vec{R}_0|^{3/2}}{a^{3/2}} (\vec{r} - \vec{R}_0) = \frac{2\rho_0}{9\epsilon_0} \frac{|z-3a|^{3/2}}{(a)^{3/2}} (z-3a) \hat{z}$$

2 pts

$$\rightarrow \vec{E}(0,0,z) = \vec{E}_{slab} + \vec{E}_{sphere} = \left[\frac{\rho_E a}{\epsilon_0} + \frac{2\rho_0}{9\epsilon_0} \frac{|z-3a|^{3/2}}{(a)^{3/2}} (z-3a) \right] \hat{z}$$

1 pts

(iii) $0 < z < 2a$, use Gaussian surfaces S_1 (for slab) and S_3 (for sphere)

$$\oiint_{S_1} \vec{E} \cdot d\vec{A} = \oiint (E(z)\hat{z}) \cdot d\vec{A} = 2EA = \frac{\rho_E 2(z-a)A}{\epsilon_0} \rightarrow \vec{E}_{slab}(0,0,z) = \frac{\rho_E (z-a)}{\epsilon_0} \hat{z}$$

2 pts

$$\rightarrow \vec{E}(0,0,z) = \vec{E}_{slab} + \vec{E}_{sphere} = \left[\frac{\rho_E (z-a)}{\epsilon_0} - \frac{2\rho_0 a^3}{9\epsilon_0} \frac{1}{(z-3a)^2} \right] \hat{z}$$

(iii) $\vec{r} = (2a, 0, 3a)$, use Gaussian surfaces S_2 (for slab) and S_3 (for sphere)

$$\vec{E}(2a,0,3a) = \vec{E}_{slab} + \vec{E}_{sphere} = \frac{\rho_E a}{\epsilon_0} \hat{z} + \frac{2\rho_0 a^3}{9\epsilon_0} \frac{\vec{r} - \vec{R}_0}{|\vec{r} - \vec{R}_0|^3} = \frac{\rho_E a}{\epsilon_0} \hat{z} + \frac{2\rho_0 a^3}{9\epsilon_0} \frac{\hat{x}}{4a^2}$$

2 pts