

With PyTorch 0.2.0_2



Lab 2

Linear Regression

Sung Kim <hunkim+ml@gmail.com>

Code: <https://github.com/hunkim/DeepLearningZeroToAll/>



<https://github.com/hunkim/DeepLearningZeroToAll/tree/master/pytorch>

https://github.com/hunkim/DeepLearningZeroToAll/blob/master/pytorch/lab-02-1%262-linear_regression.py

Hypothesis and cost function

$$H(x) = Wx + b$$

$$cost(W, b) = \frac{1}{m} \sum_{i=1}^m (H(x^{(i)}) - y^{(i)})^2$$

1 Build model using PyTorch operations

$$H(x) = Wx + b$$

```
# X and Y data
x_train = [[1], [2], [3]]
y_train = [[1], [2], [3]]

X = Variable(torch.Tensor(x_train))
Y = Variable(torch.Tensor(y_train))
# Our hypothesis  $XW+b$ 
model = nn.Linear(1, 1, bias=True)
```

$$\text{cost}(W, b) = \frac{1}{m} \sum_{i=1}^m (H(x^{(i)}) - y^{(i)})^2$$

```
# cost criterion
criterion = nn.MSELoss()
```

1 Build model using PyTorch operations

$$\text{cost}(W, b) = \frac{1}{m} \sum_{i=1}^m (H(x^{(i)}) - y^{(i)})^2$$

```
# cost criterion  
criterion = nn.MSELoss()
```

Optimizer

```
# Minimize  
optimizer = torch.optim.SGD(model.parameters(), lr=0.01)
```

2 Train the model

Train the model

```
for step in range(2001):  
    optimizer.zero_grad()  
    # Our hypothesis  
    hypothesis = model(X)  
    cost = criterion(hypothesis, Y)  
    cost.backward()  
    optimizer.step()  
  
    if step % 20 == 0:  
        print(step, cost.data.numpy(), model.weight.data.numpy(),  
              model.bias.data.numpy())
```

3 Test the model

Testing our model

```
predicted = model(Variable(torch.Tensor([[5]])))  
print(predicted.data.numpy())  
predicted = model(Variable(torch.Tensor([[2.5]])))  
print(predicted.data.numpy())  
predicted = model(Variable(torch.Tensor([[1.5], [3.5]])))  
print(predicted.data.numpy())
```

Full code

Lab 2 Linear Regression

```
import torch
import torch.nn as nn
from torch.autograd import Variable
```

```
torch.manual_seed(777) # for reproducibility
```

X and Y data

```
x_train = [[1], [2], [3]]
y_train = [[1], [2], [3]]
```

```
X = Variable(torch.Tensor(x_train))
Y = Variable(torch.Tensor(y_train))
```

Our hypothesis $XW+b$

```
model = nn.Linear(1, 1, bias=True)
```

cost criterion

```
criterion = nn.MSELoss()
```

Minimize

```
optimizer = torch.optim.SGD(model.parameters(), lr=0.01)
```

Train the model

```
for step in range(2001):
    optimizer.zero_grad()
    # Our hypothesis
    hypothesis = model(X)
    cost = criterion(hypothesis, Y)
    cost.backward()
    optimizer.step()

    if step % 20 == 0:
        print(step, cost.data.numpy(), model.weight.data.numpy(),
              model.bias.data.numpy())
```

Testing our model

```
predicted = model(Variable(torch.Tensor([[5]])))
print(predicted.data.numpy())
predicted = model(Variable(torch.Tensor([[2.5]])))
print(predicted.data.numpy())
predicted = model(Variable(torch.Tensor([[1.5], [3.5]])))
print(predicted.data.numpy())
```


With PyTorch 0.2.0_2



Lab 4

Multi-variable linear regression

Sung Kim <hunkim+ml@gmail.com>