

CONDENSED MATHEMATICS MEETS TOPOLOGICAL QUANTUM FIELD THEORY: A FORMALLY VERIFIED FOUNDATION

SEAN MAHDAVIAN

ABSTRACT. We present a formally verified investigation into using condensed abelian groups (Clausen-Scholze) as a target category for topological quantum field theories, replacing topological vector spaces which fail to be abelian. Over six sessions of AI-assisted formal verification using Lean 4, Mathlib v4.28.0 [The24], and Harmonic's Aristotle system [ABD⁺25], we establish: (1) a sorry-free symmetric monoidal structure on CondensedAb via sheaf localization; (2) a sorry-free abstract TQFT transfer theorem; (3) a sorry-free embedding functor $\text{SemiNormedGrp} \rightarrow \text{CondensedAb}$ (the first bridge between Mathlib's normed space and condensed libraries); (4) a sorry-free proof, at the level of presheaves on CompHaus, that the corresponding embedding functor is faithful but *not* full, with the obstruction witnessed by an explicit unbounded continuous additive map; and (5) sorry-free commutative Frobenius algebras and a combinatorial 2d cobordism category.

The project comprises approximately 1380 active lines of Lean 4 across 5 files, with 5 remaining sorries (all with documented proof strategies) and 0 custom axioms. The accompanying formalization is available as a self-contained Lean 4 project.

CONTENTS

1. Introduction	2
1.1. The Categorical Obstruction in Infinite-Dimensional TQFT	2
1.2. The Condensed Fix	2
1.3. This Paper	2
2. The Formalization: Six Sessions	3
2.1. Session 1: Abstract TQFT Framework	3
2.2. Session 2: Manual Monoidal Construction	3
2.3. Session 3: The Localization Breakthrough	4
2.4. Session 4: The Banach Embedding	4
2.5. Session 5: Faithful but Not Full	4
2.6. Session 6: Combinatorial Cobordisms	5
3. Results Summary	5
3.1. Theorem Inventory	5
3.2. Remaining Sorries	5
3.3. Key Findings	6
4. Roadmap for Further Development	6
4.1. Near-term	6
4.2. Medium-term	6
4.3. Long-term	6

Date: June 19, 2026.

2020 Mathematics Subject Classification. 18M05, 57R56, 18F20, 46B99, 68V15.

Key words and phrases. condensed mathematics, topological quantum field theory, formal verification, Lean 4, monoidal categories, Frobenius algebras.

Formal verification assisted by Aristotle (Harmonic). Mathematical synthesis and prompt engineering by Claude (Anthropic).

4.4. Frontier	6
5. Methodology	6
5.1. Tools	7
6. Conclusion	7
Code Availability	7
Acknowledgments	7
References	7

1. INTRODUCTION

1.1. The Categorical Obstruction in Infinite-Dimensional TQFT. A topological quantum field theory, in Atiyah’s formulation [Ati88], is a symmetric monoidal functor $Z : \text{Cob}_{d+1} \rightarrow C$ from a cobordism category to some symmetric monoidal target category C . For finite-dimensional state spaces (Dijkgraaf–Witten, Reshetikhin–Turaev [RT91], and Turaev–Viro theories), the target $C = \text{Vect}$ works perfectly.

The physically interesting theories force infinite-dimensional state spaces. Chern–Simons theory [Wit88] with non-compact gauge group $\text{SL}(2, \mathbb{C})$, quantum gravity partition functions, and path integrals over infinite-dimensional moduli all produce state spaces $Z(\Sigma)$ that cannot live in finite-dimensional Vect . The natural target becomes topological vector spaces.

Here a precise categorical obstruction arises. The category TopAb of topological abelian groups is *not abelian*: a continuous bijective homomorphism need not have a continuous inverse, so a morphism can be simultaneously monic and epic without being an isomorphism. This propagates through the homological algebra machinery. Exact sequences break, derived functors misbehave, and the TQFT gluing axiom (which decomposes state spaces via exact sequences when cutting manifolds) becomes ill-defined.

The completed tensor product compounds the problem. It is not exact: tensoring a short exact sequence with a topological vector space can destroy exactness. Since the TQFT tensor product (disjoint union of boundaries corresponds to tensor product of state spaces) requires this operation, infinite-dimensional TQFTs built on TopVect are categorically deficient.

1.2. The Condensed Fix. Clausen and Scholze’s condensed mathematics [Sch19] resolves this obstruction. The category of condensed abelian groups (sheaves of abelian groups on the coherent site of compact Hausdorff spaces) is an abelian category with all limits and colimits. Every morphism has a kernel and cokernel. Every monic epic is an isomorphism.

Liquid vector spaces, a refinement of condensed modules, admit an exact completed tensor product. This was the content of the Liquid Tensor Experiment [Sch22, CT⁺22], Lean-verified by Commelin et al. in 2022. The exactness of this tensor product is precisely the property TopVect lacks and TQFT gluing requires.

1.3. This Paper. We report on a formal verification effort investigating whether CondensedAb can serve as a TQFT target category. The work was conducted iteratively over six sessions using Harmonic’s Aristotle system [ABD⁺25] for Lean 4 proof search, with Claude (Anthropic) providing mathematical synthesis, prompt engineering, and analysis.

The project produced both expected confirmations and genuine mathematical surprises. The monoidal structure on CondensedAb turned out to already exist in Mathlib (we just had to find it). The embedding from seminormed groups turned out not to be full: a counterexample found while attempting to formalize fullness shows the obstruction, and we subsequently machine-checked it at the presheaf level. Both findings reshaped the project’s direction in real time.

2. THE FORMALIZATION: SIX SESSIONS

2.1. Session 1: Abstract TQFT Framework. The first session established the categorical scaffolding in the file `LiquidTQFT.lean`.

Definition 2.1. An *abstract TQFT* with source category S and target category C (both braided monoidal) is a braided monoidal functor $Z : S \rightarrow C$.

```
structure AbstractTQFT
  (S : Type*) [Category S] [MonoidalCategory S] [BraidedCategory S]
  (C : Type*) [Category C] [MonoidalCategory C] [BraidedCategory C]
  where
    Z : S      C
    monoidal : Z.Monoidal
    braided   : Z.Braided
```

We work at the level of braided (not symmetric) monoidal functors. This is strictly more general than Atiyah’s original symmetric formulation and covers non-symmetric examples relevant to 3-dimensional TQFTs (e.g., Reshetikhin–Turaev invariants [RT91] from modular tensor categories). Lurie’s cobordism hypothesis [Lur09] provides the fully extended framework in which these structures are most naturally understood.

Theorem 2.2 (Transfer, sorry-free). *If T is a TQFT valued in C and $F : C \rightarrow D$ is a braided monoidal functor, then $T \circ F$ is a TQFT valued in D .*

```
def AbstractTQFT.transfer
  (T : AbstractTQFT S C)
  (F : C      D) [hF : F.Monoidal] [hFb : F.Braided] :
  AbstractTQFT S D where
    Z := T.Z      F
    monoidal := by letI := T.monoidal; infer_instance
    braided   := by letI := T.monoidal; letI := T.braided; infer_instance
```

The proof is Lean’s typeclass inference composing the monoidal and braided structures. Additional sorry-free results from this session: `CondensedAb` is abelian, has kernels, cokernels, and finite (co)limits, and satisfies the balanced category property (mono + epi = iso).

The session also recorded structural observations about gluing: in any abelian category, short exact sequences provide the decomposition structure needed for TQFT gluing. These take exactness as a hypothesis. The substantive analytic claim (that the liquid tensor product is exact) depends on the LTE and is not verified in this codebase.

2.2. Session 2: Manual Monoidal Construction. The second session (`CondensedMonoidal.lean`) attempted to build `MonoidalCategory CondensedAb` directly, defining the tensor product as sheafification of the pointwise tensor:

$$F \otimes_{\text{cond}} G = \text{sheafify}(F \otimes_{\text{presheaf}} G).$$

This yielded a complete `MonoidalCategoryStruct` (sorry-free) and 5/10 `MonoidalCategory` axioms. The remaining 5 reduced to two “sheafification comparison” isomorphisms:

$$\text{sheafify}(P \otimes Q) \cong \text{sheafify}(\text{sheafify}(P)^{\text{val}} \otimes Q).$$

This analysis was essential for the breakthrough in Session 3. As this manual construction was entirely superseded, it is not included in the final repository; we describe it here because the failed attempt is what motivated the search that found the localization approach.

2.3. Session 3: The Localization Breakthrough. The third session discovered that `Mathlib.CategoryTheory` already contained the complete infrastructure.

Theorem 2.3 (Sorry-free). *CondensedAb is a symmetric monoidal category.*

The construction assembles four existing Mathlib components:

- (1) **Presheaf monoidal structure:** pointwise tensor on $\text{CompHaus}^{\text{op}} \rightarrow \text{Ab}$.
- (2) **Sheafification as localization:** `presheafToSheaf` is a localization functor for the class $J.W$ of local isomorphisms.
- (3) **W is monoidal:** $J.W$ is closed under tensoring, proved via the internal hom (monoidal closed structure), not stalks.
- (4) **Localized monoidal category:** general construction from [Thea].

```
instance condensedAb_W_isMonoidal :
  ((coherentTopology CompHaus).W
   (A := ModuleCat (ULift      ))).IsMonoidal :=
  GrothendieckTopology.W.monoidal

instance condensedAb_monoidalCategory :
  MonoidalCategory CondensedAb :=
  Sheaf.monoidalCategory _ _
```

Six lines, zero sorries. The internal hom argument (rather than stalks) powers the `W.IsMonoidal` proof, meaning the result holds for any closed braided target category. A direct stalk-based approach has since been formalized by Riou (Mathlib PR #35584), providing an alternative proof path.

2.4. Session 4: The Banach Embedding. The fourth session (`BanachEmbedding.lean`) audited Mathlib for connections between normed spaces and condensed mathematics. The finding: *zero existing bridge*.

Definition 2.4. For a seminormed abelian group V , the presheaf `banachPresheaf V` sends $S \in \text{CompHaus}$ to $C(S, V)$, the abelian group of continuous maps, with precomposition as functorial action.

Theorem 2.5 (Sorry-free). *banachPresheaf V is a sheaf for the coherent topology on CompHaus.*

The proof transfers the sheaf condition from the Type-valued `yonedaPresheaf` through the forgetful functor. The main technical obstacle was universe arithmetic, bridged using `hasLimitsOfSizeShrink` and `preservesLimitsOfSize_of_univLE`.

Theorem 2.6 (Sorry-free). *There exists a functor $\text{SemiNormedGrp} \rightarrow \text{CondensedAb}$.*

2.5. Session 5: Faithful but Not Full. The fifth session established the central structural property of the embedding, and did so at two levels.

Theorem 2.7 (Sorry-free). *The sheaf-level embedding $\text{SemiNormedGrp} \rightarrow \text{CondensedAb}$ is faithful.*

The faithfulness proof is machine-checked: constant functions at the one-point space separate the points of any seminormed group, so distinct bounded maps induce distinct condensed morphisms.

To machine-check non-fullness as well, we work one categorical layer down, with the presheaf $S \mapsto C(S, A)$ valued in abelian groups, assembled into a functor

$$E : \text{SemiNormedGrp} \longrightarrow \text{PSh}(\text{CompHaus}, \text{Ab}).$$

This is the presheaf underlying the condensed embedding; passing to it costs only the sheaf condition, which is irrelevant to the fullness obstruction (a statement purely about morphisms).

Theorem 2.8 (Sorry-free). *The functor E is faithful but **not** full. Both statements are machine-checked for the same functor.*

Proof. Faithfulness is the injectivity of postcomposition on bounded maps, verified by evaluation at the one-point space. For non-fullness, let $V = \mathbb{N} \rightarrow_0 \mathbb{Z}$ (finitely supported integer sequences) with the supremum norm. Because every nonzero integer entry has absolute value at least 1, the norm satisfies $\|a\| \geq 1$ for $a \neq 0$, so V carries the *discrete* topology; consequently every additive map out of V is continuous. The summation map $f(a) = \sum_n a_n$ is therefore a continuous additive homomorphism, but it is not bounded: the indicators w_N of $\{0, \dots, N\}$ satisfy $\|w_N\| = 1$ while $f(w_N) = N + 1$. Hence the natural transformation E assigns to f has no preimage among bounded maps, and E is not full. $\square$

The discreteness of V is the engine: the condensed (here, presheaf) setting sees *all* additive maps as morphisms, while `SemiNormedGrp` admits only bounded ones, so the embedding cannot be full. The entire development is sorry-free and uses no custom axioms.

From presheaves to sheaves. Because morphisms of sheaves coincide with morphisms of presheaves between sheaf-valued objects, the non-fullness of E captures the full obstruction for the genuine functor into `CondensedAb`. Lifting Theorem 2.8 to a single sheaf-level statement requires only identifying $S \mapsto C(S, A)$ as a sheaf for the coherent topology, which the current Mathlib version does not provide. We therefore prove faithfulness at the sheaf level and the sharper faithful-but-not-full statement at the presheaf level, with the gap between them isolated to this one missing lemma.

Root cause. Continuous additive maps between seminormed abelian groups need not be bounded. The standard proof that “continuous linear implies bounded” requires scalar multiplication by a dense subfield. Fullness is recovered by restricting to `NormedSpace R` for R a nontrivially normed field.

The session also constructed `SemiNormedGrp.hasFiniteProducts` (sorry-free, not previously in Mathlib).

2.6. Session 6: Combinatorial Cobordisms. The sixth session (`Cob2.lean`) formalized the algebraic structure classifying 2-dimensional TQFTs [Koc03].

Definition 2.9 (Sorry-free). A *Frobenius object* in a monoidal category extends Mathlib’s monoid and comonoid objects with the Frobenius relation:

$$(\mu \otimes \text{id}) \circ (\text{id} \otimes \delta) = \delta \circ \mu.$$

A *commutative Frobenius object* additionally requires $\mu \circ \beta = \mu$.

Theorem 2.10 (Sorry-free). *In any braided monoidal category, the unit object carries a canonical commutative Frobenius algebra structure.*

The 2-dimensional cobordism category `Cob2` is defined as a category on the natural numbers, with morphisms generated by μ (pants), η (cap), δ (copants), ε (cup), plus composition, tensor, and swap, quotiented by the Frobenius relations.

3. RESULTS SUMMARY

3.1. Theorem Inventory.

3.2. Remaining Sorries. Five sorry placeholders remain across three incomplete results:

- (1) `PreservesEqualizers` for the embedding (hard; 4–5 layers of limit transfer).
- (2) `PreservesFiniteProducts` for the embedding (hard; `ContinuousMap.piEquiv` path).
- (3) `CommFrobeniusData.toCob2Functor` (tedious; three placeholders for the functor’s action on morphisms and its two functoriality proofs, all blocked on case analysis over the quotient).

Result	File	Status
CondensedAb is abelian	LiquidTQFT.lean	Sorry-free
Mono + epi = iso	LiquidTQFT.lean	Sorry-free
MonoidalCategory CondensedAb	LiquidTQFT.lean	Sorry-free
BraidedCategory CondensedAb	LiquidTQFT.lean	Sorry-free
SymmetricCategory CondensedAb	LiquidTQFT.lean	Sorry-free
AbstractTQFT.transfer	LiquidTQFT.lean	Sorry-free
W.IsMonoidal for coherent topology	MonoidalViaLoc.lean	Sorry-free
presheafToSheaf is monoidal	MonoidalViaLoc.lean	Sorry-free
banachPresheaf V is a sheaf	BanachEmbedding.lean	Sorry-free
SemiNormedGrp $\rightarrow$ CondensedAb functor	BanachEmbedding.lean	Sorry-free
Embedding is faithful (sheaf level)	BanachEmbedding.lean	Sorry-free
Embedding E faithful, not full (presheaf)	FullnessCounterexample.lean	Sorry-free
SemiNormedGrp.hasFiniteProducts	BanachEmbedding.lean	Sorry-free
FrobeniusObj, CommFrobeniusObj	Cob2.lean	Sorry-free
Trivial Frobenius on $\mathbf{1}_C$	Cob2.lean	Sorry-free
Cob ₂ category	Cob2.lean	Sorry-free

TABLE 1. Theorem inventory for the machine-checked development. The faithful-but-not-full result (Theorem 2.8) is verified at the presheaf level; the sheaf-level lift requires one additional lemma.

3.3. Key Findings. Finding 1. The monoidal structure on CondensedAb was already in Mathlib. The iterative process (axiom $\rightarrow$ manual construction $\rightarrow$ localization discovery) demonstrates the difficulty of navigating large formal libraries.

Finding 2. No prior bridge existed between Mathlib’s Analysis.NormedSpace and Condensed components. The embedding functor is the first such connection.

Finding 3. Fullness fails for the embedding (Theorem 2.8), machine-checked at the presheaf level. The condensed setting sees strictly more morphisms than the normed category, because the sup-norm topology on integer sequences is discrete and admits unbounded continuous additive maps.

Finding 4. SemiNormedGrp.hasFiniteProducts was not previously in Mathlib.

Finding 5. The classification “2d TQFT = commutative Frobenius algebra” [Koc03] formalizes cleanly from existing Mon_/Comon_ infrastructure.

4. ROADMAP FOR FURTHER DEVELOPMENT

4.1. Near-term. Preserve finite limits for the embedding; complete the Cob₂ functor; integrate the project files.

4.2. Medium-term. Define NormedSpaceCat R and prove fullness (which holds for normed spaces over valued fields); construct a concrete Frobenius object in CondensedAb; prove right exactness via the open mapping theorem.

4.3. Long-term. Formalize the projective tensor product of normed spaces (not in Mathlib); port the LTE exactness result; formalize smooth cobordism categories.

4.4. Frontier. Concrete Chern–Simons constructions valued in CondensedAb; Costello–Gwilliam [CG17] factorization algebras in the condensed setting.

5. METHODOLOGY

The work was conducted in six sessions of AI-assisted formal verification. Each session consisted of: (1) a carefully scoped prompt from Claude to Aristotle, based on analysis of previous results;

(2) Aristotle producing a Lean 4 file with Mathlib API audit, constructions, and proofs; (3) Claude analyzing the output and designing the next prompt.

The prompts evolved from exploratory to targeted. The most productive prompts front-loaded reconnaissance (searching Mathlib for existing infrastructure) before attempting construction. The Session 3 breakthrough directly resulted from this “search before build” approach.

5.1. Tools.

- **Lean 4** with **Mathlib v4.28.0** [The24] for formal verification.
- **Harmonic Aristotle** [ABD⁺25] for proof search and Mathlib API discovery.
- **Claude (Anthropic)** for mathematical synthesis, prompt engineering, and documentation.
- All formal results independently verifiable via `lake build`.

6. CONCLUSION

Six rounds of AI-assisted formal verification, starting from a blank slate, produced approximately 1380 active lines of Lean 4 across 5 files with 5 sorries and 0 custom axioms. The central results: CondensedAb is a sorry-free symmetric monoidal abelian category, the TQFT transfer theorem is sorry-free, the embedding from seminormed groups exists sorry-free with the sheaf condition verified, the presheaf-level embedding is machine-checked to be faithful but not full, and the commutative Frobenius algebra structure classifying 2d TQFTs [Koc03] is sorry-free.

A notable result was machine-checking that the embedding, presented as a functor E into presheaves on CompHaus, is faithful but not full. This is a precise mathematical boundary: the condensed setting sees more morphisms between normed groups than the normed category itself does, because the sup-norm topology on integer sequences is discrete and admits unbounded continuous additive maps. Faithfulness holds at the sheaf level as well; lifting the non-fullness to the sheaf level requires only identifying $S \mapsto C(S, A)$ as a sheaf, the one piece absent from the current Mathlib.

The remaining barriers are increasingly specific: projective tensor products in Mathlib (for the monoidal embedding), porting the LTE exactness result (for full gluing), and smooth cobordism formalization (for geometric TQFTs). The most promising near-term mathematical application is reformulating Costello–Gwilliam [CG17] factorization algebras in the condensed setting.

Code Availability. The complete Lean 4 formalization is available at <https://github.com/seanm27101/Liquid-tft-lean-CM4CM-> and builds against Mathlib v4.28.0.

Acknowledgments. Formal verification assisted by Aristotle [ABD⁺25] (Harmonic). Mathematical synthesis and prompt engineering by Claude (Anthropic). The symmetric monoidal structure on CondensedAb assembled in this project relies entirely on Mathlib infrastructure built by Joël Riou and Dagur Asgeirsson. We thank Yaël Dillies and Joël Riou for feedback on the Lean Zulip.

REFERENCES

- [ABD⁺25] Tudor Achim, Alex Best, Kevin Der, Mathis Federico, Sergei Gukov, Daniel Halpern-Leister, et al., *Aristotle: IMO-level automated theorem proving*, arXiv preprint (2025).
- [Ati88] Michael F. Atiyah, *Topological quantum field theories*, Publications Mathématiques de l’IHÉS **68** (1988), 175–186.
- [CG17] Kevin Costello and Owen Gwilliam, *Factorization algebras in quantum field theory*, vol. 1, Cambridge University Press, 2017, Volume 2 published 2021.
- [CT⁺22] Johan Commelin, Adam Topaz, et al., *Liquid tensor experiment (Lean formalization)*, <https://github.com/leanprover-community/lean-liquid>, 2022, Completed July 2022. Summary: <https://xenaproject.wordpress.com/2022/09/12/beyond-the-liquid-tensor-experiment/>.
- [Koc03] Joachim Kock, *Frobenius algebras and 2D topological quantum field theories*, Cambridge University Press, 2003.
- [Lur09] Jacob Lurie, *On the classification of topological field theories*, Current Developments in Mathematics (2009), 129–280.

- [RT91] N. Reshetikhin and V. G. Turaev, *Invariants of 3-manifolds via link polynomials and quantum groups*, *Inventiones Mathematicae* **103** (1991), 547–597.
- [Sch19] Peter Scholze, *Lectures on condensed mathematics*, Lecture notes, University of Bonn, Summer 2019, 2019.
- [Sch22] ———, *Liquid tensor experiment*, *Experimental Mathematics* (2022), Challenge post: <https://xenaproject.wordpress.com/2020/12/05/liquid-tensor-experiment/>.
- [Thea] The Mathlib Community, *Mathlib.CategoryTheory.Localization.Monoidal.Basic*, https://leanprover-community.github.io/mathlib4_docs/Mathlib/CategoryTheory/Localization/Monoidal/Basic.html, Monoidal category on localized categories.
- [Theb] ———, *Mathlib.CategoryTheory.Sites.Monoidal*, https://leanprover-community.github.io/mathlib4_docs/Mathlib/CategoryTheory/Sites/Monoidal.html, Monoidal structure on sheaf categories via localization.
- [The24] ———, *Mathlib: The math library of Lean 4*, <https://github.com/leanprover-community/mathlib4>, 2024, v4.28.0. Documentation: https://leanprover-community.github.io/mathlib4_docs/.
- [Wit88] Edward Witten, *Topological quantum field theory*, *Communications in Mathematical Physics* **117** (1988), no. 3, 353–386.

PHILLIPS EXETER ACADEMY

Email address: smhdavian@exeter.edu