

The interactive origin of iconicity: Mixed effects models

Contents

Introduction	2
Spikiness ratings	2
Load libraries	2
Load data	2
Mixed effects model	3
Mixed effects model with binarised spikiness ratings	8
Binary tree analysis	13
Accuracy	14
Load data	14
Mixed effects model	14
Iconicity and accuracy	17
Mixed effects model for accuracy and iconicity	18
Iconicity and systematicity	20
Mixed effects model	21
Results	22

Introduction

This file contains an analysis of the spikiness ratings of the final output languages and the accuracy of guessing during the experiments. The spikiness ratings are not bimodally distributed, so the analysis of spikiness ratings is done using both the continuous spikiness rating values and a binarised version of the ratings.

Spikiness ratings

Load libraries

```
library(gplots)
library(lattice)
library(ggplot2)
library(lme4)
library(party)
library(sjPlot)
```

Load data

```
finalLangs = read.csv("../data/finalLanguages/FinalLanguages.csv", stringsAsFactors = F)
# convert labels to English
finalLangs$Shape[finalLangs$Shape=="Picudo"] = "Spiky"
finalLangs$Shape[finalLangs$Shape=="Redondo"] = "Round"
```


Center spikiness ratings and re-level factors.

```
finalLangs$RatedSpikiness.center =
  finalLangs$RatedSpikiness - mean(finalLangs$RatedSpikiness)

finalLangs$Cond = factor(finalLangs$Cond, levels=c("Learn", "Communication"))
finalLangs$Shape = factor(finalLangs$Shape, levels=c("Round", "Spiky"))
```

Plot the data by item (all conditions, all generations)

```
par(mar=c(8,4,2,2))
plotmeans(finalLangs$RatedSpikiness.center~finalLangs$Item, las=2, xlab="", connect=F)
```



There are differences between items

Mixed effects model

Build a series of models with random effects for Chain and Item.

```
# null model
m0 = lmer(RatedSpikiness.center ~ 1 + (1 |Chain) + (1|Item), data=finalLangs)
# + condition
m1 = lmer(RatedSpikiness.center ~ Cond + (1 |Chain) + (1|Item), data=finalLangs)
# + generation
m2 = lmer(RatedSpikiness.center ~ Cond + Gen + (1 |Chain) + (1|Item), data=finalLangs)
# + shape
m3 = lmer(RatedSpikiness.center ~ Cond + Gen + Shape + (1 |Chain)
          + (1|Item), data=finalLangs)
# + interaction between shape and generation
m4 = lmer(RatedSpikiness.center ~ Cond + (Gen * Shape) + (1 |Chain)
          + (1|Item), data=finalLangs)
# + interaction between condition and generation
m5 = lmer(RatedSpikiness.center ~ (Cond*Gen) + (Gen * Shape) + (1 |Chain)
          + (1|Item), data=finalLangs)
# + interaction between shape and condition
m6 = lmer(RatedSpikiness.center ~ (Cond*Gen) + (Gen * Shape) + (Shape:Cond)
          + (1 |Chain) + (1|Item), data=finalLangs)
# + 3-way interaction
m7 = lmer(RatedSpikiness.center ~ Cond * Gen * Shape + (1 |Chain)
          + (1|Item), data=finalLangs)
```

Results

Look inside main model

```
summary(m7)
```

```
## Linear mixed model fit by REML ['lmerMod']
## Formula: RatedSpikiness.center ~ Cond * Gen * Shape + (1 | Chain) + (1 |
##      Item)
##      Data: finallangs
##
## REML criterion at convergence: 1767.9
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -1.8411 -0.8370 -0.1665  0.7906  2.3066
##
## Random effects:
##      Groups      Name      Variance Std.Dev.
##      Item      (Intercept) 0.01058  0.1029
##      Chain      (Intercept) 0.18043  0.4248
##      Residual              1.17881  1.0857
## Number of obs: 576, groups:  Item, 12; Chain, 8
##
## Fixed effects:
##
##              Estimate Std. Error t value
## (Intercept)      0.022530   0.299064   0.075
## CondCommunication 0.096751   0.418750   0.231
## Gen              -0.033860   0.052978  -0.639
## ShapeSpiky       -0.003530   0.297764  -0.012
## CondCommunication:Gen -0.064573   0.074923  -0.862
## CondCommunication:ShapeSpiky -0.032181   0.412642  -0.078
## Gen:ShapeSpiky     0.002764   0.074923   0.037
## CondCommunication:Gen:ShapeSpiky 0.189234   0.105957   1.786
##
## Correlation of Fixed Effects:
##              (Intr) CndCmm Gen      ShpSpk CndC:G CnC:SS Gn:ShS
## CondCmmnctn -0.700
## Gen          -0.620  0.443
## ShapeSpiky   -0.498  0.341  0.623
## CndCmmnct:G  0.438 -0.626 -0.707 -0.440
## CndCmmnc:SS  0.345 -0.493 -0.449 -0.693  0.635
## Gen:ShpSpky  0.438 -0.313 -0.707 -0.881  0.500  0.635
## CndCmm:G:SS -0.310  0.443  0.500  0.623 -0.707 -0.899 -0.707
```

Test the differences between model fits.

```
anova(m0,m1,m2,m3,m4,m5,m6,m7)
```

```
## refitting model(s) with ML (instead of REML)
```

```
## Data: finallangs
```

```
## Models:
## m0: RatedSpikiness.center ~ 1 + (1 | Chain) + (1 | Item)
## m1: RatedSpikiness.center ~ Cond + (1 | Chain) + (1 | Item)
## m2: RatedSpikiness.center ~ Cond + Gen + (1 | Chain) + (1 | Item)
## m3: RatedSpikiness.center ~ Cond + Gen + Shape + (1 | Chain) + (1 |
## m3:      Item)
## m4: RatedSpikiness.center ~ Cond + (Gen * Shape) + (1 | Chain) +
## m4:      (1 | Item)
## m5: RatedSpikiness.center ~ (Cond * Gen) + (Gen * Shape) + (1 | Chain) +
## m5:      (1 | Item)
## m6: RatedSpikiness.center ~ (Cond * Gen) + (Gen * Shape) + (Shape:Cond) +
## m6:      (1 | Chain) + (1 | Item)
## m7: RatedSpikiness.center ~ Cond * Gen * Shape + (1 | Chain) + (1 |
## m7:      Item)
##      Df      AIC      BIC logLik deviance    Chisq Chi Df Pr(>Chisq)
## m0  4 1779.7 1797.1 -885.83  1771.7
## m1  5 1781.2 1803.0 -885.61  1771.2  0.4475      1 0.5035471
## m2  6 1782.8 1808.9 -885.40  1770.8  0.4234      1 0.5152634
## m3  7 1777.7 1808.2 -881.87  1763.7  7.0627      1 0.0078704 **
## m4  8 1776.4 1811.3 -880.21  1760.4  3.3049      1 0.0690737 .
## m5  9 1778.1 1817.3 -880.05  1760.1  0.3156      1 0.5742584
## m6 10 1768.1 1811.6 -874.04  1748.1 12.0326      1 0.0005228 ***
## m7 11 1766.9 1814.8 -872.43  1744.9  3.2087      1 0.0732495 .
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

There was a significant main effect of shape ($\beta = -0.0035$, $\text{std.err} = 0.3$, Wald $t = -0.012$; log likelihood difference = 3.5 , $df = 1$, Chi Squared = 7.06 , $p = 0.0079$).

There was a significant interaction between shape and condition ($\beta = -0.032$, $\text{std.err} = 0.41$, Wald $t = -0.078$; log likelihood difference = 6 , $df = 1$, Chi Squared = 12.03 , $p = 0.00052$).

There was a marginal interaction between shape and generation ($\beta = 0.0028$, $\text{std.err} = 0.075$, Wald $t = 0.037$; log likelihood difference = 1.7 , $df = 1$, Chi Squared = 3.3 , $p = 0.069$).


There was a marginal three-way interaction between shape, condition and generation ($\beta = 0.19$, $\text{std.err} = 0.11$, Wald $t = 1.8$; log likelihood difference = 1.6 , $df = 1$, Chi Squared = 3.21 , $p = 0.073$).

Plot the random effects.

```
dotplot(ranef(m7, condVar=T))
```


```
## $Item
```

Item




\$Chain

Chain



Plot the fixed effects with error estimates from the final model. The 3-way interaction between condition, generation and shape is marginally significant:


```
sjp.lmer(m7, type='fe', geom.colors=c(1,1))
```



Mixed effects model with binarised spikiness ratings

The spikiness ratings are not normally distributed:

```
hist(finalLangs$RatedSpikiness)
```



So we binarise the variable into spiky/not spiky:

```
finalLangs$RatedSpikiness.bin = finalLangs$RatedSpikiness >4
```

Run a series of models. Note that intermediate models 5 and 6 do not converge, but the final model 7 does.

```
mcontrol = glmerControl(optCtrl = list(maxfun = 500000))

mb0 = glmer(RatedSpikiness.bin ~ 1 + (1 |Chain) + (1|Item),
            data=finalLangs, family=binomial, control = mcontrol)
mb1 = glmer(RatedSpikiness.bin ~ Cond + (1 |Chain) + (1|Item),
            data=finalLangs, family=binomial, control = mcontrol)
mb2 = glmer(RatedSpikiness.bin ~ Cond + Gen + (1 |Chain) + (1|Item),
            data=finalLangs, family=binomial, control = mcontrol)
mb3 = glmer(RatedSpikiness.bin ~ Cond + Gen + Shape + (1 |Chain) + (1|Item),
            data=finalLangs, family=binomial, control = mcontrol)
mb4 = glmer(RatedSpikiness.bin ~ Cond + (Gen * Shape) + (1 |Chain) + (1|Item),
            data=finalLangs, family=binomial, control = mcontrol)
mb5 = glmer(RatedSpikiness.bin ~ (Cond*Gen) + (Gen * Shape) + (1 |Chain) + (1|Item),
            data=finalLangs, family=binomial, control = mcontrol)
```

```
## Warning in checkConv(attr(opt, "derivs"), opt$par, ctrl = control
```



```
## $checkConv, : Model failed to converge with max|grad| = 0.00112016 (tol =
## 0.001, component 1)

mb6 = glmer(RatedSpikiness.bin ~ (Cond*Gen) + (Gen * Shape) + (Shape:Cond) + (1 |Chain) + (1|Item),
            data=finalLangs, family=binomial, control = mcontrol)

## Warning in checkConv(attr(opt, "derivs"), opt$par, ctrl = control
## $checkConv, : Model failed to converge with max|grad| = 0.00254262 (tol =
## 0.001, component 1)

mb7 = glmer(RatedSpikiness.bin ~ Cond * Gen * Shape + (1 |Chain) + (1|Item),
            data=finalLangs, family=binomial, control = mcontrol)
```

Results

Look inside main model

```
summary(mb7)

## Generalized linear mixed model fit by maximum likelihood (Laplace
## Approximation) [glmerMod]
## Family: binomial ( logit )
## Formula: RatedSpikiness.bin ~ Cond * Gen * Shape + (1 | Chain) + (1 |
## Item)
## Data: finalLangs
## Control: mcontrol
##
##      AIC      BIC   logLik deviance df.resid
##    722.9    766.4   -351.4    702.9     566
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -1.4001 -0.7152 -0.4951  0.9714  2.5752
##
## Random effects:
##  Groups Name      Variance Std.Dev.
##  Item  (Intercept) 0.06298  0.2510
##  Chain (Intercept) 0.30153  0.5491
## Number of obs: 576, groups: Item, 12; Chain, 8
##
## Fixed effects:
##
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)    -0.80967    0.50900  -1.591    0.112
## CondCommunication    0.11711    0.72308   0.162    0.871
## Gen              0.06152    0.10567   0.582    0.560
## ShapeSpiky       0.52479    0.60063   0.874    0.382
## CondCommunication:Gen -0.25227    0.16195  -1.558    0.119
## CondCommunication:ShapeSpiky -0.06135    0.83301  -0.074    0.941
## Gen:ShapeSpiky    -0.16967    0.15042  -1.128    0.259
## CondCommunication:Gen:ShapeSpiky 0.39112    0.21894   1.786    0.074 .
## ---
```

```
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Correlation of Fixed Effects:
##          (Intr) CndCmm Gen      ShpSpk CndC:G CnC:SS Gn:ShS
## CondCmmnctn -0.675
## Gen          -0.736  0.518
## ShapeSpiky   -0.600  0.398  0.623
## CndCmmnct:G  0.480 -0.751 -0.653 -0.407
## CndCmmnc:SS  0.407 -0.617 -0.449 -0.679  0.652
## Gen:ShpSpky  0.518 -0.364 -0.703 -0.871  0.459  0.628
## CndCmm:G:SS -0.356  0.556  0.483  0.599 -0.740 -0.893 -0.687
```

Test model comparison:

```
anova(mb0,mb1,mb2,mb3,mb4,mb5,mb6,mb7)
```

```
## Data: finalLangs
## Models:
## mb0: RatedSpikiness.bin ~ 1 + (1 | Chain) + (1 | Item)
## mb1: RatedSpikiness.bin ~ Cond + (1 | Chain) + (1 | Item)
## mb2: RatedSpikiness.bin ~ Cond + Gen + (1 | Chain) + (1 | Item)
## mb3: RatedSpikiness.bin ~ Cond + Gen + Shape + (1 | Chain) + (1 |
## mb3:      Item)
## mb4: RatedSpikiness.bin ~ Cond + (Gen * Shape) + (1 | Chain) + (1 |
## mb4:      Item)
## mb5: RatedSpikiness.bin ~ (Cond * Gen) + (Gen * Shape) + (1 | Chain) +
## mb5:      (1 | Item)
## mb6: RatedSpikiness.bin ~ (Cond * Gen) + (Gen * Shape) + (Shape:Cond) +
## mb6:      (1 | Chain) + (1 | Item)
## mb7: RatedSpikiness.bin ~ Cond * Gen * Shape + (1 | Chain) + (1 |
## mb7:      Item)
##      Df      AIC      BIC  logLik deviance   Chisq Chi Df Pr(>Chisq)
## mb0   3 729.66 742.72 -361.83   723.66
## mb1   4 731.64 749.07 -361.82   723.64  0.0130      1 0.9092167
## mb2   5 733.09 754.87 -361.54   723.09  0.5560      1 0.4558874
## mb3   6 730.23 756.37 -359.12   718.23  4.8538      1 0.0275855 *
## mb4   7 732.22 762.71 -359.11   718.22  0.0115      1 0.9147795
## mb5   8 734.12 768.97 -359.06   718.12  0.1001      1 0.7517608
## mb6   9 724.09 763.29 -353.04   706.09 12.0352      1 0.0005221 ***
## mb7  10 722.88 766.44 -351.44   702.88  3.2044      1 0.0734423 .
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

There was a significant main effect of shape ($\beta = 0.52$, $\text{std.err} = 0.6$, $\text{Wald } t = 0.87$, $\text{Wald } p = 0.38$; \log likelihood difference = 2.4 , $df = 1$, $\text{Chi Squared} = 4.85$, $p = 0.028$).

There was a significant interaction between shape and condition ($\beta = -0.061$, $\text{std.err} = 0.83$, $\text{Wald } t = -0.074$, $\text{Wald } p = 0.94$; \log likelihood difference = 6 , $df = 1$, $\text{Chi Squared} = 12.04$, $p = 0.00052$).


There was no significant interaction between shape and generation ($\beta = -0.17$, $\text{std.err} = 0.15$, $\text{Wald } t = -1.1$, $\text{Wald } p = 0.26$; \log likelihood difference = 0.0057 , $df = 1$, $\text{Chi Squared} = 0.01$, $p = 0.91$).

There was a marginal three-way interaction between shape, condition and generation ($\beta = 0.39$, $\text{std.err} = 0.22$, $\text{Wald } t = 1.8$, $\text{Wald } p = 0.074$; \log likelihood difference = 1.6 , $df = 1$, $\text{Chi Squared} = 3.2$, $p = 0.073$).

Plot random effects of final model

```
dotplot(ranef(mb7, condVar=T))
```


```
## $Item
```



```
##
```

```
## $Chain
```


Chain



Plot fixed effects with standard error from final model.

```
sjp.lmer(mb7, type='fe', geom.colors=c(1,1))
```

Fixed effects




Binary tree analysis

We use a binary decision tree to predict spikiness ratings by condition, generation, item shape, item colour and item border type.

The results agree with those above, namely that the main effects are for shape, but spiky meanings are rated as more spiky in the communication condition

```
finalLangs2 = finalLangs
finalLangs2$Shape = factor(finalLangs2$Shape)
finalLangs2$Colour = factor(finalLangs2$Colour)
finalLangs2$Border = factor(finalLangs2$Border)
finalLangs2$Cond = factor(finalLangs2$Cond)

cx = ctree(RatedSpikiness~Cond+Gen+Shape+Colour+Border, data=finalLangs2)
plot(cx)
```



Accuracy

Load data


Note that the column *Human* in the data indicates whether the signal was sent by a human. This is always the case in the communication condition, but only true for half of the trials in the learning condition. In the learning condition, when *Human* is FALSE, the human participant is guessing meaning from the signal sent by the program.

```
datax = read.csv("../results/IncreaseInIconicity.csv", stringsAsFactors = F)
alldatx = read.csv("../results/AllTrialData.csv", stringsAsFactors = F)
```

The mean proportion of correct guesses in the communication condition was 45.14%. The mean proportion of correct guesses by the human participant in the learning condition was 51.39%.

Plot the correct guesses by generation (means and 95% confidence intervals):

```
plotmeans(correctGuess~gen,alldatx[alldatx$condition=='Learn' & !alldatx$Human,], n.label = F)
plotmeans(correctGuess~gen,alldatx[alldatx$condition=='Comm',],add=T,col=2,barcol=2, n.label = F)
```



Mixed effects model

Binomial mixed effects model, with random effects for chain, target item. Test whether there are differences between conditions.

```
ctrl = glmerControl(optCtrl = list(maxfun=50000))
# we want to exclude trials where the computer is guessing meanings
# from the participant's signals in the learning condition
m0 = glmer(correctGuess ~ 1 + (1|chain) + (1|target.meaning) ,
  data=alldatx[alldatx$condition=='Comm' | (!alldatx$Human),],
```

```

    family = binomial, control= ctrl)

m1 = glmer(correctGuess ~ 1 + (1|chain) + (1|target.meaning) + (1|gen),
  data=alldatx[alldatx$condition=='Comm' | (!alldatx$Human)],,
  family = binomial, control= ctrl)
m2 = glmer(correctGuess ~ condition + (1|chain) + (1|target.meaning)+ (1|gen),
  data=alldatx[alldatx$condition=='Comm' | (!alldatx$Human)],,
  family = binomial, control= ctrl)
anova(m0,m1,m2)

```

```

## Data: alldatx[alldatx$condition == "Comm" | (!alldatx$Human), ]
## Models:
## m0: correctGuess ~ 1 + (1 | chain) + (1 | target.meaning)
## m1: correctGuess ~ 1 + (1 | chain) + (1 | target.meaning) + (1 |
## m1:      gen)
## m2: correctGuess ~ condition + (1 | chain) + (1 | target.meaning) +
## m2:      (1 | gen)
##      Df      AIC      BIC logLik deviance  Chisq Chi Df Pr(>Chisq)
## m0   3 2375.7 2392.0 -1184.8   2369.7
## m1   4 2372.8 2394.6 -1182.4   2364.8 4.9062      1 0.02676 *
## m2   5 2373.1 2400.4 -1181.5   2363.1 1.6748      1 0.19562
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```


There was no significant main effect of condition ($\beta = 0.26$, $\text{std.err} = 0.19$, $\text{Wald } t = 1.4$, $\text{Wald } p = 0.17$; $\log \text{ likelihood difference} = 0.84$, $\text{df} = 1$, $\text{Chi Squared} = 1.67$, $p = 0.2$).

There was a significant difference between generations ($\log \text{ likelihood difference} = 2.5$, $\text{df} = 1$, $\text{Chi Squared} = 4.91$, $p = 0.027$). There is a weak trend for the proportion of correct guesses to increase by generation, as shown by the estimates for the random effects for generation:

```

x = sjp.lmer(m2, sort.est='sort.all', prnt.plot=F,
  axis.labels=c("Chain", "Item", "Generation"),
  geom.colors=c(1,1))
x$plot.list[[3]] +
  xlab("Generation") +
  ylab("Random effect (fit of increase in correct guesses)")

```




Iconicity and accuracy

Innovations are either more or less iconic than the words they replace. There is no difference in how accurate the guesses are in terms of choosing the right item (see below, left), but the innovation tends to be more iconic when the shape of a meaning is guessed correctly (spiky or round). That is, the iconicity is helping participants guess the shape of a target meaning correctly.

Note that this analysis only makes sense for the communication condition.

```
par(mfrow=c(1,2))
ylimx = c(-0.045,0.045)
plotmeans(increaseIconicity ~ paste(condition, correctGuess),
  data = datax[datax$Human & datax$condition=="Comm",],
  ylim=ylimx, legends = c("Incorrect","Correct"),
  xlab='',
  ylab="Increase in iconicity")
title("Guessing Item")
abline(h=0)
plotmeans(increaseIconicity ~ paste(condition, correctSpikiness),
  data = datax[datax$Human & datax$condition=="Comm",],
  ylim=ylimx, legends = c("Incorrect","Correct"),
  xlab='',
  ylab="Increase in iconicity")
title("Guessing Shape")
abline(h=0)
```



Mixed effects model for accuracy and iconicity

A mixed effects model predicting the increase in iconicity by whether the receiver selected the correct target item, and by whether the receiver selected an item which matched the target in the shape dimension, with random effects for chain, generation and item. Note that it would make more intuitive sense to predict accuracy by increase in iconicity, but this way we can compare the effects of item accuracy versus shape accuracy.

```
m0 = lmer(increaseIconicity ~ 1 + (1|chain) + (1|gen) + (1|meaning),
          data=datax[datax$condition=="Comm",])

m1 = lmer(increaseIconicity ~ correctGuess + (1|chain) + (1|gen) + (1|meaning),
          data=datax[datax$condition=="Comm",])

m2 = lmer(increaseIconicity ~ correctGuess + correctSpikiness + (1|chain) + (1|gen) + (1|meaning),
          data=datax[datax$condition=="Comm",])

anova(m0,m1,m2)
```

```
## refitting model(s) with ML (instead of REML)
```

```
## Data: datax[datax$condition == "Comm", ]
## Models:
## m0: increaseIconicity ~ 1 + (1 | chain) + (1 | gen) + (1 | meaning)
## m1: increaseIconicity ~ correctGuess + (1 | chain) + (1 | gen) +
## m1:      (1 | meaning)
## m2: increaseIconicity ~ correctGuess + correctSpikiness + (1 | chain) +
## m2:      (1 | gen) + (1 | meaning)
##      Df      AIC      BIC logLik deviance Chisq Chi Df Pr(>Chisq)
## m0   5 -692.34 -669.66 351.17 -702.34
## m1   6 -690.34 -663.13 351.17 -702.34 0.0004      1 0.984852
## m2   7 -698.34 -666.59 356.17 -712.34 9.9963      1 0.001569 **
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
summary(m2)
```

```
## Linear mixed model fit by REML ['lmerMod']
## Formula:
## increaseIconicity ~ correctGuess + correctSpikiness + (1 | chain) +
##      (1 | gen) + (1 | meaning)
##      Data: datax[datax$condition == "Comm", ]
##
## REML criterion at convergence: -689.9
##
## Scaled residuals:
##      Min       1Q   Median       3Q      Max
## -3.3006 -0.3909 -0.0257  0.4642  3.2271
##
## Random effects:
##      Groups      Name      Variance Std.Dev.
##      meaning (Intercept) 0.00000 0.0000
```


```
## gen      (Intercept) 0.00000 0.0000
## chain    (Intercept) 0.00000 0.0000
## Residual                0.02091 0.1446
## Number of obs: 689, groups: meaning, 12; gen, 6; chain, 4
##
## Fixed effects:
##              Estimate Std. Error t value
## (Intercept)   -0.019121   0.009932  -1.925
## correctGuessTRUE  -0.019429   0.013283  -1.463
## correctSpikinessTRUE 0.042482   0.013417   3.166
##
## Correlation of Fixed Effects:
##              (Intr) cGTRUE
## crrctGsTRUE  0.000
## crrctSpTRUE -0.740 -0.457
```

There was no significant main effect of guessing the item correctly ($\beta = -0.019$, $\text{std.err} = 0.013$, Wald $t = -1.5$; log likelihood difference = 0.00018 , $df = 1$, Chi Squared = 0 , $p = 0.98$).

There was a significant main effect of guessing the shape correctly ($\beta = 0.042$, $\text{std.err} = 0.013$, Wald $t = 3.2$; log likelihood difference = 5 , $df = 1$, Chi Squared = 10 , $p = 0.0016$).

Plot the fixed effects:

```
sjp.glmer(m2, type='fe', geom.colors=c(1,1) )
```



Note that the model is probably overfitted, since the random effects are singular. But the effect is clear from the plot of the raw data.

Iconicity and systematicity

We would like to test whether there is a link between the increase in iconicity and the increase in systematicity for innovations.

Overall correlation between systematicity increase and iconicity increase:

```
cor.test(datax[datax$Human,]$increaseIconicity,datax[datax$Human,]$systematicity.increase)

##
## Pearson's product-moment correlation
##
## data: datax[datax$Human,]$increaseIconicity and datax[datax$Human,]$systematicity.increase
## t = 1.6028, df = 969, p-value = 0.1093
## alternative hypothesis: true correlation is not equal to 0
## 95 percent confidence interval:
## -0.01152866 0.11396482
## sample estimates:
## cor
## 0.05142107
```

For the communication condition:

```
cor.test(
  datax[datax$condition=="Comm",]$increaseIconicity,
  datax[datax$condition=="Comm",]$systematicity.increase)

##
## Pearson's product-moment correlation
##
## data: datax[datax$condition == "Comm",]$increaseIconicity and datax[datax$condition == "Comm",]$systematicity.increase
## t = 2.5225, df = 687, p-value = 0.01188
## alternative hypothesis: true correlation is not equal to 0
## 95 percent confidence interval:
## 0.02125801 0.16927945
## sample estimates:
## cor
## 0.09579831
```

For the learning condition:

```
cor.test(
  datax[datax$condition=="Learn" & datax$Human,]$increaseIconicity,
  datax[datax$condition=="Learn" & datax$Human,]$systematicity.increase)

##
## Pearson's product-moment correlation
##
## data: datax[datax$condition == "Learn" & datax$Human,]$increaseIconicity and datax[datax$condition == "Learn" & datax$Human,]$systematicity.increase
## t = -0.9347, df = 280, p-value = 0.3508
## alternative hypothesis: true correlation is not equal to 0
## 95 percent confidence interval:
```

```
## -0.17145923 0.06143279
## sample estimates:
##      cor
## -0.0557718
```

Simple linear model:

```
summary(lm(increaseIconicity~systematicity.increase*condition, data=datax[datax$Human,]))
```

```
##
## Call:
## lm(formula = increaseIconicity ~ systematicity.increase * condition,
##     data = datax[datax$Human, ])
##
## Residuals:
##      Min       1Q   Median       3Q      Max
## -0.51356 -0.06968 -0.00254  0.07290  0.46513
##
## Coefficients:
##                                Estimate Std. Error t value
## (Intercept)                   0.003534   0.005393   0.655
## systematicity.increase         0.231376   0.089539   2.584
## conditionLearn                 0.000833   0.010027   0.083
## systematicity.increase:conditionLearn -0.342597   0.155334  -2.206
##                                Pr(>|t|)
## (Intercept)                   0.51240
## systematicity.increase         0.00991 **
## conditionLearn                 0.93381
## systematicity.increase:conditionLearn 0.02765 *
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## Residual standard error: 0.1414 on 967 degrees of freedom
## Multiple R-squared:  0.007642,    Adjusted R-squared:  0.004563
## F-statistic: 2.482 on 3 and 967 DF,  p-value: 0.0596
```

Significant main effect for systematicity increase and interaction.

Mixed effects model

Build a series of mixed effects models predicting the increase in iconicity with random effects for chain and item.

```
# Null model, predicting increase in iconicity by condition and generation
m0 = lmer(increaseIconicity~condition*gen + (1|chain) + (1|meaning),
          data = datax[datax$Human,])

# Add main effect of systematicity increase
m1 = lmer(increaseIconicity~systematicity.increase+(condition*gen) + (1|chain) + (1|meaning),
          data = datax[datax$Human,])

# Add interaction between Sys. and condition
```

```

m2 = lmer(increaseIconicity~systematicity.increase + (systematicity.increase:condition) +
          (condition*gen) + (1|chain) + (1|meaning),
          data = datax[datax$Human,])

# Add 3-way interaction
m3 = lmer(increaseIconicity~systematicity.increase*condition*gen +
          (1|chain) + (1|meaning),
          data = datax[datax$Human,])

```

Results

Test the model fit. Note that the model converges on signalive random effect estimates.

```
anova(m0,m1,m2,m3)
```

```

## refitting model(s) with ML (instead of REML)

## Data: datax[datax$Human, ]
## Models:
## m0: increaseIconicity ~ condition * gen + (1 | chain) + (1 | meaning)
## m1: increaseIconicity ~ systematicity.increase + (condition * gen) +
## m1:      (1 | chain) + (1 | meaning)
## m2: increaseIconicity ~ systematicity.increase + (systematicity.increase:condition) +
## m2:      (condition * gen) + (1 | chain) + (1 | meaning)
## m3: increaseIconicity ~ systematicity.increase * condition * gen +
## m3:      (1 | chain) + (1 | meaning)
##      Df      AIC      BIC logLik deviance Chisq Chi Df Pr(>Chisq)
## m0   7 -1025.8 -991.71 519.93 -1039.8
## m1   8 -1026.5 -987.44 521.23 -1042.5 2.6088      1 0.1063
## m2   9 -1029.2 -985.33 523.62 -1047.2 4.7734      1 0.0289 *
## m3  11 -1027.6 -973.93 524.80 -1049.6 2.3605      2 0.3072
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

There was a significant interaction between systematicity increase and condition (log likelihood difference = 2.4 , df = 1 , Chi Squared = 4.77 , p = 0.029).

Plot the fixed effects of model 2. The relationship between systematicity and iconicity is more negative in the learning condition:

```
sjp.lmer(m2,type='fe')
```


```
## Computing p-values via Wald-statistics approximation (treating t as Wald z).
```



Plot differences in raw data:

```
ylimx= c(-0.015,0.018)
par(mfrow=c(1,2))
plotmeans(systematicity.increase ~ increaseIconicity>0,
  data=datax[datax$condition=="Comm",],
  legends = c("Decrease","Increase"),
  xlab="Change in iconicity",
  ylab="Change in systematicity",
  main = "Communication",
  ylim = ylimx)
abline(h=0)
plotmeans(systematicity.increase ~ increaseIconicity>0,
  data=datax[datax$Human & datax$condition=="Learn",],
  legends = c("Decrease","Increase"),
  xlab="Change in iconicity",
  ylab="Change in systematicity",
  main = "Learning",
  ylim = ylimx)
abline(h=0)
```

Communication



Learning

