

Jacinda - Functional Stream Processing Language

Vanessa McHale

Contents

Tutorial	2
Language	2
Patterns + Implicits, Streams	2
Fold	3
Map	3
Functions	4
Zips	4
Scans	4
Prior	5
Deduplicate	5
Filter	5
Formatting Output	5
Libraries	6
System Interaction	7
Examples	7
Error Span	7
Vim Tags	8
Unix Command-Line Tools	9
grep	9
wc	9
head	9
uniq	10

nl	10
Data Processing	10
CSV Processing	10
Machinery	11
Functor	11
IsPrintf	12

Tutorial

Jacinda has fluent support for filters, maps and folds that are familiar to functional programmers; the syntax in particular is derivative of J or APL.

Jacinda is at its best when piped through other command-line tools (including awk).

Language

Patterns + Implicits, Streams

Awk is oriented around patterns and actions. Jacinda has support for a similar style: one defines a pattern and an expression defined by the lines that this matches, viz.

```
{% <pattern>}{<expr>}
```

This defines a stream of expressions.

One can search a file for all occurrences of a string:

```
ja '% /Bloom/}'{0}' -i ulysses.txt
```

{0 here functions like \$0 in awk: it means the whole line.

Thus, the above functions like ripgrep. We could imitate fd with, say:

```
ls -1 -R | ja '% /\.hs$/}'{0}'
```

This would print all Haskell source files in the current directory.

There is another form,

`{<expr>}{<expr>}`

where the initial expression is of boolean type, possibly involving the line context. An example:

`{#‘0>110}{‘0}`

This defines a stream of lines that are more than 110 bytes (`#` is ‘tally’, it returns the length of a string).

There is also a syntax that defines a stream on *all* lines,

`{|<expr>}`

So `{|`0}` would define a stream of text corresponding to the lines in the file.

Fold

Then, count lines with the word “Bloom”:

```
ja ‘(+)|0 {% /Bloom/}{1}’ -i ulysses.txt
```

Note the *fold*, `|`. It is a ternary operator taking `(+)`, `0`, and `{% /Bloom/}{1}` as arguments. The general syntax is:

`<expr>|<expr> <expr>`

It takes a binary operator, a seed, and a stream and returns an expression.

There is also `|>`, which folds without a seed.

Map

Suppose we wish to count the lines in a file. We have nearly all the tools to do so:

```
(+)|0 {|1}
```

This uses aforementioned `{|<expr>}` syntax. It this defines a stream of 1s for each line, and takes its sum.

We could also do the following:

```
(+)|0 [:1"$0
```

`$0` is the stream of all lines. `[:` is the constant operator, `a -> b -> a`, so `[:1` sends anything to 1.

`"` maps over a stream. So the above maps 1 over every line and takes the sum.

Functions

We could abstract away `sum` in the above example like so:

```
let val
  sum := [(+) | 0 x]
in sum {% /Bloom/}{1} end
```

In Jacinda, one can define functions with a `dfn` syntax in, like in APL. We do not need to bind `x`; the variables `x` and `y` are implicit. Since `[(+) | 0 x]` only mentions `x`, it is treated as a unary function.

Note also that `:=` is used for definition. The general syntax is

```
let (val <name> := <expr>)* in <expr> end
```

Lambdas There is syntactical support for lambdas;

```
\x. (+) | 0 x
```

would be equivalent to the above example.

Zips

The syntax is:

```
, <expr> <expr> <expr>
```

One could (for instance) calculate population density:

```
, (%) $5:f $6:f
```

The postfix `:` parses the column based on inferred type; here it parses as a float.

Scans

The syntax is:

```
<expr> ^ <expr> <expr>
```

Scans are like folds, except that the intermediate value is tracked at each step. One could define a stream containing line numbers for a file with:

```
(+)^0 [:1"$0
```

(this is the same as `{|ix}`)

Prior

Jacinda has a binary operator, `\.`, like q's each prior or J's dyadic infix. One could write:

```
succDiff := [(-) \. x]
```

to track successive differences.

Currying Jacinda allows partially applied (curried) functions; one could write

```
succDiff := ((-)\.)
```

Deduplicate

Jacinda has stream deduplication built in with the `~.` operator.

```
~.$0
```

This is far better than `sort | uniq` as it preserves order; it is equivalent to `!a[$0]++` in awk.

Filter

We can filter an extant stream with `#.`, viz.

```
(>110) #. $1:i
```

`#.` takes as its left argument a unary function returning a boolean.

```
[#x>110] #. $0
```

would filter to those lines >110 bytes wide.

Formatting Output

One can format output with `sprintf`, which works like `printf` in Awk or C.

As an example,

```
{|sprintf '%i: %s' (ix.'0')}
```

would display a file annotated with line numbers. Note the atypical syntax for tuples, we use `.` as a separator rather than `,`.

Libraries

There is a syntax for functions:

```
fn sum(x) :=
  (+)|0 x;

fn drop(n, str) :=
  let val l := #str
  in substr str n l end;
```

Note the `:=` and also the semicolon at the end of the expression that is the function body.

Since Jacinda has support for higher-order functions, one could write:

```
fn any(p, xs) :=
  (|)|#f p"xs;

fn all(p, xs) :=
  (&)|#t p"xs;
```

File Includes One can `@include` files.

As an example, one could write:

```
@include'lib/string.jac'

fn path(x) :=
  intercalate '\n' (splitc x ':');

path"$0
```

`intercalate` is defined in `lib/string.jac`.

Parting Shots

```
or := [(|)|#f x]

and := [&)|#t x]

count := [(+)|0 [:1"x]
```

`#t` and `#f` are boolean literals.

System Interaction

Jacinda ignores any line beginning with `#!`, thus one could write a script like so:

```
#!/usr/bin/env -S ja run

fn path(x) :=
  ([x+'\n'+y])|'' (splitc x ':');

path"$0
```

Examples

Error Span

Suppose we wish to extract span information from compiler output for editor integration. Vim ships with a similar script, `mve.awk`, to present column information in a suitable format.

```
src/Jacinda/Backend/TreeWalk.hs:319:58: error:
  • The constructor ‘TyArr’ should have 3 arguments, but has been given 4
  • In the pattern:
      TyArr _ _ (TyArr _ (TyApp _ (TyB _ TyStream) _)) _
  In the pattern:
      TyArr _ _ (TyArr _ _ (TyArr _ (TyApp _ (TyB _ TyStream) _)) _)
  In the pattern:
      TBuiltin (TyArr _ _
                  (TyArr _ _ (TyArr _ (TyApp _ (TyB _ TyStream) _)) _))
                  Fold
  |
319 | eWith re i (EApp _ (EApp _ (EApp _ (TBuiltin (TyArr _ _ (TyArr _ _ (TyArr _ (TyApp _ (
  |                                                                                                     ~~~~~~
```

To get what we want, we use `match`, which returns indices that match a regex - in our case, `/\^+/,` which spans the error location.

From the manpages, we see it has type

```
match : Str -> Regex -> Option (Int . Int)

:set fs:=/\^+/,;

fn printSpan(str) :=
```

```
(sprintf '%i-%i')(match str /\^+\/);

printSpan:{% /\|/}{‘2}
```

Our program uses | as a file separator, thus ‘2 will present us with:

~~~~~

which is exactly the relevant bit.

First, note that " is used to map (sprintf '%i-%i') over (match ...). This works because match returns an Option, which is a functor. The builtin :? is mapMaybe. Thus, we define a stream

```
printSpan:{% /\|/}{‘2}
```

which only collects when printSpan returns a Some.

## Vim Tags

Suppose we wish to generate vim tag files for our Jacinda programs. According to :help tags-file-format the desired format is

```
{tagname}          {TAB} {tagfile} {TAB} {tagaddress}
```

where {tagaddress} is an ex command. In fact, addresses defined by regular expressions are preferable as they become outdated less quickly.

As an example, suppose we have the function declaration

```
fn sum(x) :=
  (+)|0 x;
```

Then we need to extract sum and give a regex that points to where it is defined.

To do so:

```
fn mkEx(s) :=
  '/^' + s + '$/;';
```

```
fn processStr(s) :=
  let
    val line := split s /[ \|+\/
    val outLine := sprintf '%s\t%s\t%s' (line.2 . fp . mkEx s)
  in outLine end;
```

```
processStr"{%/fn +[:lower:][:latin:]]*.*:=/}{‘0}
```



Note the builtin `split`; according to the manpages it has type

```
split : Str -> Regex -> List Str
```

`.2` is the syntax for accessing a list - `line.2` extracts the second element.

## Unix Command-Line Tools

To get a flavor of Jacinda, see how it can be used in place of familiar tools:

### `grep`

```
ja '%/the/'){0}' -i FILE
```

### `wc`

To count lines:

```
(+)|0 [:1"$0
```

or

```
[y]|0 {|ix}
```

To count bytes in a file:

```
(+)|0 [#x+1]"$0
```

or

```
(+)|0 {|#0+1}
```

### `head`

To emulate `head -n60`, for instance:

```
{ix<=60){0}
```

## uniq

```
fn step(acc, this) :=
  if this = acc->1
  then (this . None)
  else (this . Some this);

(->2):?step^(''.None) $0
```

This tracks the previous line in a state and only adds the current line to the stream if it is different.

## nl

We can emulate `nl -b a` with:

```
{|sprintf '    %i %s' (ix.'0')}
```

To count only non-blank lines:

```
fn empty(str) :=
  #str = 0;

fn step(acc, line) :=
  if empty line
  then (acc->1 . '')
  else (acc->1 + 1 . line);

fn process(x) :=
  if !empty (x->2)
  then sprintf '    %i\t%s' x
  else '';

process"step^(0 . '') $0
```

## Data Processing

### CSV Processing

We can process `.csv` data with the aid of `csvformat`, viz.

```
csvformat file.csv -D'|' | ja -F'\|' '$1'
```

For “well-behaved” `csv` data, we can simply split on `,`:

```
ja -F, '$1'
```

**Vaccine Effectiveness** As an example, NYC publishes weighted data on vaccine breakthroughs.

We can download it:

```
curl -L https://raw.githubusercontent.com/nychealth/coronavirus-data/master/latest/now-weekly-breakthrough.csv
```

And then process its columns with `ja`

```
ja ',[1.0-x%y] {ix>1}{5:} {ix>1}{11:}' -F, -i /tmp/now-weekly-breakthrough.csv
```

As of writing:

```
0.8793436293436293
0.8524501884760366
0.8784741144414169
0.8638045891931903
0.8644207066557108
0.8572567783094098
0.8475274725274725
0.879263670817542
0.8816131830008673
0.8846732911773563
0.8974564390146205
0.9692181407757029
```

This extracts the 5th and 11th columns (discarding headers), and then computes effectiveness.

## Machinery

Under the hood, Jacinda has typeclasses, inspired by Haskell. These are used to disambiguate operators and witness with an implementation.

The language does not allow custom typeclasses.

## Functor

The map operator `"` works on all functors, not just streams. `Stream`, `List`, and `Option` are instances.

## IsPrintf

The `IsPrintf` typeclass is used to type `sprintf`; strings, integers, floats, booleans, and tuples of such are members.

```
sprintf '%i' 3
```

and

```
sprintf '%s-%i' ('str' . 2)
```

are both valid.