



Harco Fittings LLC

P.O. BOX 10335 • LYNCHBURG, VIRGINIA 24506 • PHONE: (434) 845-7094
FAX: (434) 845-8562

PVC GASKETED DR18 C900 NON-PRESSURE FITTINGS

LETTER OF COMPLIANCE

Scope:

This letter of compliance covers Harco Fittings' requirements for **PVC DR18 Gasketed Sewer Fittings for use with cast iron outside diameter PVC pipe in non-pressure sewer and drain applications**. These products, when applicable, meet or exceed performance standards set by the American Society for Testing and Materials (ASTM), and the Uni-Bell PVC Pipe Association.

DR18 CIOD Non-Pressure Gasketed Sewer Fittings are molded in sizes 4" to 8" with some exceptions which are fabricated from pipe or assembled from components. Sizes above 8" are fabricated from pipe with some use of molded components. Molded fitting thicknesses are that of the same size DR18 pipe. Fabricated fittings are manufactured from DR18 PVC pipe per AWWA C900 with formed bells using Rieber style gaskets.

Materials:

PVC Poly(Vinyl Chloride) compounds used in the manufacturing of **DR18 CIOD Gasketed Sewer Fittings** for use with C900 pipe in non-pressure sewer and drain applications comply with ASTM D1784, *Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds*, having a cell classification 12454 or 13343.

Gasket materials used in these fittings comply with the requirements of ASTM F477 "*Standard Specification for Elastomeric Seals (Gaskets) for Joining Plastic Pipe*".

Gasket Joints:

DR18 CIOD Gasketed Sewer Fittings have a gasket joint design that meets the requirements of ASTM D3212 "*Standard Specification for Joints for Drain and Sewer Plastic Pipes Using Flexible Elastomeric Seals*". All

DR18 CIOD Gasketed Sewer Fittings can be supplied with either a standard SBR gasket or a nitrile gasket.

Nitrile gaskets are to be used when a more chemically resistant gasket is necessary because of ground contaminants. Gaskets in formed bells of fabricated fittings are locked in Rieber style gaskets.

Replacement gaskets are available to allow **molded** fittings to also be installed on IPS-OD PVC pipe.

Lubricant:

All **DR18 CIOD Gasketed Sewer Fittings** for use with C900 pipe in non-pressure sewer and drain applications must be assembled with the nontoxic, water-soluble, NSF-listed lubricant recommended by the manufacturer.

Color Coding:

DR18 CIOD Molded Gasketed Sewer Fittings for use with C900 pipe in non-pressure sewer and drain applications are color-coded white.

Note: *Modifications to products may occur at any time without notice. Should you require that a product meets a given standard or application, you must ensure that the information provided herein is current by consulting with a Harco Fittings LLC representative.*

Sincerely,

John E. Riordan
Vice President
Harco Fittings LLC