

THE HARRINGTON CORPORATION

P.O. BOX 10335 • LYNCHBURG, VIRGINIA 24506 • PHONE: (434) 845-7094
PLANT : 3721 COHEN PLACE TELEFAX (434) 845-8562
EMAIL: sales@harcofittings.com

PVC-IPS PRESSURE FITTINGS FOR VACUUM SERVICE

TO WHOM IT MAY CONCERN:

HARCO PVC IPS SIZE PRESSURE FITTINGS AND GASKETS FOR VACUUM SERVICE ARE LONG TERM PRESSURE RATED 200 PSI IF NOT OTHERWISE INDICATED AND MEET THE FOLLOWING SPECIFICATIONS, STANDARDS AND APPROVALS:


- NSF STANDARDS 14 & 61
- ASTM D-1784 MATERIALS
- ASTM D-3139 JOINTS
- SDR 21 DIMENSIONS AND PRESSURE RATINGS PER ASTM D2241
- ASTM F-477 GASKETS, SBR Material
- NSF APPROVAL
- PRESSURE RATING METHOD: AWWA C907

HARCO PVC IPS PRESSURE FITTINGS AND GASKETS FOR VACUUM SERVICE:

- Will operate at 22 inches of mercury vacuum and withstand a vacuum test at 22 inches of mercury vacuum with no leakage after 1 hour with joints deflected as per ASTM D3139.
- Feature a "vacuum ridge" in push on joint gasket groove.
- Are subjected to 100% production vacuum test before shipment and marked for vacuum service.

Harco PVC IPS fittings are made in the United States. Both fitting body and gasket are made in the United States from raw materials made in the United States.

THE HARRINGTON CORPORATION



Michael B. Harrington
President