



# Value Iteration and Policy Iteration

Sid Banerjee  
Cornell University



## Infinite Horizon Discounted

A **MDP** is defined by:  $\mathcal{M} = \{\mathcal{S}, \mathcal{A}, r, T, s_0, \gamma\}$

$\mathcal{S}$  State space

$\mathcal{A}$  Action space

$r : \mathcal{S} \times \mathcal{A} \rightarrow [0, 1]$  Reward

$T : \mathcal{S} \times \mathcal{A} \rightarrow \Delta(\mathcal{S})$  Transitions

$\gamma \in [0, 1)$  Discount

## Value Function

The **Value Function** is expected return for policy

$$V^\pi(s) = \mathbb{E} \left[ \sum_{h=0}^{\infty} \gamma^h r(S_h, A_h) \mid S_0 = s, A_h \sim \pi(S_h), S_{h+1} \sim T(\cdot \mid S_h, A_h) \right]$$
$$Q^\pi(s, a) = \mathbb{E} \left[ \sum_{h=0}^{\infty} \gamma^h r(S_h, A_h) \mid (S_0, A_0) = (s, a), A_h \sim \pi(S_h), S_{h+1} \sim T(\cdot \mid S_h, A_h) \right]$$

The **Bellman Equations** note that:

$$V^\pi(s) = \mathbb{E}_{A \sim \pi(s)} [r(s, A) + \gamma \mathbb{E}_{S' \sim T(\cdot \mid s, A)} [V^\pi(S')]]$$
$$Q^\pi(s, a) = r(s, a) + \gamma \mathbb{E}_{S' \sim T(\cdot \mid s, a)} [V^\pi(S')]$$

## Main Question

Given a MDP, how do we find the optimal policy?

# Main Question

Given a MDP, how do we find the optimal policy?

## Fully Known Model

- Reward function, transition distribution fully known
- Understand computational complexity to scale to large problems

## Generative Model

- Sample from reward function / transition distribution from arbitrary (state,action)
- Understand statistical complexity to scale to large problems
- No issue of dynamic environment

## Online Model

- Sample trajectory under current policy, update policy, repeat
- Understand statistical complexity
- “*Most complex*”, additional correlations in estimates

## Main Question

Maybe a better model....

### Exogenous MDP

- Unknown distribution over exogenous inputs (i.e. arrivals)
- Known reward and transition as function of exogenous trace
- Access to historical data of exogenous inputs

# Main Question

Given a MDP, how do we find the optimal policy?

## Fully Known Model

- Reward function, transition distribution fully known
- Understand computational complexity to scale to large problems

## Generative Model

- Sample from reward function / transition distribution from arbitrary (state,action)
- Understand statistical complexity to scale to large problems
- No issue of dynamic environment

## Online Model

- Sample trajectory under current policy, update policy, repeat
- Understand statistical complexity
- “*Most complex*”, additional correlations in estimates

# Main Question

Given a MDP, how do we find the optimal policy?

## Fully Known Model

- Reward function, transition distribution fully known
- Understand computational complexity to scale to large problems

## Two Approaches

Value Iteration  
Policy Iteration



## Bellman Operator

Define the Bellman Operator, which given an arbitrary function:

$$(\mathcal{T}f)(s, a) = r(s, a) + \gamma \mathbb{E}_{S' \sim T(\cdot|s, a)} [\max_{a' \in \mathcal{A}} f(S', a')]$$

By **Bellman Optimality** we know:  $\mathcal{T}Q^* = Q^*$

## Bellman Operator

Define the Bellman Operator, which given an arbitrary function:

$$(\mathcal{T}f)(s, a) = r(s, a) + \gamma \mathbb{E}_{S' \sim T(\cdot|s, a)} [\max_{a' \in \mathcal{A}} f(S', a')]$$

By **Bellman Optimality** we know:  $\mathcal{T}Q^* = Q^*$

If it was a contraction (it is), iterate!

## Value Iteration

$$(\mathcal{T}f)(s, a) = r(s, a) + \gamma \mathbb{E}_{S' \sim T(\cdot | s, a)} [\max_{a' \in \mathcal{A}} f(S', a')]$$

Initialize:  $Q^0(s, a) \in \left(0, \frac{1}{1-\gamma}\right)$

Iterate until convergence:  $Q^{t+1} = \mathcal{T}Q^t$

## Value Iteration

$$(\mathcal{T}f)(s, a) = r(s, a) + \gamma \mathbb{E}_{S' \sim T(\cdot | s, a)} [\max_{a' \in \mathcal{A}} f(S', a')]$$

Initialize:  $Q^0(s, a) \in \left(0, \frac{1}{1-\gamma}\right)$

Iterate until convergence:  $Q^{t+1} = \mathcal{T}Q^t$

Couple notes:

- Explicitly using **known** model
- Storage/time scales with size of action + state space

## Value Iteration

$$(\mathcal{T}f)(s, a) = r(s, a) + \gamma \mathbb{E}_{S' \sim T(\cdot | s, a)} [\max_{a' \in \mathcal{A}} f(S', a')]$$

Initialize:  $Q^0(s, a) \in \left(0, \frac{1}{1-\gamma}\right)$

Iterate until convergence:  $Q^{t+1} = \mathcal{T}Q^t$

The Bellman operator is a  $\gamma$  contraction,  
so:

$$\|Q^t - Q^*\| \leq \gamma^t \|Q^0 - Q^*\|$$

## Value Iteration

The Bellman operator is a  $\gamma$  contraction,  
so:

$$\|Q^t - Q^*\| \leq \gamma^t \|Q^0 - Q^*\|$$

Not a guarantee on value of final policy, since  $Q^t \neq Q^{\pi^t}$   
 $\pi^t(s) = \operatorname{argmax}_{a \in \mathcal{A}} Q^t(s, a)$

$$V^{\pi^t}(s) \geq V^*(s) - \frac{2\gamma^t}{1-\gamma} \|Q^0 - Q^*\|_\infty$$

# Main Question

Given a MDP, how do we find the optimal policy?

## Fully Known Model

- Reward function, transition distribution fully known
- Understand computational complexity to scale to large problems

## Two Approaches

Value Iteration  
Policy Iteration

## Value Function

The Bellman Equations note that:

$$\begin{aligned}V^\pi(s) &= \mathbb{E}_{A \sim \pi(s)}[r(s, A) + \gamma \mathbb{E}_{S' \sim T(\cdot | s, A)}[V^\pi(S')]] \\Q^\pi(s, a) &= r(s, a) + \gamma \mathbb{E}_{S' \sim T(\cdot | s, a)}[V^\pi(S')]\end{aligned}$$

Via some linear algebra....  $T^\pi(s', s) = \sum_a \pi(a | s) T(s' | s, a)$

$$V^\pi = (I - \gamma T^\pi)^{-1} r$$

$$Q^\pi = r + \gamma V^\pi$$



## Policy Iteration

Initialize:  $\pi^0(s) : \mathcal{A} \rightarrow \Delta(\mathcal{A})$

Evaluate / solve Bellman Eqs for:  $Q^{\pi^t}(s, a)$

Policy Improvement:  $\pi^{t+1}(s) = \operatorname{argmax}_{a \in \mathcal{A}} Q^{\pi^t}(s, a)$

## Policy Iteration

Initialize:  $\pi^0(s) : \mathcal{A} \rightarrow \Delta(\mathcal{A})$

Evaluate / solve Bellman Eqs for:  $Q^{\pi^t}(s, a)$

Policy Improvement:  $\pi^{t+1}(s) = \operatorname{argmax}_{a \in \mathcal{A}} Q^{\pi^t}(s, a)$

Couple notes:

- Explicitly using **known** model
- Storage/time scales with size of action + state space (solving Bellman Eqs)

## Natural Question

### Value Iteration vs Policy Iteration

Which one is faster? How many iterations (computational complexity) are needed to find optimal policy?

## Value Iteration

$$(\mathcal{T}f)(s, a) = r(s, a) + \gamma \mathbb{E}_{S' \sim T(\cdot | s, a)} [\max_{a' \in \mathcal{A}} f(S', a')]$$

Initialize:  $Q^0(s, a) \in \left(0, \frac{1}{1-\gamma}\right)$

Iterate until convergence:  $Q^{t+1} = \mathcal{T}Q^t$

Per iteration complexity:  $S^2A$

## Policy Iteration

Initialize:  $\pi^0(s) : \mathcal{A} \rightarrow \Delta(\mathcal{A})$

Evaluate / solve Bellman Eqs for:  $Q^{\pi^t}(s, a)$

Policy Improvement:  $\pi^{t+1}(s) = \operatorname{argmax}_{a \in \mathcal{A}} Q^{\pi^t}(s, a)$

Per iteration complexity: hard to quantify, need to evaluate Q value for current policy at each iteration

## Natural Question


### Value Iteration vs Policy Iteration

Which one is faster? How many iterations (computational complexity) are needed to find optimal policy?

Neither are strongly polynomial time, but PI observed to be faster than VI

## Natural Question

Neither are strongly polynomial time, but PI observed to be faster than VI



## Natural Question

Can we design a polynomial time algorithm?

Well, linear programming.....



## References

---

- [Puterman1994] Martin Puterman. “Markov Decision Processes: Discrete Stochastic Dynamic Programming”. *John Wiley + Sons*, 1994.
- [Sutton2018] Richard Sutton. “Reinforcement Learning: An Introduction.” *MIT Press*, 2018.
- [Agarwal2021] Alekh Agarwal, Nan Jiang, Sham M. Kakade, Wen Sun. “Reinforcement Learning: Theory and Algorithms”. 2021.
- [Slivkins2019] Aleksandrs Slivkins. “Introduction to Multi-Armed Bandits.” *Foundations and Trends in ML*, 2019.
- [Powell2021] Warren Powell. “Reinforcement Learning and Stochastic Optimization.” 2021.
- [Meyn2021] Sean Meyn. “Control Systems and Reinforcement Learning”. *Cambridge University Press*, 2021.
- [Neu2020] Gergely Neu, Ciara Pike-Burke. “[A Unifying View of Optimism in Episodic Reinforcement Learning](#)”. *NeurIPS*, 2020.