

ECSE 543

Assignment 3

Sean Stappas
260639512

December 7th, 2017

Contents

1	BH Interpolation	2
1.a	Lagrange Polynomials	2
1.b	Full-Domain Lagrange Polynomials	2
1.c	Cubic Hermite Polynomials	2
2	Magnetic Circuit	2
2.a	Flux Equation	2
2.b	Newton-Raphson	2
2.c	Successive Substitution	2
3	Diode Circuit	2
3.a	Voltage Equations	2
3.b	Newton-Raphson	2
4	Function Integration	2
4.a	Cosine Integration	2
4.b	Log Integration	2
4.c	Log Integration Improvement	2
	Appendix A Code Listings	3
	Appendix B Output Logs	7


Introduction

The code for this assignment was created in Python 2.7 and can be seen in Appendix A. To perform the required tasks in this assignment, the `Matrix` class from Assignment 1 was used, with useful methods such as `add`, `multiply`, `transpose`, etc. This package can be seen in the `matrices.py` file shown in Listing 1. The only packages used that are not built-in are those for creating the plots for this report, i.e., `matplotlib` for plotting. The structure of the rest of the code will be discussed as appropriate for each question. Output logs of the program are provided in Appendix B.

1 BH Interpolation

The source code for the Question 1 program can be seen in the `q1.py` file shown in Listing 2.


1.a Lagrange Polynomials



Missing figure

Interpolate the first 6 points using full-domain Lagrange polynomials.

1.b Full-Domain Lagrange Polynomials



Missing figure

Now use the same type of interpolation for the 6 points at $B = 0, 1.3, 1.4, 1.7, 1.8, 1.9$.

1.c Cubic Hermite Polynomials

2 Magnetic Circuit

The source code for the Question 2 program can be seen in the `q2.py` file shown in Listing 3.

2.a Flux Equation

$$f(\psi) = 0 \quad (1)$$

2.b Newton-Raphson

2.c Successive Substitution

3 Diode Circuit

The source code for the Question 3 program can be seen in the `q3.py` file shown in Listing 4.


3.a Voltage Equations

3.b Newton-Raphson

4 Function Integration

The source code for the Question 4 program can be seen in the `q4.py` file shown in Listing 5.


4.a Cosine Integration



Missing figure

Plot $\log_{10}(E)$ versus $\log_{10}(N)$ for $N=1, 2, \dots, 20$, where E is the absolute error in the computed integral.

4.b Log Integration



Missing figure

Repeat part (a) for the function $\log_e(x)$, only this time plot for $N=10, 20, \dots, 200$.

4.c Log Integration Improvement

A Code Listings

Listing 1: Custom matrix package (*matrices.py*).

```
1  from __future__ import division
2
3  import copy
4  import csv
5  from ast import literal_eval
6
7  import math
8
9
10 class Matrix:
11     def __init__(self, data):
12         self.data = data
13         self.num_rows = len(data)
14         self.num_cols = len(data[0])
15
16     def __str__(self):
17         string = ''
18         for row in self.data:
19             string += '\n'
20             for val in row:
21                 string += '{:6.2f} '.format(val)
22         return string
23
24     def integer_string(self):
25         string = ''
26         for row in self.data:
27             string += '\n'
28             for val in row:
29                 string += '{:3.0f} '.format(val)
30         return string
31
32     def __add__(self, other):
33         if len(self) != len(other) or len(self[0]) != len(other[0]):
34             raise ValueError('Incompatible matrix sizes for addition. Matrix A is {}x{}, but matrix B is
35                 ↪ {}x{}.'.format(len(self), len(self[0]), len(other), len(other[0])))
36
37         return Matrix([[self[row][col] + other[row][col] for col in range(self.num_cols)]
38             for row in range(self.num_rows)])
39
40     def __sub__(self, other):
41         if len(self) != len(other) or len(self[0]) != len(other[0]):
42             raise ValueError('Incompatible matrix sizes for subtraction. Matrix A is {}x{}, but matrix B
43                 ↪ is {}x{}.'.format(len(self), len(self[0]), len(other), len(other[0])))
44
45         return Matrix([[self[row][col] - other[row][col] for col in range(self.num_cols)]
46             for row in range(self.num_rows)])
47
48     def __mul__(self, other):
49         if type(other) == float or type(other) == int:
50             return self.scalar_multiply(other)
51
52         if self.num_cols != other.num_rows:
53             raise ValueError('Incompatible matrix sizes for multiplication. Matrix A is {}x{}, but matrix
54                 ↪ B is {}x{}.'.format(self.num_rows, self.num_cols, other.num_rows, other.num_cols))
55
56         # Inspired from https://en.wikipedia.org/wiki/Matrix_multiplication
57         product = Matrix.empty(self.num_rows, other.num_cols)
58         for i in range(self.num_rows):
59             for j in range(other.num_cols):
60                 row_sum = 0
61                 for k in range(self.num_cols):
62                     row_sum += self[i][k] * other[k][j]
```

```

63         product[i][j] = row_sum
64     return product
65
66 def scalar_multiply(self, scalar):
67     return Matrix([[self[row][col] * scalar for col in range(self.num_cols)] for row in
        ↪ range(self.num_rows)])
68
69 def __div__(self, other):
70     """
71     Element-wise division.
72     """
73     if self.num_rows != other.num_rows or self.num_cols != other.num_cols:
74         raise ValueError('Incompatible matrix sizes.')
75     return Matrix([[self[row][col] / other[row][col] for col in range(self.num_cols)]
76                    for row in range(self.num_rows)])
77
78 def __neg__(self):
79     return Matrix([[-self[row][col] for col in range(self.num_cols)] for row in range(self.num_rows)])
80
81 def __deepcopy__(self, memo):
82     return Matrix(copy.deepcopy(self.data))
83
84 def __getitem__(self, item):
85     return self.data[item]
86
87 def __len__(self):
88     return len(self.data)
89
90 def item(self):
91     """
92     :return: the single element contained by this matrix, if it is 1x1.
93     """
94     if not (self.num_rows == 1 and self.num_cols == 1):
95         raise ValueError('Matrix is not 1x1')
96     return self.data[0][0]
97
98 def is_positive_definite(self):
99     """
100     :return: True if the matrix is positive-definite, False otherwise.
101     """
102     A = copy.deepcopy(self.data)
103     for j in range(self.num_rows):
104         if A[j][j] <= 0:
105             return False
106         A[j][j] = math.sqrt(A[j][j])
107         for i in range(j + 1, self.num_rows):
108             A[i][j] = A[i][j] / A[j][j]
109             for k in range(j + 1, i + 1):
110                 A[i][k] = A[i][k] - A[i][j] * A[k][j]
111     return True
112
113 def transpose(self):
114     """
115     :return: the transpose of the current matrix
116     """
117     return Matrix([[self.data[row][col] for row in range(self.num_rows)] for col in
        ↪ range(self.num_cols)])
118
119 def mirror_horizontal(self):
120     """
121     :return: the horizontal mirror of the current matrix
122     """
123     return Matrix([[self.data[self.num_rows - row - 1][col] for col in range(self.num_cols)]
124                    for row in range(self.num_rows)])
125
126 def empty_copy(self):
127     """
128     :return: an empty matrix of the same size as the current matrix.
129     """
130     return Matrix.empty(self.num_rows, self.num_cols)

```

```

131
132 def infinity_norm(self):
133     if self.num_cols > 1:
134         raise ValueError('Not a column vector.')
135     return max([abs(x) for x in self.transpose()[0]])
136
137 def two_norm(self):
138     if self.num_cols > 1:
139         raise ValueError('Not a column vector.')
140     return math.sqrt(sum([x ** 2 for x in self.transpose()[0]]))
141
142 def save_to_csv(self, filename):
143     """
144     Saves the current matrix to a CSV file.
145
146     :param filename: the name of the CSV file
147     """
148     with open(filename, "wb") as f:
149         writer = csv.writer(f)
150         for row in self.data:
151             writer.writerow(row)
152
153 def save_to_latex(self, filename):
154     """
155     Saves the current matrix to a latex-readable matrix.
156
157     :param filename: the name of the CSV file
158     """
159     with open(filename, "wb") as f:
160         for row in range(self.num_rows):
161             for col in range(self.num_cols):
162                 f.write('{}'.format(self.data[row][col]))
163                 if col < self.num_cols - 1:
164                     f.write('& ')
165             if row < self.num_rows - 1:
166                 f.write('\n')
167
168 @staticmethod
169 def multiply(*matrices):
170     """
171     Computes the product of the given matrices.
172
173     :param matrices: the matrix objects
174     :return: the product of the given matrices
175     """
176     n = matrices[0].rows
177     product = Matrix.identity(n)
178     for matrix in matrices:
179         product = product * matrix
180     return product
181
182 @staticmethod
183 def empty(num_rows, num_cols):
184     """
185     Returns an empty matrix (filled with zeroes) with the specified number of columns and rows.
186
187     :param num_rows: number of rows
188     :param num_cols: number of columns
189     :return: the empty matrix
190     """
191     return Matrix([[0 for _ in range(num_cols)] for _ in range(num_rows)])
192
193 @staticmethod
194 def identity(n):
195     """
196     Returns the identity matrix of the given size.
197
198     :param n: the size of the identity matrix (number of rows or columns)
199     :return: the identity matrix of size n
200     """

```

```

201         return Matrix.diagonal_single_value(1, n)
202
203     @staticmethod
204     def diagonal(values):
205         """
206         Returns a diagonal matrix with the given values along the main diagonal.
207
208         :param values: the values along the main diagonal
209         :return: a diagonal matrix with the given values along the main diagonal
210         """
211         n = len(values)
212         return Matrix([[values[row] if row == col else 0 for col in range(n)] for row in range(n)])
213
214     @staticmethod
215     def diagonal_single_value(value, n):
216         """
217         Returns a diagonal matrix of the given size with the given value along the diagonal.
218
219         :param value: the value of each element on the main diagonal
220         :param n: the size of the matrix
221         :return: a diagonal matrix of the given size with the given value along the diagonal.
222         """
223         return Matrix([[value if row == col else 0 for col in range(n)] for row in range(n)])
224
225     @staticmethod
226     def column_vector(values):
227         """
228         Transforms a row vector into a column vector.
229
230         :param values: the values, one for each row of the column vector
231         :return: the column vector
232         """
233         return Matrix([[value] for value in values])
234
235     @staticmethod
236     def csv_to_matrix(filename):
237         """
238         Reads a CSV file to a matrix.
239
240         :param filename: the name of the CSV file
241         :return: a matrix containing the values in the CSV file
242         """
243         with open(filename, 'r') as csv_file:
244             reader = csv.reader(csv_file)
245             data = []
246             for row_number, row in enumerate(reader):
247                 data.append([literal_eval(val) for val in row])
248         return Matrix(data)

```

Listing 2: Question 1 (q1.py).

```

1  def q1():
2      print('\n=== Question 1 ===')
3
4
5  if __name__ == '__main__':
6      q1()

```

Listing 3: Question 2 (q2.py).

```

1  def q2():
2      print('\n=== Question 2 ===')
3
4
5  if __name__ == '__main__':
6      q2()

```

Listing 4: Question 3 (q3.py).

```
1  def q3():
2      print('\n=== Question 3 ===')
3
4
5  if __name__ == '__main__':
6      q3()
```

Listing 5: Question 4 (q4.py).

```
1  def q4():
2      print('\n=== Question 4 ===')
3
4
5  if __name__ == '__main__':
6      q4()
```

B Output Logs

Listing 6: Output of Question 1 program (q1.txt).

1

Listing 7: Output of Question 2 program (q2.txt).

1

Listing 8: Output of Question 3 program (q3.txt).

1

Listing 9: Output of Question 4 program (q4.txt).

1