

# Event Loop

```
while (taskQueue.waitForNextTask()) {  
  const task = taskQueue.dequeueNext();  
  task.execute();  
}
```

Note: `taskQueue.waitForNextTask` waits synchronously for tasks to arrive

## Event Loop w/ Microtasks

```
while (taskQueue.waitForNextTask()) {  
  const task = taskQueue.dequeueNext();  
  task.execute();  
  while (!microtaskQueue.isEmpty()) {  
    const microtask = microtaskQueue.dequeueNext();  
    microTask.execute();  
  }  
}
```

Note: `taskQueue.waitForNextTask` waits synchronously for tasks to arrive

## Microtasks are enqueued when\*

- `queueMicrotask` is invoked
- A Promise settles with a corresponding invocation of one of the instance methods:
  - `then`
  - `catch`
  - `finally`

\* There are a few other situations beyond this list depending on js execution context. However, these are out of scope for this lesson.

## exercise1.js

```
01: setTimeout(() => {  
02:   Promise.resolve()  
03:     .then(() => console.log("A"));  
04:   console.log("B");  
05: }, 0);  
06:  
07: Promise.resolve()  
08:   .then(() => console.log("C"));  
09:  
10: console.log("D");
```

### exercise1.js

```
01: setTimeout(() => {  
02:   Promise.resolve()  
03:     .then(() => console.log("A"));  
04:   console.log("B");  
05: }, 0);  
06:  
07: Promise.resolve()  
08:   .then(() => console.log("C"));  
09:  
10: console.log("D");
```

#### Option 1

D A C B

#### Option 2

D C A B

#### Option 3

D C B A

#### Option 4

None of the above

## exercise2.js

```
01: const pr0 = Promise.resolve();  
02: const pr1 = pr0.then(() => console.log("A"));  
03: const pr2 = pr1.then(() => console.log("B"));  
04:  
05: const pr3 = Promise.resolve();  
06: const pr4 = pr3.then(() => console.log("C"));  
07: const pr5 = pr4.then(() => console.log("D"));  
08:  
09: console.log("E");
```

## exercise2.js

```
01: const pr0 = Promise.resolve();  
02: const pr1 = pr0.then(() => console.log("A"));  
03: const pr2 = pr1.then(() => console.log("B"));  
04:  
05: const pr3 = Promise.resolve();  
06: const pr4 = pr3.then(() => console.log("C"));  
07: const pr5 = pr4.then(() => console.log("D"));  
08:  
09: console.log("E");
```

### Option 1

E A C B D

### Option 2

E A B C D

### Option 3

E B D A C

### Option 4

None of the above

## exercise3.js

```
01: Promise.resolve()  
02:   .then(() => console.log("A"))  
03:   .then(() => console.log("B"))  
04:   .then(() => console.log("C"));  
05:  
06: Promise.reject()  
07:   .then(() => console.log("D"))  
08:   .catch(() => console.log("E"));
```



### exercise3.js

```
01: Promise.resolve()  
02:   .then(() => console.log("A"))  
03:   .then(() => console.log("B"))  
04:   .then(() => console.log("C"));  
05:  
06: Promise.reject()  
07:   .then(() => console.log("D"))  
08:   .catch(() => console.log("E"));
```

#### Option 1

A B C E

#### Option 2

A E B C

#### Option 3

A B E C

#### Option 4

None of the above

## exercise4.js

```
01: setTimeout(() => console.log("A"), 0);
```

```
02:
```

```
03: queueMicrotask(() => {
```

```
04:   queueMicrotask(() => {
```

```
05:     queueMicrotask(() => {
```

```
06:       console.log("B");
```

```
07:     });
```

```
08:     console.log("C");
```

```
09:   });
```

```
10:   console.log("D");
```

```
11: });
```

```
12:
```

```
13: console.log("E");
```

### exercise4.js

```
01: setTimeout(() => console.log("A"), 0);
02:
03: queueMicrotask(() => {
04:   queueMicrotask(() => {
05:     queueMicrotask(() => {
06:       console.log("B");
07:     });
08:     console.log("C");
09:   });
10:   console.log("D");
11: });
12:
13: console.log("E");
```

#### Option 1

E D A C B

#### Option 2

E D C B A

#### Option 3

E B C D A

#### Option 4

None of the above

## interactive-logger.html

```
01: <!DOCTYPE html>
02: <html>
03:   <body>
04:     <textarea id="userText"></textarea>
05:     <button onclick="startLogging()">Start Log</button>
06:     <button onclick="stopLogging()">Stop Log</button>
07:   </body>
08:   <script>
09:     let toid = null;
10:
11:     function startLogging() {
12:       const v = document.getElementById("userText").value;
13:       console.log(v);
14:       toid = setTimeout(startLogging, 0);
15:     }
16:
17:     function stopLogging() {
18:       if (toid !== null) {
19:         clearTimeout(toid);
20:         toid = null;
21:       }
22:     }
23:   </script>
24: </html>
```

## cache-client.js

```
01: import Cache from "./cache-v1.mjs";
02:
03: const cache = new Cache("memory");
04: cache.on(
05:   "connected",
06:   () => console.log("cache connected")
07: );
08: cache.on(
09:   "error",
10:   (err) => console.log(err)
11: );
```

## cache-v1.mjs

```
01: import { EventEmitter } from "node:events";
02: import { open } from "fs/promises";
03:
04: export default class Cache extends EventEmitter {
05:   constructor(type) {
06:     super();
07:     switch (type) {
08:       case "memory":
09:         this._memCache = new Map();
10:         this.emit("connected");
11:         break;
12:       case "file":
13:         open("./cache-file.txt", "w+")
14:           .then((fileHandle) => {
15:             this._fileCache = fileHandle;
16:             this.emit("connected");
17:           })
18:           .catch((err) => this.emit("error", err));
19:         break;
20:       default:
21:         throw new Error("invalid type");
22:     }
23:   }
24: }
```

## batch-requests.js

```
01: const messageQueue = [];  
02:  
03: let sendMessage = (message) => {  
04:   messageQueue.push(message);  
05:  
06:   if (messageQueue.length === 1) {  
07:     queueMicrotask(() => {  
08:       const json = JSON.stringify(messageQueue);  
09:       messageQueue.length = 0;  
10:       fetch("url-of-receiver", json);  
11:     });  
12:   }  
13: };
```