OpenClaw Social Pipeline

Complete Documentation

Version: 1.0.0 **Date:** April 2026 **Repository:** github.com/seantunley/openclaw-social-pipeline

---

Table of Contents

1. Overview
2. Architecture
3. Installation
4. Configuration
5. The Content Pipeline
6. Dashboard Guide
7. Agent Tool Reference
8. Skills Reference
9. Postiz Integration
10. Supported Platforms
11. API Reference
12. Troubleshooting

---

1. Overview

The OpenClaw Social Pipeline is a native OpenClaw plugin that provides end-to-end social media content creation and publishing. It handles everything from research and content generation to approval workflows, scheduling, and analytics — all orchestrated through OpenClaw's agent system.

What It Does

- **Researches** topics and trends, saves findings to a browsable library
- **Generates** multiple content draft variants using AI
- **Applies Marketing Psychology** — 30+ behavioral persuasion principles
- **Humanizes** content — detects and rewrites 29 AI writing patterns
- **Optimizes for SEO & GEO** — platform search discoverability + AI search citation
- **Generates images and videos** — fal.ai integration with editorial-quality prompt engineering
- **Manages approvals** — human review gate before any publishing
- **Publishes via Postiz** — media upload, scheduling, and publishing to 11 platforms
- **Tracks analytics** — pulls performance data back from Postiz
- **Learns continuously** — extracts patterns from edits, rejections, and analytics to improve future content

Key Components

Component	Purpose
OpenClaw Plugin	55 agent-facing tools, registered via `openclaw.plugin.json`
Lobster Workflows	Deterministic pipeline execution (research → publish)
Task Flow	Durable state tracking across 20 pipeline statuses
Dashboard	Standalone React app for operators (localhost:3001)
Dashboard API	Fastify REST server backing the dashboard (localhost:3000)
4 Vendored Skills	Humanizer, Marketing Psychology, Content Learning, Social SEO & GEO
Postiz Adapter	Swappable CLI/API integration for publishing

2. Architecture

System Diagram

```
                    OpenClaw Agent
                         |
                    55 Plugin Tools
                         |
         ┌───────────────┼───────────────┐
         |               |               |
    Lobster Workflows  Task Flow    Skills (4)
    (3 YAML files)   (State Machine)    |
         |               |         ┌────┴────┐
         |               |    Humanizer  Marketing
         |               |    SEO/GEO    Psychology
         |               |    Learning
         |               |
    ┌────┴────┐     ┌────┴────┐
    |         |     |         |
Pipeline   Media  Approval  Analytics
Service   Service Service   Service
    |         |
    |    fal.ai (images/video)
    |
    └── Postiz Adapter ──┐
              |               |
         CLI Adapter    API Adapter
              |               |
         Postiz CLI     Postiz REST API
              |               |
              └───────┬───────┘
                      |
            11 Social Platforms
```

Data Flow

```
Research → Psychology → Draft Variants → Score → Select → Humanize
    → SEO/GEO → Compliance → Media Gen → Approval → Postiz Upload
```

```
→ Create Post → Schedule → Publish → Analytics Sync → Learning
```

Technology Stack

Layer	Technology
Plugin Runtime	TypeScript, Node.js
Database	SQLite via Drizzle ORM
API Server	Fastify + CORS
Dashboard	React 18, Vite, Tailwind CSS, TanStack Query, Recharts
LLM	Anthropic Claude SDK
Media Generation	fal.ai (nano-banana-2, Kling v3, Wan 2.7, Sora 2, LongCat)
Publishing	Postiz API / CLI

---

3. Installation

Prerequisites

- Node.js 18+
- npm
- An OpenClaw workspace (or standalone mode)

Install as OpenClaw Plugin

```
cd your-openclaw-workspace/plugins
git clone https://github.com/seantunley/openclaw-social-pipeline.git
cd openclaw-social-pipeline/plugins/openclaw-social-pipeline
npm install
npm run build
```

Reference in your OpenClaw agent configuration:

```
{
  "plugins": ["./plugins/openclaw-social-pipeline"]
}
```

Environment Variables

Create a `.env` file in the plugin directory:

```
# Required
ANTHROPIC_API_KEY=sk-ant-...          # LLM content generation

# Required for publishing
POSTIZ_API_KEY=your-postiz-api-key    # Postiz publishing
POSTIZ_API_BASE_URL=https://app.postiz.com/api

# Required for media generation (when fal.ai is selected)
FAL_API_KEY=your-fal-key              # fal.ai image/video generation

# Optional
```

```
IMGBB_API_KEY=your-imgbb-key         # Permanent image hosting
DATABASE_PATH=./data/social-pipeline.db
API_PORT=3000
DASHBOARD_PORT=3001
IMAGE_PROVIDER=fal                    # 'fal' or leave empty
VIDEO_PROVIDER=fal                    # 'fal' or leave empty
```

Run the Dashboard

```
# Terminal 1: API server
cd plugins/openclaw-social-pipeline
npm run start:api

# Terminal 2: Dashboard
cd dashboard/social-pipeline-dashboard
npm install
npm run dev
```

Dashboard opens at **http://localhost:3001** API runs at **http://localhost:3000**

4. Configuration

All settings are configurable via the **Settings** page in the dashboard or through the `social_config_set` agent tool.

General Settings

Setting	Default	Description
Default Platforms	`["linkedin"]`	Platforms for new content runs
Max Variants	3	Draft variants generated per run
Approval Before Schedule	`true`	Require approval before scheduling
Approval Before Publish	`true`	Require approval before publishing

Humanizer Settings

Setting	Default	Description
Enabled	`true`	Run humanizer on all drafts
Aggressiveness	5	1-10 scale (1=light fixes, 10=full rewrite)

Marketing Psychology Settings

Setting	Default	Description
Enabled	`true`	Apply psychology principles to drafts
Default Intensity	5	1-10 scale (1=subtle, 10=maximum persuasion)

Media Generation Settings

Setting	Default	Description
Default Mode	`image`	`image` , `video` , `both` , or `none`
Provider	`fal`	`fal` for fal.ai integration
Image Model	`nano-banana-2`	fal.ai image model
Video Model	`kling-v3`	`kling-v3` , `wan-2.7` , `sora-2` , `longcat`

Postiz Settings

Setting	Default	Description
Adapter Mode	`api`	`api` or `cli`
API Base URL	(from env)	Postiz API endpoint
Analytics Sync Frequency	`6h`	How often to pull analytics

Pipeline Settings

Setting	Default	Description
Stage Retry Limit	`3`	Max retries per failed stage
Auto Analytics Sync	`true`	Automatically sync analytics
Nightly Summary Job	`false`	Run daily performance summary

5. The Content Pipeline

Pipeline Stages

The Lobster workflow executes these stages in order:

#	Stage	Status	Description
1	**Collect**	`collecting`	Gathers content brief, campaign context
2	**Research**	`researching`	Researches topic, audience, trends. Saves to Research Library
3	**Marketing Psychology**	`applying_psychology`	Applies 30+ persuasion principles
4	**Draft Variants**	`drafting`	Generates multiple content versions
5	**Score & Select**	`scoring`	Ranks drafts on relevance, engagement, clarity, brand fit
6	**Humanize**	`humanizing`	Removes 29 AI writing patterns
7	**SEO & GEO**	`checking_compliance`	Optimizes for platform search + AI citation
8	**Compliance**	`checking_compliance`	Brand voice and tone validation
9	**Media Generation**	`generating_media`	Creates images/video via fal.ai
10	**Approval**	`awaiting_approval`	Pauses for human review
11	**Upload to Postiz**	`uploading_to_postiz`	Uploads media assets
12	**Create Post**	`creating_post`	Creates the post in Postiz
13	**Schedule**	`scheduled`	Schedules for publishing
14	**Publish**	`published`	Post goes live
15	**Analytics Sync**	`analytics_synced`	Pulls performance data back

Pipeline State Machine

Valid status transitions:

```
queued → collecting → researching → applying_psychology → drafting
→ scoring → humanizing → checking_compliance → generating_media
→ awaiting_approval → approved → uploading_to_postiz → creating_post
```

```
→ scheduled → published → analytics_pending → analytics_synced

Any stage can transition to: failed, cancelled
failed → queued (retry), cancelled
rejected → queued (retry), cancelled
```

Starting a Pipeline Run

Via the agent:

```
"Create a LinkedIn campaign about AI in supply chain for logistics managers"
```

The agent calls `social_campaign_create` → `social_run_create` → pipeline executes automatically.

Via the dashboard: Navigate to Campaigns → Create Campaign → then Runs → New Run.

Via API:

```
POST /api/social/runs
{
  "campaign_id": "...",
  "platform": "linkedin",
  "brief": { "topic": "AI in supply chain", "audience": "logistics managers" },
  "media_mode": "image"
}
```

---

6. Dashboard Guide

The dashboard is a standalone React application at **http://localhost:3001**.

Pages

Overview

The main dashboard showing:

- Pipeline health (total runs, pending approvals, scheduled, published)
- Status breakdown chart
- Recent failures
- Upcoming scheduled posts

Runs

Searchable, filterable list of all content runs.

- Filter by status, platform, campaign
- Click any run to see full detail
- Actions: View, Cancel, Retry

Run Detail

Full pipeline view for a single run:

- Vertical timeline showing all stages with status icons
- Tabbed panels: Brief, Research, Psychology, Drafts, Humanized, Compliance, Media, Approval, Postiz State, Analytics
- Actions: Retry Stage, Regenerate Media, Approve, Reject, Send to Postiz

Approvals

Dedicated approval queue:

- Cards showing content preview, platform, media thumbnail
- Quick actions: Approve, Reject, Request Revision
- Notes input for rejection/revision

Campaigns

Campaign management:

- Create campaigns with target platforms, audience, objectives
- View runs per campaign
- Campaign performance overview

Research Library

Research findings from pipeline runs:

- Expandable rows with topic, brief, angle, sources
- Filter tabs: Pending, Approved, Promoted, Rejected
- **"Create Content Run"** button promotes a finding to a queued run
- Source links with platform badges

Learnings

Content patterns learned from edits, rejections, and analytics:

- Category filters (tone, hook, CTA, vocabulary, etc.)
- Confidence bars showing pattern strength
- Source badges (from edit, rejection, analytics, operator rule)
- **"Add Rule"** button for explicit brand rules (100% confidence)

Media Studio

Image and video gallery:

- Filter by type, run, status
- Expand for prompt text, regenerate controls
- Aspect ratio selection

Schedule (Drag-and-Drop Calendar)

Publishing calendar with three views:

- **Month view** — 42-cell grid with draggable post cards
- **Week view** — Hourly slots with drag-and-drop
- **List view** — Chronological list
- Drag a post to reschedule it
- Color-coded by platform

Inbox

Postiz social inbox — mentions, comments, likes, shares:

- Filter by type: All, Comments, Mentions, Likes, Shares
- Reply inline to any comment
- Like/react to posts
- Platform-colored author badges
- Relative timestamps

Analytics

Performance dashboard:

- Summary cards (impressions, engagement, clicks, CTR)
- Engagement over time line chart
- Performance by platform bar chart

- Top performing posts list

Settings

Full configuration panel:

- General, Humanizer, Marketing Psychology, Media, Postiz, Pipeline sections
- Toggle switches, number inputs, multi-select for platforms
- Save button with confirmation

---

7. Agent Tool Reference

The plugin exposes **55 tools** to the OpenClaw agent. Below is the complete reference.

Campaign Tools

Tool	Parameters	Description
`social_campaign_create`	`name` , `description` , `target_platforms[]` , `audience` , `objective` , `cta_style` , `posting_windows`	Create a new campaign
`social_campaign_update`	`id` , `...partial fields`	Update a campaign
`social_brief_create`	`campaign_id` , `platform` , `topic` , `audience_segment` , `goal` , `tone` , `cta`	Create a content brief
`social_brief_list`	`campaign_id?`	List briefs

Example conversation:

> ***User:*** *"Create a campaign for our Q2 product launch on LinkedIn and Twitter"* ***Agent:*** `social_campaign_create({ name: "Q2 Product Launch", target_platforms: ["linkedin", "twitter"], objective: "product_launch" })`

Run Tools

Tool	Parameters	Description
`social_run_create`	`campaign_id` , `platform` , `brief{}` , `media_mode?`	Create a content run
`social_run_list`	`status?` , `campaign_id?` , `platform?` , `limit?` , `offset?`	List runs with filters
`social_run_get`	`run_id`	Full run detail with all stages
`social_run_retry_stage`	`run_id` , `stage_name`	Retry a failed stage
`social_run_cancel`	`run_id`	Cancel a run

Example conversation:

> ***User:*** *"What's the status of our pipeline?"* ***Agent:*** `social_run_list({ status: "awaiting_approval" })` → *"You have 3 runs waiting for approval..."*

Drafting Tools

Tool	Parameters	Description
`social_research_generate`	`run_id`	Generate research for a run
`social_draft_generate`	`run_id` , `variant_count?`	Generate draft variants
`social_draft_score`	`run_id`	Score all drafts
`social_draft_select`	`run_id` , `draft_id`	Select a draft

Skill Application Tools

Tool	Parameters	Description
`social_apply_marketing_psychology`	`run_id` , `principles?[]` , `intensity?`	Apply psychology principles
`social_apply_humanizer`	`run_id` , `aggressiveness?`	Remove AI writing patterns

Media Tools

Tool	Parameters	Description
`social_image_generate`	`run_id` , `prompt?` , `aspect_ratio?`	Generate image via fal.ai
`social_video_generate`	`run_id` , `prompt?` , `aspect_ratio?` , `duration?`	Generate video via fal.ai
`social_media_regenerate`	`run_id` , `asset_id` , `new_prompt?`	Regenerate specific media
`social_media_select`	`run_id` , `asset_id`	Select media for the run

fal.ai Models:

Type	Model	Max Duration	Quality
Image	`nano-banana-2`	—	Editorial photography quality
Video	`kling-v3` (default)	10s	Best quality/cost
Video	`wan-2.7`	15s	Smooth motion

Video	`sora-2`	25s	Premium quality
Video	`longcat`	60s	Long-form content

Approval Tools

Tool	Parameters	Description
`social_submit_for_approval`	`run_id`	Submit for human review
`social_approve`	`run_id` , `reviewer` , `notes?`	Approve content
`social_reject`	`run_id` , `reviewer` , `notes`	Reject content
`social_request_revision`	`run_id` , `reviewer` , `notes` , `rerun_stages?[]`	Request changes

Example conversation:

> ***User:*** *"Approve the LinkedIn post about supply chain AI"* ***Agent:*** `social_approve({ run_id: "...", reviewer: "Sean", notes: "Good to go" })`

Postiz Publishing Tools

Tool	Parameters	Description
`social_postiz_auth_status`	—	Check Postiz connection
`social_postiz_integrations_list`	—	List connected platforms
`social_postiz_upload_media`	`run_id` , `asset_id`	Upload media to Postiz
`social_postiz_create_post`	`run_id` , `integration_id` , `content?`	Create post in Postiz
`social_postiz_schedule_post`	`run_id` , `post_id` , `scheduled_for`	Schedule post
`social_postiz_set_post_status`	`post_id` , `status`	Update post status
`social_postiz_list_posts`	`integration_id?` , `status?`	List posts
`social_postiz_post_analytics`	`post_id`	Get post analytics
`social_postiz_platform_analytics`	`integration_id` , `start_date?` , `end_date?`	Platform analytics

Inbox Tools

Tool	Parameters	Description
`social_inbox_status`	—	Check if inbox is available
`social_inbox_list`	`page?` , `filter?`	List notifications (comments, mentions, likes, shares)
`social_inbox_post_comments`	`post_id`	Get comments for a post
`social_inbox_reply`	`post_id` , `content` , `comment_id?`	Reply to a comment
`social_inbox_react`	`post_id` , `reaction?`	Like/react to a post

Example conversation:

> ***User:*** *"Check our social inbox"* ***Agent:*** `social_inbox_list({ filter: "mention" })` → *"3 new mentions: @jane on LinkedIn mentioned your AI article..."*

Research Library Tools

Tool	Parameters	Description
`social_research_list`	`status?` , `campaign_id?` , `topic?` , `limit?`	List research findings
`social_research_get`	`research_id`	Full detail of a finding
`social_research_save`	`topic` , `title` , `brief?` , `angle?` , `platforms?[]` , `sources?[]` , `tags?[]`	Save a finding
`social_research_update_status`	`research_id` , `status`	Approve/reject/archive
`social_research_promote`	`research_id` , `platform?` , `campaign_id?`	Promote to content run

Example conversation:

> ***User:*** *"Show me pending research"* ***Agent:*** `social_research_list({ status: "pending" })` → *"5 pending findings..."* ***User:*** *"Promote the supply chain one to a LinkedIn run"* ***Agent:*** `social_research_promote({ research_id: "...", platform: "linkedin" })`

SEO & GEO Tools

Tool	Parameters	Description

`social_seo_geo_score`	`content , platform`	Score for SEO + GEO without modifying
`social_seo_geo_enhance`	`content , platform , context?`	Enhance content for SEO + GEO
`social_seo_geo_generate`	`topic , platform , key_facts?[] , experience_statement? , target_audience?`	Generate SEO/GEO-optimized post from scratch

SEO Scoring (platform search):

- Keyword Optimization (25%)
- Hashtag Strategy (15%)
- Content Discoverability (20%)
- Technical Elements (15%)
- Search Intent Alignment (25%)

GEO Scoring (AI citation):

- Citability (30%)
- Authority / E-E-A-T (25%)
- Structural Clarity (20%)
- Entity Clarity (15%)
- Cross-Platform Amplification (10%)

Content Learning Tools

Tool	Parameters	Description
`social_learning_list`	`category? , platform? , active? , limit?`	List learned patterns
`social_learning_get_applicable`	`platform , campaign_id? , min_confidence?`	Get learnings for prompt injection
`social_learning_extract_from_edit`	`original_draft , edited_draft , platform , run_id?`	Extract patterns from edits
`social_learning_extract_from_feedback`	`notes , action , draft_content? , platform`	Extract from rejections
`social_learning_add_rule`	`category , content , platform? , tags?[]`	Add explicit rule (100% confidence)
`social_learning_deactivate`	`learning_id`	Deactivate a learning

Learning Categories: `tone`, `structure`, `hook`, `cta`, `vocabulary`, `platform`, `topic`, `media`, `timing`, `audience`, `avoidance`, `psychology`

Example conversation:

> ***User:*** *"Add a rule: never use clickbait on LinkedIn"* ***Agent:*** `social_learning_add_rule({ category: "avoidance", content: "Never use clickbait headlines on LinkedIn", platform: "linkedin" })`

Configuration Tools

Tool	Parameters	Description
`social_config_get`	`key?`	Get config or specific key
`social_config_set`	`key`, `value`	Set config value
`social_dashboard_summary`	—	Dashboard summary stats
`social_dashboard_pipeline_state`	—	Current pipeline state

---

8. Skills Reference

Humanizer

Detects and rewrites 29 AI writing patterns. Configured via aggressiveness level (1-10).

Patterns detected: overuse of "delve", "in today's landscape", "it's important to note", "game-changer", excessive hedging, "leverage", "unlock the power of", tricolon abuse, "seamless integration", "cutting-edge", "empower", "revolutionize", em-dash overuse, and 16 more.

Marketing Psychology

Applies 30+ behavioral psychology principles across 6 categories:

- **Attention & Hook:** Pattern Interrupt, Curiosity Gap, Negativity Bias, Specificity, Contrast
- **Trust & Credibility:** Social Proof, Authority, Consistency, Mere Exposure, Halo Effect
- **Engagement & Action:** Loss Aversion, Scarcity, Reciprocity, Zeigarnik Effect, IKEA Effect
- **Memory & Shareability:** Von Restorff Effect, Rhyme-as-Reason, Story Arc, Peak-End Rule, Chunking
- **Emotional Triggers:** Identity Appeal, Aspiration Gap, Belonging, Autonomy, Competence
- **Platform-Specific:** LinkedIn Professional Identity, Twitter Hot Takes, Instagram Visual Metaphor, TikTok Pattern Interrupt, YouTube Curiosity Thumbnail

Social SEO & GEO

Dual optimization for platform search (SEO) and AI search citation (GEO).

SEO: Keyword placement, hashtag strategy (platform-specific counts and mix), discoverability signals, technical elements (alt text, captions), search intent alignment.

GEO: Citability (quotable facts in 134-167 word blocks), E-E-A-T authority signals, structural readability, entity clarity, cross-platform amplification potential.

Includes platform-specific playbooks for LinkedIn, YouTube, Reddit, Instagram, TikTok, Pinterest, and VK.

Content Learning

Continuous learning from operator behavior:

- **Draft edits** → extracts tone, structure, vocabulary patterns
- **Rejections** → extracts avoidance rules from reviewer notes
- **Analytics** → compares top vs bottom performers for winning patterns
- **Operator rules** → explicit rules at 100% confidence

Confidence scoring (0.0-1.0) with monthly decay. Learnings are injected into drafting prompts automatically.

---

9. Postiz Integration

Connection Modes

Mode	When to Use
API (default)	Dashboard + server-side integrations. Set `POSTIZ_API_KEY` and `POSTIZ_API_BASE_URL`
CLI	Local automation via `npx postiz` commands

Supported Operations

- Check authentication status
- List connected platform integrations
- Upload media (images, videos)
- Create posts with media attachments
- Schedule posts for specific times
- Update post status
- Fetch post analytics (impressions, clicks, likes, shares, engagement rate)
- Fetch platform-level analytics

Publishing Flow

```
1. Content approved
2. Media uploaded to Postiz → receives media IDs
3. Post created in Postiz with content + media IDs
4. Post scheduled for configured time slot
5. Postiz publishes at scheduled time
6. Analytics synced back periodically
```

10. Supported Platforms

Platform	ID	Character Limit	Hashtag Strategy
LinkedIn	`linkedin`	3,000	3-5 (broad + niche mix)
Twitter/X	`twitter`	280 / 4,000 (premium)	1-2
Instagram	`instagram`	2,200	5-15 (broad + mid + niche)
Facebook	`facebook`	63,206	1-3
TikTok	`tiktok`	2,200	3-5
YouTube	`youtube`	5,000	3-5 in description
Threads	`threads`	500	1-3
Bluesky	`bluesky`	300	0-2
Pinterest	`pinterest`	500	0 (keyword SEO only)
Reddit	`reddit`	40,000	0 (no hashtags)
VK	`vk`	15,895	3-7

Platform Aspect Ratios

Platform	Image Aspect Ratio	Video Aspect Ratio
Instagram Feed	4:5	4:5
Instagram Reel	9:16	9:16
Instagram Carousel	4:5	—
LinkedIn	1:1	16:9
Twitter/X	16:9	16:9
TikTok	9:16	9:16
YouTube	16:9	16:9
YouTube Short	9:16	9:16
Facebook	1:1	16:9
Pinterest	4:5	9:16

Reddit	16:9	16:9
VK	16:9	16:9

---

11. API Reference

The dashboard API runs on port 3000. All endpoints are prefixed with `/api/social/`.

Runs

Method	Endpoint	Description
GET	`/api/social/runs`	List runs (query: `status`, `campaign_id`, `platform`)
POST	`/api/social/runs`	Create run
GET	`/api/social/runs/:id`	Get run detail
POST	`/api/social/runs/:id/retry-stage`	Retry stage (body: `stage_name`)
POST	`/api/social/runs/:id/cancel`	Cancel run
PATCH	`/api/social/runs/:id/reschedule`	Reschedule (body: `scheduledAt`)

Approvals

Method	Endpoint	Description
POST	`/api/social/runs/:id/approve`	Approve (body: `reviewer`, `notes?`)
POST	`/api/social/runs/:id/reject`	Reject (body: `reviewer`, `notes`)
POST	`/api/social/runs/:id/request-revision`	Request revision

Drafts & Media

Method	Endpoint	Description
POST	`/api/social/runs/:id/regenerate-draft`	Regenerate drafts
POST	`/api/social/runs/:id/regenerate-media`	Regenerate media
POST	`/api/social/runs/:id/select-draft`	Select draft (body: `draft_id`)
POST	`/api/social/runs/:id/select-media`	Select media (body: `asset_id`)

Postiz

Method	Endpoint	Description
GET	`/api/social/postiz/auth-status`	Check Postiz connection
GET	`/api/social/postiz/integrations`	List connected platforms
POST	`/api/social/runs/:id/postiz/upload`	Upload media
POST	`/api/social/runs/:id/postiz/create-post`	Create post
POST	`/api/social/runs/:id/postiz/schedule`	Schedule post
GET	`/api/social/runs/:id/postiz/analytics`	Get analytics

Research

Method	Endpoint	Description
GET	`/api/social/research`	List research (query: `status` , `topic`)
POST	`/api/social/research`	Create research item
GET	`/api/social/research/:id`	Get research detail
PATCH	`/api/social/research/:id`	Update status
POST	`/api/social/research/:id/promote`	Promote to content run
DELETE	`/api/social/research/:id`	Delete

Learnings

Method	Endpoint	Description
GET	`/api/social/learnings`	List learnings (query: `category` , `platform`)
POST	`/api/social/learnings/rule`	Add operator rule
DELETE	`/api/social/learnings/:id`	Deactivate

Inbox

Method	Endpoint	Description
GET	`/api/social/inbox/status`	Check availability
GET	`/api/social/inbox`	List notifications
GET	`/api/social/inbox/post/:postId/comments`	Get comments

POST	/api/social/inbox/post/:postId/reply	Reply
POST	/api/social/inbox/post/:postId/react	React

Config & Summary

Method	Endpoint	Description
GET	/api/social/config	Get full config
PUT	/api/social/config	Update config
GET	/api/social/summary	Dashboard summary
GET	/api/social/health	Health check

12. Troubleshooting

Common Issues

Issue	Solution
Dashboard shows no data	Start the API server: `npm run start:api` in the plugin directory
Settings won't save	Verify API is running and base URL is `/api/social`
fal.ai images not generating	Set `FAL_API_KEY` in `.env` and `IMAGE_PROVIDER=fal`
Postiz connection fails	Verify `POSTIZ_API_KEY` and `POSTIZ_API_BASE_URL` in `.env`
Pipeline stuck at a stage	Use `social_run_retry_stage` or retry from the Run Detail page
No inbox notifications	Connect platforms in Postiz first, then check `POSTIZ_API_KEY`
Learnings not applied	Check confidence > 0.3 and learning is `active: true`

Database Location

Default: `./data/social-pipeline.db` (SQLite)

Override with `DATABASE_PATH` environment variable.

Logs

API server logs to stdout at the configured `LOG_LEVEL` (default: `info`).

Set `LOG_LEVEL=debug` for verbose output.

OpenClaw Social Pipeline | Version 1.0.0 | April 2026 **Repository:** github.com/seantunley/openclaw-social-pipeline **License:** MIT