

HANDOFF PACKET (Claude Code Mastery) — v1

0) TL;DR (8 bullets max)

- **Philosophy Shift:** Success requires treating Claude Code as an OS to be configured, not just a chatbot.
- **Context Strategy:** Use the "**Pointer Pattern**" in CLAUDE.md (index of paths) rather than stuffing full docs.
- **Safety Layer:** Implement **PreToolUse hooks** to block dangerous commands (rm -rf) and inject protocols just-in-time.
- **Automation:** Use **PostToolUse hooks** to auto-format (Prettier/Black) and lint code after every agent edit.
- **Memory:** Externalize state using **beads** (JSONL task tracking) to solve context amnesia and enable session resumption.
- **Discipline:** Enforce TDD and planning via **superpowers** to prevent "drift" and regression bugs.
- **Scale:** Use **Subagents** (Researcher/Implementer split) to keep context windows clean and costs low.
- **Learning:** Adopt "**Instinct**" workflows to auto-extract patterns from git history into reusable SKILL.md files.

1) What matters most (Top 12 findings)

- **The "Pointer Pattern" works best:** CLAUDE.md should contain file paths to docs, not the docs themselves (Source:).
- **Hooks are the nervous system:** They transform the CLI from reactive to proactive (Source:).
- **Subagents reduce hallucinations:** Splitting "Research" from "Implementation" keeps the context clean (Source:).
- **External memory is mandatory:** Native session history is too volatile; use beads or plan.md (Source:).
- **"Read-Me-First" Injection:** Injecting protocol files via hooks right before tool use prevents errors (Source:).
- **Auto-formatting is a non-negotiable:** It saves tokens and interaction turns (Source:).

- **Native Plan Mode is for exploration:** Use manual Markdown plans for execution (Source:).
- **Sandboxing is solvable:** viwo allows safe use of `--dangerously-skip-permissions` via Docker (Source:).
- **Instincts beat explicit rules:** Learning from git history is more scalable than writing rules manually (Source:).
- **Voice input is higher bandwidth:** Speaking complex logic yields better initial prompts (Source:).
- **Parallelism is the future:** Using multiple agents in git worktrees scales output linearly (Source:).
- **Security starts at the prompt:** Use trailofbits/skills to audit code before it's committed (Source:).

2) Practical “Superuser Moves” (Top 15)

- **Move:** Inject "Read-Me-First" Protocols
 - **When to use:** To force the agent to read safety rules *before* editing critical files.
 - **Exact trigger:** PreToolUse hook running `cat.claude/protocols/safety.md`.
 - **Gotcha:** Must use `cat`, not `open`.
 - **Source:**
- **Move:** Auto-Format on Edit
 - **When to use:** To stop wasting turns asking "please run prettier."
 - **Exact trigger:** PostToolUse hook: `prettier --write $CLAUDE_FILE_PATH`.
 - **Gotcha:** Ensure Prettier is in your PATH.
 - **Source:**
- **Move:** The "Beads" Resume
 - **When to use:** Returning to a task after closing the terminal.
 - **Exact trigger:** `/beads:resume` (after `/beads:init`).
 - **Gotcha:** Requires `.beads/` directory to exist.
 - **Source:**
- **Move:** Force "Plan First"
 - **When to use:** Preventing the agent from rushing into coding.
 - **Exact trigger:** `/superpowers:brainstorm` followed by `/superpowers:write-plan`.
 - **Gotcha:** Agent will refuse to code until plan is approved.

- **Source:**
- **Move:** Auto-Extract Instincts
 - **When to use:** Teaching the agent your team's coding style without writing docs.
 - **Exact trigger:** /skill-create (from everything-claude-code).
 - **Gotcha:** Requires a clean git history for best results.
 - **Source:**
- **Move:** Subagent Delegation
 - **When to use:** Analyzing a large repo without polluting main context.
 - **Exact trigger:** "Use the researcher subagent to map the auth flow."
 - **Gotcha:** Subagent must be defined in .claude/agents/.
 - **Source:**
- **Move:** Cost Monitoring Dashboard
 - **When to use:** Tracking token burn in real-time.
 - **Exact trigger:** npx ccusage statusline.
 - **Gotcha:** Requires ccusage installation.
 - **Source:**
- **Move:** Voice Mode Input
 - **When to use:** Dump-ing complex logic quickly.
 - **Exact trigger:** /voicemode:converse.
 - **Gotcha:** Requires local Python 3.10+ environment.
 - **Source:**
- **Move:** Docker Sandbox Run
 - **When to use:** Giving the agent "God Mode" safely.
 - **Exact trigger:** viwo start.
 - **Gotcha:** Docker must be running.
 - **Source:**
- **Move:** One-Shot Context Prime
 - **When to use:** Starting a new session on an old project.
 - **Exact trigger:** /context-prime (via just-prompt).
 - **Gotcha:** Can consume high initial tokens.
 - **Source:**
- **Move:** Parallel Agent Swarm
 - **When to use:** Implementing 3 distinct features at once.
 - **Exact trigger:** /pm:issue-start <id> (via ccpm).
 - **Gotcha:** Requires git worktree setup.
 - **Source:**

- **Move:** Security Audit Gate
 - **When to use:** Before merging any AI-generated code.
 - **Exact trigger:** /code-review (triggers trailofbits skills).
 - **Gotcha:** Activates Semgrep/CodeQL.
 - **Source:**
- **Move:** Theme Customization
 - **When to use:** Differentiating between multiple agent windows.
 - **Exact trigger:** /theme (via tweakcc).
 - **Gotcha:** Purely cosmetic.
 - **Source:**
- **Move:** Manual Plan Mode
 - **When to use:** When you need a persistent plan that survives session clear.
 - **Exact trigger:** "Create a docs/plans/feature-x.md file and keep it updated."
 - **Gotcha:** You must manually tell the agent to update it.
 - **Source:**
- **Move:** "Dangerously Skip" Safe Mode
 - **When to use:** When "Click Fatigue" sets in.
 - **Exact trigger:** claude --dangerously-skip-permissions (ONLY inside viwo container).
 - **Gotcha:** Never run this on bare metal host.
 - **Source:**

3) Configuration + Artifacts Map

- **CLAUDE.md:** Root context file. Controls project rules and path pointers. (Source:)
- **.claude/settings.json:** Global hooks and permissions. Controls PreToolUse and PostToolUse. (Source:)
- **.claude/agents/*.md:** Subagent definitions (YAML frontmatter). Controls delegated personas. (Source:)
- **.beads/issues.jsonl:** Task database. Controls long-term memory of tasks. (Source:)
- **.claude/skills/:** Reusable capabilities. Controls what the agent "knows" how to do. (Source:)

4) Plugins / MCP / Integrations shortlist

- **steveyegge/beads: Must Install.** Solves memory amnesia. Critical for multi-day work.
- **obra/superpowers: Must Install.** Enforces TDD and planning discipline. Prevents bugs.
- **affaan-m/everything-claude-code: Must Install.** The best collection of "Instincts" and patterns.
- **ryoppippi/ccusage: Must Install.** Essential cost tracking to avoid billing shock.
- **mbailey/voicemode: Consider.** High-bandwidth input for complex logic.
- **OverseedAI/viwo: Consider.** Essential for safe autonomous execution via Docker.

5) Security / safety notes (Top 8)

- **Regex Blocking:** Use PreToolUse hooks to regex block edits to .env or *.pem files.
- **Sandboxing:** Run risky agents inside viwo (Docker) to limit blast radius.
- **Click Fatigue:** Constant permission prompts lead to user error; use viwo to safely skip them.
- **Subagent Permissions:** Explicitly deny Write tools to "Researcher" subagents.
- **Prompt Injection:** Be wary of pasting untrusted text into the CLI; hooks can execute arbitrary code.
- **Audit Trails:** Use PostToolUse to log every command executed to a specialized audit log.
- **Worktree Isolation:** Use ccpm to keep agent work isolated in git worktrees, protecting the main branch.
- **Security Skills:** Run trailofbits skills to scan for vulnerabilities before committing.

6) Conflicts / version-sensitive items

- **Native Plan Mode vs. Manual Plans:**
 - *Conflict:* Native mode is ephemeral; manual files are durable.
 - *Verify:* Check if Shift+Tab plan persists after restart (it doesn't).

- *Guess*: Use Manual for long tasks.
- **Permissions vs. Autonomy:**
 - *Conflict*: High security (prompts) kills autonomy.
 - *Verify*: Run a 50-step loop with permissions on vs off.
 - *Guess*: Sandboxing (viwo) is the only viable path for autonomy.
- **Monolith vs. Subagents:**
 - *Conflict*: One agent is easier to manage but hallucinates more.
 - *Verify*: Check token usage on long tasks.
 - *Guess*: Subagents are mandatory for complex projects.

7) Prompt B launchpad

Follow-up Questions:

1. "Generate the specific sed command to insert the 'Read-Me-First' hook into my existing settings.json."
2. "Create a viwo configuration file for a Node.js/TypeScript project."
3. "Write the beads command sequence to initialize a project and create 3 dependency-linked tasks."
4. "Show me the PreToolUse regex to block any edits to files containing 'API_KEY'."
5. "Generate a researcher subagent definition that has access to Grep but not Edit."
6. "Explain how to set up ccusage to alert me when a session costs more than \$5."
7. "Provide a CLAUDE.md template optimized for a Python/Django project using the 'Pointer Pattern'."
8. "What is the exact syntax for the trailofbits security audit command?"
9. "How do I configure voicemode to use a local Whisper model instead of OpenAI?"
10. "Generate a script to auto-commit beads changes to a separate git branch."

Search Terms:

- "Claude Code PreToolUse hook regex examples"
- "steveyegge beads tutorial cli"
- "obra superpowers workflow diagram"
- "claude code viwo docker setup"
- "affaan-m everything-claude-code instincts guide"
- "claude code subagent yaml schema"
- "ryoppippi ccusage configuration"
- "trailofbits claude code skills list"

8) Source pack (Top 15 URLs)

1. <https://github.com/steveyegge/beads> (Task persistence & memory)
2. <https://github.com/obra/superpowers> (SDLC enforcement & TDD)
3. <https://github.com/affaan-m/everything-claude-code> (Instincts & patterns)
4. <https://github.com/hesreallyhim/awesome-claude-code> (Comprehensive resource list)
5. <https://docs.anthropic.com/en/docs/claude-code/hooks> (Official Hooks docs)
6. <https://github.com/OverseedAI/viwo> (Docker sandboxing)
7. <https://github.com/mbailey/voicemode> (Voice control)
8. <https://github.com/ryoppippi/ccusage> (Cost monitoring)
9. <https://github.com/trailofbits/skills> (Security auditing)
10. <https://github.com/automazeio/ccpm> (Project management)
11. <https://code.claude.com/docs/en/sub-agents> (Official Subagents docs)
12. https://www.reddit.com/r/ClaudeAI/comments/1loodjn/claude_code_now_supports_hooks/ (Hooks community discussion)
13. <https://medium.com/@lakshminp/claude-code-hooks-the-feature-youre-ignoring-while-babysitting-your-ai-789d39b46f6c> (Hooks tutorial)
14. <https://github.com/davepoon/claude-code-subagents-collection> (Subagent collection)
15. https://www.reddit.com/r/ClaudeCode/comments/1pyxtad/beads_claude_code_reduced_my_compaction/ (Beads workflow discussion)

9) JSON Appendix (for Labs/NotebookLM)

JSON

```
{
  "key_findings":,
  "superuser_moves":,
  "tools_and_configs":,
  "risks":,
  "open_questions": [
    {"question": "How to persist native Plan Mode?", "why_it_matters": "Native mode is ephemeral, losing long-term plans"}
  ]
}
```