

Competitive Programming Reference

First, solve the problem. Then, write the code.

John Johnson

By

Sergio Gabriel Sanchez Valencia

gabrielsanv97@gmail.com

searleser97

Contents

Coding Resources	5
C++	5
Competitive Programming Template	5
Decimal Precision	5
Double Comparisons With Given Precision	5
Include All Libraries	5
IO Optimization	5
Map Value To Int	5
Number To String	6
Permutations	6
Print Vector	6
Priority Queue Of Object	6
Random	6
Read Line	6
Set of Object	6
Sort Vector Of Object	6
Sort Vector of Pairs	7
Split String	7
String To Int	7
Typedef	7
Unordered Map with pair as key	7
Python	7
Combinations	7
Fast IO	7
Permutations	7
Random	7
Sort List	7
Sort List Of Object	8
BITs Manipulation	8
Bit Count	8
Bits To Int	8
Count Leading Zeroes	8
Count Set Bits	8
Count Trailing Zeroes	8
Divide By 2	8
Is Even	8
Is i-th Bit Set	8
Is Odd	8
Is Power Of 2	8
Least Significant Set Bit	9
Log2	9
Most Significant Set Bit	9
Multiply By 2	9
One's Complement	9
Parity Check	9
Print Bits	9
Set i-th Bit	10
Swap Integer Variables	10
To Lower Case	10
To Upper Case	10
Toggle Case	10
Toggle i-th Bit	10
Two's Complement	10
Unset i-th Bit	10

Geometry	10
Data Structures	10
Circle	10
Point	10
Vector	11
Angle Between Vectors	11
Max Interval Overlap	11
Rotate Vector	11
Graphs	12
Data Structures	12
Union Find	12
Union Find (Partially Persistent)	12
Articulation Points And Bridges	12
Connected Components	13
Flood Fill	13
Heavy Light Decomposition	13
Is Bipartite	14
LCA	14
MST Kruskal	15
MST Prim	15
Strongly Connected Components	16
Topological Sort	16
Topological Sort (All possible sorts)	16
Topological Sort (lowest lexicographically)	17
Cycles	17
Get Some Cycles	17
Has Cycle	17
Flow	17
Max Flow Min Cut Dinic	17
Maximum Bipartite Matching	18
ShortestPaths	18
0 - 1 BFS	18
Bellman Ford	18
Bellman Ford Fast	19
Dijkstra	19
Floyd Warshall	20
Shortest Path in Directed Acyclic Graph	20
Maths	20
Data Structures	20
Matrix	20
Number Theory	21
Binary Exponentiation	21
Divisibility Criterion	21
Divisors	21
Divisors Pollard Rho	21
Euler's Phi	22
Extended Euclidean	22
GCD	22
LCM	22
Modular Exponentiation	22
Modular Multiplication	22
Modulo with negative numbers	22
Primes	23
Is Prime Miller Rabin	23
Prime Factorization	23
Prime Factorization (Sieve)	23
Prime Factorization (Sieve) 2	23
Prime Factorization Pollard Rho	23

Primes Sieve	24
Ranges	24
Data Structures	24
BIT	24
BIT Range Update	25
Segment Tree	25
Segment Tree Lazy Propagation	25
Sparse Table	26
Wavelet Tree	27
Wavelet Tree Compressed	27
Strings	28
Data Structures	28
Suffix Automaton	28
Trie	28
Distinct Substring Count	29
KMP	29
Lexicographically K-th Substring	29
Lexicographically Smallest Cyclic Shift	30
Longest Common Substring of 2 Strings	30
Longest Common Substring of Multiple Strings	30
Number of Occurrences	30
Occurrences Positions	30
Rabin Karp	31
Techniques	31
Binary Search	31
Binary Search	31
Bitonic Search	32
C++ lower bound	32
C++ upper bound	32
Lower Bound	32
Upper Bound	32
Multiple Queries	32
Mo	32
SQRT Decomposition	33
Trees And Heaps	34
Red Black Tree	34
Problems Solved	34
Maths	34
N as Sum of different numbers from 1 to M	34
Extras	35
Data Structures	35
Strings	35
C++	35
Automatic Type Conversions	35
Integer Types Properties	36
Maths	36
Common Sums	36
Logarithm Rules	36

Coding Resources

C++

Competitive Programming Template

```

/*****
https://searleser97.gitlab.io/algorithms/template.cpp
*****/

#include <bits/stdc++.h>
using namespace std;
#define endl '\n'
#define forr(_, x, n) for (int _ = x; ~_; _--)
#define fos(_, x, n, s) for (int _ = x; _ < n; _ += s)
#define forn(_, x, n) fos(_, x, n, 1)
#define rep(_, n) forn(_, 0, n)
#define fi first
#define se second
#define pb push_back
#define pairii pair<int, int>
// typedef __int128_t lli;
typedef long long int li;
typedef long double ld;

void _main(int tc) {

}

int main() {
    ios_base::sync_with_stdio(0), cin.tie(0);
    _main(0);
    return 0;
    int tc;
    cin >> tc;
    rep(i, tc) _main(i + 1);
}

```

Decimal Precision

```

// rounds up the decimal number
cout << setprecision(N) << n << endl;
// specify N fixed number of decimals
cout << fixed << setprecision(N) << n << endl;

```

Double Comparisons With Given Precision

```

typedef long double ld;
const ld eps = 1e-9;

bool eq(ld a, ld b) { return abs(a - b) <= eps; }
bool neq(ld a, ld b) { return abs(a - b) > eps; }
bool gr(ld a, ld b) { return a - b > eps; }
bool le(ld a, ld b) { return b - a > eps; }
bool geq(ld a, ld b) { return a - b >= -eps; }
bool leq(ld a, ld b) { return b - a >= -eps; }

```

Include All Libraries

```

#include <bits/stdc++.h>
using namespace std;

```

IO Optimization

```

int main() {
    ios_base::sync_with_stdio(0);
    cin.tie(0);
}

```

Map Value To Int

```

// val = value
typedef string Val;
unordered_map<Val, int> intForVal;
unordered_map<int, Val> valForInt;
int mapId = 0;

int Map(Val val) {
    if (intForVal.count(val)) return intForVal[val];
    valForInt[mapId] = val;
    return intForVal[val] = mapId++;
}

```

```

Val IMap(int n) { return valForInt[n]; }

```

```

void initMapping() {
    mapId = 0;
    intForVal.clear();
    valForInt.clear();
}

```

Number To String

```
#include <bits/stdc++.h>
using namespace std;

int main() {
    // to_string method converts any type of number
    // (int, double, long long int, ...) to string
    string str = "str" + to_string(123 + 1);
    cout << str << endl; // output: str+124
    return 0;
}
```

Permutations

```
typedef vector<int> T; // typedef string T;

vector<T> permutations(T v) {
    vector<vector<int>> ans;
    sort(v.begin(), v.end());
    do
        ans.push_back(v);
    while (next_permutation(v.begin(), v.end()));
    return ans;
}
```

Print Vector

```
void printv(vector<int> v) {
    if (v.size() == 0) {
        cout << "[]" << endl;
        return;
    }
    cout << "[" << v[0];
    for (int i = 1; i < v.size(); i++)
        cout << ", " << v[i];
    cout << "]" << endl;
}
```

Priority Queue Of Object

```
struct Object {
    char first;
    int second;
};

int main() {
    auto cmp = [](const Object& a, const Object& b) {
        return a.second > b.second;
    };
    priority_queue<Object, vector<Object>,
        decltype(cmp)>
        pq(cmp);
}
```

Random

```
mt19937_64 seed(chrono::steady_clock::now()
    .time_since_epoch()
    .count());

int random(int min, int max) { // [min, max]
    return uniform_int_distribution<int>(min,
        max)(seed);
}

double random(double min, double max) { // [min, max]
    return uniform_real_distribution<double>(min,
        max)(seed);
}
```

Read Line

```
// when reading lines, don't mix 'cin' with
// 'getline' just use getline and split
string input() {
    string ans;
    cin >> ws;
    cin.ignore(numeric_limits<streamsize>::max(), '\n');
    getline(cin, ans);
    return ans;
}
```

Set of Object

```
struct Object {
    char first;
    int second;
};

int main() {
    auto cmp = [](const Object& a, const Object& b) {
        return a.second > b.second;
    };
    set<Object, decltype(cmp)> pq(cmp);
}
```

Sort Vector Of Object

```
struct Object {
    char first;
    int second;
};

bool cmp(const Object& a, const Object& b) {
    return a.second > b.second;
}

int main() {
    vector<Object> v = {{'c', 3}, {'a', 1}, {'b', 2}};
    sort(v.begin(), v.end(), cmp);
}
```

Sort Vector of Pairs

```
vector<pair<int, int>> pairs;
// sorts array on the basis of the first element
sort(pairs.begin(), pairs.end());
```

Split String

```
vector<string> split(string str, char token) {
    stringstream ss(str);
    vector<string> v;
    while (getline(ss, str, token)) v.push_back(str);
    return v;
}
```

String To Int

```
#include <bits/stdc++.h>
using namespace std;

int main() {
    int n = stoi("123") + 1;
    cout << n << endl; // output: 124
    // stoll for long long int
    // stoull for unsigned long int
    // stod for double
    // stold for long double
}
```

Typedef

```
typedef TYPE ALIAS;
// example:
typedef int T;
```

Unordered Map with pair as key

```
typedef int T;

struct pairhash {
    template <class T1, class T2>
    size_t operator()(const pair<T1, T2> &p) const {
        return hash<T1>{}(p.first) ^
            (hash<T2>{}(p.second) << 32);
    }
};

int main() {
    unordered_map<pair<int, int>, T, hash_pair> um;
    um[{1, 2}] = 5;
    cout << um[{1, 2}] << endl;
}
```

Python

Combinations

```
import itertools
# from arr choose k = > combinations(arr, k)
print(list(itertools.combinations([1, 2, 3], 3)))
```

Fast IO

```
from sys import stdin, stdout

N = 10
# Reads N chars from stdin(it counts '\n' as char)
stdin.read(N)
# Reads until '\n' or EOF
line = stdin.readline()
# Reads all lines in stdin until EOF
lines = stdin.readlines()
# Writes a string to stdout, it doesn't add '\n'
stdout.write(line)
# Writes a list of strings to stdout
stdout.writelines(lines)
# Reads numbers separated by space in a line
numbers = list(map(int, stdin.readline().split()))
```

Permutations

```
import itertools
print(list(itertools.permutations([1, 2, 3])))
```

Random

```
import random
# Initialize the random number generator.
random.seed(None)
# Returns a random integer N such that a <= N <= b.
random.randint(a, b)
# Returns a random integer N such that 0 <= N < b
random.randrange(b)
# Returns a random integer N such that a <= N < b.
random.randrange(a, b)
# Returns and integer with k random bits.
random.getrandbits(k)
# shuffles a list
random.shuffle(li)
```

Sort List

```
li = ['a', 'c', 'b']
# sorts inplace in descending order
li.sort(reverse=True)
# returns sorted list ascending order
ol = sorted(li)
```

Sort List Of Object

```
class MyObject :
    def __init__(self, first, second, third):
        self.first = first
        self.second = second
        self.third = third

li = [MyObject('b', 3, 1), MyObject('a', 3, 2),
      ↪ MyObject('b', 3, 3)]
# returns list sorted by first then by second then by
↪ third in increasing order
ol = sorted(li, key = lambda x: (x.first, x.second,
    ↪ x.third), reverse=False)
# sorts inplace by first then by second then by third
↪ in increasing order
li.sort(key = lambda x: (x.first, x.second, x.third),
    ↪ reverse=False)
```

BITS Manipulation

Bit Count

```
int bitCount(int n) {
    return sizeof(n) * 8 - __builtin_clz(n);
}

int bitCount(int n) {
    int c = 0;
    while (n) c++, n >>= 1;
    return c;
}
```

Bits To Int

```
typedef __int128_t lli

lli bitsToInt(string bits, bool isneg) {
    lli ans = 0;
    for (int i = bits.size() - 1, j = 0; ~i; i--, j++) {
        if (isneg) bits[i] = bits[i] == '0' ? '1' : '0';
        ans |= (lli)(bits[i] - '0') << j;
    }
    return isneg ? -(++ans) : ans;
}
```

Count Leading Zeroes

```
int clz(int n) {
    return __builtin_clz(n);
    // return __builtin_clzl(n); for long
    // return __builtin_clzll(n); for long long
}
```

```
int clz(int n) {
    // return sizeof(n) * 8 - bitCount(n);
    int c = 0;
    while (n) c++, n >>= 1;
    return sizeof(n) * 8 - c;
}
```

Count Set Bits

```
int popCount(int n) {
    return __builtin_popcount(n);
    // return __builtin_popcountl(n); for long
    // return __builtin_popcountll(n); for long long
}

int popCount(int n) {
    int c = 0;
    while (n) c++, n &= n - 1;
    return c;
}
```

Count Trailing Zeroes

```
int ctz(int n) {
    return __builtin_ctz(n);
    // return __builtin_ctzl(n); for long
    // return __builtin_ctzll(n); for long long
}

int ctz(int n) {
    int c = 0;
    n = ~n;
    while(n & 1) c++, n >>= 1;
    return c;
}
```

Divide By 2

```
int divideBy2(int n) { return n >> 1; }
```

Is Even

```
bool isEven(int n) { return ~n & 1; }
```

Is i-th Bit Set

```
bool isIthBitSet(int n, int i) {
    return n & (1 << i);
}
```

Is Odd

```
bool isOdd(int n) { return n & 1; }
```

Is Power Of 2

```
bool isPowerOf2(int n) { return n && !(n & (n - 1)); }
```


Least Significant Set Bit

First thing we need to notice is that when we add 1 to a number N , what we are doing is just converting the first (right to left) 0-bit into a 1-bit and the 1-bits before get converted to 0-bits because $1 + 1 = 0$ with carry of 1 in binary, therefore we will be having a carry of 1-bit until we find a 0-bit.

Example:

$$00100111 + 1 = 00101000$$

Second thing we need to notice is very simple, let's start by denoting \overline{N} as N with all its bits inverted (1-bits change to 0-bit and viceversa), if we perform an *AND* operation between N and \overline{N} we will get all bits in 0 as result.

Example:

$$N = 00100111$$

$$\overline{N} = 11011000$$

So, to achieve our main objective which is to extract the least significant bit (rightmost bit) we can just invert N and add 1 to it that will convert the first 0-bit to 1-bit so if we make an *AND* operation with N and \overline{N} we get everything before the lsb as 0-bit and after the lsb we also get everything as 0-bit.

And we can write this as the 2's complement since what we did was just to invert bits and add one, which is just the exact definition of 2's complement.

C++ Code:

```
int lsb(int n) {
    return n & -n;
}
```

Log2

```
int Log2(int n) {
    return sizeof(n) * 8 - __builtin_clz(n) - 1;
}
```

```
int Log2(int n) {
    int lg2 = 0;
    while (n >= 1) lg2++;
    return lg2;
}
```

Most Significant Set Bit

```
int msb(int n) {
    return 1 << (sizeof(n) * 8 - __builtin_clz(n) - 1);
}
```

Multiply By 2

```
int multiplyBy2(int n) { return n << 1; }
```

One's Complement

```
int onesComplement(int n) { return ~n; }
```

Parity Check

```
bool parityCheck(int n) {
    return !__builtin_parity(n);
    // return !__builtin_parityl(n); for long
    // return !__builtin_parityll(n); for long long
}
```

```
bool parityCheck(int n) {
    return isEven(popCount(n));
}
```

Print Bits

```
void printBits(int n) {
    for (int i = sizeof(n) * 8 - 1; ~i; i--)
        cout << ((n >> i) & 1);
    cout << endl;
}
```

Set i-th Bit

```
int setIthBit(int n, int i) { return n | (1 << i); }
```

Swap Integer Variables

```
void swap(int &a, int &b) {
    a ^= b;
    b ^= a;
    a ^= b;
}
```

To Lower Case

```
char lowerCase(char c) {
    return c | ' ';
}
```

To Upper Case

```
char upperCase(char c) {
    return c & '_';
}
```

Toggle Case

```
char toggleCase(char c) {
    return c ^ ' ';
}
```

Toggle i-th Bit

```
int toggleIthBit(int n, int i) {
    return n ^ (1 << i);
}
```

Two's Complement

```
int twosComplement(int n) { return ~n + 1; }
```

Unset i-th Bit

```
int unsetIthBit(int n, int i) {
    return n & ~(1 << i);
}
```

Geometry

Data Structures

Circle

```
// c = center, r = radius;
#include "Point.cpp"
```

```
struct Circle {
    Point c;
    ld r;
    Circle(Point c, ld r) : c(c), r(r) {}
};
```

Point

```
#include "../Coding Resources/C++/Double
↳ Comparisons With Given Precision.cpp"
```

```
const ld pi = acos(-1);
```

```
struct Point {
    ld x, y;
    Point() : x(0), y(0) {}
    Point(ld x, ld y) : x(x), y(y) {}

    Point operator+(const Point &p) {
        return Point(x + p.x, y + p.y);
    }

    Point operator-(const Point &p) {
        return Point(x - p.x, y - p.y);
    }

    Point operator*(const ld &k) {
        return Point(x * k, y * k);
    }

    Point operator/(const ld &k) {
        return Point(x / k, y / k);
    }

    bool operator==(const Point &p) {
        return eq(x, p.x) && eq(y, p.y);
    }

    bool operator!=(const point &p) const {
        return !(*this == p);
    }

    bool operator<(const point &p) const {
        if (eq(x, p.x)) return le(y, p.y);
        return le(x, p.x);
    }
}
```

```

bool operator>(const point &p) const {
    if (eq(x, p.x)) return gr(y, p.y);
    return gr(x, p.x);
}

ld norm() { return sqrt(x * x + y * y); }

ld dot(const Point &p) { return x * p.x + y * p.y; }

ld cross(const Point &p) {
    return x * p.y - y * p.x;
}

Point perpendicularLeft() { return Point(-y, x); }

Point perpendicularRight() { return Point(y, -x); }

Point rotate(ld deg) {
    ld rad = (deg * pi) / 180.0;
    return Point(x * cos(rad) - y * sin(rad),
                x * sin(rad) + y * cos(rad));
}

Point unit() { return (*this) / norm(); }
};

```

Vector

```
#include "Point.cpp"
```

```

struct Vect {
    Point u, v;
    Vect(const Point& from, const Point& to)
        : u(from), v(to) {}
};

```

Angle Between Vectors

```
double angleBetween(Point& a, Point&)
```

Max Interval Overlap

```

typedef long long int T;
typedef pair<T, T> Interval;
vector<Interval> maxIntervals;

```

```

// O(N * lg(N))
int maxOverlap(vector<Interval> &arr) {
    maxIntervals.clear();
    map<T, int> m;
    int maxI = 0, curr = 0, isFirst = 1;
    T l = -1LL, r = -1LL;
    for (auto &i : arr) m[i.first]++, m[i.second + 1]--;
    for (auto &p : m) {
        curr += p.second;
        if (curr > maxI) maxI = curr, l = p.first;
        if (curr == maxI) r = p.first;
    }
    curr = 0;
    for (auto &p : m) {
        curr += p.second;
        if (curr == maxI && isFirst)
            l = p.first, isFirst = 0;
        if (curr < maxI && !isFirst)
            maxIntervals.push_back({l, p.first - 1}),
                isFirst = 1;
    }
    return maxI;
}

```

```

// O(MaxPoint) maxPoint < vector::max_size
int maxOverlap(vector<Interval> &arr) {
    maxIntervals.clear();
    T maxPoint = 0;
    for (auto &i : arr)
        if (i.second > maxPoint) maxPoint = i.second;
    vector<int> x(maxPoint + 2);
    for (auto &i : arr) x[i.first]++, x[i.second + 1]--;
    int maxI = 0, curr = 0, isFirst = 1;
    T l = -1LL, r = -1LL;
    for (int i = 0; i < x.size(); i++) {
        curr += x[i];
        if (curr > maxI) maxI = curr;
    }
    curr = 0;
    for (int i = 0; i < x.size(); i++) {
        curr += x[i];
        if (curr == maxI && isFirst) l = i, isFirst = 0;
        if (curr < maxI && !isFirst)
            maxIntervals.push_back({l, i - 1}), isFirst = 1;
    }
    return maxI;
}

```

Rotate Vector

```

Point rotate(Point& from, Point& to) {

}

```

Graphs

Data Structures

Union Find

```
struct UnionFind {
    int n;
    vector<int> dad, size;

    UnionFind(int N) : n(N), dad(N), size(N, 1) {
        while (N--) dad[N] = N;
    }

    // O(lg*(N))
    int root(int u) {
        if (dad[u] == u) return u;
        return dad[u] = root(dad[u]);
    }

    // O(1)
    void join(int u, int v) {
        int Ru = root(u), Rv = root(v);
        if (Ru == Rv) return;
        if (size[Ru] > size[Rv]) swap(Ru, Rv);
        --n, dad[Ru] = Rv;
        size[Rv] += size[Ru];
    }

    // O(lg*(N))
    bool areConnected(int u, int v) {
        return root(u) == root(v);
    }

    int getSize(int u) { return size[root(u)]; }

    int numberOfSets() { return n; }
};
```

Union Find (Partially Persistent)

```
// jTime = join time, t = time
struct UnionFind {
    int Time = 0;
    vector<int> dad, size, jTime;

    UnionFind(int N) : dad(N), size(N, 1), jTime(N) {
        while (N--) dad[N] = N;
    }

    // O(lg(N))
    int root(int u, int t) {
        while (jTime[u] <= t && u != dad[u]) u = dad[u];
        return u;
    }
};
```

```
// O(1)
void join(int u, int v, bool newTime = 1) {
    int Ru = root(u, Time), Rv = root(v, Time);
    if (newTime) Time++;
    if (Ru == Rv) return;
    if (size[Ru] > size[Rv]) swap(Ru, Rv);
    jTime[Ru] = Time;
    dad[Ru] = Rv;
    size[Rv] += size[Ru];
}

// O(lg(N))
bool areConnected(int u, int v, int t) {
    return root(u, t) == root(v, t);
}

// O(lg(N))
int getLastVersionSize(int u) {
    return size[root(u, Time)];
}

// O(lg(Time) * lg(N))
int joinTime(int u, int v) {
    int l = 0, r = Time, ans = -1;
    while (l <= r) {
        int mid = (l + r) >> 1;
        if (areConnected(u, v, mid))
            ans = mid, r = mid - 1;
        else
            l = mid + 1;
    }
    return ans;
}
};
```

Articulation Points And Bridges

```
// APB = articulation points and bridges
// Ap = Articulation Point
// br = bridges, p = parent
// disc = discovery time
// low = lowTime, ch = children
// nup = number of edges from u to p

typedef pair<int, int> Edge;
int Time;
vector<vector<int>> adj;
vector<int> disc, low, isAp;
vector<Edge> br;

void init(int N) { adj.assign(N, vector<int>()); }

void addEdge(int u, int v) {
    adj[u].push_back(v);
    adj[v].push_back(u);
}
```

```

int dfsAPB(int u, int p) {
    int ch = 0, nup = 0;
    low[u] = disc[u] = ++Time;
    for (int &v : adj[u]) {
        if (v == p && !nup++) continue;
        if (!disc[v]) {
            ch++, dfsAPB(v, u);
            if (disc[u] <= low[v]) isAp[u]++;
            if (disc[u] < low[v]) br.push_back({u, v});
            low[u] = min(low[u], low[v]);
        } else
            low[u] = min(low[u], disc[v]);
    }
    return ch;
}

// O(N)
void APB() {
    br.clear();
    isAp = low = disc = vector<int>(adj.size());
    Time = 0;
    for (int u = 0; u < adj.size(); u++)
        if (!disc[u]) isAp[u] = dfsAPB(u, u) > 1;
}

```

Connected Components

```

// comp = component
int compId;
vector<vector<int>>> adj;
vector<int> getComp;

void init(int N) {
    adj.assign(N, vector<int>());
    getComp.assign(N, -1);
    compId = 0;
}

void addEdge(int u, int v) {
    adj[u].push_back(v);
    adj[v].push_back(u);
}

void dfsCC(int u, vector<int> &comp) {
    if (getComp[u] > -1) return;
    getComp[u] = compId;
    comp.push_back(u);
    for (auto &v : adj[u]) dfsCC(v, comp);
}

// O(N)
vector<vector<int>>> connectedComponents() {
    vector<vector<int>>> comps;
    for (int u = 0; u < adj.size(); u++) {
        vector<int> comp;
        dfsCC(u, comp);
        if (!comp.empty())
            comps.push_back(comp), compId++;
    }
    return comps;
}

```

Flood Fill

```

int n, m, oldColor = 0, color = 1;
vector<vector<int>>> mat;
vector<vector<int>>> movs = {
    {1, 0}, {0, 1}, {-1, 0}, {0, -1}};

void floodFill(int i, int j) {
    if (i >= mat.size() || i < 0 ||
        j >= mat[i].size() || j < 0 ||
        mat[i][j] != oldColor)
        return;
    mat[i][j] = color;
    for (auto move : movs)
        floodFill(i + move[1], j + move[0]);
}

void floodFill() {
    for (int i = 0; i < n; i++)
        for (int j = 0; j < m; j++)
            if (mat[i][j] == oldColor) floodFill(i, j);
}

```

Heavy Light Decomposition

```

// p = parent;
#include "../Data Structures/Ranges/Segment Tree.cpp"
typedef int T;
vector<vector<int>>> adj;
vector<int> p, heavy, depth, root, stPos, vals;
SegmentTree<T> st(0);

void init(int n) {
    adj.assign(n, vector<int>());
    heavy.assign(n, -1);
    vals.assign(n, 0);
    p = root = stPos = depth = heavy;
    st = SegmentTree<T>(n);
}

void addEdge(int u, int v, T val) {
    adj[u].push_back(v);
    p[v] = u, vals[v] = val;
}

T F(T a, T b) { return a + b; }

// O(N)
int dfs(int u) {
    int size = 1, maxSubtree = 0;
    for (int &v : adj[u]) {
        depth[v] = depth[u] + 1;
        int subtree = dfs(v);
        if (subtree > maxSubtree)
            heavy[u] = v, maxSubtree = subtree;
        size += subtree;
    }
    return size;
}

```

```
// O(N)
void initHeavyLight() {
    for (int i = 0; i < adj.size(); i++)
        if (p[i] < 0) dfs(i);
    for (int i = 0, pos = 0; i < adj.size(); i++)
        if (p[i] < 0 || heavy[p[i]] != i)
            for (int j = i; ~j; j = heavy[j]) {
                st.setValAt(vals[j], stPos[j] = pos++);
                root[j] = i;
            }
    st.build();
}

// O(lg^2(N))
template <class Op>
void processPath(int u, int v, Op op) {
    for (; root[u] != root[v]; v = p[root[v]]) {
        if (depth[root[u]] > depth[root[v]]) swap(u, v);
        op(stPos[root[v]], stPos[v]);
    }
    if (depth[u] > depth[v]) swap(u, v);
    // for values on edges
    if (u != v) op(stPos[u] + 1, stPos[v]);
    // for values on nodes
    // op(stPos[u], stPos[v]);
}

// O(lg^2(N))
void update(int u, int v, T val) {
    processPath(u, v, [&val](int l, int r) {
        st.update(l, r, val);
    });
}

// O(lg^2(N))
T query(int u, int v) {
    T ans = T();
    processPath(u, v, [&ans](int l, int r) {
        ans = F(ans, st.query(l, r));
    });
    return ans;
}
```

Is Bipartite

```
vector<vector<int>> adj;

void init(int N) { adj.assign(N, vector<int>()); }

void addEdge(int u, int v) {
    adj[u].push_back(v);
    adj[v].push_back(u);
}
```

```
// O(N)
bool isBipartite() {
    vector<int> color(adj.size(), -1);
    for (int s = 0; s < adj.size(); s++) {
        if (color[s] > -1) continue;
        color[s] = 0;
        queue<int> q;
        q.push(s);
        while (!q.empty()) {
            int u = q.front();
            q.pop();
            for (int &v : adj[u]) {
                if (color[v] < 0)
                    q.push(v), color[v] = !color[u];
                if (color[v] == color[u]) return false;
            }
        }
    }
    return true;
}
```

LCA

```
// st = sparse table, p = parent
typedef pair<int, int> T;
int neutro = 0;
vector<vector<T>> st;
vector<int> first;
vector<T> tour;
vector<vector<int>> adj;

void init(int N) { adj.assign(N, vector<int>()); }

void addEdge(int u, int v) {
    adj[u].push_back(v);
    adj[v].push_back(u);
}

T F(T a, T b) { return a.first < b.first ? a : b; }

void build() {
    st.assign(log2(tour.size()),
              vector<T>(tour.size()));
    st[0] = tour;
    for (int i = 1; (1 << i) <= tour.size(); i++)
        for (int j = 0; j + (1 << i) <= tour.size(); j++)
            st[i][j] = F(st[i - 1][j],
                          st[i - 1][j + (1 << (i - 1))]);
}

void eulerTour(int u, int p, int h) {
    first[u] = tour.size();
    tour.push_back({h, u});
    for (int v : adj[u])
        if (v != p) {
            eulerTour(v, u, h + 1);
            tour.push_back({h, u});
        }
}
```

```
// O(N * lg(N))
void preprocess() {
    tour.clear();
    first.assign(adj.size(), -1);
    vector<int> roots = {0};
    for (auto &root : roots) eulerTour(root, -1, 0);
    build();
}

// O(1)
int lca(int u, int v) {
    int l = min(first[u], first[v]);
    int r = max(first[u], first[v]);
    int i = log2(r - l + 1);
    return F(st[i][l], st[i][r + 1 - (1 << i)]).second;
}
```

MST Kruskal

```
// N = number of nodes, Wedge = Weighted Edge
#include "../Data Structures/Graphs/UnionFind.cpp"
typedef int T;
typedef pair<int, int> Edge;
typedef pair<T, Edge> Wedge;
vector<Wedge> Wedges;
vector<Wedge> mst;
UnionFind uf(0);

void init(int N) {
    mst.clear();
    Wedges.clear();
    uf = UnionFind(N);
}

void addEdge(int u, int v, T w) {
    Wedges.push_back({w, {u, v}});
}

T kruskal() {
    T cost = 0;
    sort(Wedges.begin(), Wedges.end());
    // reverse(Wedges.begin(), Wedges.end());
    for (Wedge &wedge : Wedges) {
        int u = wedge.second.first,
            v = wedge.second.second;
        if (!uf.areConnected(u, v))
            uf.join(u, v), mst.push_back(wedge),
            cost += wedge.first;
    }
    return cost;
}
```

MST Prim

```
// st = spanning tree, p = parent
// vis = visited, dist = distance
typedef int T;
typedef pair<int, int> Edge;
typedef pair<T, Edge> Wedge;
typedef pair<T, int> DistNode;
long long int inf = (1ll << 62) - 1;
vector<vector<int>> adj;
unordered_map<int, unordered_map<int, T>> weight;
vector<int> p, vis;
vector<T> dist;
vector<vector<Wedge>> msts;

void init(int N) {
    adj.assign(N, vector<int>());
    p.assign(N, 0);
    vis.assign(N, 0);
    dist.assign(N, inf);
    weight.clear();
    msts.clear();
}

void addEdge(int u, int v, T w) {
    adj[u].push_back(v);
    weight[u][v] = w;
    adj[v].push_back(u);
    weight[v][u] = w;
}

// ~ O(E * log(V))
T prim(int s) {
    vector<Wedge> mst;
    vector<T> dist(adj.size(), inf);
    priority_queue<DistNode> q;
    T cost = dist[s] = 0;
    q.push({0, s});
    while (q.size()) {
        pair<int, int> aux = q.top();
        int u = aux.second;
        q.pop();
        if (dist[u] < -aux.first) continue;
        vis[u] = 1, cost += dist[u];
        mst.push_back({dist[u], {p[u], u}});
        for (int &v : adj[u]) {
            T w = weight[u][v];
            if (!vis[v] && w < dist[v])
                q.push({-(dist[v] = w), v});
        }
    }
    msts.push_back(
        vector<Wedge>(mst.begin() + 1, mst.end()));
    return cost;
}
```

```
// O(V + E * log(V))
T prim() {
    T cost = 0;
    map<int, T> q;
    for (int i = 0; i < adj.size(); i++)
        if (!vis[i]) cost += prim(i);
    return cost;
}
```

Strongly Connected Components

```
// tv = top value from stack
// sccs = strongly connected components
// scc = strongly connected component
// disc = discovery time, low = low time
// s = stack, top = top index of the stack

int Time, top;
vector<vector<int>> adj, sccs;
vector<int> disc, low, s;

void init(int N) { adj.assign(N, vector<int>()); }

void addEdge(int u, int v) { adj[u].push_back(v); }

void dfsSCCS(int u) {
    if (disc[u]) return;
    low[u] = disc[u] = ++Time;
    s[++top] = u;
    for (int &v : adj[u])
        dfsSCCS(v), low[u] = min(low[u], low[v]);
    if (disc[u] == low[u]) {
        vector<int> scc;
        while (true) {
            int tv = s[top--];
            scc.push_back(tv);
            low[tv] = adj.size();
            if (tv == u) break;
        }
        sccs.push_back(scc);
    }
}

// O(N)
void SCCS() {
    s = low = disc = vector<int>(adj.size());
    Time = 0, top = -1, sccs.clear();
    for (int u = 0; u < adj.size(); u++) dfsSCCS(u);
}
```

Topological Sort

```
// vis = visited
vector<vector<int>> adj;
vector<int> vis, toposorted;
```

```
void init(int N) {
    adj.assign(N, vector<int>());
    vis.assign(N, 0);
    toposorted.clear();
}

void addEdge(int u, int v) { adj[u].push_back(v); }
// returns false if there is a cycle
// O(N)
bool toposort(int u) {
    vis[u] = 1;
    for (auto &v : adj[u])
        if (v != u && vis[v] != 2 &&
            (vis[v] || !toposort(v)))
            return false;
    vis[u] = 2;
    toposorted.push_back(u);
    return true;
}
// O(N)
bool toposort() {
    for (int u = 0; u < adj.size(); u++)
        if (!vis[u] && !toposort(u)) return false;
    return true;
}
```

Topological Sort (All possible sorts)

```
// indeg0 = indegree 0
vector<int> vis, indegree, path;
vector<vector<int>> adj, toposorts;
deque<int> indeg0;
void init(int n) {
    adj.assign(n, vector<int>());
    vis.assign(n, 0);
    indegree = vis;
}
void addEdge(int u, int v) {
    adj[u].push_back(v);
    indegree[v]++;
}
// O(V!)
void dfs() {
    for (int i = 0; i < indeg0.size(); i++) {
        int u = indeg0.front();
        indeg0.pop_front();
        path.push_back(u);
        for (auto &v : adj[u])
            if (!--indegree[v]) indeg0.push_back(v);
        if (!indeg0.size()) toposorts.push_back(path);
        dfs();
        for (int v = adj[u].size() - 1; ~v; v--) {
            indegree[adj[u][v]]++;
            if (indeg0.back() == adj[u][v])
                indeg0.pop_back();
        }
        indeg0.push_back(u);
        path.pop_back();
    }
}
```



```
// O(V + V!)
void allToposorts() {
    for (int u = 0; u < adj.size(); u++)
        if (!indegree[u]) indeg0.push_back(u);
    dfs();
}
```

Topological Sort (lowest lexicographically)

Cycles

Get Some Cycles

```
// at least detects one cycle per component
vector<vector<int>> adj, cycles;
vector<int> vis, cycle;
bool flag = false, isDirected = false;
int root = -1;

void init(int N) {
    adj.assign(N, vector<int>());
    vis.assign(N, 0);
    cycles.clear();
    root = -1, flag = false;
}

void addEdge(int u, int v) {
    adj[u].push_back(v);
    if (!isDirected) adj[v].push_back(u);
}

// O(N)
bool hasCycle(int u, int prev) {
    vis[u] = 1;
    for (auto &v : adj[u]) {
        if (v == u || vis[v] == 2 ||
            (!isDirected && v == prev))
            continue;
        if (flag) {
            if (!vis[v]) hasCycle(v, u);
            continue;
        }
        if (vis[v] || hasCycle(v, u)) {
            if (root == -1) root = v, flag = true;
            cycle.push_back(u);
            if (root == u)
                flag = false, root = -1,
                cycles.push_back(cycle), cycle.clear();
        }
    }
    vis[u] = 2;
    return flag;
}
```

```
// O(N)
bool hasCycle() {
    for (int u = 0; u < adj.size(); u++)
        if (!vis[u]) cycle.clear(), hasCycle(u, -1);
    return cycles.size() > 0;
}
```

Has Cycle

```
vector<vector<int>> adj;
vector<int> vis;
bool isDirected = false;
void init(int N) {
    adj.assign(N, vector<int>());
    vis.assign(N, 0);
}

void addEdge(int u, int v) {
    adj[u].push_back(v);
    if (!isDirected) adj[v].push_back(u);
}

bool hasCycle(int u, int prev) {
    vis[u] = 1;
    for (auto &v : adj[u])
        if (v != u && vis[v] != 2 &&
            (isDirected || v != prev) &&
            (vis[v] || hasCycle(v, u)))
            return true;
    vis[u] = 2;
    return false;
}

// O(N)
bool hasCycle() {
    for (int u = 0; u < adj.size(); u++)
        if (!vis[u] && hasCycle(u, -1)) return true;
}
```

Flow

Max Flow Min Cut Dinic

```
// cap[a][b] = Capacity from a to b
// flow[a][b] = flow occupied from a to b
// level[a] = level in graph of node a
// iflow = initial flow, icap = initial capacity
// pathMinCap = capacity bottleneck for a path (s->t)
typedef int T;
vector<int> level;
vector<vector<int>> adj;
unordered_map<int, unordered_map<int, T>> cap, flow;
long long int inf = (1ll << 62) - 1;
void init(int N) {
    adj.assign(N, vector<int>());
    cap.clear();
    flow.clear();
}
```

```

void addEdge(int u, int v, T icap, T iflow = 0) {
    cap[u][v] = icap;
    flow[u][v] += iflow;
    flow[v][u] -= iflow;
    adj[u].push_back(v);
    adj[v].push_back(u);
}

bool levelGraph(int s, int t) {
    level.assign(adj.size(), 0);
    level[s] = 1;
    queue<int> q;
    q.push(s);
    while (!q.empty()) {
        int u = q.front();
        q.pop();
        for (int &v : adj[u]) {
            if (!level[v] && flow[u][v] < cap[u][v]) {
                q.push(v);
                level[v] = level[u] + 1;
            }
        }
    }
    return level[t];
}

T blockingFlow(int u, int t, T pathMinCap) {
    if (u == t) return pathMinCap;
    for (int v : adj[u]) {
        T capLeft = cap[u][v] - flow[u][v];
        if (level[v] == (level[u] + 1) && capLeft > 0)
            if (T pathMaxFlow = blockingFlow(
                v, t, min(pathMinCap, capLeft))) {
                flow[u][v] += pathMaxFlow;
                flow[v][u] -= pathMaxFlow;
                return pathMaxFlow;
            }
    }
    return 0;
}

// O(E * V^2)
T maxFlowMinCut(int s, int t) {
    if (s == t) return inf;
    T maxFlow = 0;
    while (levelGraph(s, t))
        while (T flow = blockingFlow(s, t, inf))
            maxFlow += flow;
    return maxFlow;
}

```

Maximum Bipartite Matching

```

// mbm = maximum bipartite matching
#include "Max Flow Min Cut Dinic.cpp"

void addEdgeMBM(int u, int v) {
    addEdge(u += 2, v += 2, 1);
    addEdge(0, u, 1);
    addEdge(v, 1, 1);
}

```

```

// O(E * V^2)
T mbm() { return maxFlowMinCut(0, 1); }

```

ShortestPaths

0 - 1 BFS

```

// s = source
typedef int T;
long long int inf = (1ll << 62) - 1;
vector<vector<int>>> adj;
unordered_map<int, unordered_map<int, T>> weight;

void init(int N) {
    adj.assign(N, vector<int>());
    weight.clear();
}

void addEdge(int u, int v, T w, bool isDirected = 0) {
    adj[u].push_back(v);
    weight[u][v] = w;
    if (isDirected) return;
    adj[v].push_back(u);
    weight[v][u] = w;
}

// O(E)
vector<T> bfs(int s) {
    vector<T> dist(adj.size(), inf);
    dist[s] = 0;
    deque<int> q;
    q.push_front(s);
    while (q.size()) {
        int u = q.front();
        for (auto& v : adj[u]) {
            T d = dist[u] + weight[u][v];
            if (d < dist[v])
                weight[u][v] ? q.push_back(v)
                    : q.push_front(v);
        }
    }
    return dist;
}

```

Bellman Ford

```

// s = source
// returns {} if there is a negative weight cycle
typedef int T;
long long int inf = (1ll << 62) - 1;
vector<vector<int>>> adj;
unordered_map<int, unordered_map<int, T>> weight;

void init(int N) {
    adj.assign(N, vector<int>());
    weight.clear();
}

```

```
void addEdge(int u, int v, T w, bool isDirected = 0) {
    adj[u].push_back(v);
    weight[u][v] = w;
    if (isDirected) return;
    adj[v].push_back(u);
    weight[v][u] = w;
}
```

*// $O(V * E)$*

```
vector<T> bellmanFord(int s) {
    vector<T> dist(adj.size(), inf);
    dist[s] = 0;
    for (int i = 1; i <= adj.size(); i++)
        for (int u = 0; u < adj.size(); u++)
            for (auto &v : adj[u]) {
                T d = dist[u] + weight[u][v];
                if (dist[u] != inf && d < dist[v]) {
                    if (i == adj.size()) return {};
                    dist[v] = d;
                }
            }
    return dist;
}
```

Bellman Ford Fast

// s = source, its = iterations of node u
// returns {} if there is a negative weight cycle
 typedef int T;
 long long int inf = (1ll << 62) - 1;
 vector<vector<int>> adj;
 unordered_map<int, unordered_map<int, T>> weight;

```
void init(int N) {
    adj.assign(N, vector<int>());
    weight.clear();
}
```

```
void addEdge(int u, int v, T w, bool isDirected = 0) {
    adj[u].push_back(v);
    weight[u][v] = w;
    if (isDirected) return;
    adj[v].push_back(u);
    weight[v][u] = w;
}
```

*// $O(V * E)$*

```
vector<T> bellmanFordFast(int s) {
    vector<T> dist(adj.size(), inf);
    vector<int> its(adj.size()), inqueue(adj.size());
    queue<int> q;
    q.push(s), dist[s] = 0, its[s] = 1;
    while (!q.empty()) {
        int u = q.front();
        q.pop(), inqueue[u] = 0;
        for (auto &v : adj[u]) {
            T d = dist[u] + weight[u][v];
            if (d < dist[v]) {
                dist[v] = d;
                if (!inqueue[v]) q.push(v), its[v]++;
                if (its[v] == adj.size()) return {};
            }
        }
    }
    return dist;
}
```

Dijkstra

// s = source
 typedef int T;
 typedef pair<T, int> DistNode;
 long long int inf = (1ll << 62) - 1;
 vector<vector<int>> adj;
 unordered_map<int, unordered_map<int, T>> weight;
 void init(int N) {
 adj.assign(N, vector<int>());
 weight.clear();
 }

```
void addEdge(int u, int v, T w, bool isDirected = 0) {
    adj[u].push_back(v);
    weight[u][v] = w;
    if (isDirected) return;
    adj[v].push_back(u);
    weight[v][u] = w;
}
```

*// $\sim O(E * \lg(V))$*

```
vector<T> dijkstra(int s) {
    vector<T> dist(adj.size(), inf);
    priority_queue<DistNode> q;
    q.push({0, s}), dist[s] = 0;
    while (q.size()) {
        DistNode top = q.top();
        q.pop();
        int u = top.second;
        if (dist[u] < -top.first) continue;
        for (int &v : adj[u]) {
            T d = dist[u] + weight[u][v];
            if (d < dist[v]) q.push({-(dist[v] = d), v});
        }
    }
    return dist;
}
```

Floyd Warshall

```
// d = distance
typedef int T;
long long int inf = (1ll << 62) - 1;
vector<vector<T>> d;

void init(int n) {
    d.assign(n, vector<T>(n, inf));
    for (int i = 0; i < n; i++) d[i][i] = 0;
}

void addEdge(int u, int v, T w, bool isDirected = 0) {
    d[u][v] = w;
    if (isDirected) return;
    d[v][u] = w;
}

// O(V^3)
void floydwarshall() {
    for (int k = 0; k < d.size(); k++)
        for (int u = 0; u < d.size(); u++)
            for (int v = 0; v < d.size(); v++)
                d[u][v] = min(d[u][v], d[u][k] + d[k][v]);
}
```

Shortest Path in Directed Acyclic Graph

```
// s = source
#include "../Topological Sort.cpp"
typedef int T;
long long int inf = (1ll << 62) - 1;
unordered_map<int, unordered_map<int, T>> weight;

void init(int N) {
    adj.assign(N, vector<int>());
    vis.assign(N, 0);
    toposorted.clear();
    weight.clear();
}

void addEdge(int u, int v, int w) {
    adj[u].push_back(v);
    weight[u][v] = w;
}

// O(N)
vector<T> dagsssp(int s) {
    vector<T> dist(adj.size(), inf);
    dist[s] = 0;
    toposort(s);
    while (toposorted.size()) {
        int u = toposorted.back();
        toposorted.pop_back();
        for (auto &v : adj[u]) {
            T d = dist[u] + weight[u][v];
            if (d < dist[v]) dist[v] = d;
        }
    }
    return dist;
}
```

Maths

Data Structures

Matrix

```
template <class T>
struct Matrix {
    int rows, cols;
    vector<vector<T>> m;

    Matrix(int r, int c) : rows(r), cols(c) {
        m.assign(r, vector<T>(c));
    }

    Matrix(const vector<vector<T>>& b)
        : rows(b.size()), cols(b[0].size()), m(b) {}

    vector<T>& operator[](int i) const {
        return const_cast<Matrix*>(this)->m[i];
    }

    // O(N * M)
    Matrix operator+(const Matrix& b) {
        Matrix ans(rows, cols);
        for (int i = 0; i < rows; i++)
            for (int j = 0; j < m[i].size(); j++)
                ans[i][j] = m[i][j] + b[i][j];
        return ans;
    }

    // O(N * M)
    Matrix operator-(const Matrix& b) {
        Matrix ans(rows, cols);
        for (int i = 0; i < rows; i++)
            for (int j = 0; j < m[i].size(); j++)
                ans[i][j] = m[i][j] - b[i][j];
        return ans;
    }

    // O(N^3)
    Matrix operator*(const Matrix& b) {
        if (cols != b.rows) return Matrix(0, 0);
        Matrix ans(rows, b.cols);
        for (int i = 0; i < rows; i++)
            for (int j = 0; j < b[i].size(); j++)
                for (int k = 0; k < b.rows; k++)
                    ans[i][j] += m[i][k] * b[k][j];
        return ans;
    }

    Matrix& operator+=(const Matrix& b) {
        return *this = *this + b;
    }
}
```

```

Matrix& operator--(const Matrix& b) {
    return *this = *this - b;
}

Matrix& operator*=(const Matrix& b) {
    return *this = *this * b;
}
};

```

Number Theory

Binary Exponentiation

```

typedef __int128_t lli;

lli binPow(lli a, lli p) {
    lli ans = 1LL;
    while (p) {
        if (p & 1LL) ans *= a;
        a *= a, p >>= 1LL;
    }
    return ans;
}

```

Divisibility Criterion

```

def divisorCriteria(n, lim):
    results = []
    tenElevated = 1
    for i in range(lim):
        # remainder = pow(10, i, n)
        remainder = tenElevated % n
        negremainder = remainder - n
        if(remainder <= abs(negremainder)):
            results.append(remainder)
        else:
            results.append(negremainder)
        tenElevated *= 10
    return results

def testDivisibility(dividend, divisor,
    ↪ divisor_criteria):
    dividend = str(dividend)
    addition = 0
    dividendSize = len(dividend)
    i = dividendSize - 1
    j = 0
    while j < dividendSize:
        addition += int(dividend[i]) *
            ↪ divisor_criteria[j]
        i -= 1
        j += 1
    return addition % divisor == 0

```

```

if __name__ == '__main__':
    dividend, divisor = map(int, input().split())
    divisor_criteria = divisorCriteria(divisor,
        ↪ len(str(dividend)))
    print(divisor_criteria)
    print(testDivisibility(dividend, divisor,
        ↪ divisor_criteria))

```

Divisors

```

// divs = divisors

typedef long long int li;
typedef vector<li> V;

// O(sqrt(N))
V getDivisors(li n) {
    V divs;
    for (li i = 1; i * i <= n; i++)
        if (!(n % i)) {
            divs.push_back(i);
            if (i * i != n) divs.push_back(n / i);
        }
    return divs;
}

```

Divisors Pollard Rho

```

// pf = primeFactors, divs = divisors

#include "../Primes/Prime Factorization Pollard
    ↪ Rho.cpp"

typedef vector<li> V;

void divisors(Map &pf, V &divs, li ans, li p) {
    auto next = ++pf.find(p);
    int power = pf[p];
    for (li k = 0; k <= power; k++, ans *= p) {
        if (next == pf.end()) divs.push_back(ans);
        else divisors(pf, divs, ans, next->first);
    }
}

// O(number of pf)
V getDivisors(li n) {
    Map pf = getPrimeFactors(n);
    V divs;
    divisors(pf, divs, 1, pf.begin()->first);
    return divs;
}

```

Euler's Phi

```
#include "../Primes/Prime Factorization Pollard
→ Rho.cpp"
// #include "../Primes/Prime Factorization.cpp"

// counts the number of integers (Xi) between 1 and n
// which are coprime (gcd(Xi, n) = 1) to n
lli phi(lli n) {
    if (isPrime(n)) return n - 1;
    Map pf = getPrimeFactors(n);
    for (auto &p : pf) n -= n / p.first;
    return n;
}
```

Extended Euclidean

```
// r = remainder

typedef __int128_t lli;
// gcd(a, b) = ax + by
vector<lli> extendedGCD(lli a, lli b) {
    if (a > 0 && b == 0) return {a, 1, 0};
    lli x = 1, y, prevx, prevy = 1, q, r;
    while (true) {
        q = a / b, r = a - b * q;
        if (!r) break;
        a = b, b = r;
        x -= prevx * q;
        swap(x, prevx);
        y -= prevy * q;
        swap(y, prevy);
    }
    // gcd = b, x = prevx, y = prevy
    return {b, prevx, prevy};
}
```

GCD

```
typedef __int128_t lli;

lli gcd(lli a, lli b) {
    return !b ? a : gcd(b, a % b);
}

// Iterative version
lli gcdI(lli a, lli b) {
    while (b) a %= b, swap(a, b);
    return a;
}
```

LCM

```
#include "GCD.cpp"

int lcm(lli a, lli b) {
    int c = gcd(a, b);
    return c ? a / c * b : 0;
}
```

Modular Exponentiation

```
#include "../Modular Multiplication.cpp"

// O(lg(p))
lli pow(lli a, lli p, lli m) {
    a %= m;
    lli ans = 1;
    while (p) {
        if (p & 1LL) ans = multiply(ans, a, m);
        a = multiply(a, a, m), p >>= 1;
    }
    return ans;
}
```

Modular Multiplication

```
typedef __int128_t lli;

// O(lg(b))
lli multiply(lli a, lli b, lli m) {
    a %= m;
    lli ans = 0;
    while (b) {
        if (b & 1)
            ans += a, ans = (ans >= m ? ans - m : ans);
        b >>= 1, a <<= 1;
        a = (a >= m ? a - m : a);
    }
    return ans;
}
```

Modulo with negative numbers

```
typedef int T;

T mod(T a, T b) {
    if (a < 0 && b >= 0) return a % b + b;
    if (a >= 0 && b < 0) return -(a % b + b);
    return a % b;
}
```

Primes

Is Prime Miller Rabin

```
#include "../Number Theory/Modular Exponentiation.cpp"
```

```
bool isPrime(lli p, int k = 20) {
    if (p == 2 || p == 3) return 1;
    if ((~p & 1) || p == 1) return 0;
    lli d = p - 1, phi = d, r = 0;
    while (~d & 1) d >>= 1, r++;
    while (k--) {
        // set seed with: int main() { srand(time(0)); }
        lli a = 2 + rand() % (p - 3); // [2, p - 2]
        lli e = pow(a, d, p), r2 = r;
        if (e == 1 || e == phi) continue;
        bool flag = 1;
        while (--r2) {
            e = multiply(e, e, p);
            if (e == 1) return 0;
            if (e == phi) {
                flag = 0;
                break;
            }
        }
        if (flag) return 0;
    }
    return 1;
}
```

Prime Factorization

```
typedef long long int li;
// if li == __int128_t: use map<li, int> Map;
typedef unordered_map<li, int> Map;

// ~O(sqrt(N) * lg(N))
Map getPrimeFactors(li n) {
    Map pf;
    while (~n & 1) pf[2]++, n >>= 1;
    for (li i = 3; i * i <= n; i += 2)
        while (!(n % i)) pf[i]++, n /= i;
    if (n > 1) pf[n]++;
    return pf;
}
```

Prime Factorization (Sieve)

```
#include "Primes Sieve.cpp"

typedef unordered_map<int, int> Map;

// O(lg(N)) n <= sieve.size()
Map getPrimeFactors(int n) {
    Map pf;
    while (n > 1) {
        int p = n & 1 ? sieve[n] : 2, c;
        if (!p) p = n;
        while (n % p == 0) n /= p, c++;
        pf[p] = c;
    }
    return pf;
}
```

Prime Factorization (Sieve) 2

```
#include "Primes Sieve.cpp"

typedef long long int li;
// if li == __int128_t: use map<li, int> Map;
typedef unordered_map<li, int> Map;

// O(sqrt(N)) n <= sieve.size() ^ 2
Map getPrimeFactors(li n) {
    Map pf;
    for (int& p : primes) {
        if (p * p > n) break;
        int c;
        while (n % p == 0) n /= p, c++;
        if (c) pf[p] = c;
    }
    if (n > 1) pf[n] = 1;
    return pf;
}
```

Prime Factorization Pollard Rho

```
// pf = prime factors

#include "../Number Theory/GCD.cpp"
#include "../Is Prime Miller Rabin.cpp"

typedef long long int li;
// if li == __int128_t: use map<li, int> Map;
typedef unordered_map<li, int> Map;

li _abs(li a) { return a < 0 ? -a : a; }
```

```

li getRandomDivisor(li n) {
    if (~n & 1) return 2;
    li c = 1 + rand() % (n - 1), a = 2, b = 2, d = 1;
    auto f = [&](li x) {
        return multiply(x, x, n) + c) % n;
    };
    while (d == 1)
        a = f(a), b = f(b), d = gcd(_abs(a - b), n);
    return d;
}

void getpf(li n, Map &pf) {
    if (n == 1LL) return;
    if (isPrime(n)) {
        pf[n]++;
        return;
    }
    li divisor = getRandomDivisor(n);
    getpf(divisor, pf);
    getpf(n / divisor, pf);
}

// ~O(N^(1/4))
Map getPrimeFactors(li n) {
    Map pf;
    getpf(n, pf);
    return pf;
}

```

Primes Sieve

```

vector<int> sieve, primes;

// ~O(N * lg(lg(N)))
void primeSieve(int n) {
    sieve.assign(n + 1, 0);
    primes = {};
    for (int i = 3; i * i <= n; i += 2)
        if (!sieve[i])
            for (int j = i * i; j <= n; j += 2 * i)
                if (!sieve[j]) sieve[j] = i;
    primes.push_back(2);
    for (int i = 3; i < n; i++)
        if (!sieve[i] && (i & 1)) primes.push_back(i);
}

```

Ranges

Data Structures

BIT

```

template <class T>
struct BIT {
    T neutro = 0;
    vector<T> bit;

    BIT(int n) { bit.assign(++n, neutro); }

    inline T F(T a, T b) {
        return a + b;
        // return a * b;
    }

    // Inverse of F
    inline T I(T a, T b) {
        return a - b;
        // return a / b;
    }

    // O(N)
    void build() {
        for (int i = 1; i < bit.size(); i++) {
            int j = i + (i & -i);
            if (j < bit.size()) bit[j] = F(bit[j], bit[i]);
        }
    }

    // O(lg(N))
    void update(int i, T val) {
        for (i++; i < bit.size(); i += i & -i)
            bit[i] = F(bit[i], val);
    }

    // O(lg(N))
    T query(int i) {
        T ans = neutro;
        for (i++; i; i -= i & -i) ans = F(ans, bit[i]);
        return ans;
    }

    // O(lg(N)), [l, r]
    T query(int l, int r) {
        return I(query(r), query(--l));
    }

    T& operator[](int i) { return bit[++i]; }
};

```


BIT Range Update

```
typedef long long int T;
T neutro = 0;
vector<T> bit1, bit2;

void initVars(int n) {
    bit1.assign(++n, neutro);
    bit2 = bit1;
}

// O(lg(N))
void update(vector<T> &bit, int i, T val) {
    for (i++; i < bit.size(); i += i & -i)
        bit[i] += val;
}

// O(lg(N)), [l, r]
void update(int l, int r, T val) {
    update(bit1, l, val);
    update(bit1, r + 1, -val);
    update(bit2, r + 1, val * r);
    update(bit2, l, -val * (l - 1));
}

// O(lg(N))
T query(vector<T> &bit, int i) {
    T ans = neutro;
    for (i++; i; i -= i & -i) ans += bit[i];
    return ans;
}

// O(lg(N))
T query(int i) {
    return query(bit1, i) * i + query(bit2, i);
}

// O(lg(N)), [l, r]
T query(int l, int r) {
    return query(r) - query(l - 1);
}
```

Segment Tree

```
// st = segment tree. st[1] = root;
// neutro = operation neutral value
// e.g. for sum is 0, for multiplication
// is 1, for gcd is 0, for min is INF, etc.

template <class T>
struct SegmentTree {
    T neutro = 0;
    int N;
    vector<T> st;

    SegmentTree(int n) : st(2 * n, neutro), N(n) {}

    inline T F(T a, T b) {
        return a + b;
        // return __gcd(a, b);
        // return a * b;
        // return min(a, b);
    }
}
```

```
// O(2N)
void build() {
    for (int i = N - 1; i > 0; i--)
        st[i] = F(st[i << 1], st[i << 1 | 1]);
}

// O(lg(2N)), works like replacing arr[i] with val
void update(int i, T val) {
    for (st[i += N] = val; i > 1; i >>= 1)
        st[i >> 1] = F(st[i], st[i ^ 1]);
}

// O(3N), [l, r]
void update(int l, int r, T val) {
    if (l == r)
        update(l, val);
    else {
        for (l += N, r += N; l <= r; l++) st[l] = val;
        build();
    }
}

// O(lg(2N)), [l, r]
T query(int l, int r) {
    T ans = neutro;
    for (l += N, r += N; l <= r; l >>= 1, r >>= 1) {
        if (l & 1) ans = F(ans, st[l++]);
        if (~r & 1) ans = F(ans, st[r--]);
    }
    return ans;
}

T& operator[](int i) { return st[i + N]; }
};
```

Segment Tree Lazy Propagation

```
// st = segment tree, st[1] = root, H = height of d
// u = updates, d = delayed updates
// neutro = operation neutral val
// e.g. for sum is 0, for multiplication
// is 1, for gcd is 0, for min is INF, etc.
```

```
template <class T>
struct SegmentTree {
    T neutro = 0;
    int N, H;
    vector<T> st, d;
    vector<bool> u;

    SegmentTree(int n, T val)
        : st(2 * n, val), d(n), u(n) {
        H = sizeof(int) * 8 - __builtin_clz(N = n);
    }

    inline T kTimesF(T a, T k) {
        return a * k;
        // return pow(a, k);
        // return a;
    }
}
```

```

inline T F(T a, T b) {
    return a + b;
    // return a * b;
    // return __gcd(a, b);
    // return min(a, b);
}

inline T UF(T a, T b) {
    return b; // replace update
    // return F(a, b); // apply F to current value
}

void apply(int i, T val, int k) {
    st[i] = UF(st[i], kTimesF(val, k));
    if (i < N) d[i] = UF(d[i], val), u[i] = 1;
}

void calc(int i) {
    if (!u[i]) st[i] = F(st[i << 1], st[i << 1 | 1]);
}

// O(2N)
void build() {
    for (int i = N - 1; i > 0; i--) calc(i);
}

// O(lg(N))
void build(int p) {
    while (p > 1) p >>= 1, calc(p);
}

// O(lg(N))
void push(int p) {
    for (int s = H, k = 1 << (H - 1); s > 0;
         s--, k >>= 1) {
        int i = p >> s;
        if (u[i]) {
            apply(i << 1, d[i], k);
            apply(i << 1 | 1, d[i], k);
            u[i] = 0, d[i] = neutro;
        }
    }
}

// O(lg(N)), [l, r]
void update(int l, int r, T val) {
    push(l += N);
    push(r += N);
    int ll = l, rr = r, k = 1;
    for (; l <= r; l >>= 1, r >>= 1, k <== 1) {
        if (l & 1) apply(l++, val, k);
        if (~r & 1) apply(r--, val, k);
    }
    build(ll);
    build(rr);
}

```

```

// O(lg(2N)), [l, r]
T query(int l, int r) {
    push(l += N);
    push(r += N);
    T ans = neutro;
    for (; l <= r; l >>= 1, r >>= 1) {
        if (l & 1) ans = F(ans, st[l++]);
        if (~r & 1) ans = F(ans, st[r--]);
    }
    return ans;
}

T& operator[](int i) { return st[i + N]; }
};

```

Sparse Table

```

// st = sparse table, Arith = Arithmetic
typedef int T;
int neutro = 0;
vector<vector<T>> st;

T F(T a, T b) {
    // return min(a, b);
    return __gcd(a, b);
    // return a + b; // Arith
    // return a * b; // Arith
}

// O(Nlg(N))
void build(vector<T> &arr) {
    st.assign(log2(arr.size()), vector<T>(arr.size()));
    st[0] = arr;
    for (int i = 1; (1 << i) <= arr.size(); i++)
        for (int j = 0; j + (1 << i) <= arr.size(); j++)
            st[i][j] = F(st[i - 1][j],
                          st[i - 1][j + (1 << (i - 1))]);
}

// O(1), [l, r]
T query(int l, int r) {
    int i = log2(r - l + 1);
    return F(st[i][l], st[i][r + 1 - (1 << i)]);
}

// O(lg(N)), [l, r]
T queryArith(int l, int r) {
    T ans = neutro;
    while (true) {
        int k = log2(r - l + 1);
        ans = F(ans, st[k][l]);
        l += 1 << k;
        if (l > r) break;
    }
    return ans;
}

```

Wavelet Tree

```
// pref = prefix sum
// lte = less than or equal, 1-indexed
// A = max_element(from, to)
// lcount = left children count
struct WaveletTree {
    WaveletTree *l, *r;
    int lo, hi;
    vector<int> lcount, pref;

    // O(N*lg(A))
    WaveletTree(vector<int>::iterator from,
                vector<int>::iterator to, int lo,
                int hi) {
        this->lo = lo, this->hi = hi;
        if (lo == hi or from == to) return;
        int mid = (lo + hi) >> 1;
        auto f = [mid](int x) { return x <= mid; };
        lcount.reserve(to - from + 1);
        pref.reserve(to - from + 1);
        lcount.push_back(0);
        pref.push_back(0);
        for (auto it = from; it != to; it++)
            lcount.push_back(lcount.back() + f(*it)),
            pref.push_back(pref.back() + *it);
        auto pivot = stable_partition(from, to, f);
        l = new WaveletTree(from, pivot, lo, mid);
        r = new WaveletTree(pivot, to, mid + 1, hi);
    }

    // O(lg(A)) frequency of k in [a, b]
    int freq(int a, int b, int k) {
        if (a > b or k < lo or k > hi) return 0;
        if (lo == hi) return b - a + 1;
        int lc = lcount[a - 1], rc = lcount[b];
        if (k > ((lo + hi) >> 1))
            return r->freq(a - lc, b - rc, k);
        return l->freq(lc + 1, rc, k);
    }

    // O(lg(A)) kth-Smallest element in [a, b]
    int kth(int a, int b, int k) {
        if (a > b) return 0;
        if (lo == hi) return lo;
        int lc = lcount[a - 1], rc = lcount[b],
            inleft = rc - lc;
        if (k > inleft)
            return r->kth(a - lc, b - rc, k - inleft);
        return l->kth(lc + 1, rc, k);
    }

    // O(lg(A)) count of elements <= to k in [a, b]
    int lte(int a, int b, int k) {
        if (a > b or k < lo) return 0;
        if (hi <= k) return b - a + 1;
        int lc = lcount[a - 1], rc = lcount[b];
        return l->lte(lc + 1, rc, k) +
            r->lte(a - lc, b - rc, k);
    }
}
```

```
// O(lg(A)) sum of numbers <= to k in [a, b]
int sumlte(int a, int b, int k) {
    if (a > b or k < lo) return 0;
    if (hi <= k) return pref[b] - pref[a - 1];
    int lc = lcount[a - 1], rc = lcount[b];
    return l->sumlte(lc + 1, rc, k) +
        r->sumlte(a - lc, b - rc, k);
}
};
```

Wavelet Tree Compressed

```
// lte = less than or equal, c = compressed
// o = original, 1-indexed
#include "../Techniques/Binary Search.cpp"
#include "Wavelet Tree.cpp"

template <class T>
struct WaveletTreeCompressed {
    unordered_map<int, T> imap;
    unordered_map<T, int> Map;
    WaveletTree* wt;
    vector<T> o;

    // O(N*lg(N))
    WaveletTreeCompressed(vector<T>& v) {
        o = v;
        int inf = 1 << 30, n = 0, lo = inf, hi = -inf;
        set<T> s(v.begin(), v.end());
        vector<int> c(v.size());
        for (auto& e : s) Map[e] = n++;
        for (int i = 0; i < v.size(); i++)
            c[i] = Map[v[i]], imap[Map[v[i]]] = v[i];
        for (auto& e : c)
            lo = min(lo, e), hi = max(hi, e);
        wt = new WaveletTree(c.begin(), c.end(), lo, hi);
    }

    // O(lg(N)) frequency of k in [a, b]
    int freq(int l, int r, T k) {
        return wt->freq(l, r, Map[k]);
    }

    // O(lg(N)) kth-Smallest element in [l, r]
    T kth(int l, int r, int k) {
        return imap[wt->kth(l, r, k)];
    }

    // O(lg(N)) count of numbers <= to k in [l, r]
    T lte(int l, int r, T k) {
        int kk = Map[bSearch<T>(o, k, l, r)[1]];
        return imap[wt->lte(l, r, kk)];
    }

    // O(lg(N)) sum of numbers <= to k in [l, r]
    T sumlte(int l, int r, T k) {
        int kk = Map[bSearch<T>(o, k, l, r)[1]];
        return imap[wt->sumlte(l, r, kk)];
    }
};
```

Strings

Data Structures

Suffix Automaton

```
// link[u]: links to the longest suffix which is
//           not in the same endpos-equivalence class
// len[u]: length of the longest suffix that
//           corresponds to u's endpos-equivalence class
```

```
struct SuffixAutomaton {
    vector<int> len, link, isClone, first;
    vector<map<char, int>> next;
    int size, last;

    void init(int n) {
        first = isClone = len = link = vector<int>(2 * n);
        next.resize(2 * n);
        len[0] = 0, link[0] = -1, size = 1, last = 0;
    }

    // O(N)
    SuffixAutomaton(const string& s) {
        init(s.size());
        for (const auto& c : s) add(c);
    }

    // O(1)
    void add(const char& c) {
        int p = last, u = size++;
        len[u] = len[p] + 1, first[u] = len[p];
        while (p != -1 && !next[p].count(c))
            next[p][c] = u, p = link[p];
        if (p == -1) link[u] = 0;
        else {
            int q = next[p][c];
            if (len[p] + 1 == len[q]) link[u] = q;
            else {
                int clone = size++;
                first[clone] = first[q];
                len[clone] = len[p] + 1, isClone[clone] = 1;
                link[clone] = link[q], next[clone] = next[q];
                while (p != -1 && next[p][c] == q)
                    next[p][c] = clone, p = link[p];
                link[q] = link[u] = clone;
            }
        }
        last = u;
    }
}
```

```
// O(N)
unordered_set<int> getTerminals() {
    unordered_set<int> terminals;
    for (int p = last; p; p = link[p])
        terminals.insert(p);
    return terminals;
}
};
```

Trie

```
// wpt = number of words passing through
// w = number of words ending in the node
// c = character
```

```
struct Trie {
    struct Node {
        // for lexicographical order use 'map'
        // map<char, Node*> ch;
        unordered_map<char, Node*> ch;
        int w = 0, wpt = 0;
    };

    Node *root = new Node();

    // O(STR.SIZE)
    void insert(string str) {
        Node *curr = root;
        for (auto &c : str) {
            if (!curr->ch.count(c))
                curr->ch[c] = new Node();
            curr->wpt++, curr = curr->ch[c];
        }
        curr->wpt++, curr->w++;
    }

    // O(STR.SIZE)
    Node *find(string &str) {
        Node *curr = root;
        for (auto &c : str) {
            if (!curr->ch.count(c)) return nullptr;
            curr = curr->ch[c];
        }
        return curr;
    }

    // O(STR.SIZE) number of words with given prefix
    int prefixCount(string prefix) {
        Node *node = find(prefix);
        return node ? node->wpt : 0;
    }

    // O(STR.SIZE) number of words matching str
    int strCount(string str) {
        Node *node = find(str);
        return node ? node->w : 0;
    }
}
```

```

// O(N)
void getWords(Node *curr, vector<string> &words,
              string &word) {
    if (!curr) return;
    if (curr->w) words.push_back(word);
    for (auto &c : curr->ch) {
        getWords(c.second, words, word += c.first);
        word.pop_back();
    }
}

// O(N)
vector<string> getWords() {
    vector<string> words;
    string word = "";
    getWords(root, words, word);
    return words;
}

// O(N)
vector<string> getWordsByPrefix(string prefix) {
    vector<string> words;
    getWords(find(prefix), words, prefix);
}

// O(STR.SIZE)
bool remove(Node *curr, string &str, int &i) {
    if (i == str.size()) {
        curr->wpt--;
        return curr->w ? !(curr->w = 0) : 0;
    }
    int c = str[i];
    if (!curr->ch.count(c)) return false;
    if (remove(curr->ch[c], str, ++i)) {
        if (!curr->ch[c]->wpt)
            curr->wpt--, curr->ch.erase(c);
        return true;
    }
    return false;
}

// O(STR.SIZE)
int remove(string str) {
    int i = 0;
    return remove(root, str, i);
}
};

```

Distinct Substring Count

```

#include "../Data Structures/Strings/Suffix
↳ Automaton.cpp"

// O(N)
int distinctSubstrCount(const string& s) {
    SuffixAutomaton sa(s);
    vector<int> dp(sa.size);
    function<int(int)> dfs = [&](int u) {
        if (dp[u]) return dp[u];
        for (auto& v : sa.next[u]) dp[u] += dfs(v.second);
        return ++dp[u];
    };
    return dfs(0) - 1;
}

```

KMP

```

// p = pattern, t = text
// f = error function, cf = create error function
// pos = positions where pattern is found in text

int MAXN = 1000000;
vector<int> f(MAXN + 1);

vector<int> kmp(string &p, string &t, int cf) {
    vector<int> pos;
    if (cf) f[0] = -1;
    for (int i = cf, j = 0; j < t.size(); i = f[i], j++) {
        while (i > -1 && p[i] != t[j]) i = f[i];
        if (cf) f[j] = i;
        if (!cf && i == p.size())
            pos.push_back(j - i), i = f[i];
    }
    return pos;
}

vector<int> search(string &p, string &t) {
    kmp(p, p, -1); // create error function
    return kmp(p, t, 0); // search in text
}

```

Lexicographically K-th Substring

```

#include "../Data Structures/Strings/Suffix
↳ Automaton.cpp"

// O(N * ks.size)
vector<string> kthSubstr(string& s, vector<int>& ks) {
    SuffixAutomaton sa(s);
    vector<int> dp(sa.size);
    function<int(int)> dfs = [&](int u) {
        if (dp[u]) return dp[u];
        for (auto& v : sa.next[u]) dp[u] += dfs(v.second);
        return ++dp[u];
    };
}

```

```

dfs(0);
vector<string> ans;
for (auto k : ks) {
    int u = 0;
    string ss;
    while (k)
        for (auto& v : sa.next[u])
            if (k <= dp[v.second]) {
                ss += v.first, u = v.second, k--;
                break;
            } else
                k -= dp[v.second];
    ans.push_back(ss);
}
return ans;
}

```

Lexicographically Smallest Cyclic Shift

```

#include "../Data Structures/Strings/Suffix
→ Automaton.cpp"

// O(N)
string smallestCyclicShift(const string& s) {
    SuffixAutomaton sa(s + s);
    int k = s.size(), u = 0;
    string ans;
    while (k)
        for (auto& v : sa.next[u]) {
            ans += v.first, u = v.second, k--;
            break;
        }
    return ans;
}

```

Longest Common Substring of 2 Strings

```

#include "../Data Structures/Strings/Suffix
→ Automaton.cpp"

string lcs(string& a, string& b) {
    SuffixAutomaton sa(a);
    int bestLen = 0, bestPos = -1;
    for (int i = 0, u = 0, l = 0; i < b.size(); i++) {
        while (u && !sa.next[u].count(b[i]))
            u = sa.link[u], l = sa.len[u];
        if (sa.next[u].count(b[i]))
            u = sa.next[u][b[i]], l++;
        if (l > bestLen) bestLen = l, bestPos = i;
    }
    return b.substr(bestPos - bestLen + 1, bestLen);
}

```

Longest Common Substring of Multiple Strings

```

#include <bits/stdc++.h>
using namespace std;

#include "../Data Structures/Strings/Suffix
→ Automaton.cpp"

string lcs(vector<string>& ss) {
}

int main() {
}

```

Number of Occurrences

```

// t: text, ps: patterns
// cnt[u]: size of u's endpos set

#include "../Data Structures/Strings/Suffix
→ Automaton.cpp"

// O(T * Lg(T) + p.size() * ps.size())
vector<int> nOccurrences(string& t,
                        vector<string>& ps) {
    SuffixAutomaton sa(t);
    vector<int> cnt(sa.size(), aux(sa.size()), ans;
    for (int u = 0; u < sa.size; aux[u] = u, u++)
        if (!sa.isClone[u]) cnt[u] = 1;
    sort(aux.begin(), aux.end(), [&](int& a, int& b) {
        return sa.len[b] < sa.len[a];
    });
    for (auto& u : aux)
        if (u) cnt[sa.link[u]] += cnt[u];
    for (auto& p : ps)
        for (int u = 0, i = 0; i < p.size(); i++) {
            if (!sa.next[u].count(p[i])) {
                ans.push_back(0);
                break;
            }
            u = sa.next[u][p[i]];
            if (i + 1 == p.size()) ans.push_back(cnt[u]);
        }
    return ans;
}

```

Ocurrences Positions

```

// invLink = inverse suffix-link

#include "../Data Structures/Strings/Suffix
→ Automaton.cpp"

```

```
// O(T + OCURRENCES(ps[i]) * ps.size())
vector<vector<int>> occurrencesPos(
    string& t, vector<string>& ps) {
    SuffixAutomaton sa(t);
    vector<vector<int>> ans, invLink(sa.size());
    for (int u = 1; u < sa.size; u++)
        invLink[sa.link[u]].push_back(u);
    function<void(int, int, vector<int>&)> dfs =
        [&](int u, int pLen, vector<int>& oc) {
            if (!sa.isClone[u])
                oc.push_back(sa.first[u] - pLen + 1);
            for (auto& v : invLink[u]) dfs(v, pLen, oc);
        };

    for (auto& p : ps)
        for (int u = 0, i = 0; i < p.size(); i++) {
            if (!sa.next[u].count(p[i])) {
                ans.push_back({});
                break;
            }
            u = sa.next[u][p[i]];
            if (i + 1 == p.size()) {
                vector<int> oc;
                dfs(u, p.size(), oc), ans.push_back(oc);
            }
        }
    return ans;
}
```

Rabin Karp

```
class RollingHash {
public:
    vector<unsigned long long int> pow;
    vector<unsigned long long int> hash;
    unsigned long long int B;

    RollingHash(const string &text) : B(257) {
        int N = text.size();
        pow.resize(N + 1);
        hash.resize(N + 1);
        pow[0] = 1;
        hash[0] = 0;
        for (int i = 1; i <= N; ++i) {
            // in c++ an unsigned long long int is
            // automatically modulated by 2^64
            pow[i] = pow[i - 1] * B;
            hash[i] = hash[i - 1] * B + text[i - 1];
        }
    }

    unsigned long long int getWordHash() {
        return hash[hash.size() - 1];
    }
}
```

```
unsigned long long int getSubstrHash(int begin,
                                     int end) {
    return hash[end] -
           hash[begin - 1] * pow[end - begin + 1];
}

int size() { return hash.size(); }
};

vector<int> rabinKarp(RollingHash &rhStr,
                     string &pattern) {
    vector<int> positions;
    RollingHash rhPattern(pattern);
    unsigned long long int patternHash =
        rhPattern.getWordHash();
    int windowSize = pattern.size(), end = windowSize;
    for (int i = 1; end < rhStr.size(); i++) {
        if (patternHash == rhStr.getSubstrHash(i, end))
            positions.push_back(i);
        end = i + windowSize;
    }
    return positions;
}
```

Techniques

Binary Search

Binary Search

```
/* if e in v and lower = false (upper_bound):
   r = position of e in v
   l = r + 1
if e in v and lower = true (lower_bound):
   l = position of e in v
   r = l - 1
if e not in v and inv = false it means that:
   v[r] < e < v[l]
if e not in v and inv = true it means that:
   v[r] > e > v[l] */
```



```
// O(lg(r - l)) [l, r]
template <class T>
vector<T> bSearch(vector<T> &v, T e, int l, int r,
                  bool lower = 0, bool inv = 0) {
    int ll = l, rr = r;
    while (l <= r) {
        int mid = l + (r - l) >> 1;
        if (e < v[mid]) inv ? l = mid + 1 : r = mid - 1;
        else if (e > v[mid])
            inv ? r = mid - 1 : l = mid + 1;
        else
            lower ? r = mid - 1 : l = mid + 1;
    } // bSearch[0] tells if the element was found
    return {lower ?
            v[min(rr, l)] == e : v[max(ll, r)] == e, r, l};
}
```

Bitonic Search

```
/* assumes that the bitonic point is the greastest
 * value in v*/

#include "Binary Search.cpp"

template <class T>
vector<vector<int>>> bitonicSearch(vector<T> &v, T e) {
    int l = 0, r = v.size() - 1, mid;
    while (l <= r) {
        mid = l + (r - l) / 2;
        if (!mid || (mid >= v.size() - 1)) break;
        if (v[mid - 1] <= v[mid] && v[mid] > v[mid + 1])
            break;
        if (v[mid - 1] <= v[mid] && v[mid] <= v[mid + 1])
            l = mid + 1;
        if (v[mid - 1] > v[mid] && v[mid] > v[mid + 1])
            r = mid - 1;
    } // at the end of the loop mid = bitonic point
    return {
        bSearch<T>(v, e, 0, mid),
        bSearch<T>(v, e, mid, v.size() - 1, false,
            ↪ true)};
}
```

C++ lower bound

```
// ans[0] = true if e is in v else false
// ans[1] = index pointing to the first element in
// the range [l, r] which compares >= to e.
template <class T>
vector<int> lowerBound(vector<T> &v, T e, int l,
                       int r) {
    auto it = v.begin();
    int i = lower_bound(it + l, it + r, e) - it;
    return {v[i] == e, i};
}
```

C++ upper bound

```
// ans[0] = true if e is in v else false
// ans[1] = index pointing to the first element in
// the range [l, r] which compares > to e.
template <class T>
vector<int> upperBound(vector<T> &v, T e, int l,
                       int r) {
    auto it = v.begin();
    int i = upper_bound(it + l, it + r, e) - it;
    return {v[i - 1] == e, i};
}
```

Lower Bound

```
// ans[0] = true if e is in v else false
// ans[1] = index pointing to the first element in
// the range [l, r] which compares >= to e.
```

```
// O(lg(r - l)) [l, r]
template <class T>
vector<int> lowerBound(vector<T> &v, T e, int l,
                       int r) {
    int rr = r;
    while (l <= r) {
        int mid = l + (r - l) >> 1;
        e <= v[mid] ? r = mid - 1, l = mid + 1;
    }
    return {v[min(rr, l)] == e, l};
}
```

Upper Bound

```
// ans[0] = true if e is in v else false
// ans[1] = index pointing to the first element in
// the range [l, r] which compares > to e.
```

```
// O(lg(r - l)) [l, r]
template <class T>
vector<int> upperBound(vector<T> &v, T e, int l,
                       int r) {
    int ll = l;
    while (l <= r) {
        int mid = l + (r - l) >> 1;
        e < v[mid] ? r = mid - 1, l = mid + 1;
    }
    return {v[max(ll, r)] == e, l};
}
```

Multiple Queries

Mo

```
// q = query
// qs = queries
```



```

struct Query {
    int l, r;
};

int blksize;
vector<Query> qs;
vector<int> arr;

void initVars(int N, int M) {
    arr = vector<int>(N);
    qs = vector<Query>(M);
}

bool cmp(Query &a, Query &b) {
    if (a.l == b.l) return a.r < b.r;
    return a.l / blksize < b.l / blksize;
}

void getResults() {
    blksize = (int)sqrt(arr.size());
    sort(qs.begin(), qs.end(), cmp);
    int prevL = 0, prevR = -1;
    int sum = 0;
    for (auto &q : qs) {
        int L = q.l, R = q.r;
        while (prevL < L) {
            sum -= arr[prevL]; // problem specific
            prevL++;
        }
        while (prevL > L) {
            prevL--;
            sum += arr[prevL]; // problem specific
        }
        while (prevR < R) {
            prevR++;
            sum += arr[prevR]; // problem specific
        }
        while (prevR > R) {
            sum -= arr[prevR]; // problem specific
            prevR--;
        }

        cout << "sum[" << L << ", " << R << "] = " << sum
              << endl;
    }
}

int main() {
    initVars(9, 2);
    arr = {1, 1, 2, 1, 3, 4, 5, 2, 8};
    qs = {{0, 8}, {3, 5}};
    getResults();
}

```

SQRT Decomposition

```

// sum of elements in range
int neutro = 0;
vector<int> arr;
vector<int> blks;

```

```

void initVars(int n) {
    arr.assign(n, neutro);
    blks.assign(sqrt(n), neutro);
}

void preprocess() {
    for (int i = 0, j = 0; i < arr.size(); i++) {
        if (i == blks.size() * j) j++;
        blks[j - 1] += arr[i]; // problem specific
    }
}

// problem specific
void update(int i, int val) {
    blks[i / blks.size()] += val - arr[i];
    arr[i] = val;
}

int query(int l, int r) {
    int sum = 0;
    int lblk = l / blks.size();
    if (l != blks.size() * lblk++) {
        while (l < r && l != lblk * blks.size()) {
            sum += arr[l]; // problem specific
            l++;
        }

        while (l + blks.size() <= r) {
            sum += blks[l / blks.size()]; // problem specific
            l += blks.size();
        }
        while (l <= r) {
            sum += arr[l]; // problem specific
            l++;
        }
    }
    return sum;
}

int main() {
    initVars(10);
    arr = {1, 5, 2, 4, 6, 1, 3, 5, 7, 10};
    preprocess();
    for (int i = 0; i < blks.size() + 1; i++)
        cout << blks[i] << " ";
    // output: 8 11 15 10
    cout << endl;
    cout << query(3, 8) << " ";
    cout << query(1, 6) << " ";
    update(8, 0);
    cout << query(8, 8) << endl;
    // output: 26 21 0
    return 0;
}

```

Trees And Heaps

Red Black Tree

```
template <class K, class V>
struct RedBlackTree {

    struct Node {
        K key;
        V val;
        Node *l, *r; // left, right
        bool isRed;
        Node(K k, V v, bool isRed)
            : key(k), val(v), isRed(isRed) {}
    };

    Node *root = nullptr;

    int compare(K a, K b) {
        if (a < b) return -1;
        if (a > b) return 1;
        return 0;
    }

    // O(lg(N))
    V at(K key) {
        Node *x = root;
        while (x) {
            int cmp = compare(key, x->key);
            if (!cmp) return x->val;
            if (cmp < 0) x = x->l;
            if (cmp > 0) x = x->r;
        }
        throw runtime_error("Key doesn't exist");
    }

    Node *rotateLeft(Node *h) {
        Node *x = h->r;
        h->r = x->l;
        x->l = h;
        x->isRed = h->isRed;
        h->isRed = 1;
        return x;
    }

    Node *rotateRight(Node *h) {
        Node *x = h->l;
        h->l = x->r;
        x->r = h;
        x->isRed = h->isRed;
        h->isRed = 1;
        return x;
    }

    void flipColors(Node *h) {
        h->isRed = 1;
        h->l->isRed = 0;
        h->r->isRed = 0;
    }
};
```

```
// O(lg(N))
Node *insert(Node *h, K key, V val) {
    if (!h) return new Node(key, val, 1);
    int cmp = compare(key, h->key);
    if (!cmp) h->val = val;
    if (cmp < 0) h->l = insert(h->l, key, val);
    if (cmp > 0) h->r = insert(h->r, key, val);
    if (h->r && h->r->isRed && !(h->l && h->l->isRed))
        h = rotateLeft(h);
    if (h->l && h->l->isRed && h->l->l &&
        h->l->l->isRed)
        h = rotateRight(h);
    if (h->l && h->l->isRed && h->r && h->r->isRed)
        flipColors(h);
    return h;
}

// O(lg(N))
void insert(K key, V val) {
    root = insert(root, key, val);
}
}
```

Problems Solved

Maths

N as Sum of different numbers from 1 to M

```
int main() {
    int t;
    scanf("%d", &t);
    for (int j = 1; j <= t; j++) {
        lli x;
        scanf("%lld", &x);
        lli count = 0;
        V divisors = getDivisors(2LL * x);
        for (auto &div : divisors) {
            double d =
                ((double)x / div) + ((1.00 - div) / 2.00);
            if (d > 0 && div > 1 && d == floor(d) &&
                div < x &&
                (2 * d * div + (div - 1) * div == 2 * x)) {
                count++;
            }
        }
        printf("case %d: %lld\n", j, count);
    }
}
```

Extras

Data Structures

Strings

Suffix Automaton

- Each node u corresponds to an endpos-equivalence class for which its longest suffix corresponds to the path from root to u .

C++

Automatic Type Conversions

When performing operations with different primitive data types in C++, the operand with smaller rank gets converted to the data type of the operand with the greater rank.

Data Type Ranks	
Rank	Data Type
1	<code>bool</code>
2	<code>char</code> , <code>signed char</code> , <code>unsigned char</code>
3	<code>short int</code> , <code>unsigned short int</code>
4	<code>int</code> , <code>unsigned int</code>
5	<code>long int</code> , <code>unsigned long int</code>
6	<code>long long int</code> , <code>unsigned long long int</code>
7	<code>__int128_t</code>
8	<code>float</code>
9	<code>double</code>
10	<code>long double</code>

Source: <https://en.cppreference.com/w/c/language/conversion>

Integer Types Properties

Properties	
Width in bits	Data Type
8	<code>bool</code>
At least 8	<code>char</code> , <code>signed char</code> , <code>unsigned char</code>
At least 16	<code>short int</code> , <code>unsigned short int</code>
At least 16	<code>int</code> , <code>unsigned int</code>
At least 32	<code>long int</code> , <code>unsigned long int</code>
At least 64	<code>long long int</code> , <code>unsigned long long int</code>
128	<code>__int128_t</code>

Sources:

<https://en.cppreference.com/w/cpp/language/types>

<https://www.geeksforgeeks.org/c-data-types/>

<https://stackoverflow.com/questions/2064550/c-why-bool-is-8-bits-long>

Maths

Common Sums

$\sum_{k=0}^n k = \frac{n(n+1)}{2}$	$\sum_{k=0}^n k^2 = \frac{n(n+1)(2n+1)}{6}$	$\sum_{k=0}^n k^3 = \frac{n^2(n+1)^2}{4}$
$\sum_{k=0}^n k^4 = \frac{n}{30}(n+1)(2n+1)(3n^2+3n-1)$		$\sum_{k=0}^n a^k = \frac{1-a^{n+1}}{1-a}$
$\sum_{k=0}^n ka^k = \frac{a[1-(n+1)a^n+na^{n+1}]}{(1-a)^2}$	$\sum_{k=0}^n k^2a^k = \frac{a[(1+a)-(n+1)^2a^n+(2n^2+2n-1)a^{n+1}-n^2a^{n+2}]}{(1-a)^3}$	
$\sum_{k=0}^{\infty} a^k = \frac{1}{1-a}, a < 1$	$\sum_{k=0}^{\infty} ka^k = \frac{a}{(1-a)^2}, a < 1$	$\sum_{k=0}^{\infty} k^2a^k = \frac{a^2+a}{(1-a)^3}, a < 1$
$\sum_{k=0}^{\infty} \frac{1}{a^k} = \frac{a}{a-1}, a > 1$	$\sum_{k=0}^{\infty} \frac{k}{a^k} = \frac{a}{(a-1)^2}, a > 1$	$\sum_{k=0}^{\infty} \frac{k^2}{a^k} = \frac{a^2+a}{(a-1)^3}, a > 1$
$\sum_{k=0}^{\infty} \frac{a^k}{k!} = e^a$	$\sum_{k=0}^n \binom{n}{k} = 2^n$	$\sum_{k=0}^n \binom{k}{m} = \binom{n+1}{m+1}$

Logarithm Rules

$\log_b(b^k) = k$	$\log_b(1) = 0$	$\log_b(X) = \frac{\log_c(X)}{\log_c(b)}$
$\log_b(X \cdot Y) = \log_b(X) + \log_b(Y)$	$\log_b\left(\frac{X}{Y}\right) = \log_b(X) - \log_b(Y)$	$\log_b(X^k) = k \cdot \log_b(X)$