



EDUCACIÓN
SECRETARÍA DE EDUCACIÓN PÚBLICA



TECNOLÓGICO
NACIONAL DE MÉXICO®

TECNOLÓGICO NACIONAL DE MÉXICO

INSTITUTO TECNOLÓGICO DE TIJUANA

SUBDIRECCIÓN ACADÉMICA

DEPARTAMENTO DE SISTEMAS Y COMPUTACIÓN

NOMBRE DE LOS ALUMNOS:

GALAVIZ LONA OSCAR EDUARDO (N.CONTROL: 17212993)

MARQUEZ MILLAN SEASHELL VANESSA (N.CONTROL:)

Carrera: Ingeniería Informática

Semestre: 9no

MATERIA: Datos Masivos

PROFESOR: JOSE CHRISTIAN ROMERO HERNANDEZ

Practica evaluatoria 1

Unidad 1

2-. File Netflix Stock CSV

First need import the library, and is important you have the dataFrame in this address "/home/"name computer"/"name dataFrame" because the comand stearchh the archive here, then only print the data types

```
import org.apache.spark.sql.SparkSession

val spark = SparkSession.builder().getOrCreate()

val df = spark.read.option("header",
"true").option("inferSchema", "true").csv("Netflix_2011_2016.csv")
df
df.printSchema()
```

```
scala> df.printSchema()
root
|-- Date: timestamp (nullable = true)
|-- Open: double (nullable = true)
|-- High: double (nullable = true)
|-- Low: double (nullable = true)
|-- Close: double (nullable = true)
|-- Volume: integer (nullable = true)
|-- Adj Close: double (nullable = true)

scala> df
res47: org.apache.spark.sql.DataFrame = [Date: timestamp, Open: double ... 5 more fields]

scala> □
```

3-.Names columns

Here only we want see the column names, but we want see all columns on the DataFrame.

```
df.columns
```

```

cr: Int = 0
scala> while(cr < 5){
|   df.columns(cr)
|   cr=cr+1
| }

scala> var cr = 0
Recr: Int = 0

scala> while(cr < 5){
|   println( df.columns(cr))
|   cr=cr+1
| }

scala> df.columns
res5: Array[String] = Array(Date, Open, High, Low, Close, Volume, Adj Close)

scala>

```

4-.Schema

For know thw schema only need the dataFrame and the next reserved word, is for can you know the structure and the types of each column

```
df.printSchema()
```

```

scala> df.printSchema()
root
|-- Date: timestamp (nullable = true)
|-- Open: double (nullable = true)
|-- High: double (nullable = true)
|-- Low: double (nullable = true)
|-- Close: double (nullable = true)
|-- Volume: integer (nullable = true)
|-- Adj Close: double (nullable = true)

scala>

```

5-Print first 5 columns

For that need create a variable in this case `cr` and `i` say is equals to 0, then use `while` for create a bucle ever `cr` is less than 5, print the columns and increase `cr` if i don't do that is a infinite bucle

```
var cr = 0
while(cr < 5){
  println( df.columns(cr))
  cr=cr+1
}
```

```
seashell@seashell-VirtualBox: ~
scala> var cr = 0
cr: Int = 0
scala> while(cr < 5){
  |   df.columns(cr)
  |   cr=cr+1
  | }
Date
Open
High
Low
Close
scala>
```

6-.Uses describe ()

That comand is for knows more informations about the dataFrame, statistical data

```
df.describe().show()
```

```

Actividades Terminal 24 de sep 20:13
seashell@seashell-VirtualBox: ~

min| 53.990001| 55.480001| 52.81| 53.8| 3531300| 7.685714|
max| 708.900017| 716.159996| 697.569984| 707.610001| 315541800| 130.929993|
+-----+-----+-----+-----+-----+-----+-----+
scala>

scala> df.head(5)
res10: Array[org.apache.spark.sql.Row] = Array([2011-10-24 00:00:00.0,119.100002,120.28000300000001,115.100004,118.839996,120460200,16.97714
2], [2011-10-25 00:00:00.0,74.899999,79.390001,74.249997,77.370002,315541800,11.052857000000001], [2011-10-26 00:00:00.0,78.73,81.420001,75.
399997,79.400002,148733900,11.342857], [2011-10-27 00:00:00.0,82.179998,82.71999699999999,79.249998,80.86000200000001,71190000,11.5514289999
99999], [2011-10-28 00:00:00.0,80.280002,84.660002,79.599999,84.14000300000001,57769600,12.02])

scala> for(row <- df.head(5)){
  |   println(row)
  | }
[2011-10-24 00:00:00.0,119.100002,120.28000300000001,115.100004,118.839996,120460200,16.977142]
[2011-10-25 00:00:00.0,74.899999,79.390001,74.249997,77.370002,315541800,11.052857000000001]
[2011-10-26 00:00:00.0,78.73,81.420001,75.399997,79.400002,148733900,11.342857]
[2011-10-27 00:00:00.0,82.179998,82.71999699999999,79.249998,80.86000200000001,71190000,11.551428999999999]
[2011-10-28 00:00:00.0,80.280002,84.660002,79.599999,84.14000300000001,57769600,12.02]

scala> df.describe().show()
+-----+-----+-----+-----+-----+-----+-----+
|summary|      Open|      High|      Low|      Close|      Volume|      Adj Close|
+-----+-----+-----+-----+-----+-----+-----+
|count|      1259|      1259|      1259|      1259|      1259|      1259|
|mean|230.39351086656092|233.97320872915006|226.80127876251044|230.522453845909|2.5634836060365368E7|55.610540036536875|
|stddev|164.37456353264244|165.9705082667129|162.6506358235739|164.40918905512854|2.306312683388607E7|35.186669331525486|
|min|      53.990001|      55.480001|      52.81|      53.8|      3531300|      7.685714|
|max|      708.900017|      716.159996|      697.569984|      707.610001|      315541800|      130.929993|
+-----+-----+-----+-----+-----+-----+-----+

scala>

```

7.-Create new DataFrame with new column

We need create a new dataFrame for can to do some modification so here to make a new column with the relationship of column High and Volume

```
val newData = df.withColumn("HVRatio", df("High")/df("Volume"))
newData.show()
```

```

Actividades Terminal 24 de sep 21:47
seashell@seashell-VirtualBox: ~

scala> newData.show()
+-----+-----+-----+-----+-----+-----+-----+-----+
|Date|      Open|      High|      Low|      Close|      Volume|      Adj Close|      HVRatio|
+-----+-----+-----+-----+-----+-----+-----+-----+
|2011-10-24 00:00:00|119.100002|120.28000300000001|115.100004|118.839996|120460200|16.977142|9.985040951285156E-7|
|2011-10-25 00:00:00|74.899999|79.390001|74.249997|77.370002|315541800|11.052857000000001|2.515989989281927E-7|
|2011-10-26 00:00:00|78.73|81.420001|75.399997|79.400002|148733900|11.342857|5.474206014903126E-7|
|2011-10-27 00:00:00|82.179998|82.71999699999999|79.249998|80.86000200000001|71190000|11.551428999999999|1.161960907430818...|
|2011-10-28 00:00:00|80.280002|84.660002|79.599999|84.14000300000001|57769600|12.02|1.465476686700271...|
|2011-10-31 00:00:00|83.63999799999999|84.090002|81.450002|82.080003|39653600|11.725715|2.120614572195210...|
|2011-11-01 00:00:00|80.109998|80.999998|78.74|80.089997|33016200|11.441428|2.453341026526372E-6|
|2011-11-02 00:00:00|80.709998|84.400002|80.109998|83.389999|41384000|11.912857|2.039435578967717E-6|
|2011-11-03 00:00:00|84.130003|92.600003|81.800003|92.290003|94685500|13.184285999999998|9.77974483949496E-7|
|2011-11-04 00:00:00|91.46999699999999|92.89000300000001|87.749999|90.019998|84483700|12.86|1.099502069629999...|
|2011-11-07 00:00:00|91.0|93.839998|89.979997|90.830003|47485200|12.975715|1.976194645910725...|
|2011-11-08 00:00:00|91.22999899999999|92.600003|89.650002|90.470001|31906000|12.924286|2.902275528113834...|
|2011-11-09 00:00:00|89.000001|90.440001|87.999998|88.049999|28756000|12.578571|3.145082800111281E-6|
|2011-11-10 00:00:00|89.290001|90.29999699999999|84.839999|85.11999899999999|39614400|12.16|2.279474054889131E-6|
|2011-11-11 00:00:00|85.899997|87.949997|83.7|87.749999|38140200|12.535714|2.305965805108520...|
|2011-11-14 00:00:00|87.989998|88.1|85.45|85.719999|21811300|12.245714|4.039190694731629...|
|2011-11-15 00:00:00|85.15|87.050003|84.499998|86.279999|21372400|12.325714|4.073010190713256...|
|2011-11-16 00:00:00|86.460003|86.460003|80.890002|81.180002|34560400|11.597142999999999|2.501707242971725E-6|
|2011-11-17 00:00:00|80.77|80.999998|75.789999|76.460001|52823400|10.922857|1.533411291208063...|
|2011-11-18 00:00:00|76.7|78.999999|76.039998|78.059998|34729100|11.151428|2.274749388841058...|
+-----+-----+-----+-----+-----+-----+-----+-----+
only showing top 20 rows

scala>

```

8-.Max Open

We need know the date of the maxium data, so first we order the column Open and save in maxp then select Date of de maxp but only the first row

```
val maxp = newData.orderBy(desc("Open"))
maxp.select("Date").limit(1).show()
```

```

Actividades  Terminal  24 de sep 22:34
seashell@seashell-VirtualBox: ~

5|
|2015-07-09 00:00:00|      664.300011|      670.919975|      659.999992|      670.089996|16076900|      95.727142|4.173192437596800..
.|
|2015-07-01 00:00:00|663.6400219999999|666.6699980000001|652.5300219999999|655.449982|14699300|93.635712|4.535386025184873E-
5|
|2015-06-18 00:00:00|662.5599980000001|667.3900150000001|660.579979|663.200012|8962800|94.742859|7.446222330075424E-
5|
|2015-06-16 00:00:00|659.700012|669.249977|655.840004|666.910004|16043300|95.272858|4.171523171666676..
.|
|2015-07-02 00:00:00|657.990013|659.389992|652.500008|658.31002|11053000|94.044289|5.965710594408758E-
5|
|2015-07-06 00:00:00|654.309982|664.5000150000001|653.3799740000001|661.9999849999999|11808300|94.571426|5.627397804933818E-
5|
|2015-07-08 00:00:00|654.299995|657.9699860000001|645.990005|654.549988|12990600|93.507141|5.064969947500500..
.|
+-----+-----+-----+-----+-----+-----+-----+-----+
+-+
only showing top 20 rows

maxp: Unit = ()

scala>

scala> val maxp = newData.orderBy(desc("Open"))
maxp: org.apache.spark.sql.Dataset[org.apache.spark.sql.Row] = [Date: timestamp, Open: double ... 6 more fields]

scala> maxp.select("Date").limit(1).show()
+-----+
|          Date|
+-----+
|2015-07-14 00:00:00|
+-----+

scala> 
```

9-.Meaning Close in DataFrame

When the price of the High column goes up it seems to be the same for the Close column only that it is always less than High, which means that as High it goes up, the most probable thing is that Close will also do it but in less quantity

```
newData.orderBy(desc("Close")).show()
```

10-.Maximum and minimum of Volume

This is only to know thw first row the most big and the most lowest, and oly select the volume and your minium or maximun

```
df.select(max("Volume")).show()
df.select(min("Volume")).show()
```

```

Actividades Terminal 24 de sep 22:56
seashell@seashell-VirtualBox: ~
at org.apache.spark.sql.catalyst.analysis.Analyzer.checkAnalysis(Analyzer.scala:95)
at org.apache.spark.sql.catalyst.analysis.Analyzer$$anonfun$executeAndCheck$1.apply(Analyzer.scala:108)
at org.apache.spark.sql.catalyst.analysis.Analyzer$$anonfun$executeAndCheck$1.apply(Analyzer.scala:105)
at org.apache.spark.sql.catalyst.plans.logical.AnalysisHelper.markInAnalyzer(AnalysisHelper.scala:201)
at org.apache.spark.sql.catalyst.analysis.Analyzer.executeAndCheck(Analyzer.scala:105)
at org.apache.spark.sql.execution.QueryExecution.analyzed$lzycompute(QueryExecution.scala:57)
at org.apache.spark.sql.execution.QueryExecution.analyzed(QueryExecution.scala:55)
at org.apache.spark.sql.execution.QueryExecution.assertAnalyzed(QueryExecution.scala:47)
at org.apache.spark.sql.Dataset$.ofRows(Dataset.scala:78)
at org.apache.spark.sql.Dataset.org$apache$spark$sql$Dataset$withPlan(Dataset.scala:3406)
at org.apache.spark.sql.Dataset.select(Dataset.scala:1334)
... 49 elided

scala> df.select(max("Volume")).show()
+-----+
|max(Volume)|
+-----+
| 315541800|
+-----+

scala> df.select(min("Volume")).show()
+-----+
|min(Volume)|
+-----+
| 3531300|
+-----+

scala>
scala> val dfvol = maxV+minV
<console>:25: error: not found: value maxV
    val dfvol = maxV+minV
                  ^

```

11-.With Scala/Spark \$ resolve the next

A-.With Scala/Spark \$ resolve the next

Need to know the data less than numbers 600 and cout that

```
df.filter($"Close"<600).count()
```



```
Actividades Terminal 24 de sep 22:58
seashell@seashell-VirtualBox: ~

+-----+
| 3531300|
+-----+

scala>
scala> val dfvol = maxV+minV
<console>:25: error: not found: value maxV
    val dfvol = maxV+minV
                  ^
<console>:25: error: not found: value minV
    val dfvol = maxV+minV
                  ^

scala> val maxV = df.select(max("Volume"))
maxV: org.apache.spark.sql.DataFrame = [max(Volume): int]

scala> val minV = df.select(min("Volume"))
minV: org.apache.spark.sql.DataFrame = [min(Volume): int]

scala> val dfvol = maxV+minV
<console>:29: error: type mismatch;
 found   : org.apache.spark.sql.DataFrame
        (which expands to)  org.apache.spark.sql.Dataset[org.apache.spark.sql.Row]
 required: String
    val dfvol = maxV+minV
                  ^

scala>
scala> df.filter($"Close"<600).count()
res31: Long = 1218

scala> 
```

B.-We need to know what is the percentage of time in this question

```
val tiempo:Double = df.filter($"High">500).count()
val porcentaje:Double = (tiempo*100)/1259
```

```

scala> import sqlContext.implicits._
<console>:24: error: not found: value sqlContext
      import sqlContext.implicits._
      ^

scala> import org.apache.spark.sql._
import org.apache.spark.sql._

scala> import spark.implicits._
import spark.implicits._

scala> val tiempo:Double = df.filter($"High">500).count()
tiempo: Double = 62.0

scala> val porcentaje double = (tiempo*100)/1259
<console>:1: error: illegal start of simple pattern
val porcentaje double = (tiempo*100)/1259
      ^

scala> val porcentaje:Double = (tiempo*100)/1259
porcentaje: Double = 4.924543288324067

scala>

```

C-.We need to know what is the correlation of high and volumen

```
df.select(corr("High","Volume").alias("Correlacion")).show()
```

```

at org.apache.spark.util.ClosureCleaner$$anonfun$org$apache$spark$util$ClosureCleaner$$clean$14.apply(ClosureCleaner.scala:271)
at scala.collection.immutable.List.foreach(List.scala:392)
at org.apache.spark.util.ClosureCleaner$.org$apache$spark$util$ClosureCleaner$$clean(ClosureCleaner.scala:271)
at org.apache.spark.util.ClosureCleaner$.clean(ClosureCleaner.scala:163)
at org.apache.spark.sql.execution.SparkContext.clean(SparkContext.scala:2332)
at org.apache.spark.sql.execution.SparkContext.runJob(SparkContext.scala:2106)
at org.apache.spark.sql.execution.SparkContext.runJob(SparkContext.scala:2132)
at org.apache.spark.rdd.RDD$$anonfun$collect$1.apply(RDD.scala:990)
at org.apache.spark.rdd.RDDOperationScope$.withScope(RDDOperationScope.scala:151)
at org.apache.spark.rdd.RDDOperationScope$.withScope(RDDOperationScope.scala:112)
at org.apache.spark.rdd.RDD.withScope(RDD.scala:385)
at org.apache.spark.rdd.RDD.collect(RDD.scala:989)
at org.apache.spark.sql.execution.SparkPlan.executeCollect(SparkPlan.scala:304)
at org.apache.spark.sql.Dataset$$anonfun$count$1.apply(Dataset.scala:2836)
at org.apache.spark.sql.Dataset$$anonfun$count$1.apply(Dataset.scala:2835)
at org.apache.spark.sql.Dataset$$anonfun$53.apply(Dataset.scala:3369)
at org.apache.spark.sql.execution.SQLExecution$$anonfun$withNewExecutionId$1.apply(SQLExecution.scala:80)
at org.apache.spark.sql.execution.SQLExecution$.withSQLConfPropagated(SQLExecution.scala:127)
at org.apache.spark.sql.execution.SQLExecution$.withNewExecutionId(SQLExecution.scala:75)
at org.apache.spark.sql.Dataset.org$apache$spark$sql$Dataset$$withAction(Dataset.scala:3368)
at org.apache.spark.sql.Dataset.count(Dataset.scala:2835)
... 49 elided

scala> df.select(corr("High","Volume").alias("Correlacion")).show()
+-----+
|          Correlacion|
+-----+
|-0.20960233287942157|
+-----+

scala>

```

D-.We need to know which are the maximun for each year

```
df.groupBy(year(df("Date"))).alias("Year")).max("High").sort(asc("Year")).show()
```

```

at org.apache.spark.sql.Dataset$$anonfun$count$1.apply(Dataset.scala:2836)
at org.apache.spark.sql.Dataset$$anonfun$count$1.apply(Dataset.scala:2835)
at org.apache.spark.sql.Dataset$$anonfun$53.apply(Dataset.scala:3369)
at org.apache.spark.sql.execution.SQLExecution$$anonfun$withNewExecutionId$1.apply(SQLExecution.scala:80)
at org.apache.spark.sql.execution.SQLExecution$.withSQLConfPropagated(SQLExecution.scala:127)
at org.apache.spark.sql.execution.SQLExecution$.withNewExecutionId(SQLExecution.scala:75)
at org.apache.spark.sql.Dataset.org$apache$spark$sql$Dataset$$withAction(Dataset.scala:3368)
at org.apache.spark.sql.Dataset.count(Dataset.scala:2835)
... 49 elided

scala> df.select(corr("High","Volume").alias("Correlacion")).show()
+-----+
|          Correlacion|
+-----+
|-0.20960233287942157|
+-----+

scala> df.groupBy(year(df("Date")).alias("Year")).max("High").sort(asc("Year")).show()
+-----+-----+
|Year|      max(High)|
+-----+-----+
|2011|120.28000300000001|
|2012|   133.429996|
|2013|   389.159988|
|2014|   489.290024|
|2015|   716.159996|
|2016|129.28999299999998|
+-----+-----+

scala> 

```

E-.This question deals with knowing the average close for each month

```
df.groupBy(month(df("Date"))).alias("Month")).avg("Close").sort(asc("Month")).show()
```

```
usuario@ubuntu-20: ~  
+-----+  
|Year|      max(High)|  
+-----+  
|2011|120.28000300000001|  
|2012|      133.429996|  
|2013|      389.159988|  
|2014|      489.290024|  
|2015|      716.159996|  
|2016|129.28999299999998|  
+-----+  
  
scala> df.groupBy(month(df("Date")).alias("Month")).avg("Close").sort(asc("Month")).show()  
+-----+  
|Month|      avg(Close)|  
+-----+  
|  1|212.22613874257422|  
|  2| 254.1954634020619|  
|  3| 249.5825228971963|  
|  4|246.97514271428562|  
|  5|264.37037614150944|  
|  6| 295.1597153490566|  
|  7|243.64747528037387|  
|  8|195.25599892727263|  
|  9|206.09598121568627|  
| 10|205.93297300900903|  
| 11| 194.3172275445545|  
| 12| 199.3700942358491|  
+-----+  
  
scala> █
```