

Assignment 2: Coding Basics

Christopher Starr

OVERVIEW

This exercise accompanies the lessons/labs in Environmental Data Analytics on coding basics.

Directions

1. Rename this file `<FirstLast>_A02_CodingBasics.Rmd` (replacing `<FirstLast>` with your first and last name).
2. Change “Student Name” on line 3 (above) with your name.
3. Work through the steps, **creating code and output** that fulfill each instruction.
4. Be sure to **answer the questions** in this assignment document.
5. When you have completed the assignment, **Knit** the text and code into a single PDF file.
6. After Knitting, submit the completed exercise (PDF file) to Canvas.

Basics, Part 1

1. Generate a sequence of numbers from one to 55, increasing by fives. Assign this sequence a name.
2. Compute the mean and median of this sequence.
3. Ask R to determine whether the mean is greater than the median.
4. Insert comments in your code to describe what you are doing.

```
#1. Generate a sequence of numbers from one to 55, increasing by fives. Assign this sequence a name.
seq1.55.5.assignment01 <- seq(1,55,5) #naming the sequence "seq1.55.5.assignment01" then generating the

#2. Compute the mean and median of this sequence.

meanseq1.55.5.assignment01 <- mean(seq1.55.5.assignment01) #naming the mean of "seq1..."
medianseq1.55.5.assignment01 <- median(seq1.55.5.assignment01) #naming the med of "seq1..."

#3. Ask R to determine whether the mean is greater than the median.

meanseq1.55.5.assignment01 > medianseq1.55.5.assignment01 #asking R to evaluate the statement Mean is g

## [1] FALSE
```

Basics, Part 2

5. Create three vectors, each with four components, consisting of (a) student names, (b) test scores, and (c) whether they are on scholarship or not (TRUE or FALSE).
6. Label each vector with a comment on what type of vector it is.
7. Combine each of the vectors into a data frame. Assign the data frame an informative name.
8. Label the columns of your data frame with informative titles.

```
studentnames <- c("Tom","Mick", "Harry", "Angie") #create student names vector
testscores <- c(75,79,68,97) #create a list of test scores
scholarshipstatus <- c(TRUE,FALSE,FALSE,TRUE) #designation of scholarship status TRUE=on a scholarship
studentrecords <- data.frame(studentnames, testscores, scholarshipstatus) #combine each independent vec
```

9. QUESTION: How is this data frame different from a matrix?

Answer: This data frame has different kinds of data. Student names are strings, test scores are numbers, scholarship T/F is logic (or maybe could be a 1 or 0 or even string).

10. Create a function with one input. In this function, use `if...else` to evaluate the value of the input: if it is greater than 50, print the word “Pass”; otherwise print the word “Fail”.
11. Create a second function that does the exact same thing as the previous one but uses `ifelse()` instead of `if...else`.
12. Run both functions using the value 52.5 as the input
13. Run both functions using the **vector** of student test scores you created as the input. (Only one will work properly...)

```
#10. Create a function using if...else
evaluatingcoreif...else <- function(x){
  if (x>50) print("Pass") else
  print("Fail") #creating the recipe for if...else version
}
#11. Create a function using ifelse()
evaluatingcoreifelse <- function(x){
  ifelse(x>50, "Pass", "Fail")
} #creating the recipe for ifelse version

#12a. Run the first function with the value 52.5
simplefunctionif...else <- evaluatingcoreif...else(52.5) #writing instruction for asking evaluatingcoreif...else

## [1] "Pass"

simplefunctionif...else #telling the function to run with 52.5 added for x.

## [1] "Pass"
```

```
#12b. Run the second function with the value 52.5
simplefunctionifelse <- evaluatingscoreifelse(52.5) #writing instructions for asking function evaluation

simplefunctionifelse #telling the function to run with 52.5

## [1] "Pass"
```

```
#13a. Run the first function with the vector of test scores

###commenting out as this code throws an error ### simplefunctionif.else_testscore_list <- evaluatingscoreifelse(testscores)

###commenting out as this code throws an error ### simplefunctionif.else_testscore_list #telling the function to run with test scores

#13b. Run the second function with the vector of test scores
simplefunctionifelse_testscore_list <- evaluatingscoreifelse(testscores) #writing instructions for asking function evaluation

simplefunctionifelse_testscore_list #telling the function to run with test scores for x

## [1] "Pass" "Pass" "Pass" "Pass"
```

14. QUESTION: Which option of `if...else` vs. `ifelse` worked? Why? (Hint: search the web for “R vectorization”)

Answer: it seems `if/else` does not loop itself, or it can’t run multiple times the function automatically. it says it can only do it once: “Error in `if (x > 50) print(“Pass”) else print(“Fail”) :the condition has length > 1`”

it seems `ifelse()` is able to vectorize or run all values from the list as a sort of loop function.

NOTE Before knitting, you’ll need to comment out the call to the function in Q13 that does not work. (A document can’t knit if the code it contains causes an error!)