

1.0 COMPOSITION

119 is a black rubber cloth inserted sheet of high strength. The spun polyester cloth insertion is on the inside. Both sides are protected by a Styrene Butadiene Rubber (SBR) cover.

2.0 USAGE

This material is designed for use in light hydraulic service, hot or cold water, low pressure steam and ammonia to 180°F (82°C).

3.0 SPECIFIC PROPERTIES

- A. Width - 36" \pm 1" (91cm \pm 2,5)
- B. Thickness, Inches - 1/16, 3/32, 1/8, 3/16, 1/4
- C. Elongation, % - 200 Minimum
- D. Durometer - 70 to 85
- E. Specific Gravity - 1.46 g/cc
- F. Tensile Strength - 400 PSI (28 BAR)
- G. Color - Black

A.W. CHESTERTON CO.

225 FALLON ROAD, MIDDLESEX INDUSTRIAL PARK
STONEHAM, MASSACHUSETTS 02180-9101 USA
TELEX: 94-9417 • FAX: (617) 438-8971
TEL: (617) 438-7000
CABLE: Chesterton Stoneham, Mass.

©A.W. CHESTERTON CO., 1994. All Rights Reserved.
® Registered trademark owned and licensed by
A.W. CHESTERTON CO. in USA and other countries.