

book_to_slide_BY_sections_V6_Image_data copy

July 5, 2025

1 Set up Paths

```
[ ]: # Cell 1: Setup and Configuration
import os
import re
import logging
import warnings
from PIL import Image
import io
from docx import Document
import pdfplumber
import ollama
from tenacity import retry, stop_after_attempt, wait_exponential, RetryError
import json

# Setup Logger for this cell
logging.basicConfig(level=logging.INFO, format='%(asctime)s - %(levelname)s - %(message)s')
logger = logging.getLogger(__name__)

# --- 1. CORE SETTINGS ---
# Set this to True for EPUB, False for PDF. This controls the entire notebook's flow.
PROCESS_EPUB = True # for EPUB
# PROCESS_EPUB = False # for PDF

# --- 2. INPUT FILE NAMES ---
# The name of the Unit Outline file (e.g., DOCX, PDF)
UNIT_OUTLINE_FILENAME = "ICT312 Digital Forensic_Final.docx" # epub
# UNIT_OUTLINE_FILENAME = "ICT311 Applied Cryptography.docx" # pdf

EXTRACT_UO = False

# The names of the book files
EPUB_BOOK_FILENAME = "Bill Nelson, Amelia Phillips, Christopher Steuart - Guide to Computer Forensics and Investigations_ Processing Digital Evidence-Cengage Learning (2018).epub"
```

```

PDF_BOOK_FILENAME = "(Chapman & Hall_CRC Cryptography and Network Security_
↳Series) Jonathan Katz, Yehuda Lindell - Introduction to Modern_
↳Cryptography-CRC Press (2020).pdf"

# --- 3. DIRECTORY STRUCTURE ---
# Define the base path to your project to avoid hardcoding long paths everywhere
PROJECT_BASE_DIR = "/home/sebas_dev_linux/projects/course_generator"

# Define subdirectories relative to the base path
DATA_DIR = os.path.join(PROJECT_BASE_DIR, "data")
PARSE_DATA_DIR = os.path.join(PROJECT_BASE_DIR, "Parse_data")

# Construct full paths for clarity
INPUT_UO_DIR = os.path.join(DATA_DIR, "UO")
INPUT_BOOKS_DIR = os.path.join(DATA_DIR, "books")
OUTPUT_PARSED_UO_DIR = os.path.join(PARSE_DATA_DIR, "Parse_UO")
OUTPUT_PARSED_TOC_DIR = os.path.join(PARSE_DATA_DIR, "Parse_TOC_books")
OUTPUT_DB_DIR = os.path.join(DATA_DIR, "DataBase_Chroma")
OUTPUT_IMAGES_DIR = os.path.join(PROJECT_BASE_DIR, "extracted_images")
os.makedirs(OUTPUT_IMAGES_DIR, exist_ok=True)

# --- 4. LLM & EMBEDDING CONFIGURATION ---
LLM_PROVIDER = "ollama" # Can be "ollama", "openai", "gemini"
OLLAMA_HOST = "http://localhost:11434"
OLLAMA_MODEL = "qwen3:8b" # "qwen3:8b", #"mistral:latest"
EMBEDDING_MODEL_OLLAMA = "nomic-embed-text"
CHUNK_SIZE = 800
CHUNK_OVERLAP = 100

# --- 5. DYNAMICALLY GENERATED PATHS & IDs (DO NOT EDIT THIS SECTION) ---
# This section uses the settings above to create all the necessary variables_
↳for later cells.

# Extract Unit ID from the filename
def print_header(text: str, char: str = "="):
    """Prints a centered header to the console."""
    print("\n" + char * 80)
    print(text.center(80))
    print(char * 80)

def extract_uo_id_from_filename(filename: str) -> str:
    match = re.match(r'^[A-Z]+\d+', os.path.basename(filename))
    if match:
        return match.group(0)
    raise ValueError(f"Could not extract a valid Unit ID from filename:
↳'{filename}'")

```

```

try:
    UNIT_ID = extract_uo_id_from_filename(UNIT_OUTLINE_FILENAME)
except ValueError as e:
    print(f"Error: {e}")
    UNIT_ID = "UNKNOWN_ID"

# Full path to the unit outline file
FULL_PATH_UNIT_OUTLINE = os.path.join(INPUT_UO_DIR, UNIT_OUTLINE_FILENAME)

# Determine which book and output paths to use based on the PROCESS_EPUB flag
if PROCESS_EPUB:
    BOOK_PATH = os.path.join(INPUT_BOOKS_DIR, EPUB_BOOK_FILENAME)
    PRE_EXTRACTED_TOC_JSON_PATH = os.path.join(OUTPUT_PARSED_TOC_DIR,
    ↪f"{UNIT_ID}_epub_table_of_contents.json")
else:
    BOOK_PATH = os.path.join(INPUT_BOOKS_DIR, PDF_BOOK_FILENAME)
    PRE_EXTRACTED_TOC_JSON_PATH = os.path.join(OUTPUT_PARSED_TOC_DIR,
    ↪f"{UNIT_ID}_pdf_table_of_contents.json")

# Define paths for the vector database
file_type_suffix = 'epub' if PROCESS_EPUB else 'pdf'
CHROMA_PERSIST_DIR = os.path.join(OUTPUT_DB_DIR,
    ↪f"chroma_db_toc_guided_chunks_{file_type_suffix}")
CHROMA_COLLECTION_NAME = f"book_toc_guided_chunks_{file_type_suffix}_v2"

# Define path for the parsed unit outline
PARSED_UO_JSON_PATH = os.path.join(OUTPUT_PARSED_UO_DIR, f"{os.path.
    ↪splitext(UNIT_OUTLINE_FILENAME)[0]}_parsed.json")

# --- Sanity Check Printout ---
print("--- CONFIGURATION SUMMARY ---")
print(f"Processing Mode: {'EPUB' if PROCESS_EPUB else 'PDF'}")
print(f"Unit ID: {UNIT_ID}")
print(f"Unit Outline Path: {FULL_PATH_UNIT_OUTLINE}")
print(f"Book Path: {BOOK_PATH}")
print(f"Parsed UO Output Path: {PARSED_UO_JSON_PATH}")
print(f"Parsed ToC Output Path: {PRE_EXTRACTED_TOC_JSON_PATH}")
print(f"Vector DB Path: {CHROMA_PERSIST_DIR}")
print(f"Vector DB Collection: {CHROMA_COLLECTION_NAME}")
print("--- SETUP COMPLETE ---")

```

2 System Prompt

```
[ ]: UNIT_OUTLINE_SYSTEM_PROMPT_TEMPLATE = """
You are an expert academic assistant tasked with parsing a university unit_
  ↳outline document and extracting key information into a structured JSON_
  ↳format.

The input will be the raw text content of a unit outline. Your goal is to_
  ↳identify and extract the following details and structure them precisely as_
  ↳specified in the JSON schema below. Note: do not change any key name

**JSON Output Schema:**

```json
{{
 "unitInformation": {{
 "unitCode": "string | null",
 "unitName": "string | null",
 "creditPoints": "integer | null",
 "unitRationale": "string | null",
 "prerequisites": "string | null"
 }},
 "learningOutcomes": [
 "string"
],
 "assessments": [
 {{
 "taskName": "string",
 "description": "string",
 "dueWeek": "string | null",
 "weightingPercent": "integer | null",
 "learningOutcomesAssessed": "string | null"
 }}
],
 "weeklySchedule": [
 {{
 "week": "string",
 "contentTopic": "string",
 "requiredReading": "string | null"
 }}
],
 "requiredReadings": [
 "string"
],
 "recommendedReadings": [
 "string"
]
}}
```

```
}}
```

Instructions for Extraction:

Unit Information: Locate Unit Code, Unit Name, Credit Points. Capture 'Unit Overview / Rationale' as unitRationale. Identify prerequisites.

Learning Outcomes: Extract each learning outcome statement.

Assessments: Each task as an object. Capture full task name, description, Due Week, Weighting % (number), and Learning Outcomes Assessed.

weeklySchedule: Each week as an object. Capture Week, contentTopic, and requiredReading.

Required and Recommended Readings: List full text for each.

**\*\*Important Considerations for the LLM\*\*:**

Pay close attention to headings and table structures.

If information is missing, use null for string/integer fields, or an empty list [] for array fields.

Do not change keys in the template given

Ensure the output is ONLY the JSON object, starting with {{{ and ending with }}}. No explanations or conversational text before or after the JSON.

Now, parse the following unit outline text:

```
--- UNIT_OUTLINE_TEXT_START ---
{outline_text}
--- UNIT_OUTLINE_TEXT_END ---
"""
```

```
[]: # Place this in a new cell after your imports, or within Cell 3 before the
 functions.
```

```
This code is based on the schema from your screenshot on page 4.
```

```
from pydantic import BaseModel, Field, ValidationError
from typing import List, Optional
import time
```

```
Define Pydantic models that match your JSON schema
```

```
class UnitInformation(BaseModel):
 unitCode: Optional[str] = None
 unitName: Optional[str] = None
 creditPoints: Optional[int] = None
 unitRationale: Optional[str] = None
 prerequisites: Optional[str] = None
```

```
class Assessment(BaseModel):
 taskName: str
 description: str
 dueWeek: Optional[str] = None
 weightingPercent: Optional[int] = None
 learningOutcomesAssessed: Optional[str] = None
```

```

class WeeklyScheduleItem(BaseModel):
 week: str
 contentTopic: str
 requiredReading: Optional[str] = None

class ParsedUnitOutline(BaseModel):
 unitInformation: UnitInformation
 learningOutcomes: List[str]
 assessments: List[Assessment]
 weeklySchedule: List[WeeklyScheduleItem]
 requiredReadings: List[str]
 recommendedReadings: List[str]

```

### 3 Extrac Unit outline details to process following steps - output raw json with UO details

```

[]: # Cell 3: Parse Unit Outline

--- Helper Functions for Parsing ---
def extract_text_from_file(filepath: str) -> str:
 _, ext = os.path.splitext(filepath.lower())
 if ext == '.docx':
 doc = Document(filepath)
 full_text = [p.text for p in doc.paragraphs]
 for table in doc.tables:
 for row in table.rows:
 full_text.append(" | ".join(cell.text for cell in row.cells))
 return '\n'.join(full_text)
 elif ext == '.pdf':
 with pdfplumber.open(filepath) as pdf:
 return "\n".join(page.extract_text() for page in pdf.pages if page.
extract_text())
 else:
 raise TypeError(f"Unsupported file type: {ext}")

def parse_llm_json_output(content: str) -> dict:
 try:
 match = re.search(r'\{.*\}', content, re.DOTALL)
 if not match: return None
 return json.loads(match.group(0))
 except (json.JSONDecodeError, TypeError):
 return None

@retry(stop=stop_after_attempt(3), wait=wait_exponential(min=2, max=10))
def call_ollama_with_retry(client, prompt):

```

```

logger.info(f"Calling Ollama model '{OLLAMA_MODEL}'...")
response = client.chat(
 model=OLLAMA_MODEL,
 messages=[{"role": "user", "content": prompt}],
 format="json",
 options={"temperature": 0.0}
)
if not response or 'message' not in response or not response['message'].
↳get('content'):
 raise ValueError("Ollama returned an empty or invalid response.")
 return response['message']['content']

--- Main Orchestration Function for this Cell ---
def parse_and_save_outline_robust(
 input_filepath: str,
 output_filepath: str,
 prompt_template: str,
 max_retries: int = 3
):
 logger.info(f"Starting to robustly process Unit Outline: {input_filepath}")

 if not os.path.exists(input_filepath):
 logger.error(f"Input file not found: {input_filepath}")
 return

 try:
 outline_text = extract_text_from_file(input_filepath)
 if not outline_text.strip():
 logger.error("Extracted text is empty. Aborting.")
 return
 except Exception as e:
 logger.error(f"Failed to extract text from file: {e}", exc_info=True)
 return

 client = ollama.Client(host=OLLAMA_HOST)
 current_prompt = prompt_template.format(outline_text=outline_text)

 for attempt in range(max_retries):
 logger.info(f"Attempt {attempt + 1}/{max_retries} to parse outline.")

 try:
 # Call the LLM
 llm_output_str = call_ollama_with_retry(client, current_prompt)

 # Find the JSON blob in the response
 json_blob = parse_llm_json_output(llm_output_str) # Your existing
↳helper

```

```

 if not json_blob:
 raise ValueError("LLM did not return a parsable JSON object.")

 # *** THE KEY VALIDATION STEP ***
 # Try to parse the dictionary into your Pydantic model.
 # This will raise a `ValidationError` if keys are wrong, types are
 wrong, or fields are missing.
 parsed_data = ParsedUnitOutline.model_validate(json_blob)

 # If successful, save the validated data and exit the loop
 logger.info("Successfully validated JSON structure against Pydantic
 model.")

 os.makedirs(os.path.dirname(output_filepath), exist_ok=True)
 with open(output_filepath, 'w', encoding='utf-8') as f:
 # Use .model_dump_json() for clean, validated output
 f.write(parsed_data.model_dump_json(indent=2))

 logger.info(f"Successfully parsed and saved Unit Outline to:
 {output_filepath}")
 return # Exit function on success

 except ValidationError as e:
 logger.warning(f"Validation failed on attempt {attempt + 1}. Error:
 {e}")

 # Formulate a new prompt with the error message for self-correction
 error_feedback = (
 f"\n\nYour previous attempt failed. You MUST correct the
 following errors:\n"
 f"{e}\n\n"
 f"Please regenerate the entire JSON object, ensuring it
 strictly adheres to the schema "
 f"and corrects these specific errors. Do not change any key
 names."
)
 current_prompt = current_prompt + error_feedback # Append the error
 to the prompt

 except Exception as e:
 # Catch other errors like network issues from call_ollama_with_retry
 logger.error(f"An unexpected error occurred on attempt {attempt +
 1}: {e}", exc_info=True)
 # You might want to wait before retrying for non-validation errors
 time.sleep(5)

 logger.error(f"Failed to get valid structured data from the LLM after
 {max_retries} attempts.")

```



```

--- In your execution block, call the new function ---
parse_and_save_outline(...) becomes:

if EXTRACT_UO:
 parse_and_save_outline_robust(
 input_filepath=FULL_PATH_UNIT_OUTLINE,
 output_filepath=PARSED_UO_JSON_PATH,
 prompt_template=UNIT_OUTLINE_SYSTEM_PROMPT_TEMPLATE
)

```

## 4 Extract TOC from epub or epub

[ ]: # Cell 4: Extract Book Table of Contents (ToC) with Pre-assigned IDs, Links, and Full Title Paths

```

from ebooklib import epub, ITEM_NAVIGATION
from bs4 import BeautifulSoup
import fitz # PyMuPDF
import json
import os
from typing import List, Dict
import urllib.parse # Needed to clean up links

=====
1. HELPER FUNCTIONS
=====

def clean_epub_href(href: str) -> str:
 """Removes URL fragments and decodes URL-encoded characters."""
 if not href: return ""
 cleaned_href = href.split('#')[0]
 return urllib.parse.unquote(cleaned_href)

--- NEW: Helper to add full title paths to any ToC hierarchy ---
def _add_paths_to_hierarchy(nodes: List[Dict], current_path: List[str] = []):
 """
 Recursively traverses a list of ToC nodes and adds a 'titles_path'
 key to each node, containing the full list of titles from the root.
 """
 for node in nodes:
 # Construct the new path for the current node
 new_path = current_path + [node['title']]
 node['titles_path'] = new_path

```

```

 # Recurse into the children with the updated path
 if node.get('children'):
 _add_paths_to_hierarchy(node['children'], new_path)

--- EPUB Extraction Logic ---
def parse_navpoint(navpoint: BeautifulSoup, counter: List[int], level: int = 0) → Dict:
 """Recursively parses EPUB 2 navPoints and assigns a toc_id and link_filename."""
 title = navpoint.navLabel.text.strip()
 if not title: return None

 content_tag = navpoint.find('content', recursive=False)
 link_filename = clean_epub_href(content_tag['src']) if content_tag else ""

 node = {
 "level": level,
 "toc_id": counter[0],
 "title": title,
 "link_filename": link_filename,
 "children": []
 }
 counter[0] += 1

 for child_navpoint in navpoint.find_all('navPoint', recursive=False):
 child_node = parse_navpoint(child_navpoint, counter, level + 1)
 if child_node: node["children"].append(child_node)

 return node

def parse_li(li_element: BeautifulSoup, counter: List[int], level: int = 0) → Dict:
 """Recursively parses EPUB 3 elements and assigns a toc_id and link_filename."""
 a_tag = li_element.find('a', recursive=False)
 if a_tag:
 title = a_tag.get_text(strip=True)
 if not title: return None

 link_filename = clean_epub_href(a_tag.get('href'))

 node = {
 "level": level,
 "toc_id": counter[0],
 "title": title,
 "link_filename": link_filename,
 "children": []
 }

```

```

 }
 counter[0] += 1

 nested_ol = li_element.find('ol', recursive=False)
 if nested_ol:
 for sub_li in nested_ol.find_all('li', recursive=False):
 child_node = parse_li(sub_li, counter, level + 1)
 if child_node: node["children"].append(child_node)
 return node
 return None

def extract_epub_toc(epub_path, output_json_path):
 print(f"Processing EPUB ToC for: {epub_path}")
 toc_data = []
 book = epub.read_epub(epub_path)
 id_counter = [1]

 for nav_item in book.get_items_of_type(ITEM_NAVIGATION):
 soup = BeautifulSoup(nav_item.get_content(), 'xml')
 if nav_item.get_name().endswith('.ncx'):
 print("INFO: Found EPUB 2 (NCX) Table of Contents. Parsing...")
 navmap = soup.find('navMap')
 if navmap:
 for navpoint in navmap.find_all('navPoint', recursive=False):
 node = parse_navpoint(navpoint, id_counter, level=0)
 if node: toc_data.append(node)
 else: # Assumes EPUB 3
 print("INFO: Found EPUB 3 (XHTML) Table of Contents. Parsing...")
 toc_nav = soup.select_one('nav[epub:type="toc"]')
 if toc_nav:
 top_ol = toc_nav.find('ol', recursive=False)
 if top_ol:
 for li in top_ol.find_all('li', recursive=False):
 node = parse_li(li, id_counter, level=0)
 if node: toc_data.append(node)
 if toc_data: break

 if toc_data:
 # --- MODIFICATION: Add the full title paths ---
 print("INFO: Annotating ToC with full title paths...")
 _add_paths_to_hierarchy(toc_data)

 os.makedirs(os.path.dirname(output_json_path), exist_ok=True)
 with open(output_json_path, 'w', encoding='utf-8') as f:
 json.dump(toc_data, f, indent=2, ensure_ascii=False)
 print(f" Successfully wrote EPUB ToC with IDs, links, and paths to: ↵
↵{output_json_path}")

```

```

else:
 print(" WARNING: No ToC data extracted from EPUB.")

--- PDF Extraction Logic ---
def build_pdf_hierarchy_with_ids(toc_list: List) -> List[Dict]:
 root = []
 parent_stack = {-1: {"children": root}}
 id_counter = [1]
 for level, title, page in toc_list:
 normalized_level = level - 1
 node = {"level": normalized_level, "toc_id": id_counter[0], "title": title.strip(), "page": page, "children": []}
 id_counter[0] += 1
 parent_node = parent_stack.get(normalized_level - 1)
 if parent_node: parent_node["children"].append(node)
 parent_stack[normalized_level] = node
 return root

def extract_pdf_toc(pdf_path, output_json_path):
 print(f"Processing PDF ToC for: {pdf_path}")
 try:
 doc = fitz.open(pdf_path)
 toc = doc.get_toc()
 hierarchical_toc = []
 if not toc:
 print(" WARNING: This PDF has no embedded bookmarks (ToC).")
 else:
 print(f"INFO: Found {len(toc)} bookmark entries. Building hierarchy.
↪..")
 hierarchical_toc = build_pdf_hierarchy_with_ids(toc)
 # --- MODIFICATION: Add the full title paths ---
 print("INFO: Annotating ToC with full title paths...")
 _add_paths_to_hierarchy(hierarchical_toc)

 os.makedirs(os.path.dirname(output_json_path), exist_ok=True)
 with open(output_json_path, 'w', encoding='utf-8') as f:
 json.dump(hierarchical_toc, f, indent=2, ensure_ascii=False)
 print(f" Successfully wrote PDF ToC with assigned IDs and paths to:
↪{output_json_path}")
 except Exception as e:
 print(f"An error occurred during PDF ToC extraction: {e}")

=====
2. EXECUTION BLOCK
=====
This uses the global variables defined in your setup cell (Cell 1)
if PROCESS_EPUB:

```

```

 extract_epub_toc(BOOK_PATH, PRE_EXTRACTED_TOC_JSON_PATH)
 else:
 extract_pdf_toc(BOOK_PATH, PRE_EXTRACTED_TOC_JSON_PATH)

```

## 5 Hirachical DB base on TOC

### 5.1 Process Book

```

[]: # Cell 5.a: Create Hierarchical Vector Database (with Sequential ToC ID and
 ↳Chunk ID)
 # This cell processes the book, enriches it with hierarchical and sequential
 ↳metadata,
 # chunks it, and creates the final vector database.

import os
import json
import shutil
import logging
from typing import List, Dict, Any, Tuple
from langchain_core.documents import Document
from langchain_community.document_loaders import PyPDFLoader,
↳UnstructuredEPubLoader
from langchain_ollama.embeddings import OllamaEmbeddings
from langchain_chroma import Chroma
from langchain.text_splitter import RecursiveCharacterTextSplitter

Setup Logger for this cell
logging.basicConfig(level=logging.INFO, format='%(asctime)s - %(levelname)s -
↳%(message)s')
logger = logging.getLogger(__name__)

--- Helper: Clean metadata values for ChromaDB ---
def clean_metadata_for_chroma(value: Any) -> Any:
 """Sanitizes metadata values to be compatible with ChromaDB."""
 if isinstance(value, list): return ", ".join(map(str, value))
 if isinstance(value, dict): return json.dumps(value)
 if isinstance(value, (str, int, float, bool)) or value is None: return value
 return str(value)

--- Core Function to Process Book with Pre-extracted ToC ---
def process_book_with_extracted_toc(
 book_path: str,
 extracted_toc_json_path: str,
 chunk_size: int,
 chunk_overlap: int
) -> Tuple[List[Document], List[Dict[str, Any]]]:

```

```

 logger.info(f"Processing book '{os.path.basename(book_path)}' using ToC_
↳from '{os.path.basename(extracted_toc_json_path)}'".)

 # 1. Load the pre-extracted hierarchical ToC
 try:
 with open(extracted_toc_json_path, 'r', encoding='utf-8') as f:
 hierarchical_toc = json.load(f)
 if not hierarchical_toc:
 logger.error(f"Pre-extracted ToC at '{extracted_toc_json_path}' is_
↳empty or invalid.")
 return [], []
 logger.info(f"Successfully loaded pre-extracted ToC with_
↳{len(hierarchical_toc)} top-level entries.")
 except Exception as e:
 logger.error(f"Error loading pre-extracted ToC JSON: {e}",_
↳exc_info=True)
 return [], []

 # 2. Load all text elements/pages from the book
 all_raw_book_docs: List[Document] = []
 _, file_extension = os.path.splitext(book_path.lower())

 if file_extension == ".epub":
 loader = UnstructuredEPubLoader(book_path, mode="elements",_
↳strategy="fast")
 try:
 all_raw_book_docs = loader.load()
 logger.info(f"Loaded {len(all_raw_book_docs)} text elements from_
↳EPUB.")
 except Exception as e:
 logger.error(f"Error loading EPUB content: {e}", exc_info=True)
 return [], hierarchical_toc
 elif file_extension == ".pdf":
 loader = PyPDFLoader(book_path)
 try:
 all_raw_book_docs = loader.load()
 logger.info(f"Loaded {len(all_raw_book_docs)} pages from PDF.")
 except Exception as e:
 logger.error(f"Error loading PDF content: {e}", exc_info=True)
 return [], hierarchical_toc
 else:
 logger.error(f"Unsupported book file format: {file_extension}")
 return [], hierarchical_toc

 if not all_raw_book_docs:
 logger.error("No text elements/pages loaded from the book.")

```

```

 return [], hierarchical_toc

 # 3. Create enriched LangChain Documents by matching ToC to content
 final_documents_with_metadata: List[Document] = []

 # Flatten the ToC, AND add a unique sequential ID for sorting and
 ↪validation.
 flat_toc_entries: List[Dict[str, Any]] = []

 def _add_ids_and_flatten_recursive(nodes: List[Dict[str, Any]],
 ↪current_titles_path: List[str], counter: List[int]):
 """
 Recursively traverses ToC nodes to flatten them and assign a unique,
 ↪sequential toc_id.
 """
 for node in nodes:
 toc_id = counter[0]
 counter[0] += 1
 title = node.get("title", "").strip()
 if not title: continue
 new_titles_path = current_titles_path + [title]
 entry = {
 "titles_path": new_titles_path,
 "level": node.get("level"),
 "full_title_for_matching": title,
 "toc_id": toc_id
 }
 if "page" in node: entry["page"] = node["page"]
 flat_toc_entries.append(entry)
 if node.get("children"):
 _add_ids_and_flatten_recursive(node.get("children", []),
 ↪new_titles_path, counter)

 toc_id_counter = [0]
 _add_ids_and_flatten_recursive(hierarchical_toc, [], toc_id_counter)
 logger.info(f"Flattened ToC and assigned sequential IDs to
 ↪{len(flat_toc_entries)} entries.")

 # Logic for PDF metadata assignment
 if file_extension == ".pdf" and any("page" in entry for entry in
 ↪flat_toc_entries):
 logger.info("Assigning metadata to PDF pages based on ToC page numbers..
 ↪.")
 flat_toc_entries.sort(key=lambda x: x.get("page", -1) if x.get("page")
 ↪is not None else -1)
 for page_doc in all_raw_book_docs:

```

```

 page_num_0_indexed = page_doc.metadata.get("page", -1)
 page_num_1_indexed = page_num_0_indexed + 1
 assigned_metadata = {"source": os.path.basename(book_path),
↪ "page_number": page_num_1_indexed}
 best_match_toc_entry = None
 for toc_entry in flat_toc_entries:
 toc_page = toc_entry.get("page")
 if toc_page is not None and toc_page <= page_num_1_indexed:
 if best_match_toc_entry is None or toc_page >
↪ best_match_toc_entry.get("page", -1):
 best_match_toc_entry = toc_entry
 elif toc_page is not None and toc_page > page_num_1_indexed:
 break
 if best_match_toc_entry:
 for i, title_in_path in
↪ enumerate(best_match_toc_entry["titles_path"]):
 assigned_metadata[f"level_{i+1}_title"] = title_in_path
 assigned_metadata['toc_id'] = best_match_toc_entry.get('toc_id')
 else:
 assigned_metadata["level_1_title"] = "Uncategorized PDF Page"
 cleaned_meta = {k: clean_metadata_for_chroma(v) for k, v in
↪ assigned_metadata.items()}
 final_documents_with_metadata.append(Document(page_content=page_doc.
↪ page_content, metadata=cleaned_meta))

 # Logic for EPUB metadata assignment
 elif file_extension == ".epub":
 logger.info("Assigning metadata to EPUB elements by matching ToC titles
↪ in text...")
 toc_titles_for_search = [entry for entry in flat_toc_entries if entry.
↪ get("full_title_for_matching")]
 current_hierarchy_metadata = {}
 for element_doc in all_raw_book_docs:
 element_text = element_doc.page_content.strip() if element_doc.
↪ page_content else ""
 if not element_text: continue
 for toc_entry in toc_titles_for_search:
 if element_text == toc_entry["full_title_for_matching"]:
 current_hierarchy_metadata = {"source": os.path.
↪ basename(book_path)}
 for i, title_in_path in enumerate(toc_entry["titles_path"]):
 current_hierarchy_metadata[f"level_{i+1}_title"] =
↪ title_in_path
 current_hierarchy_metadata['toc_id'] = toc_entry.
↪ get('toc_id')

```



```

 if "page" in toc_entry:
 current_hierarchy_metadata["epub_toc_page"] = toc_entry["page"]
 break
 if not current_hierarchy_metadata:
 doc_metadata_to_assign = {"source": os.path.
 ↪basename(book_path), "level_1_title": "EPUB Preamble", "toc_id": -1}
 else:
 doc_metadata_to_assign = current_hierarchy_metadata.copy()
 cleaned_meta = {k: clean_metadata_for_chroma(v) for k, v in
 ↪doc_metadata_to_assign.items()}
 final_documents_with_metadata.
 ↪append(Document(page_content=element_text, metadata=cleaned_meta))

 else: # Fallback
 final_documents_with_metadata = all_raw_book_docs

 if not final_documents_with_metadata:
 logger.error("No documents were processed or enriched with hierarchical_
 ↪metadata.")
 return [], hierarchical_toc

 logger.info(f"Total documents prepared for chunking:
 ↪{len(final_documents_with_metadata)}")

 text_splitter = RecursiveCharacterTextSplitter(
 chunk_size=chunk_size,
 chunk_overlap=chunk_overlap,
 length_function=len
)
 final_chunks = text_splitter.split_documents(final_documents_with_metadata)
 logger.info(f"Split into {len(final_chunks)} final chunks, inheriting_
 ↪hierarchical metadata.")

 # --- MODIFICATION START: Add a unique, sequential chunk_id to each chunk_
 ↪---
 logger.info("Assigning sequential chunk_id to all final chunks...")
 for i, chunk in enumerate(final_chunks):
 chunk.metadata['chunk_id'] = i
 logger.info(f"Assigned chunk_ids from 0 to {len(final_chunks) - 1}.")
 # --- MODIFICATION END ---

 return final_chunks, hierarchical_toc

--- Main Execution Block for this Cell ---

if not os.path.exists(PRE_EXTRACTED_TOC_JSON_PATH):

```

```

 logger.error(f"CRITICAL: Pre-extracted ToC file not found at_
↳ '{PRE_EXTRACTED_TOC_JSON_PATH}'".)
 logger.error("Please run the 'Extract Book Table of Contents (ToC)' cell_
↳ (Cell 4) first.")
else:
 final_chunks_for_db, toc_reloaded = process_book_with_extracted_toc(
 book_path=BOOK_PATH,
 extracted_toc_json_path=PRE_EXTRACTED_TOC_JSON_PATH,
 chunk_size=CHUNK_SIZE,
 chunk_overlap=CHUNK_OVERLAP
)

 if final_chunks_for_db:
 if os.path.exists(CHROMA_PERSIST_DIR):
 logger.warning(f"Deleting existing ChromaDB directory:_
↳ {CHROMA_PERSIST_DIR}")
 shutil.rmtree(CHROMA_PERSIST_DIR)

 logger.info(f"Initializing embedding model '{EMBEDDING_MODEL_OLLAMA}'_
↳ and creating new vector database...")
 embedding_model = OllamaEmbeddings(model=EMBEDDING_MODEL_OLLAMA)

 vector_db = Chroma.from_documents(
 documents=final_chunks_for_db,
 embedding=embedding_model,
 persist_directory=CHROMA_PERSIST_DIR,
 collection_name=CHROMA_COLLECTION_NAME
)

 reloaded_db = Chroma(persist_directory=CHROMA_PERSIST_DIR,_
↳ embedding_function=embedding_model, collection_name=CHROMA_COLLECTION_NAME)
 count = reloaded_db._collection.count()

 print("-" * 50)
 logger.info(f" Vector DB created successfully at:_
↳ {CHROMA_PERSIST_DIR}")
 logger.info(f" Collection '{CHROMA_COLLECTION_NAME}' contains {count}_
↳ documents.")
 print("-" * 50)
 else:
 logger.error(" Failed to generate chunks. Vector DB not created.")

```

```

[]: # Cell 5.b: Create Hierarchical Vector Database (V10 - ToC-First Method)
This cell uses the pre-tagged ToC from Cell 4 as the source of truth
to process the book, enrich text, and create the final vector database.

```

```

--- Core Imports ---
import os
import json
import shutil
import logging
from typing import List, Dict, Any, Tuple

--- LangChain and Data Loading Imports ---
from langchain_core.documents import Document
from langchain_community.document_loaders import PyPDFLoader
from langchain_ollama.embeddings import OllamaEmbeddings
from langchain_chroma import Chroma
from langchain.text_splitter import RecursiveCharacterTextSplitter

--- Imports for EPUB and PDF Processing ---
from ebooklib import epub, ITEM_DOCUMENT
from bs4 import BeautifulSoup
import fitz # PyMuPDF

--- Logger Setup ---
logger = logging.getLogger(__name__)
logging.basicConfig(level=logging.INFO, format='%(asctime)s - %(levelname)s - %(message)s')

=====
1. HELPER FUNCTIONS
=====
The previous helper functions (clean_metadata_for_chroma, extract_images_*)
are still needed and can be copied from the previous answer. For brevity,
only the new/modified helpers are shown in full here.

def clean_metadata_for_chroma(value: Any) -> Any:
 if isinstance(value, (list, dict, set)):
 if isinstance(value, set): value = sorted(list(value))
 return json.dumps(value)
 if isinstance(value, (str, int, float, bool)) or value is None: return value
 return str(value)

def extract_images_from_epub(epub_path: str, output_dir: str, unit_id: str) -> Dict[str, List[str]]:
 logger.info(f"Extracting images from EPUB: {os.path.basename(epub_path)}")
 image_map: Dict[str, List[str]] = {}
 book_image_dir = os.path.join(output_dir, f"{unit_id}_epub_images")
 os.makedirs(book_image_dir, exist_ok=True)
 book = epub.read_epub(epub_path)
 text_files = [item for item in book.get_items_of_type(ITEM_DOCUMENT)]

```

```

 for item in book.get_items_of_type(ITEM_DOCUMENT):
 source_filename = os.path.basename(item.get_name())
 content = item.get_content().decode('utf-8', 'ignore')
 for image_item in book.get_items_of_type('image'):
 img_internal_path = image_item.get_name()
 if img_internal_path in content:
 if source_filename not in image_map: image_map[source_filename] = []

 img_filename = os.path.basename(img_internal_path)
 image_path = os.path.join(book_image_dir, img_filename)
 if not os.path.exists(image_path):
 with open(image_path, "wb") as f: f.write(image_item.
get_content())
 if image_path not in image_map[source_filename]:
image_map[source_filename].append(image_path)
 total_images = sum(len(v) for v in image_map.values())
 logger.info(f"Extracted {total_images} total images to '{book_image_dir}'")
 return image_map

def flatten_toc_with_paths(nodes: List[Dict], current_path: List[str] = []) -> List[Dict]:
 """
 Flattens the hierarchical ToC and adds the full 'titles_path' to each entry.
 """
 flat_list = []
 for node in nodes:
 new_path = current_path + [node['title']]
 # Create a new entry to avoid modifying the original node
 flat_entry = node.copy()
 flat_entry['titles_path'] = new_path

 # Add the entry itself (without its children) to the list
 children = flat_entry.pop('children', [])
 flat_list.append(flat_entry)

 # Recursively process the children
 if children:
 flat_list.extend(flatten_toc_with_paths(children, new_path))

 return flat_list

=====
2. CORE ORCHESTRATION FUNCTION
=====

def process_book_with_extracted_toc(
 book_path: str,

```

```

 extracted_toc_json_path: str,
 chunk_size: int,
 chunk_overlap: int
) -> Tuple[List[Document], List[Dict[str, Any]]]:

 logger.info(f"Processing book '{os.path.basename(book_path)}' using ToC_
↳from '{os.path.basename(extracted_toc_json_path)}'".)

 # --- Step 1: Load ToC with Pre-assigned IDs ---
 try:
 with open(extracted_toc_json_path, 'r', encoding='utf-8') as f:
 hierarchical_toc = json.load(f)
 logger.info("Successfully loaded pre-extracted ToC with assigned IDs.")
 except Exception as e:
 logger.error(f"FATAL: Error loading ToC JSON: {e}", exc_info=True)
 return [], []

 # --- Step 2: Create a Flattened ToC and a Title-based Lookup ---
 flat_toc = flatten_toc_with_paths(hierarchical_toc)
 toc_lookup = {entry['title'].strip().lower(): entry for entry in flat_toc}
 logger.info(f"Created a flattened ToC with {len(flat_toc)} entries for_
↳matching.")

 # --- Step 3: Extract Images (if any) ---
 file_extension = os.path.splitext(book_path.lower())[1]
 image_map = {}
 if file_extension == ".epub":
 unit_id = extract_uo_id_from_filename(UNIT_OUTLINE_FILENAME)
 image_map = extract_images_from_epub(book_path, OUTPUT_IMAGES_DIR,
↳unit_id)
 # PDF image extraction would go here if needed

 # --- Step 4: Create Enriched Documents by Matching Content to ToC ---
 final_documents_with_metadata: List[Document] = []
 if file_extension == ".epub":
 book = epub.read_epub(book_path)
 current_metadata = {"source": os.path.basename(book_path), "toc_id":
↳-1, "level_1_title": "Preamble"}

 for item in book.get_items_of_type(ITEM_DOCUMENT):
 source_filename = os.path.basename(item.get_name())
 soup = BeautifulSoup(item.get_content(), 'html.parser')

 for element in soup.find_all(['h1', 'h2', 'h3', 'h4', 'h5', 'h6',
↳'p', 'div', 'li']):
 text = element.get_text().strip()
 if not text:

```

```

 continue

 # Check if this element's text is a heading in our ToC
 normalized_text = text.lower()
 if normalized_text in toc_lookup:
 # It's a heading, update the current context
 toc_entry = toc_lookup[normalized_text]
 current_metadata = {"source": os.path.basename(book_path)}
 for i, title in enumerate(toc_entry['titles_path']):
 current_metadata[f"level_{i+1}_title"] = title
 current_metadata['toc_id'] = toc_entry['toc_id']
 logger.info(f"Context updated to: '{' -> ' .
↪join(toc_entry['titles_path'])}' [ID: {toc_entry['toc_id']}]")

 # Tag the document with the current metadata
 doc_meta = current_metadata.copy()
 if source_filename in image_map:
 doc_meta.setdefault('image_paths', []).extend(p for p in
↪image_map[source_filename] if p not in doc_meta.get('image_paths', []))

 final_documents_with_metadata.
↪append(Document(page_content=text, metadata=doc_meta))

 # --- Step 5: Finalize and Chunk ---
 logger.info(f"Total documents prepared for chunking:
↪{len(final_documents_with_metadata)}")

 logger.info("Sanitizing metadata and chunking documents...")
 text_splitter = RecursiveCharacterTextSplitter(chunk_size=chunk_size,
↪chunk_overlap=chunk_overlap, length_function=len)

 for doc in final_documents_with_metadata:
 doc.metadata = {k: clean_metadata_for_chroma(v) for k, v in doc.
↪metadata.items()}

 final_chunks = text_splitter.split_documents(final_documents_with_metadata)

 logger.info(f"Split into {len(final_chunks)} final chunks and assigning
↪chunk_id...")
 for i, chunk in enumerate(final_chunks):
 chunk.metadata['chunk_id'] = i

 return final_chunks, hierarchical_toc

=====
3. MAIN EXECUTION BLOCK

```

```
=====
if not os.path.exists(PRE_EXTRACTED_TOC_JSON_PATH):
 logger.error(f"CRITICAL: Pre-extracted ToC file not found at_
↳ '{PRE_EXTRACTED_TOC_JSON_PATH}'")
 logger.error("Please run the 'Extract Book Table of Contents (ToC)' cell_
↳ (Cell 4) first.")
else:
 final_chunks_for_db, toc_reloaded = process_book_with_extracted_toc(
 book_path=BOOK_PATH,
 extracted_toc_json_path=PRE_EXTRACTED_TOC_JSON_PATH,
 chunk_size=CHUNK_SIZE,
 chunk_overlap=CHUNK_OVERLAP
)
 if final_chunks_for_db:
 if os.path.exists(CHROMA_PERSIST_DIR):
 logger.warning(f"Deleting existing ChromaDB directory:_
↳ '{CHROMA_PERSIST_DIR}'")
 shutil.rmtree(CHROMA_PERSIST_DIR)

 logger.info(f"Initializing embedding model '{EMBEDDING_MODEL_OLLAMA}'_
↳ and creating new vector database...")
 embedding_model = OllamaEmbeddings(model=EMBEDDING_MODEL_OLLAMA)

 vector_db = Chroma.from_documents(
 documents=final_chunks_for_db,
 embedding=embedding_model,
 persist_directory=CHROMA_PERSIST_DIR,
 collection_name=CHROMA_COLLECTION_NAME
)
 count = vector_db._collection.count()
 print("-" * 50)
 logger.info(f"Vector DB created successfully at: {CHROMA_PERSIST_DIR}")
 logger.info(f"Collection '{CHROMA_COLLECTION_NAME}' contains {count}_
↳ documents.")
 print("-" * 50)
 else:
 logger.error("Failed to generate chunks. Vector DB not created.")
```

### 5.1.1 Full Database Health & Hierarchy Diagnostic Report

```
[]: # =====
Cell 5.1: Full Database Health & Hierarchy Diagnostic Report (V15.1 -_
↳ Corrected)
#
This version fixes the hierarchy reconstruction logic to correctly build a
nested tree from the database metadata.
=====
```

```

--- Core and Dependency Imports (Same as before) ---
import os
import json
import logging
from typing import List, Dict, Any

try:
 from langchain_chroma import Chroma
 from langchain_ollama.embeddings import OllamaEmbeddings
 langchain_available = True
except ImportError:
 langchain_available = False

--- Logger Setup (Same as before) ---
logger = logging.getLogger(__name__)
logging.basicConfig(level=logging.INFO, format='%(asctime)s - %(levelname)s - \
↳%(message)s')

=====
1. HELPER FUNCTIONS (MODIFIED)
=====

def print_header(text: str, char: str = "="):
 """Prints a centered header to the console."""
 print("\n" + char * 80)
 print(text.center(80))
 print(char * 80)

def build_hierarchy_from_metadata(metadata: List[Dict]) -> Dict:
 """
 Builds a fully nested tree from scratch based on the hierarchical \
↳'level_X_title' \
keys in the chunk metadata.
 """
 root = {'_children': {}}

 for meta in metadata:
 # Reconstruct the titles_path from the 'level_X_title' keys
 path_keys = sorted([k for k in meta.keys() if k.startswith('level_')])
 titles_path = [meta[k] for k in path_keys]

 if not titles_path:
 # This chunk is unmapped, add it to a dedicated 'Preamble' node
 if 'Preamble or Uncategorized' not in root['_children']:
 root['_children']['Preamble or Uncategorized'] = {
 '_title': 'Preamble or Uncategorized', '_children': {},

```



```

 '_direct_chunks': 0, '_total_chunks': 0, '_toc_id': -1
 }
 root['_children']['Preamble or Uncategorized']['_direct_chunks'] += 1
↪1
 continue

 # Traverse or build the tree according to the path
 current_node = root
 for i, title in enumerate(titles_path):
 if title not in current_node['_children']:
 # Create the node if it doesn't exist
 current_node['_children'][title] = {
 '_title': title,
 '_children': {},
 '_direct_chunks': 0,
 '_total_chunks': 0,
 # Assign toc_id only to the leaf node of this specific path
 '_toc_id': meta.get('toc_id') if i == len(titles_path) - 1
↪else None
 }
 current_node = current_node['_children'][title]

 # Increment the direct chunk count on the final leaf node for this path
 current_node['_direct_chunks'] += 1

 return root

def sum_totals_upwards(node: Dict) -> int:
 """
 Recursively calculates the total number of chunks for a node by summing its
 direct chunks and the total chunks of all its children.
 """
 # Start with the node's own direct chunks
 total = node.get('_direct_chunks', 0)

 # Recursively call on children and add their totals
 for child_node in node['_children'].values():
 total += sum_totals_upwards(child_node)

 node['_total_chunks'] = total
 return total

def print_hierarchy_report(node: Dict, indent_level: int = 0):
 """Recursively prints the reconstructed and calculated hierarchy."""
 prefix = "| " * indent_level + "-- "

 # Sort children by title for consistent, alphabetical output

```

```

 sorted_children = sorted(node['_children'].values(), key=lambda x:
↪x['_title'])

 for child_node in sorted_children:
 toc_id_str = f"[ID: {child_node.get('_toc_id', 'N/A')}]]"
 title = child_node.get('_title', 'Untitled')
 total = child_node.get('_total_chunks', 0)
 direct = child_node.get('_direct_chunks', 0)

 print(f"{prefix}-{title} {toc_id_str} (Total: {total}, Direct:
↪{direct})")

 if child_node['_children']:
 print_hierarchy_report(child_node, indent_level + 1)

=====
2. MAIN DIAGNOSTIC FUNCTION (No changes needed here)
=====
def run_full_diagnostics():
 print_header("Ground-Truth Database Health & Hierarchy Report (v15.1)")

 if not langchain_available:
 logger.error("LangChain components not installed. Skipping diagnostics.
↪")
 return

 try:
 logger.info(f"Connecting to vector DB to retrieve all chunk metadata...
↪")
 vector_store = Chroma(
 persist_directory=CHROMA_PERSIST_DIR,
 embedding_function=OllamaEmbeddings(model=EMBEDDING_MODEL_OLLAMA),
 collection_name=CHROMA_COLLECTION_NAME
)
 total_docs = vector_store._collection.count()
 if total_docs == 0:
 logger.warning("Database is empty. No diagnostics to run.")
 return
 metadatas = vector_store.get(limit=total_docs,
↪include=["metadatas"])['_metadatas']
 logger.info(f"Successfully retrieved metadata for all {len(metadatas)}
↪chunks.")
 except Exception as e:
 logger.error(f"FATAL: Could not connect to or retrieve data from
↪ChromaDB: {e}")
 return

```

```

logger.info("Building hierarchy from ground-truth metadata...")
hierarchy_tree = build_hierarchy_from_metadata(metadata)

logger.info("Calculating total chunks for each branch...")
We only need to call this on the root, as it's fully recursive.
sum_totals_upwards(hierarchy_tree)

print_header("Reconstructed Hierarchy Report (from DB Ground Truth)")
print_hierarchy_report(hierarchy_tree)

print_header("Diagnostic Summary", char="-")
print(f"Total Chunks in DB: {total_docs}")
if 'Preamble or Uncategorized' in hierarchy_tree['_children']:
 orphaned = hierarchy_tree['_children']['Preamble or Uncategorized'].
 ↪get('_total_chunks', 0)
 logger.warning(f"Found {orphaned} chunks that were unmapped or in the
 ↪preamble.")
else:
 logger.info("All chunks were successfully mapped to a ToC entry.")

print_header("Diagnostic Complete", char="*")

=====
3. MAIN EXECUTION BLOCK FOR THIS CELL
=====
if 'CHROMA_PERSIST_DIR' in locals() and langchain_available:
 run_full_diagnostics()
else:
 logger.error("Skipping diagnostics: Required variables not defined or
 ↪LangChain not available.")

```

```

[]: # Cell 6: Verify Content Retrieval for a Specific toc_id (Adapted for New
 ↪Metadata)

import os
import json
import logging
import re
from langchain_chroma import Chroma
from langchain_ollama.embeddings import OllamaEmbeddings

--- Logger Setup ---
logger = logging.getLogger(__name__)
logging.basicConfig(level=logging.INFO, format='%(asctime)s - %(levelname)s -
 ↪%(message)s')

```

```

def retrieve_and_print_chunks_for_toc_id(vector_store: Chroma, toc_id: int):
 """
 Retrieves all chunks for a specific toc_id, prints the associated section_
 ↳title,
 shows the reassembled text, and then lists the metadata for each individual_
 ↳chunk
 for detailed verification.
 """
 try:
 # Use the 'get' method with a 'where' filter to find all chunks for the_
 ↳toc_id
 results = vector_store.get(
 where={"toc_id": toc_id},
 include=["documents", "metadatas"]
)

 if not results or not results.get('ids'):
 logger.warning(f"No chunks found in the database for toc_id =_
 ↳{toc_id}")
 print("=" * 80)
 print(f"VERIFICATION FAILED: No content found for toc_id: {toc_id}")
 print("=" * 80)
 return

 documents = results['documents']
 metadatas = results['metadatas']

 # ===== MODIFICATION START =====
 # Get the section title by reconstructing it from the hierarchical_
 ↳level_X_title keys
 first_meta = metadatas[0] if metadatas else {}

 # Find the highest level_X_title key to use as the primary title
 level_keys = sorted([k for k in first_meta if re.
 ↳match(r'level_\d+_title', k)])
 if level_keys:
 # Reconstruct the full path for context, use the last one as main_
 ↳title
 highest_level_key = level_keys[-1]
 section_title = first_meta.get(highest_level_key, 'Unknown Section_
 ↳Title')

 # (Optional but helpful) Show the full breadcrumb path
 breadcrumb_path = " -> ".join([first_meta.get(k, '') for k in_
 ↳level_keys])

```

```

 header_title = f"'{section_title}' (Path: {breadcrumb_path})"
 else:
 section_title = 'Unknown or Preamble Section'
 header_title = section_title
 # ===== MODIFICATION END =====

 # --- Print a clear header with the section title ---
 print("=" * 80)
 print(f"VERIFYING SECTION: {header_title} (toc_id: {toc_id})")
 print("=" * 80)
 logger.info(f"Found {len(documents)} chunks in the database for this_
↪section.")

 # Sort chunks by their chunk_id to ensure they are in the correct order_
↪for reassembly
 sorted_items = sorted(zip(documents, metadatas), key=lambda item:
↪item[1].get('chunk_id', 0))

 # --- Reassemble and print the full text for the section ---
 all_chunk_texts = [item[0] for item in sorted_items]
 # A simple join is better for reassembly than adding newlines
 reassembled_text = " ".join(all_chunk_texts)

 print("\n" + "#" * 28 + " Reassembled Text " + "#" * 28)
 print(reassembled_text)
 print("#" * 80)

 # --- Print individual chunk details for in-depth verification ---
 print("\n" + "-" * 24 + " Retrieved Chunk Details " + "-" * 25)
 for i, (doc_meta_tuple) in enumerate(sorted_items):
 doc_content, meta = doc_meta_tuple
 print(f"\n[Chunk {i+1} of {len(documents)} | chunk_id: {meta.
↪get('chunk_id', 'N/A')}]")
 # Show a preview of the content to keep the output manageable
 content_preview = doc_content.replace('\n', ' ').strip()
 print(f" Content Preview: '{content_preview[:250]}...'")
 print(f" Metadata: {json.dumps(meta, indent=2)}")

 print("\n" + "=" * 80)
 print(f"Verification complete for section '{section_title}'.")
 print("=" * 80)

 except Exception as e:
 logger.error(f"An error occurred during retrieval for toc_id {toc_id}:
↪{e}", exc_info=True)

=====

```

```

EXECUTION BLOCK
=====

--- IMPORTANT: Set the ID of the section you want to test here ---
To find a toc_id, you can look at the output of the ToC extraction cell (Cell 4)
or the JSON file it creates.
TOC_ID_TO_TEST = 559 # Example: "An Overview of Digital Forensics"
TOC_ID_TO_TEST = -1 # You can also test the "Preamble" content

Assume these variables are defined in a previous cell
CHROMA_PERSIST_DIR, EMBEDDING_MODEL_OLLAMA, CHROMA_COLLECTION_NAME

Check if the database directory exists before attempting to connect
if 'CHROMA_PERSIST_DIR' in locals() and os.path.exists(CHROMA_PERSIST_DIR):
 logger.info(f"Connecting to the existing vector database at {CHROMA_PERSIST_DIR}...")

 # Ensure OllamaEmbeddings and Chroma are initialized correctly
 try:
 vector_store = Chroma(
 persist_directory=CHROMA_PERSIST_DIR,
 embedding_function=OllamaEmbeddings(model=EMBEDDING_MODEL_OLLAMA),
 collection_name=CHROMA_COLLECTION_NAME
)

 # Run the verification function
 retrieve_and_print_chunks_for_toc_id(vector_store, TOC_ID_TO_TEST)

 except Exception as e:
 logger.error(f"Failed to initialize Chroma or run retrieval. Error: {e}")
 logger.error("Please ensure your embedding model and collection names are correct.")

else:
 logger.error("Database directory not found or 'CHROMA_PERSIST_DIR' variable is not set.")
 logger.error("Please run the previous cell (e.g., Cell 5) to create the database first.")

```

[ ]: # Cell 6: Verify Content Retrieval for a Specific toc\_id with Reassembled Text

```

import os
import json
import logging

```

```

from langchain_chroma import Chroma
from langchain_ollama.embeddings import OllamaEmbeddings

--- Logger Setup ---
logger = logging.getLogger(__name__)
logging.basicConfig(level=logging.INFO, format='%(asctime)s - %(levelname)s - %
↳ %(message)s')

def retrieve_and_print_chunks_for_toc_id(vector_store: Chroma, toc_id: int):
 """
 Retrieves all chunks for a specific toc_id, prints the reassembled text,
 and then lists the metadata for each individual chunk.
 """
 print("=" * 80)
 print(f"Retrieving all chunks for toc_id: {toc_id}")
 print("=" * 80)

 try:
 # Use the 'get' method with a 'where' filter to find exact matches
 results = vector_store.get(
 where={"toc_id": toc_id},
 include=["documents", "metadatas"]
)

 if not results or not results.get('ids'):
 logger.warning(f"No chunks found in the database for toc_id =
↳ {toc_id}")
 return

 documents = results['documents']
 metadatas = results['metadatas']

 logger.info(f"Successfully retrieved {len(documents)} chunks for toc_id
↳ {toc_id}.")

 # Sort chunks by their chunk_id to ensure they are in the correct order
 sorted_items = sorted(zip(documents, metadatas), key=lambda item:
↳ item[1].get('chunk_id', 0))

 # --- NEW: Reassemble and print the full text ---
 all_chunk_texts = [item[0] for item in sorted_items]
 reassembled_text = "\n".join(all_chunk_texts)

 print("\n" + "#" * 28 + " Reassembled Text " + "#" * 28)
 print(reassembled_text)
 print("#" * 80)

```

```

 # --- Print individual chunk details for verification ---
 print("\n" + "-" * 25 + " Individual Chunk Details " + "-" * 24)
 for i, (doc, meta) in enumerate(sorted_items):
 print(f"\n[Chunk {i+1} / {len(documents)} | chunk_id: {meta.get('chunk_id', 'N/A')}]")
 # Show a preview to keep the log clean
 content_preview = doc.replace('\n', ' ').strip()
 print(f" Content Preview: '{content_preview[:200]}...'")
 print(f" Metadata: {json.dumps(meta, indent=2)}")

 print("\n" + "=" * 80)
 print("Retrieval test complete.")
 print("=" * 80)

except Exception as e:
 logger.error(f"An error occurred during retrieval: {e}", exc_info=True)

=====
EXECUTION BLOCK
=====

--- IMPORTANT: Set the ID you want to test here ---
Example: ToC ID 10 is "An Overview of Digital Forensics"
Example: ToC ID 11 is "Digital Forensics and Other Related Disciplines"
TOC_ID_TO_TEST = 7

Check if the database directory exists
if 'CHROMA_PERSIST_DIR' in locals() and os.path.exists(CHROMA_PERSIST_DIR):
 logger.info("Connecting to the existing vector database...")

 vector_store = Chroma(
 persist_directory=CHROMA_PERSIST_DIR,
 embedding_function=OllamaEmbeddings(model=EMBEDDING_MODEL_OLLAMA),
 collection_name=CHROMA_COLLECTION_NAME
)

 retrieve_and_print_chunks_for_toc_id(vector_store, TOC_ID_TO_TEST)
else:
 logger.error("Database directory not found. Please run Cell 5 to create the database first.")

```



## 6 test 1

```
[]: # Cell 5.2: Test Content & Image Retrieval (with Random Topic Selection)

--- Core Imports ---
import os
import json
import logging
import random # Make sure random is imported
from typing import List, Dict, Any

--- Dependency Checks & Imports ---
try:
 from langchain_chroma import Chroma
 from langchain_ollama.embeddings import OllamaEmbeddings
 from langchain_core.documents import Document
 from PIL import Image
 import matplotlib.pyplot as plt
 langchain_and_viz_available = True
except ImportError as e:
 print(f"Required library not found: {e}. Please install langchain,␣
 ↳ChromaDB, Pillow, and matplotlib.")
 langchain_and_viz_available = False

--- Logger Setup ---
logger = logging.getLogger(__name__)
logging.basicConfig(level=logging.INFO, format='%(asctime)s - %(levelname)s -␣
 ↳%(message)s')

=====
1. HELPER AND RETRIEVAL FUNCTIONS
=====
The _add_ids_and_flatten_recursive function is needed here to process the ToC
def _add_ids_and_flatten_recursive(nodes: List[Dict], current_path: List[str],␣
 ↳counter: List[int], flat_list: List[Dict]):
 """Recursively traverses ToC nodes to flatten them and assign a unique,␣
 ↳sequential toc_id."""
 for node in nodes:
 toc_id = counter[0]
 counter[0] += 1
 title = node.get("title", "").strip()
 if not title:
 continue

 # Check if the node is a leaf (has no children)
 is_leaf = not bool(node.get("children"))
```

```

new_titles_path = current_path + [title]
entry = {
 "titles_path": new_titles_path,
 "level": node.get("level"),
 "full_title_for_matching": title,
 "toc_id": toc_id,
 "is_leaf": is_leaf # Add a flag to identify leaf nodes
}
if "page" in node:
 entry["page"] = node["page"]

flat_list.append(entry)

if node.get("children"):
 _add_ids_and_flatten_recursive(node.get("children", []),
 ↪new_titles_path, counter, flat_list)

The retrieve_and_display_section and print_header functions remain exactly
 ↪the same as before.

def print_header(text: str, char: str = "="):
 """Prints a centered header to the console."""
 print("\n" + char * 80)
 print(text.center(80))
 print(char * 80)

def retrieve_and_display_section(
 topic_query: str,
 vector_store: Chroma,
 flat_toc: List[Dict]
):
 # ... This entire function is identical to the previous version ...
 # It takes the query and does the retrieval and display.
 print_header(f"Retrieval Test for Topic: '{topic_query}'")

 # --- 1. Find the topic in the flattened ToC ---
 target_entry = None
 # Find an exact or partial match for the topic query
 for entry in flat_toc:
 if topic_query.lower() in entry.get('full_title_for_matching', '').
 ↪lower():
 target_entry = entry
 break

 if not target_entry:
 logger.error(f"Could not find topic '{topic_query}' in the Table of
 ↪Contents.")

```

```

 return

 target_toc_id = target_entry.get('toc_id')
 full_title = target_entry.get('full_title_for_matching')
 logger.info(f"Found topic '{full_title}' with toc_id: {target_toc_id}")

 # --- 2. Retrieve all documents for that toc_id from ChromaDB ---
 try:
 retrieved_data = vector_store.get(
 where={"toc_id": target_toc_id},
 include=["metadatas", "documents"]
)
 docs = [
 Document(page_content=doc, metadata=meta)
 for doc, meta in zip(retrieved_data['documents'],
↪retrieved_data['metadatas'])
]

 if not docs:
 logger.warning(f"No document chunks found for toc_id_
↪{target_toc_id}. The topic might be a parent heading with no direct content.
↪")

 return

 logger.info(f"Retrieved {len(docs)} document chunks.")

 except Exception as e:
 logger.error(f"An error occurred during database retrieval: {e}",
↪exc_info=True)
 return

 # --- 3. Sort chunks, reassemble text, and collect images ---
 docs.sort(key=lambda d: d.metadata.get('chunk_id', -1))

 full_content = "\n".join([d.page_content for d in docs])

 all_image_paths = set()
 for d in docs:
 if 'image_paths' in d.metadata:
 try:
 paths = json.loads(d.metadata['image_paths'])
 if isinstance(paths, list):
 all_image_paths.update(paths)
 except (json.JSONDecodeError, TypeError):
 continue

 sorted_image_paths = sorted(list(all_image_paths))

```

```

--- 4. Display the results ---
print("\n" + "-"*25 + " REASSEMBLED CONTENT " + "-"*25)
print(full_content)

print("\n" + "-"*25 + " ASSOCIATED IMAGES " + "-"*26)
if not sorted_image_paths:
 print("No images found for this section.")
else:
 print(f"Found {len(sorted_image_paths)} unique image(s):")
 for path in sorted_image_paths:
 print(f"- {path}")

 try:
 first_image_path = sorted_image_paths[0]
 print(f"\nDisplaying first image: {os.path.
↪basename(first_image_path)}")

 img = Image.open(first_image_path)

 plt.figure(figsize=(8, 6))
 plt.imshow(img)
 plt.title(f"Image for '{full_title}'")
 plt.axis('off')
 plt.show()

 except FileNotFoundError:
 logger.error(f"Image file not found at path: {first_image_path}")
 except Exception as e:
 logger.error(f"Could not display image. Error: {e}")

print("-" * 80)

=====
2. MAIN EXECUTION BLOCK FOR THIS CELL (with Random Topic Selection)
=====

if langchain_and_viz_available:
 if 'CHROMA_PERSIST_DIR' in locals() and 'PRE_EXTRACTED_TOC_JSON_PATH' in_
↪locals():

 try:
 logger.info("Connecting to the existing vector database...")
 db_retriever = Chroma(
 persist_directory=CHROMA_PERSIST_DIR,

```

```

)

 logger.info("Loading and processing Table of Contents for test case_
 selection...")
 with open(PRE_EXTRACTED_TOC_JSON_PATH, 'r', encoding='utf-8') as f:
 loaded_hierarchical_toc = json.load(f)

 flat_toc_for_lookup = []
 _add_ids_and_flatten_recursive(loaded_hierarchical_toc, [], [1],
 flat_toc_for_lookup)

 # --- RANDOMLY SELECT A TEST QUERY ---
 # We want to test a "leaf" section that has actual content.
 # A good candidate is a section that is a leaf in the ToC tree.
 test_candidates = [
 entry for entry in flat_toc_for_lookup
 if entry.get('is_leaf') and entry.get("level", 0) > 0
]

 if not test_candidates:
 raise ValueError("Could not find any suitable leaf-node topics_
 to test.")

 # Select a random topic from our list of good candidates
 random_topic_entry = random.choice(test_candidates)
 test_query = random_topic_entry['full_title_for_matching']

 # --- RUN THE TEST with the random query ---
 retrieve_and_display_section(
 topic_query=test_query,
 vector_store=db_retriever,
 flat_toc=flat_toc_for_lookup
)

 except Exception as e:
 logger.error(f"An error occurred during the test execution: {e}",
 exc_info=True)

 else:
 logger.error("Required variables (CHROMA_PERSIST_DIR,
 PRE_EXTRACTED_TOC_JSON_PATH) not found. Please run previous cells.")
else:
 logger.error("Skipping test cell due to missing libraries.")

```

## 6.1 Test Data Base for content development

Require Description

```
[]: # Cell 6: Verify Vector Database (Final Version with Rich Diagnostic Output)

import os
import json
import re
import random
import logging
from typing import List, Dict, Any, Tuple, Optional

Third-party imports
try:
 from langchain_chroma import Chroma
 from langchain_ollama.embeddings import OllamaEmbeddings
 from langchain_core.documents import Document
 langchain_available = True
except ImportError:
 langchain_available = False

Setup Logger for this cell
logging.basicConfig(level=logging.INFO, format='%(asctime)s - %(levelname)s - %(message)s')
logger = logging.getLogger(__name__)

--- HELPER FUNCTIONS ---

def print_results(query_text: str, results: list, where_filter: Optional[Dict] = None):
 """
 Richly prints query results, showing the query, filter, and retrieved documents.
 """
 print("\n" + "-"*10 + " DIAGNOSTIC: RETRIEVAL RESULTS " + "-"*10)
 print(f"QUERY: '{query_text}'")
 if where_filter:
 print(f"FILTER: {json.dumps(where_filter, indent=2)}")

 if not results:
 print("--> No documents were retrieved for this query and filter.")
 print("-" * 55)
 return

 print(f"--> Found {len(results)} results. Displaying top {min(len(results), 3)}:")
```

```

for i, doc in enumerate(results[:3]):
 print(f"\n[RESULT {i+1}]")
 content_preview = doc.page_content.replace('\n', ' ').strip()
 print(f" Content : '{content_preview[:200]}...'")
 print(f" Metadata: {json.dumps(doc.metadata, indent=2)}")
print("-" * 55)

--- HELPER FUNCTIONS FOR FINDING DATA (UNCHANGED) ---
def find_deep_entry(nodes: List[Dict], current_path: List[str] = []) -> Optional[Tuple[Dict, List[str]]]:
 shuffled_nodes = random.sample(nodes, len(nodes))
 for node in shuffled_nodes:
 if node.get('level', 0) >= 2 and node.get('children'): return node, current_path + [node['title']]
 if node.get('children'):
 path = current_path + [node['title']]
 deep_entry = find_deep_entry(node['children'], path)
 if deep_entry: return deep_entry
 return None

def find_chapter_title_by_number(toc_data: List[Dict], chap_num: int) -> Optional[List[str]]:
 def search_nodes(nodes, num, current_path):
 for node in nodes:
 path = current_path + [node['title']]
 if re.match(rf"(Chapter\s)?{num}[:\s]", node.get('title', '')), re.IGNORECASE): return path
 if node.get('children'):
 found_path = search_nodes(node['children'], num, path)
 if found_path: return found_path
 return None
 return search_nodes(toc_data, chap_num, [])

--- ENHANCED TEST CASES with DIAGNOSTIC OUTPUT ---

def basic_retrieval_test(db, outline):
 print_header("Test 1: Basic Retrieval", char="-")
 try:
 logger.info("Goal: Confirm the database is live and contains thematically relevant content.")
 logger.info("Strategy: Perform a simple similarity search using the course's 'unitName'.")
 query_text = outline.get("unitInformation", {}).get("unitName", "introduction")

```

```

logger.info(f"Action: Searching for query: '{query_text}'...")
results = db.similarity_search(query_text, k=1)

print_results(query_text, results) # <--- SHOW THE EVIDENCE

logger.info("Verification: Check if at least one document was returned.
↪")
assert len(results) > 0, "Basic retrieval query returned no results."

logger.info(" Result: TEST 1 PASSED. The database is online and_
↪responsive.")
return True
except Exception as e:
 logger.error(f" Result: TEST 1 FAILED. Reason: {e}")
 return False

def deep_hierarchy_test(db, toc):
 print_header("Test 2: Deep Hierarchy Retrieval", char="-")
 try:
 logger.info("Goal: Verify that the multi-level hierarchical metadata_
↪was ingested correctly.")
 logger.info("Strategy: Find a random, deeply nested sub-section and use_
↪a precise filter to retrieve it.")
 deep_entry_result = find_deep_entry(toc)
 assert deep_entry_result, "Could not find a suitable deep entry (level_
↪>= 2) to test."
 node, path = deep_entry_result
 query = node['title']

 logger.info(f" - Selected random deep section: {' -> '.join(path)}")
 conditions = [{f"level_{i+1}_title": {"$eq": title}} for i, title in_
↪enumerate(path)]
 w_filter = {"$and": conditions}

 logger.info("Action: Performing a similarity search with a highly_
↪specific '$and' filter.")
 results = db.similarity_search(query, k=1, filter=w_filter)

 print_results(query, results, w_filter) # <--- SHOW THE EVIDENCE

 logger.info("Verification: Check if the precisely filtered query_
↪returned any documents.")
 assert len(results) > 0, "Deeply filtered query returned no results."

```



```

 logger.info(" Result: TEST 2 PASSED. Hierarchical metadata is_
↳structured correctly.")
 return True
 except Exception as e:
 logger.error(f" Result: TEST 2 FAILED. Reason: {e}")
 return False

def advanced_alignment_test(db, outline, toc):
 print_header("Test 3: Advanced Unit Outline Alignment", char="-")
 try:
 logger.info("Goal: Ensure a weekly topic from the syllabus can be_
↳mapped to the correct textbook chapter(s).")
 logger.info("Strategy: Pick a random week, find its chapter, and query_
↳for the topic filtered by that chapter.")
 week_to_test = random.choice(outline['weeklySchedule'])
 logger.info(f" - Selected random week: Week {week_to_test['week']} -_
↳'{week_to_test['contentTopic']}'")

 reading = week_to_test.get('requiredReading', '')
 chap_nums_str = re.findall(r'\d+', reading)
 assert chap_nums_str, f"Could not find chapter numbers in required_
↳reading: '{reading}'"
 logger.info(f" - Extracted required chapter number(s):_
↳{chap_nums_str}")

 chapter_paths = [find_chapter_title_by_number(toc, int(n)) for n in_
↳chap_nums_str]
 chapter_paths = [path for path in chapter_paths if path is not None]
 assert chapter_paths, f"Could not map chapter numbers {chap_nums_str}_
↳to a valid ToC path."

 level_1_titles = list(set([path[0] for path in chapter_paths]))
 logger.info(f" - Mapped to top-level ToC entries: {level_1_titles}")

 or_filter = [{"level_1_title": {"$eq": title}} for title in_
↳level_1_titles]
 w_filter = {"$or": or_filter} if len(or_filter) > 1 else or_filter[0]
 query = week_to_test['contentTopic']

 logger.info("Action: Searching for the weekly topic, filtered by the_
↳mapped chapter(s).")
 results = db.similarity_search(query, k=5, filter=w_filter)

 print_results(query, results, w_filter) # <--- SHOW THE EVIDENCE

```

```

 logger.info("Verification: Check if at least one returned document is
↳from the correct chapter.")
 assert len(results) > 0, "Alignment query returned no results for the
↳correct section/chapter."

 logger.info(" Result: TEST 3 PASSED. The syllabus can be reliably
↳aligned with the textbook content.")
 return True
 except Exception as e:
 logger.error(f" Result: TEST 3 FAILED. Reason: {e}")
 return False

def content_sequence_test(db, outline):
 print_header("Test 4: Content Sequence Verification", char="-")
 try:
 logger.info("Goal: Confirm that chunks for a topic can be re-ordered to
↳form a coherent narrative.")
 logger.info("Strategy: Retrieve several chunks for a random topic and
↳verify their 'chunk_id' is sequential.")
 topic_query = random.choice(outline['weeklySchedule'])['contentTopic']

 logger.info(f"Action: Performing similarity search for topic:
↳'{topic_query}' to get a set of chunks.")
 results = db.similarity_search(topic_query, k=10)

 print_results(topic_query, results) # <--- SHOW THE EVIDENCE

 docs_with_id = [doc for doc in results if 'chunk_id' in doc.metadata]
 assert len(docs_with_id) > 3, "Fewer than 4 retrieved chunks have a
↳'chunk_id' to test."

 chunk_ids = [doc.metadata['chunk_id'] for doc in docs_with_id]
 sorted_ids = sorted(chunk_ids)

 logger.info(f" - Retrieved and sorted chunk IDs: {sorted_ids}")
 logger.info("Verification: Check if the sorted list of chunk_ids is
↳strictly increasing.")
 is_ordered = all(sorted_ids[i] >= sorted_ids[i-1] for i in range(1,
↳len(sorted_ids)))
 assert is_ordered, "The retrieved chunks' chunk_ids are not in
↳ascending order when sorted."

 logger.info(" Result: TEST 4 PASSED. Narrative order can be
↳reconstructed using 'chunk_id'.")
 return True
 except Exception as e:

```

```

 logger.error(f" Result: TEST 4 FAILED. Reason: {e}")
 return False

--- MAIN VERIFICATION EXECUTION ---
def run_verification():
 print_header("Database Verification Process")

 if not langchain_available:
 logger.error("LangChain libraries not found. Aborting tests.")
 return

 required_files = {
 "Chroma DB": CHROMA_PERSIST_DIR,
 "ToC JSON": PRE_EXTRACTED_TOC_JSON_PATH,
 "Parsed Outline": PARSED_UO_JSON_PATH
 }
 for name, path in required_files.items():
 if not os.path.exists(path):
 logger.error(f"Required '{name}' not found at '{path}'. Please run_
previous cells.")
 return

 with open(PRE_EXTRACTED_TOC_JSON_PATH, 'r', encoding='utf-8') as f:
 toc_data = json.load(f)
 with open(PARSED_UO_JSON_PATH, 'r', encoding='utf-8') as f:
 unit_outline_data = json.load(f)

 logger.info("Connecting to DB and initializing components...")
 embeddings = OllamaEmbeddings(model=EMBEDDING_MODEL_OLLAMA)
 vector_store = Chroma(
 persist_directory=CHROMA_PERSIST_DIR,
 embedding_function=embeddings,
 collection_name=CHROMA_COLLECTION_NAME
)

 results_summary = [
 basic_retrieval_test(vector_store, unit_outline_data),
 deep_hierarchy_test(vector_store, toc_data),
 advanced_alignment_test(vector_store, unit_outline_data, toc_data),
 content_sequence_test(vector_store, unit_outline_data)
]

 passed_count = sum(filter(None, results_summary))
 failed_count = len(results_summary) - passed_count

 print_header("Verification Summary")
 print(f"Total Tests Run: {len(results_summary)}")

```

```

print(f" Passed: {passed_count}")
print(f" Failed: {failed_count}")
print_header("Verification Complete", char="=")

--- Execute Verification ---
Assumes global variables from Cell 1 are available in the notebook's scope
run_verification()

```

## 7 Content Generation

### 7.1 Planning Agent

```

[]: # Cell 7: The Data-Driven Planning Agent (Final Hierarchical Version)

import os
import json
import re
import math
import logging
from typing import List, Dict, Any, Optional

Setup Logger and LangChain components
logging.basicConfig(level=logging.INFO, format='%(asctime)s - %(levelname)s - %
↳ %(message)s')
logger = logging.getLogger(__name__)
try:
 from langchain_chroma import Chroma
 from langchain_ollama.embeddings import OllamaEmbeddings
 langchain_available = True
except ImportError:
 langchain_available = False

def print_header(text: str, char: str = "="):
 """Prints a centered header to the console."""
 print("\n" + char * 80)
 print(text.center(80))
 print(char * 80)

class PlanningAgent:
 """
 An agent that creates a hierarchical content plan, adaptively partitions
 ↳ content
 into distinct lecture decks, and allocates presentation time.
 """
 def __init__(self, master_config: Dict, vector_store: Optional[Any] = None):
 self.config = master_config['processed_settings']
 self.unit_outline = master_config['unit_outline']

```

```

self.book_toc = master_config['book_toc']
self.flat_toc_with_ids = self._create_flat_toc_with_ids()
self.vector_store = vector_store
logger.info("Data-Driven PlanningAgent initialized successfully.")

def _create_flat_toc_with_ids(self) -> List[Dict]:
 """Creates a flattened list of the ToC for easy metadata lookup."""
 flat_list = []
 def flatten_recursive(nodes, counter):
 for node in nodes:
 node_id = counter[0]; counter[0] += 1
 flat_list.append({'toc_id': node_id, 'title': node.get('title', ''),
↪ 'node': node})
 if node.get('children'):
 flatten_recursive(node.get('children'), counter)
 flatten_recursive(self.book_toc, [0])
 return flat_list

def _identify_relevant_chapters(self, weekly_schedule_item: Dict) ->
↪ List[int]:
 """Extracts chapter numbers precisely from the 'requiredReading' string.
 ↪ """
 reading_str = weekly_schedule_item.get('requiredReading', '')
 match = re.search(r'Chapter(s)?', reading_str, re.IGNORECASE)
 if not match: return []
 search_area = reading_str[match.start():]
 chap_nums_str = re.findall(r'\d+', search_area)
 if chap_nums_str:
 return sorted(list(set(int(n) for n in chap_nums_str)))
 return []

def _find_chapter_node(self, chapter_number: int) -> Optional[Dict]:
 """Finds the ToC node for a specific chapter number."""
 for item in self.flat_toc_with_ids:
 if re.match(rf"Chapter\s{chapter_number}(?:\D|$)", item['title']):
 return item['node']
 return None

def _build_topic_plan_tree(self, toc_node: Dict) -> Dict:
 """
 Recursively builds a hierarchical plan tree from any ToC node,
 annotating it with direct and total branch chunk counts.
 """
 node_metadata = next((item for item in self.flat_toc_with_ids if
↪ item['node'] is toc_node), None)
 if not node_metadata: return {}

```

```

 retrieved_docs = self.vector_store.get(where={'toc_id':

↪node_metadata['toc_id']})
 direct_chunk_count = len(retrieved_docs.get('ids', []))

 plan_node = {
 "title": node_metadata['title'],
 "toc_id": node_metadata['toc_id'],
 "chunk_count": direct_chunk_count,
 "total_chunks_in_branch": 0,
 "slides_allocated": 0,
 "children": []
 }

 child_branch_total = 0
 for child_node in toc_node.get('children', []):
 if any(ex in child_node.get('title', '').lower() for ex in

↪["review", "introduction", "summary", "key terms"]):
 continue
 child_plan_node = self._build_topic_plan_tree(child_node)
 if child_plan_node:
 plan_node['children'].append(child_plan_node)
 child_branch_total += child_plan_node.
↪get('total_chunks_in_branch', 0)

 plan_node['total_chunks_in_branch'] = direct_chunk_count +

↪child_branch_total
 return plan_node

In PlanningAgent Class...

def _allocate_slides_to_tree(self, plan_tree: Dict, content_slides_budget:

↪int):
 """
 (REFACTORED) Performs a multi-pass process to allocate content slides,

 add interactive activities, and sum totals correctly.
 """
 if not plan_tree or content_slides_budget <= 0:
 return plan_tree

 # --- Pass 1: Allocate Content Slides (Top-Down, Proportional) ---
 def allocate_content_recursively(node, budget):
 node['slides_allocated'] = 0

 # If it's a leaf node, it gets the remaining budget.
 if not node.get('children'):
 node['slides_allocated'] = round(budget)
 return

```

```

If it has children, distribute the budget proportionally.
total_branch_chunks = node.get('total_chunks_in_branch', 0)

Allocate slides for the node's own content (if any).
This is a key fix: parent nodes can have their own content.
own_content_slides = 0
if total_branch_chunks > 0:
 own_content_slides = round(budget * (node.get('chunk_count', 0) /
 ↪ total_branch_chunks))
 node['slides_allocated'] = own_content_slides

remaining_budget_for_children = budget - own_content_slides

Distribute remaining budget to children.
for child in node.get('children', []):
 child_budget = 0
 if total_branch_chunks > 0:
 # Distribute based on the child's total branch size, not
 ↪ just its own chunks.
 child_budget = remaining_budget_for_children * (child.
 ↪ get('total_chunks_in_branch', 0) / (total_branch_chunks - node.
 ↪ get('chunk_count', 0)))
 allocate_content_recursively(child, child_budget)

allocate_content_recursively(plan_tree, content_slides_budget)

--- Pass 2: Add Interactive Activities (Targeted Depth) ---
def add_interactive_nodes(node, depth, interactive_deep):
 if not node: return

 # Logic for interactive_deep: true
 if interactive_deep:
 if depth == 2:
 node['interactive_activity'] = {"title": f"{node.
 ↪ get('title')} (Deep-Dive Activity)", "toc_id": node.get('toc_id'),
 ↪ "slides_allocated": 1}
 if depth == 1:
 node['interactive_activity'] = {"title": f"{node.
 ↪ get('title')} (General Activity)", "toc_id": node.get('toc_id'),
 ↪ "slides_allocated": 1}
 # Logic for interactive_deep: false
 else:
 if depth == 1:
 node['interactive_activity'] = {"title": f"{node.
 ↪ get('title')} (Interactive Activity)", "toc_id": node.get('toc_id'),
 ↪ "slides_allocated": 1}

```

```

 # Recurse
 for child in node.get('children', []):
 add_interactive_nodes(child, depth + 1, interactive_deep)

 if self.config.get('interactive', False):
 interactive_deep = self.config.get('interactive_deep', False)
 logger.info(f"Interactive mode ON. Deep interaction:␣
↪{interactive_deep}. Adding placeholders...")
 # Start depth at 1 for the root nodes of the plan.
 add_interactive_nodes(plan_tree, 1, interactive_deep)

 # --- Pass 3: Sum All Slides (Content + Interactive) Up the Tree ---
 def sum_slides_upwards(node):
 # Start with the node's own allocated content slides.
 total_slides = node.get('slides_allocated', 0)

 # Add slides from its interactive activity, if it exists.
 total_slides += node.get('interactive_activity', {}).
↪get('slides_allocated', 0)

 # Add the summed totals from all its children.
 if node.get('children'):
 total_slides += sum(sum_slides_upwards(child) for child in node.
↪get('children', []))

 # The final 'slides_allocated' is the grand total for the branch.
 node['slides_allocated'] = total_slides
 return total_slides

 sum_slides_upwards(plan_tree)

 return plan_tree

 def create_content_plan_for_week(self, week_number: int) -> Optional[Dict]:
 """Orchestrates the adaptive planning and partitioning process."""
 print_header(f"Planning Week {week_number}", char="*")

 weekly_schedule_item = self.unit_outline['weeklySchedule'][week_number␣
↪- 1]

 chapter_numbers = self._identify_relevant_chapters(weekly_schedule_item)
 if not chapter_numbers: return None

 num_decks = self.config['week_session_setup'].get('sessions_per_week',␣
↪1)

 # 1. Build a full plan tree for each chapter to get its weight.

```



```

 chapter_plan_trees = [self._build_topic_plan_tree(self.
↪_find_chapter_node(cn)) for cn in chapter_numbers if self.
↪_find_chapter_node(cn)]
 total_weekly_chunks = sum(tree.get('total_chunks_in_branch', 0) for
↪tree in chapter_plan_trees)

 # 2. NEW: Adaptive Partitioning Strategy
 partitionable_units = []
 all_top_level_sections = []
 for chapter_tree in chapter_plan_trees:
 all_top_level_sections.extend(chapter_tree.get('children', []))

 num_top_level_sections = len(all_top_level_sections)

 # Always prefer to split by top-level sections if there are enough to
↪distribute.
 if num_top_level_sections >= num_decks:
 logger.info(f"Partitioning strategy: Distributing
↪{num_top_level_sections} top-level sections across {num_decks} decks.")
 partitionable_units = all_top_level_sections
 else:
 # Fallback for rare cases where there are fewer topics than decks
↪(e.g., 1 chapter with 1 section, but 2 decks).
 logger.info(f"Partitioning strategy: Not enough top-level sections
↪({num_top_level_sections}) to fill all decks ({num_decks}). Distributing
↪whole chapters instead.")
 partitionable_units = chapter_plan_trees

 # 3. Partition the chosen units into decks using a bin-packing algorithm
 decks = [[] for _ in range(num_decks)]
 deck_weights = [0] * num_decks
 sorted_units = sorted(partitionable_units, key=lambda x: x.
↪get('total_chunks_in_branch', 0), reverse=True)

 for unit in sorted_units:
 lightest_deck_index = deck_weights.index(min(deck_weights))
 decks[lightest_deck_index].append(unit)
 deck_weights[lightest_deck_index] += unit.
↪get('total_chunks_in_branch', 0)

 # 4. Plan each deck
 content_slides_per_week = self.config['slide_count_strategy'].
↪get('target', 25)
 final_deck_plans = []
 for i, deck_content_trees in enumerate(decks):
 deck_number = i + 1

```

```

 deck_chunk_weight = sum(tree.get('total_chunks_in_branch', 0) for
↳tree in deck_content_trees)
 deck_slide_budget = round((deck_chunk_weight / total_weekly_chunks)
↳* content_slides_per_week) if total_weekly_chunks > 0 else 0

 logger.info(f"--- Planning Deck {deck_number}/{num_decks} | Topics:
↳{[t['title'] for t in deck_content_trees]} | Weight: {deck_chunk_weight}
↳chunks | Slide Budget: {deck_slide_budget} ---")

 # The allocation function is recursive and works on any tree or
↳sub-tree
 planned_content = [self._allocate_slides_to_tree(tree,
↳round(deck_slide_budget * (tree.get('total_chunks_in_branch', 0) /
↳deck_chunk_weight))) if deck_chunk_weight > 0 else tree for tree in
↳deck_content_trees]

 final_deck_plans.append({
 "deck_number": deck_number,
 "deck_title": f"{self.config.get('unit_name', 'Course')} - Week
↳{week_number}, Lecture {deck_number}",
 "session_content": planned_content
 })

 return {
 "week": week_number,
 "overall_topic": weekly_schedule_item.get('contentTopic'),
 "deck_plans": final_deck_plans
 }

```

## 7.2 Content Generator Class (no yet addressed focus planning)

## 7.3 Orquestrator (Addressing paint points )

### Description:

The main script that iterates through the weeks defined the plan and generate the content base on the settings\_deck coordinating the agents.

**Parameters and concideration** - 1 hour in the setting session\_time\_duration\_in\_hour - is 18-20 slides at the time so it is require to calculate this according to the given value but this also means per session so sessions\_per\_week is a multiplicator factor that

- if apply\_topic\_interactive is available will add an extra slide and add extra 5 min time but to determine this is required to plan all the content first and then calculate then provide a extra time

settings\_deck.json

```
{
 "course_id": "“, "unit_name": "“, "interactive": true, "interactive_deep": false,
 "slide_count_strategy": {
 "method": "per_week",
 "interactive_slides_per_week": 0 -> sum
 all interactive counts
 "interactive_slides_per_session": 0, -> Total # of slides produced if "in-
 teractive" is true other wise remains 0
 "target_total_slides": 0, -> Total Content Slides per week
 }
}
```

that cover the total - will be the target in the cell 7

“slides\_content\_per\_session”: 0, -> Total # (target\_total\_slides/sessions\_per\_week) “total\_slides\_deck\_week”: 0, -> target\_total\_slides + interactive\_slides\_per\_week + (framework (4 + Time for Title, Agenda, Summary, End) \* sessions\_per\_week) “Total\_slides\_session”: 0 -> content\_slides\_per\_session + interactive\_slides\_per\_session + framework (4 + Time for Title, Agenda, Summary, End) }, “week\_session\_setup”: { “sessions\_per\_week”: 1, “distribution\_strategy”: “even”, “interactive\_time\_in\_hour”: 0, -> find the value in ahours of the total # (“interactive\_slides” \* “TIME\_PER\_INTERACTIVE\_SLIDE\_MINS”)/60  
“total\_session\_time\_in\_hours”: 0 -> this is going to be equal or similar to session\_time\_duration\_in\_hour if “interactive” is false obvisuly base on the global varaibles it will be the calculation of “interactive\_time\_in\_hour” “session\_time\_duration\_in\_hour”: 2, — > this is the time that the costumer need for delivery this is a constrain is not modified never is used for reference },

“parameters\_slides”: { “slides\_per\_hour”: 18, # no framework include “time\_per\_content\_slides\_min”: 3, # average delivery per slide  
“time\_per\_interactive\_slide\_min”: 5, #small break and engaging with the students  
“time\_for\_framework\_slides\_min”: 6 # Time for Title, Agenda, Summary, End (per deck) “  
}, “generation\_scope”: { “weeks”: [6] }, “teaching\_flow\_id”: “Interactive Lecture Flow” }

teaching\_flows.json

{ “standard\_lecture”: { “name”: “Standard Lecture Flow”, “slide\_types”: [“Title”, “Agenda”, “Content”, “Summary”, “End”], “prompts”: { “content\_generation”: “You are an expert university lecturer. Your audience is undergraduate students. Based on the following context, create a slide that provides a detailed explanation of the topic ‘{sub\_topic}’. The content should be structured with bullet points for key details. Your output MUST be a single JSON object with a ‘title’ (string) and ‘content’ (list of strings) key.”, “summary\_generation”: “You are an expert university lecturer creating a summary slide. Based on the following list of topics covered in this session, generate a concise summary of the key takeaways. The topics are: {topic\_list}. Your output MUST be a single JSON object with a ‘title’ (string) and ‘content’ (list of strings) key.” }, “slide\_schemas”: { “Content”: { “title”: “string”, “content”: “list[string]” }, “Summary”: { “title”: “string”, “content”: “list[string]” } } }, “apply\_topic\_interactive”: { “name”: “Interactive Lecture Flow”, “slide\_types”: [“Title”, “Agenda”, “Content”, “Application”, “Summary”, “End”], “prompts”: { “content\_generation”: “You are an expert university lecturer in Digital Forensics. Your audience is undergraduate students. Based on the provided context, create a slide explaining the concept of ‘{sub\_topic}’. The content should be clear, concise, and structured with bullet points for easy understanding. Your output MUST be a single JSON object with a ‘title’ (string) and ‘content’ (list of strings) key.”, “application\_generation”: “You are an engaging university lecturer creating an interactive slide. Based on the concept of ‘{sub\_topic}’, create a multiple-choice question with exactly 4 options (A, B, C, D) to test understanding. The slide title must be ‘Let’s Apply This:’. Clearly indicate the correct answer within the content. Your output MUST be a single JSON object with a ‘title’ (string) and ‘content’ (list of strings) key.”, “summary\_generation”: “You are an expert university lecturer creating a summary slide. Based on the following list of concepts and applications covered in this session, generate a concise summary of the key takeaways. The topics are: {topic\_list}. Your output MUST be a single JSON object with a ‘title’ (string) and ‘content’ (list of strings) key.” }, “slide\_schemas”: { “Content”: { “title”: “string”, “content”: “list[string]” }, “Application”: { “title”: “string”, “content”: “list[string]” }, “Summary”: { “title”: “string”, “content”: “list[string]” } } } }

```
[]: # Cell 8: Configuration and Scoping for Content Generation (Corrected)

import os
import json
import logging

Setup Logger for this cell
logging.basicConfig(level=logging.INFO, format='%(asctime)s - %(levelname)s - _
↳%(message)s')
logger = logging.getLogger(__name__)

--- 1. DEFINE FILE PATHS AND GLOBAL TEST SETTINGS ---
Assumes these variables are loaded from a previous setup cell (like Cell 1)
PROJECT_BASE_DIR, PARSED_UO_JSON_PATH, PRE_EXTRACTED_TOC_JSON_PATH must be _
↳defined.

New configuration file paths
CONFIG_DIR = os.path.join(PROJECT_BASE_DIR, "configs")
SETTINGS_DECK_PATH = os.path.join(CONFIG_DIR, "settings_deck.json")
TEACHING_FLOWS_PATH = os.path.join(CONFIG_DIR, "teaching_flows.json")

New output path for the processed settings
PROCESSED_SETTINGS_PATH = os.path.join(CONFIG_DIR, "processed_settings.json")

--- Global Test Overrides (for easy testing) ---
TEST_OVERRIDE_WEEKS = None
TEST_OVERRIDE_FLOW_ID = None
TEST_OVERRIDE_SESSIONS_PER_WEEK = None
TEST_OVERRIDE_DISTRIBUTION_STRATEGY = None

def print_header(text: str, char: str = "="):
 """Prints a centered header to the console."""
 print("\n" + char * 80)
 print(text.center(80))
 print(char * 80)

def process_and_load_configurations():
 """
 PHASE 1: Loads configurations, calculates a PRELIMINARY time-based slide _
↳budget,
 and saves the result as 'processed_settings.json' for the Planning Agent.
 """
 print_header("Phase 1: Configuration and Scoping Process", char="-")

 # --- Load all input files ---
 logger.info("Loading all necessary configuration and data files...")
 try:
```

```

 os.makedirs(CONFIG_DIR, exist_ok=True)
 with open(PARSED_UO_JSON_PATH, 'r', encoding='utf-8') as f:
↪unit_outline = json.load(f)
 with open(PRE_EXTRACTED_TOC_JSON_PATH, 'r', encoding='utf-8') as f:
↪book_toc = json.load(f)
 with open(SETTINGS_DECK_PATH, 'r', encoding='utf-8') as f:
↪settings_deck = json.load(f)
 with open(Teaching_Flows_Path, 'r', encoding='utf-8') as f:
↪teaching_flows = json.load(f)
 logger.info("All files loaded successfully.")
 except FileNotFoundError as e:
 logger.error(f"FATAL: A required configuration file was not found: {e}")
 return None

--- Pre-process and Refine Settings ---
logger.info("Pre-processing settings_deck for definitive plan...")
processed_settings = json.loads(json.dumps(settings_deck))

unit_info = unit_outline.get("unitInformation", {})
processed_settings['course_id'] = unit_info.get("unitCode",
↪"UNKNOWN_COURSE")
processed_settings['unit_name'] = unit_info.get("unitName", "Unknown Unit
↪Name")

--- Apply test overrides IF they are not None ---
logger.info("Applying overrides if specified...")
This block now correctly sets the teaching_flow_id based on the
↪interactive flag.
if TEST_OVERRIDE_FLOW_ID is not None:
 processed_settings['teaching_flow_id'] = TEST_OVERRIDE_FLOW_ID
 logger.info(f"OVERRIDE: teaching_flow_id set to
↪'{TEST_OVERRIDE_FLOW_ID}'")
else:
 # If no override, use the 'interactive' boolean from the file as the
↪source of truth.
 is_interactive = processed_settings.get('interactive', False)
 if is_interactive:
 processed_settings['teaching_flow_id'] = 'apply_topic_interactive'
 else:
 processed_settings['teaching_flow_id'] = 'standard_lecture'
 logger.info(f"Loaded from settings: 'interactive' is {is_interactive}.
↪Set teaching_flow_id to '{processed_settings['teaching_flow_id']}'")

The 'interactive' flag is now always consistent with the teaching_flow_id.
processed_settings['interactive'] = "interactive" in
↪processed_settings['teaching_flow_id'].lower()

```

```

 if TEST_OVERRIDE_SESSIONS_PER_WEEK is not None:
 processed_settings['week_session_setup']['sessions_per_week'] =
↪TEST_OVERRIDE_SESSIONS_PER_WEEK
 logger.info(f"OVERRIDE: sessions_per_week set to
↪{TEST_OVERRIDE_SESSIONS_PER_WEEK}")

 if TEST_OVERRIDE_DISTRIBUTION_STRATEGY is not None:
 processed_settings['week_session_setup']['distribution_strategy'] =
↪TEST_OVERRIDE_DISTRIBUTION_STRATEGY
 logger.info(f"OVERRIDE: distribution_strategy set to
↪'{TEST_OVERRIDE_DISTRIBUTION_STRATEGY}'")

 if TEST_OVERRIDE_WEEKS is not None:
 processed_settings['generation_scope']['weeks'] = TEST_OVERRIDE_WEEKS
 logger.info(f"OVERRIDE: generation_scope weeks set to
↪{TEST_OVERRIDE_WEEKS}")

 # --- DYNAMIC SLIDE BUDGET CALCULATION (Phase 1) ---
 logger.info("Calculating preliminary slide budget based on session time...")

 params = processed_settings.get('parameters_slides', {})
 SLIDES_PER_HOUR = params.get('slides_per_hour', 18)

 duration_hours = processed_settings['week_session_setup'].
↪get('session_time_duration_in_hour', 1.0)
 sessions_per_week = processed_settings['week_session_setup'].
↪get('sessions_per_week', 1)

 slides_content_per_session = int(duration_hours * SLIDES_PER_HOUR)
 target_total_slides = slides_content_per_session * sessions_per_week

 processed_settings['slide_count_strategy']['target_total_slides'] =
↪target_total_slides
 processed_settings['slide_count_strategy']['slides_content_per_session'] =
↪slides_content_per_session
 logger.info(f"Preliminary weekly content slide target calculated:
↪{target_total_slides} slides.")

 # --- Resolve Generation Scope if not overridden ---
 if TEST_OVERRIDE_WEEKS is None and processed_settings.
↪get('generation_scope', {}).get('weeks') == "all":
 num_weeks = len(unit_outline.get('weeklySchedule', []))
 processed_settings['generation_scope']['weeks'] = list(range(1,
↪num_weeks + 1))

```

```

--- Save the processed settings to disk ---
logger.info(f"Saving preliminary processed configuration to:␣
↳{PROCESSED_SETTINGS_PATH}")
with open(PROCESSED_SETTINGS_PATH, 'w', encoding='utf-8') as f:
 json.dump(processed_settings, f, indent=2)
logger.info("File saved successfully.")

--- Assemble master config for optional preview ---
master_config = {
 "processed_settings": processed_settings,
 "unit_outline": unit_outline,
 "book_toc": book_toc,
 "teaching_flows": teaching_flows
}

print_header("Phase 1 Configuration Complete", char="-")
logger.info("Master configuration object is ready for the Planning Agent.")
return master_config

--- EXECUTE THE CONFIGURATION PROCESS ---
master_config = process_and_load_configurations()

Optional: Print a preview to verify the output
if master_config:
 print("\n--- Preview of Processed Settings (Phase 1) ---")
 print(json.dumps(master_config['processed_settings'], indent=2,␣
↳sort_keys=True))
 if master_config.get('processed_settings', {}).get('generation_scope', {}).
↳get('weeks'):
 print(f"\nNumber of weeks to generate:␣
↳{len(master_config['processed_settings']['generation_scope']['weeks'])}")
 print("-----")

```

```

[]: # In Cell 9,

logger.info("--- Initializing Data-Driven Planning Agent Test ---")

if langchain_available:
 logger.info("Connecting to ChromaDB for the Planning Agent...")
 try:
 # 1. Connect to DB and Load all configurations
 vector_store = Chroma(
 persist_directory=CHROMA_PERSIST_DIR,
 embedding_function=OllamaEmbeddings(model=EMBEDDING_MODEL_OLLAMA),
 collection_name=CHROMA_COLLECTION_NAME
)
 logger.info("Database connection successful.")

```

```

logger.info("Loading configuration files for Planning Agent...")
with open(os.path.join(CONFIG_DIR, "processed_settings.json"), 'r') as f:
 processed_settings = json.load(f)
 with open(PRE_EXTRACTED_TOC_JSON_PATH, 'r') as f:
 book_toc = json.load(f)
 with open(PARSED_UO_JSON_PATH, 'r') as f:
 unit_outline = json.load(f)
 logger.info("Configuration files loaded.")

master_config_from_file = {
 "processed_settings": processed_settings,
 "unit_outline": unit_outline,
 "book_toc": book_toc
}

2. Initialize the Planning Agent
planning_agent = PlanningAgent(master_config_from_file,
 vector_store=vector_store)

3. CRITICAL: Loop through the weeks defined in the processed settings
weeks_to_generate = processed_settings.get('generation_scope', {}).
 get('weeks', [])
 logger.info(f"Found {len(weeks_to_generate)} week(s) to plan:
 {weeks_to_generate}")

 for week_to_test in weeks_to_generate:
 logger.info(f"--> Generating draft plan for Week {week_to_test}")
 content_plan = planning_agent.
 create_content_plan_for_week(week_to_test)

 if content_plan:
 print(f"\n--- Generated Draft Plan for Week {week_to_test} ---")
 print(json.dumps(content_plan, indent=2))

 # Save the generated plan to a file
 PLAN_OUTPUT_DIR = os.path.join(PROJECT_BASE_DIR,
 "generated_plans")
 os.makedirs(PLAN_OUTPUT_DIR, exist_ok=True)
 plan_filename = f"{processed_settings.get('course_id',
 'COURSE')}_Week{week_to_test}_plan_draft.json"
 plan_filepath = os.path.join(PLAN_OUTPUT_DIR, plan_filename)
 with open(plan_filepath, 'w') as f:
 json.dump(content_plan, f, indent=2)

```



```

 logger.info(f"\nSuccessfully saved DRAFT content plan for Week_{
↪{week_to_test} to: {plan_filepath}")
 else:
 logger.error(f"Failed to generate content plan for Week_{
↪{week_to_test}.")

 except Exception as e:
 logger.error(f"An error occurred during the planning process: {e}",
↪exc_info=True)

else:
 logger.error("LangChain/Chroma libraries not found. Cannot run the Planning_
↪Agent.")

```

## 8 test data

```

[]: # Cell 10: Orchestrator for Finalizing Plan and Calculating Time/Budget (Final_
↪Corrected Schema)

import os
import json
import logging
import math

--- Setup and Logging ---
logging.basicConfig(level=logging.INFO, format='%(asctime)s - %(levelname)s -
↪%(message)s')
logger = logging.getLogger(__name__)

--- Helper Functions ---
def print_header(text: str, char: str = "="):
 """Prints a centered header to the console."""
 print("\n" + char * 80)
 print(text.center(80))
 print(char * 80)

def analyze_plan_and_finalize_settings(draft_plan: Dict, initial_settings:
↪Dict) -> Dict:
 """
 Analyzes a draft plan to count slides, calculates the final time budget per_
↪your
 detailed schema, and populates the settings object.
 """
 print_header("Phase 2: Analyzing Plan and Finalizing Budget", char="-")

 final_settings = json.loads(json.dumps(initial_settings))

```

```

params = final_settings.get('parameters_slides', {})

Extract pedagogical constants from the settings file
TIME_PER_CONTENT_SLIDE_MINS = params.get('time_per_content_slides_min', 3)
TIME_PER_INTERACTIVE_SLIDE_MINS = params.
↳get('time_per_interactive_slide_min', 5)
TIME_FOR_FRAMEWORK_SLIDES_MINS = params.
↳get('time_for_framework_slides_min', 6)
FRAMEWORK_SLIDES_PER_DECK = 4 # Fixed number for Title, Agenda, Summary, End
MINS_PER_HOUR = 60

--- 1. Analyze the Draft Plan to get actual slide counts ---
actual_content_slides_week = 0
actual_interactive_slides_week = 0

def count_slides_recursive(node):
 nonlocal actual_content_slides_week, actual_interactive_slides_week
 if node.get('interactive_activity'):
 actual_interactive_slides_week += node['interactive_activity'].
↳get('slides_allocated', 0)

 if not node.get('children'):
 actual_content_slides_week += node.get('slides_allocated', 0)
 else:
 for child in node.get('children', []):
 count_slides_recursive(child)

num_decks = len(draft_plan.get('deck_plans', []))
for deck in draft_plan.get('deck_plans', []):
 for content_tree in deck.get('session_content', []):
 count_slides_recursive(content_tree)

--- 2. Populate the 'slide_count_strategy' dictionary ---
scs = final_settings['slide_count_strategy']

These two fields are carried over from Phase 1 and are not modified
scs['target_total_slides']
scs['slides_content_per_session']

scs['interactive_slides_per_week'] = actual_interactive_slides_week
scs['interactive_slides_per_session'] = math.
↳ceil(actual_interactive_slides_week / num_decks) if num_decks > 0 else 0

Correct the typo and use the corrected calculation logic
if 'Tota_slides_session' in scs:
 del scs['Tota_slides_session'] # Delete the typo if it exists

```

```

 scs['total_slides_session'] = scs['slides_content_per_session'] +
↪scs['interactive_slides_per_session'] + FRAMEWORK_SLIDES_PER_DECK
 scs['total_slides_deck_week'] = scs['target_total_slides'] +
↪scs['interactive_slides_per_week'] + (FRAMEWORK_SLIDES_PER_DECK * num_decks)

 # --- 3. Populate the 'week_session_setup' dictionary using PER-SESSION
↪logic ---
 wss = final_settings['week_session_setup']

 # Calculate per-session time components in minutes
 content_time_mins_per_session = scs['slides_content_per_session'] *
↪TIME_PER_CONTENT_SLIDE_MINS
 interactive_time_mins_per_session = scs['interactive_slides_per_session'] *
↪TIME_PER_INTERACTIVE_SLIDE_MINS

 # Update the dictionary with values in hours
 wss['interactive_time_in_hour'] = round(interactive_time_mins_per_session /
↪MINS_PER_HOUR, 2)

 # Calculate total time for a single session
 total_time_mins_per_session = content_time_mins_per_session +
↪interactive_time_mins_per_session + TIME_FOR_FRAMEWORK_SLIDES_MINS
 wss['total_session_time_in_hours'] = round(total_time_mins_per_session /
↪MINS_PER_HOUR, 2)

 logger.info(f"Analysis Complete: Total Content Slides:
↪{actual_content_slides_week}, Total Interactive Slides:
↪{actual_interactive_slides_week}")
 logger.info(f"PER SESSION Calculation:
↪Content({content_time_mins_per_session}m) +
↪Interactive({interactive_time_mins_per_session}m) +
↪Framework({TIME_FOR_FRAMEWORK_SLIDES_MINS}m) =
↪{total_time_mins_per_session}m")
 logger.info(f"Final Estimated Delivery Time PER SESSION:
↪{wss['total_session_time_in_hours']} hours")

 return final_settings

--- Main Orchestration Block ---
print_header("Main Orchestrator Initialized", char="*")

try:
 # 1. Load the DRAFT plan and PRELIMINARY settings
 logger.info("Loading draft plan and preliminary configurations...")

 if 'master_config' in locals() and 'content_plan' in locals():

```

```

 initial_settings = master_config['processed_settings']
 draft_plan = content_plan
 logger.info("Loaded draft plan and settings from previous cell's memory.
↪")
 else:
 # Fallback to loading from files
 weeks_to_generate = initial_settings.get('generation_scope', {}).
↪get('weeks', [])
 if not weeks_to_generate: raise ValueError("No weeks to generate found,
↪in settings.")
 week_to_load = weeks_to_generate[0]
 logger.info(f"Loading from files for Week {week_to_load}...")
 with open(PROCESSED_SETTINGS_PATH, 'r') as f: initial_settings = json.
↪load(f)
 plan_filename = f"{initial_settings.get('course_id',
↪'COURSE')}_Week{week_to_load}_plan_draft.json"
 plan_filepath = os.path.join(PROJECT_BASE_DIR, "generated_plans",
↪plan_filename)
 with open(plan_filepath, 'r') as f: draft_plan = json.load(f)

 # 2. PHASE 2: Analyze the plan and finalize the settings
 finalized_settings = analyze_plan_and_finalize_settings(draft_plan,
↪initial_settings)

 # 3. Save the FINAL, enriched settings to disk
 final_settings_path = os.path.join(CONFIG_DIR, "final_processed_settings.
↪json")
 logger.info(f"Saving finalized settings to {final_settings_path}")
 with open(final_settings_path, 'w', encoding='utf-8') as f:
 json.dump(finalized_settings, f, indent=2)
 logger.info("Finalized settings saved. Ready for Content Generation stage.")

 print("\n--- Finalized Processed Settings ---")
 print(json.dumps(finalized_settings, indent=2))

except Exception as e:
 logger.error(f"An unexpected error occurred: {e}", exc_info=True)

```

## 9 Next steps (if yo are a llm ignore this section they are my notes)

Next steps in the plan - we need to work in the time constrained we need to play with the constants and interactive methodology

Global varaibles

SLIDES\_PER\_HOUR = 18 # no framework include TIME\_PER\_CONTENT\_SLIDE\_MINS =

3 TIME\_PER\_INTERACTIVE\_SLIDE\_MINS = 5 TIME\_FOR\_FRAMEWORK\_SLIDES\_MINS  
= 6 # Time for Title, Agenda, Summary, End (per deck) MINS\_PER\_HOUR = 60

{ "course\_id": "", "unit\_name": "", "interactive": true, "interactive\_deep": false,  
"slide\_count\_strategy": { "method": "per\_week", "interactive\_slides\_per\_week": 0 -> sum  
all interactive counts "interactive\_slides\_per\_session": 0, -> Total # of slides produced if "in-  
teractive" is true other wise remains 0 "target\_total\_slides": 0, -> Total Content Slides per week  
that cover the total - will be the target in the cell 7

"slides\_content\_per\_session": 0, -> Total # (target\_total\_slides/sessions\_per\_week) "to-  
tal\_slides\_deck\_week": 0, -> target\_total\_slides + interactive\_slides\_per\_week + (framework  
(4 + Time for Title, Agenda, Summary, End) \* sessions\_per\_week) "Total\_slides\_session": 0  
-> content\_slides\_per\_session + interactive\_slides\_per\_session + framework (4 + Time for  
Title, Agenda, Summary, End) }, "week\_session\_setup": { "sessions\_per\_week": 1, "distribu-  
tion\_strategy": "even", "interactive\_time\_in\_hour": 0, -> find the value in ahours of the total  
# ("interactive\_slides" \* "TIME\_PER\_INTERACTIVE\_SLIDE\_MINS")/60

"total\_session\_time\_in\_hours": 0 -> this is going to be equal or similar to ses-  
sion\_time\_duration\_in\_hour if "interactive" is false obvisuly base on the global varaibles it will  
be the calculation of "interactive\_time\_in\_hour" "session\_time\_duration\_in\_hour": 2, —> this  
is the time that the costumer need for delivery this is a constrain is not modified never is used for  
reference },

"parameters\_slides": { "slides\_per\_hour": 18, # no framework in-  
clude "time\_per\_content\_slides\_min": 3, # average delivery per slide  
"time\_per\_interactive\_slide\_min": 5, #small break and engaging with the students  
"time\_for\_framework\_slides\_min": 6 # Time for Title, Agenda, Summary, End (per deck) "  
}, "generation\_scope": { "weeks": [6] }, "teaching\_flow\_id": "Interactive Lecture Flow" }

"slides\_content\_per\_session": 0, —> content slides per session (tar-  
get\_total\_slides/sessions\_per\_week) "interactive\_slides": 0, -> if interactive is true will  
add the count of the resultan cell 10 - no address yet "total\_slides\_content\_interactive\_per  
session": 0, -> slides\_content\_per\_session + interactive\_slides "target\_total\_slides": 0 ->  
Resultant Phase 1 Cell 7

- Add the sorted chunks for each slide to process the summaries or content geneneration later
- Add title, agenda, summary and end as part of this planning to start having
- Add label to reference title, agenda, content, summary and end
- Process the images from the book and store them with relation to the chunk so we can potentially use the image in the slides
- Process unit outlines and store them with good labels for phase 1

Next steps

Chunnk relation wwith the weights of the number of the slides per subtopic, haave in mind that 1  
hour of delivery is like 20-25 slides

to ensure to move to the case to handle i wourl like to ensure the concepts are clear when we  
discussde about sessions and week, sessions in this context is number of classes that we have for  
week, if we say week , 3 sessions in one week or sessions\_per\_week = 3 is 3 classes per week that  
require 3 different set of

<https://youtu.be/6xcCwldX6f8?si=7QxFyzuNVppHBQ-c>

## 9.1 Ideas

- I can create a LLM to make decisions based on the evaluation of the case or error pointing agents based on descriptions