

sebastian-j / **streamchange-frontend** ▾

Code

Issues

**10****Pull requests****5**

Agents

Actions

Projects

Wiki

Security and quality

**127**

Insights

Settings



View status

Code ▾

Preview



# Eslint Bug Fixes #91

Open

**KrzysztofPieczka** wants to merge 3 commits into

frontend2.0 from fix/58-bugs-lint



Conversation

**0**

Commits

**3**

Checks

**1**

Files changed

**28**

All commits ▾

0 / 28

Review

**0****3**

src/components/AdFrame/index.jsx



```
...      @@ -36,19 +36,19 @@ const AdFrame = () => {
36      36          setIsOpen(false);
37      37      };
38      38
39      -    const getToday = () => {
40      -        const d = new Date();
41      -        let month = `${d.getMonth() + 1}`;
42      -        let day = `${d.getDate()}`;
43      -        const year = d.getFullYear();
39      +    useEffect(() => {
40      +        const getToday = () => {
41      +            const d = new Date();
42      +            let month = `${d.getMonth() + 1}`;
43      +            let day = `${d.getDate()}`;
44      +            const year = d.getFullYear();
44      45
45      -        if (month.length < 2) month = `0${month}`;
46      -        if (day.length < 2) day = `0${day}`;
46      +        if (month.length < 2) month = `0${month}`;
47      +        if (day.length < 2) day = `0${day}`;
47      48
48      -        return [year, month, day].join('-');
49      -    };
49      -    };
```

```

49 +     return [year, month, day].join('-');
50 +   };
50 51
51 -   const getPromotedChannels = () => {
52 52     axios.get('../static/sellers.json').then((res) => {
53 53       if (res.data.items) {
54 54         for (let i = 0; i < res.data.items.length; i += 1) {
55         @@ -59,10 +59,6 @@ const AdFrame = () => {
59 59           setPromotedContent(null);
60 60         }
61 61       });
62 -   };
63 -
64 -   useEffect(() => {
65 -     getPromotedChannels();
66 62   }, []);
67 63
68 64   if (promotedContent === null) {

```

src/components/AdFrame/PromotedBanner.jsx

```

@@ -45,9 +45,11 @@ const PromotedBanner = (props) => {
45 45     return (
46 46       <PromotedContentWrapper
47 47         offset={imgHeight}
48 +      // eslint-disable-next-line react-hooks/purity -- intentional per-
render jitter to defeat adblock DOM-pattern detection
48 49       margin={props.testMargins ? 1 : Math.round(Math.random() * 1000) / 100}
49 50     >
50 51       <AdTitle
52 +      // eslint-disable-next-line react-hooks/purity -- intentional per-
render jitter to defeat adblock DOM-pattern detection
51 53       margin={props.testMargins ? 1 : Math.round(Math.random() * 1000) /
100}
52 54     >
53 55       <FormattedMessage {...messages.title} />
54 56     </AdTitle>
55 57   </PromotedContentWrapper>
56 58 )}
57 59 </div>
58 60 {/* eslint-disable react-hooks/purity -- intentional per-render
jitter to defeat adblock DOM-pattern detection */}
59 61 <Shield

```

```

74 77      margin={
75 78      props.testMargins ? 1 : Math.round(Math.random() * 1000) / 100
    @@ -85,6 +88,7 @@ const PromotedBanner = (props) => {
85 88      props.testMargins ? 1 : Math.round(Math.random() * 1000) / 100
86 89      }
87 90    />
    91  +    { /* eslint-enable react-hooks/purity */ }
88 92    </a>
89 93    </PromotedContentWrapper>
90 94  );
    ↓

```

src/components/ChatView/InternalChat.jsx

```

    @@ -22,11 +22,11 @@
22 22  `;
23 23
24 24  export const InternalChat = (props) => {
25 25  -   let messagesEndRef = useRef(null);
    25  +   const messagesEndRef = useRef(null);
26 26  useInjectReducer({ key: 'chat', reducer });
27 27
28 28  const scrollToBottom = () => {
29 29  -   messagesEndRef.scrollToView({ behavior: 'smooth' });
    29  +   messagesEndRef.current?.scrollIntoView({ behavior: 'smooth' });
30 30  };
31 31
32 32  useEffect(() => {
    @@ -38,11 +38,7 @@
38 38      {props.messages.map((message) => (
39 39        <InternalChatMessage key={message.publishedAt} message={message} />
40 40      ))}
41 41  -   <ScrollerEnd
42 42  -     ref={el) => {
43 43  -       messagesEndRef = el;
44 44  -     }}
45 45  -   />
    41  +   <ScrollerEnd ref={messagesEndRef} />
46 42  </ItemScroller>
47 43  );
48 44  };
    @@ -56,3 +52,3 @@
56 52  });
57 53

```

```
58 54 export default connect(mapStateToProps, null)(InternalChat);
```

⚠ Check warning on line R54

Fast refresh only works when a file only exports components. Use a new file to share constants or functions between components

[View details](#)

▼ ...omponents/ChatView/InternalChatMessage.jsx

```
↑... @@ -8,21 +8,12 @@ const MessageLi = styled.li`
8 8 margin-bottom: 5px;
9 9 `;
10 10
11 - const AuthorImage = styled.img`
12 - border-radius: 50%;
13 - height: 26px;
14 - margin-right: 5px;
15 - `;
16 -
17 11 const AuthorTitle = styled.span`
18 12 color: ${(props) =>
19 13 props.userColor ? props.userColor : props.theme.secondaryTextColor};
20 14 font-family: Roboto, sans-serif;
21 15 font-weight: 500;
22 16 margin-right: 5px;
23 - .moderator {
24 - color: rgb(94, 132, 241);
25 - }
26 17 `;
27 18 const MessageText = styled.span`
28 19 color: ${(props) => props.theme.staticTextColor};
```

▼ src/components/ColorPicker/index.jsx

```
... @@ -1,4 +1,4 @@
1 - import { useEffect, useState } from 'react';
1 + import { useState } from 'react';
2 2 import PropTypes from 'prop-types';
3 3 import styled from 'styled-components';
4 4 import { SketchPicker } from 'react-color';
↓
↑... @@ -46,18 +46,17 @@ const PickerButton = styled.button`
```

```

46 46
47 47     const ColorPicker = (props) => {
48 48         const [color, setColor] = useState(props.color);
49     -   const [colorString, setColorString] = useState(props.color);
50 49     const [pickerVisible, setPickerVisible] = useState(false);
51 50
52     -   useEffect(() => {
53     -       setColorString(props.color);
54     -   }, [color]);
51 51     +   const colorString =
52 52     +       typeof color === 'string'
53 53     +       ? color
54 54     +       : `rgba(${color.r}, ${color.g}, ${color.b}, ${color.a})`;
55 55
56 56     const handleColorChange = (colorObject) => {
57 57         const rgba = colorObject.rgba;
58 58         const hex = `rgba(${rgba.r}, ${rgba.g}, ${rgba.b}, ${rgba.a})`;
59 59         setColor(rgba);
60     -   setColorString(hex);
61 60         props.handleChange(props.name, hex);
62 61     };
63 62

```

src/components/CSGORaffle/index.jsx

```

...   @@ -1,4 +1,4 @@
1     -   import { useEffect, useState } from 'react';
1     +   import { useEffect, useRef, useState } from 'react';
2     2     import PropTypes from 'prop-types';
3     3     import { connect } from 'react-redux';
4     4     import { createStructuredSelector } from 'reselect';
@@ -11,17 +11,7 @@
11    11    import './style.css';
12    12
13    13    const CSGORaffle = (props) => {

```

⚠ Check warning on line R13

Fast refresh only works when a file only exports components. Move your component(s) to a separate file. If all exports are HOCs, add them to the `extraHOCs` option



CI / ci

View details

```

14     -   const [users, setUsers] = useState([]);

```

```

15      -   const [scrollSize, setScrollSize] = useState(0);
16      -   const [winner, setWinner] = useState(null);
17      -   const [timer, setTimer] = useState(null);
18      -
19      -   const closeImmediately = () => {
20      -     props.onClose();
21      -     clearTimeout(timer);
22      -   };
23      -
24      -   useEffect(() => {
14      +   const [{ users, winner, scroll }] = useState(() => {
25      15       let eligibleUsers = props.userArray.filter(
26      16       (user) => user.isEligible === true
27      17       );
@@ -39,19 +29,30 @@
39      29       const winnerIndex =
40      30       Math.floor(Math.random() * 10) + 10 + props.duration * 3;
41      31       if (props.preWinner) shuffled[winnerIndex] = props.preWinner;
42      -   const scroll = -(winnerIndex * 150 + Math.floor(Math.random() * 65) -
290);
43      -   setUsers(shuffled);
44      -   setTimeout(() => setScrollSize(scroll), 10);
45      -   setWinner(shuffled[winnerIndex]);
46      -   setTimer(
47      -     setTimeout(
48      -       () => {
49      -         props.onWin(shuffled[winnerIndex].id);
50      -       },
51      -       (props.duration + 1) * 1000
52      -     )
32      +   return {
33      +     users: shuffled,
34      +     winner: shuffled[winnerIndex],
35      +     scroll: -(winnerIndex * 150 + Math.floor(Math.random() * 65) - 290),
36      +   };
37      +   });
38      +   const [scrollSize, setScrollSize] = useState(0);
39      +   const timerRef = useRef(null);
40      +
41      +   const closeImmediately = () => {
42      +     props.onClose();
43      +     clearTimeout(timerRef.current);
44      +   };

```

```

45 +
46 +   useEffect(() => {
47 +     const scrollTimeout = setTimeout(() => setScrollSize(scroll), 10);
48 +     timerRef.current = setTimeout(
49 +       () => {
50 +         props.onWin(winner.id);
51 +       },
52 +       (props.duration + 1) * 1000
53   53     );
54   -   }, []);
54   +   return () => clearTimeout(scrollTimeout);
55   +   }, [scroll, winner, props]);
55   56
56   57   return (
57   58     <div className="dialog-root">
@@ -73,8 +74,8 @@
73   74       transitionDuration: `${props.duration}s`,
74   75     }}
75   76   >
76   -   {users.map((item) => (
77   -     <td key={Math.round(Math.random() * 10000000)}>
77   +   {users.map((item, index) => (
78   +     <td key={`${index}-${item.id}`}>
78   79       <div className="roller-cell">
79   80         <img src={item.imageUrl} alt="logo" />
80   81         <span className="roller-label">{item.title}</span>

```

src/components/FortuneWheelRaffle/index.jsx

```

...   @@ -1,4 +1,4 @@
1     - import { useEffect, useState } from 'react';
1     + import { useEffect, useRef, useState } from 'react';
2     2     import PropTypes from 'prop-types';
3     3     import styled from 'styled-components';
4     4     //import { Howl } from 'howler';
@@ -10,7 +10,6 @@
10    10    import DialogRoot from './DialogRoot';
11    11    import FortuneWheelImg from './assets/fortune-wheel-inner.png';
12    12    import FortuneWheelBorder from './assets/fortune-wheel-outer.png';
13    -   import WheelSound from './assets/FortuneWheelSound.mp3';
14    13    import RaffleDialog from './RaffleDialog';
15    14    import RaffleWinner from './RaffleWinner';
16    15    import WheelItem from './WheelItem';

```



@@ -27,10 +26,34 @@

27 26 `;

28 27

29 28 `const FortuneWheelRaffle = (props) => {`

✓ Check warning on line R28

Fast refresh only works when a file only exports components. Move your component(s) to a separate file. If all exports are HOCs, add them to the `extraHOCs` option



CI / ci

[View details](#)

```
30 -   const [users, setUsers] = useState([]);
29 +   const [{ users, winner, scroll }] = useState(() => {
30 +     let eligibleUsers = props.userArray.filter(
31 +       (user) => user.isEligible === true
32 +     );
33 +     if (props.giveawayReq === 1) {
34 +       eligibleUsers = eligibleUsers.filter(
35 +         (user) => user.isSubscriber !== false
36 +       );
37 +     }
38 +     const shuffled = [];
39 +     for (let i = 0; i < 10; i += 1) {
40 +       shuffled.push(
41 +         eligibleUsers[Math.floor(Math.random() * eligibleUsers.length)]
42 +       );
43 +     }
44 +     const winnerIndex = Math.floor(Math.random() * 10);
45 +     return {
46 +       users: shuffled,
47 +       winner: shuffled[winnerIndex],
48 +       scroll: -(
49 +         winnerIndex * 36 +
50 +         Math.floor(Math.random() * 15) +
51 +         Math.ceil(props.duration / 2) * 360
52 +       ),
53 +     };
54 +   });
31 55   const [scrollSize, setScrollSize] = useState(0);
32 -   const [winner, setWinner] = useState(null);
33 -   const [timer, setTimer] = useState(null);
56 +   const timerRef = useRef(null);
34 57   // const [tickSound] = useState(
```

```
35 58      //      new Howl({
36 59      //      src: [WheelSound],
    ⇅      @@ -43,35 +66,13 @@
43 66
44 67      const closeImmediately = () => {
45 68          props.onClose();
46      -      clearTimeout(timer);
47      69  +      clearTimeout(timerRef.current);
48 70      //tickSound.stop();
49 71      //tickSound.unload();
50 72      };
51 73
52 74      useEffect(() => {
53      -      let eligibleUsers = props.userArray.filter(
54      -      (user) => user.isEligible === true
55      -      );
56      -      if (props.giveawayReq === 1) {
57      -      eligibleUsers = eligibleUsers.filter(
58      -      (user) => user.isSubscriber !== false
59      -      );
60      -      }
61      -      const shuffled = [];
62      -      for (let i = 0; i < 10; i += 1) {
63      -      shuffled.push(
64      -      eligibleUsers[Math.floor(Math.random() * eligibleUsers.length)]
65      -      );
66      -      }
67      -      const winnerIndex = Math.floor(Math.random() * 10);
68      -      const scroll = -(
69      -      winnerIndex * 36 +
70      -      Math.floor(Math.random() * 15) +
71      -      Math.ceil(props.duration / 2) * 360
72      -      );
73      -      setUsers(shuffled);
74      -      setTimeout(() => setScrollSize(scroll), 10);
75      -      setWinner(shuffled[winnerIndex]);
76      75  +      const scrollTimeout = setTimeout(() => setScrollSize(scroll), 10);
77  76      //const sId1 = tickSound.play('start');
78  77      // tickSound.on(
79  78      //      'end',
    ⇅      @@ -81,19 +82,21 @@
81 82      //      },
82 83      //sId1
```

```

83 84      //);
84      -      setTimeout(() => {
85      +      const tickTimeout = setTimeout(() => {
86      86          //tickSound.stop();
87      87          //tickSound.unload();
87      88      }, props.duration * 1000);
88      -      setTimer(
89      -      setTimeout(
90      -      () => {
91      -      props.onWin(shuffled[winnerIndex].id);
92      -      },
93      -      (props.duration + 1) * 1000
94      -      )
89      +      timerRef.current = setTimeout(
90      +      () => {
91      +      props.onWin(winner.id);
92      +      },
93      +      (props.duration + 1) * 1000
95      94      );
96      -      }, []);
95      +      return () => {
96      +      clearTimeout(scrollTimeout);
97      +      clearTimeout(tickTimeout);
98      +      };
99      +      }, [scroll, winner, props]);
97      100
98      101      const positions = [
99      102      { x: '43%', y: '8%' },

```



src/components/RelativeDate/index.jsx



```

...      @@ -5,7 +5,6 @@ import messages from './messages';
5      5      function RelativeDate(props) {
6      6      const dt = new Date(props.ISO8601Date);
7      7      const now = new Date();
8      -      let convertedDate = '';
9      8      if (
10     9      dt.getFullYear() === now.getFullYear() &&
11     10     dt.getMonth() === now.getMonth() &&
...
...      @@ -105,7 +104,7 @@ function RelativeDate(props) {
...
105    104      </span>
106    105      );

```

```
107 106      }
108      -   convertedDate = ` ${dt.getHours()}:${${
107 107  +   const convertedDate = ` ${dt.getHours()}:${${
109 108      dt.getMinutes() < 10 ? '0' : ''
110 109      }${dt.getMinutes()}`;
111 110      return (
```



▼ ...mponents/SettingsDialog/DarkModeSwitch.jsx



```
...    @@ -1,4 +1,4 @@
1      - import { useEffect, useState } from 'react';
1      + import { useState } from 'react';
2      2      import PropTypes from 'prop-types';
3      3      import { connect } from 'react-redux';
4      4      import { createSelector } from 'reselect';
@@ -12,11 +12,9 @@ import { toggleDarkMode } from
'../../containers/StyleProvider/actions';
12 12
13 13      const DarkModeSwitch = (props) => {
14 14          const intl = useIntl();
15      -   const [state, setState] = useState(false);
16      -
17      -   useEffect(() => {
18      -       setState(localStorage.getItem('darkMode') === 'true');
19      -   }, []);
15 15  +   const [state, setState] = useState(
16 16  +       () => localStorage.getItem('darkMode') === 'true'
17 17  +   );
20 18
21 19      const handleChange = (event) => {
22 20          setState(event.target.checked);
```



▼ src/components/SettingsDialog/index.jsx



```
...    @@ -1,4 +1,4 @@
1      - import { useEffect, useState } from 'react';
1      + import { useState } from 'react';
2      2      import PropTypes from 'prop-types';
3      3      import { FormattedMessage, useIntl } from 'react-intl';
4      4      import { connect } from 'react-redux';
@@ -25,10 +25,18 @@ import { changeColor } from
'../../containers/StyleProvider/actions';
```



```

25 25      const SettingsDialog = (props) => {
26 26          const intl = useIntl();
27 27          const [isOpen, setIsOpen] = useState(false);
28      -   const [themeColor, setThemeColor] = useState(props.themeColor);
29      -   const [saveCommands, setSaveCommands] = useState(false);
30      -   const [deleteWinner, setDeleteWinner] = useState(false);
31      -   const [abortCommand, setAbortCommand] = useState('');
      28 +   const [themeColor, setThemeColor] = useState(
      29 +       () => localStorage.getItem('themeColor') || '#0094ff'
      30 +   );
      31 +   const [saveCommands, setSaveCommands] = useState(
      32 +       () => localStorage.getItem('gv-saveCommands') === 'true'
      33 +   );
      34 +   const [deleteWinner, setDeleteWinner] = useState(
      35 +       () => localStorage.getItem('gv-deleteWinner') === 'true'
      36 +   );
      37 +   const [abortCommand, setAbortCommand] = useState(() =>
      38 +       localStorage.getItem('gv-abortCommand')
      39 +   );
32 40      const [error, setError] = useState(null);
33 41
34 42      const openDialog = () => {
      ↓
      @@ -56,13 +64,6 @@ const SettingsDialog = (props) => {
      ↑
56 64          closeDialog();
57 65      };
58 66
59      -   useEffect(() => {
60      -       setSaveCommands(localStorage.getItem('gv-saveCommands') === 'true');
61      -       setDeleteWinner(localStorage.getItem('gv-deleteWinner') === 'true');
62      -       setAbortCommand(localStorage.getItem('gv-abortCommand'));
63      -       setThemeColor(localStorage.getItem('themeColor') || '#0094ff');
64      -   }, []);
65      -
66 67      return (
67 68          <div style={{ display: 'inline-block' }}>
68 69              <Tooltip
      ↓

```

src/components/UserList/reducer.jsx



```

      ↑
      @@ -17,7 +17,6 @@ export const initialState = {
17 17      userArray: [],
18 18  };

```

```
19 19
20 - /* eslint-disable default-case, no-param-reassign */
21 20   const userListReducer = (state = initialState, action) =>
22 21     produce(state, (draft) => {
23 22       switch (action.type) {
24 23         ↓
```

▼ ...onents/WelcomeDialog/WelcomeHint/index.jsx

```
...   @@ -1,4 +1,4 @@
1      - import { useEffect, useState } from 'react';
      1 + import { useState } from 'react';
2      2   import { FormattedMessage } from 'react-intl';
3      3
4      4   import CannabisImg from '../assets/cannabis.webp';
      @@ -22,48 +22,45 @@ import { Wrapper } from '../components/Wrapper';
22 22   import messages from './messages';
23 23   import { HINTS } from '../../../config';
24 24
25      - const WelcomeHint = () => {
26      -   const [hint, setHint] = useState('');
27      -   const [image, setImage] = useState(LightBulbImg);
28      -   const [holiday, setHoliday] = useState(null);
25 + const holidaysDates = [
26 +   [/14-02/, ValentineImg, 'holiday1402'],
27 +   [/14-03/, PiImg, 'holiday1403'],
28 +   [/20-04/, CannabisImg, 'holiday2004'],
29 +   [/17-05/, RainbowFlagImg, 'holiday1705'],
30 +   [/d-06/, RainbowFlagImg, 'holidayJune'],
31 +   [/26-08/, DogImg, 'holiday2608'],
32 +   [/23-09/, FallImg, 'holiday2309'],
33 +   [/01-10/, VeganImg, 'holiday0110'],
34 +   [/11-10/, RainbowFlagImg, 'holiday1110'],
35 +   [/31-10/, HalloweenImg, 'holiday3110'],
36 +   [/06-12/, SantaClausImg, 'holiday0612'],
37 +   [/ (? : 25 | 26 ) - 12 / , ChristmasImg, 'holiday2512'],
38 +   [/31-12/, FireworksImg, 'holiday3112'],
39 + ];
29 40
30      - const holidaysDates = [
31      -   [/14-02/, ValentineImg, 'holiday1402'],
32      -   [/14-03/, PiImg, 'holiday1403'],
33      -   [/20-04/, CannabisImg, 'holiday2004'],
34      -   [/17-05/, RainbowFlagImg, 'holiday1705'],
```

```

35 -      [/d-06/, RainbowFlagImg, 'holidayJune'],
36 -      [/26-08/, DogImg, 'holiday2608'],
37 -      [/23-09/, FallImg, 'holiday2309'],
38 -      [/01-10/, VeganImg, 'holiday0110'],
39 -      [/11-10/, RainbowFlagImg, 'holiday1110'],
40 -      [/31-10/, HalloweenImg, 'holiday3110'],
41 -      [/06-12/, SantaClausImg, 'holiday0612'],
42 -      [/ (? : 25 | 26 ) -12/, ChristmasImg, 'holiday2512'],
43 -      [/31-12/, FireworksImg, 'holiday3112'],
44 -    ];
41 + const getToday = () => {
42 +   const d = new Date();
43 +   let day = `${d.getDate()}`;
44 +   let month = `${d.getMonth() + 1}`;
45
46 -   const getToday = () => {
47 -     const d = new Date();
48 -     let day = `${d.getDate()}`;
49 -     let month = `${d.getMonth() + 1}`;
46 +   if (month.length < 2) month = `0${month}`;
47 +   if (day.length < 2) day = `0${day}`;
50
51 -     if (month.length < 2) month = `0${month}`;
52 -     if (day.length < 2) day = `0${day}`;
49 +   return [day, month].join('-');
50 + };
53
54 -   return [day, month].join('-');
55 - };
52 + const getTodayHoliday = () => {
53 +   const today = getToday();
54 +   return holidaysDates.find(([, regex]) => regex.test(today)) || null;
55 + };
56
57 -   useEffect(() => {
58 -     setHint(HINTS[Math.floor(Math.random() * HINTS.length)]);
59 -     for (let i = 0; i < holidaysDates.length; i += 1) {
60 -       if (holidaysDates[i][0].test(getToday())) {
61 -         setImage(holidaysDates[i][1]);
62 -         setHoliday(holidaysDates[i][2]);
63 -         break;
64 -       }
65 -     }

```

```

66 -   }, []);
    57 + const WelcomeHint = () => {
    58 +   const [hint, setHint] = useState(
    59 +     () => HINTS[Math.floor(Math.random() * HINTS.length)]
    60 +   );
    61 +   const [todaysHoliday] = useState(getTodaysHoliday);
    62 +   const [image] = useState(() => todaysHoliday?.[1] ?? LightBulbImg);
    63 +   const [holiday] = useState(() => todaysHoliday?.[2] ?? null);
67 64
68 65     const changeHint = () => {
69 66         setHint(HINTS[Math.floor(Math.random() * HINTS.length)]);

```



src/components/WelcomeDialog/index.jsx



```

...   @@ -1,9 +1,7 @@
1      - import { useEffect, useState } from 'react';
    1 + import { useState } from 'react';
2      2   import PropTypes from 'prop-types';
3      3   import CircularProgress from '@mui/material/CircularProgress';
4      4   import TextField from '@mui/material/TextField';
5      - import Select from '@mui/material/Select';
6      - import MenuItem from '@mui/material/MenuItem';
7      5   import { FormattedMessage, useIntl } from 'react-intl';
8      6   import messages from './messages';
9      7   import { CompatibilityInfo } from './components/CompatibilityInfo';
    @@ -35,11 +33,17 @@ const parseChannelInput = (value) => {
35 33
36 34   const WelcomeDialog = (props) => {
37 35       const intl = useIntl();
38       - const [isChrome, setIsChrome] = useState(true);
39       - const [isFirstUse, setIsFirstUse] = useState(false);
    36 + const [isChrome] = useState(() => !!window.chrome);
    37 + const [isFirstUse] = useState(() => !localStorage.getItem('locale'));
40 38   const [isLoading, setIsLoading] = useState(false);
41 39   const [text, setText] = useState('');
42 40   const [isLinkInvalid, setIsLinkInvalid] = useState(false);
    41 + const [prevError, setPrevError] = useState(props.error);
    42 +
    43 + if (props.error !== prevError) {
    44 +   setPrevError(props.error);
    45 +   if (props.error) setIsLoading(false);
    46 + }

```

```
43 47
44 48     const handleInputChange = (e) => {
45 49         setText(e.target.value);
    ⚡    @@ -60,15 +64,6 @@ const WelcomeDialog = (props) => {
60 64         }
61 65     };
62 66
63     -   useEffect(() => {
64     -       setIsChrome(!window.chrome);
65     -       setIsFirstUse(!localStorage.getItem('locale'));
66     -   }, []);
67     -
68     -   useEffect(() => {
69     -       if (props.error) setIsLoading(false);
70     -   }, [props.error]);
71     -
72 67     const handleKeyPress = (e) => {
73 68         if (e.key === 'Enter' && !isLoading) {
74 69             handleConnect();
    ⚡
```

## ▼ src/components/Youtubeworker/index.jsx



```
    ⚡    @@ -196,7 +196,8 @@ const Youtubeworker = (props) => {
196 196         return () => {
197 197             ws.close();
198 198         };
199     -   }, [props.channel, props.platform]);
    199 +   // eslint-disable-next-line react-hooks/exhaustive-deps
    200 +   }, [props.channel, props.platform, dispatch]);
200 201
201 202     return (
202 203         <ThreeSections>
    ⚡
```

## ▼ src/containers/GiveawayPage/index.jsx



```
    ⚡    @@ -149,6 +149,7 @@ const GiveawayPage = (props) => {
149 149         }
150 150     };
151 151
    152 +   const { changeStreamProperties } = props;
152 153     useEffect(() => {
153 154         const channel =
```

```

154 155      localStorage.getItem('gv-channel') ||
    ⚡@@ -168,9 +169,9 @@ const GiveawayPage = (props) => {
168 169          videoId: channel,
169 170          platform: platform,
170 171      };
171      -      props.changeStreamProperties(streamProps);
    172  +      changeStreamProperties(streamProps);
172 173      }
173      -      }, []);
    174  +      }, [changeStreamProperties]);
174 175
175 176      if (props.streamInfo.videoId === '' || props.ban !== null) {
176 177          return (
    ⚡

```

▼ ...c/containers/QueuePage/QueueItem/index.jsx

```

...    @@ -1,4 +1,4 @@
1      - import { useEffect, useState } from 'react';
    1  + import { useState } from 'react';
2      2      import PropTypes from 'prop-types';
3      3      import { connect } from 'react-redux';
4      4      import clsx from 'clsx';
    ⚡@@ -20,7 +20,21 @@ import { deleteQueueItem, updateQueueItem } from
    './actions';
20 20      export const QueueItem = (props) => {
21 21          const [editMode, setEditMode] = useState(false);
22 22          const [editedDescription, setEditedDescription] = useState(props.message);
23      -      const [isActive, setIsActive] = useState(true);
    23  +      const [prevMessage, setPrevMessage] = useState(props.message);
    24  +      const [isActive, setIsActive] = useState(() => {
    25  +          const now = new Date();
    26  +          const lastActiveAt = new Date(props.lastActiveAt);
    27  +          return (
    28  +              (now.getTime() - lastActiveAt.getTime()) / 1000 <
    29  +              parseInt(localStorage.getItem('queue-timeToIdle'), 10)
    30  +          );
    31  +      });
    32  +
    33  +      if (props.message !== prevMessage) {
    34  +          setPrevMessage(props.message);
    35  +          setEditedDescription(props.message);
    36  +      }
    37  +

```

```
24 38      const convertDate = (dt) =>
25 39          `${dt.getHours()}:${dt.getMinutes() < 10 ? '0' : ''}${dt.getMinutes()}:${dt
26 40          dt.getSeconds() < 10 ? '0' : ''
    ↓
    ↑
64 78      );
65 79      };
66 80
67      -   useEffect(() => {
68      -       refresh();
69      -   }, []);
70      -
71      -   useEffect(() => {
72      -       setEditedDescription(props.message);
73      -   }, [props.message]);
74      -
75 81      if (editMode)
76 82      return (
77 83          <li>
    ↓
```

src/containers/QueuePage/index.jsx



```
    ↑...    @@ -127,6 +127,7 @@ const QueuePage = () => {
127 127      if (id !== null) {
128 128          launchWorker(id);
129 129      }
    130  +    // eslint-disable-next-line react-hooks/exhaustive-deps
130 131      }, []);
131 132
132 133      if (videoId === '') {
    ↓
```

...containers/QueuePage/QueueWidgetDialog.jsx



```
    ↑...    @@ -40,7 +40,7 @@ export const QueueWidgetDialog = (props) => {
40 40          setWidgetUrl(res.data.url);
41 41      }
42 42      });
43      -   }, []);
    43  +   }, [props.widgetCode]);
44 44
45 45      return (
46 46          <div style={{ display: 'inline-block' }}>
```



## ▼ src/containers/QueuePage/reducer.jsx



```
....      @@ -21,7 +21,6 @@ export const initialState = {  
21  21      widgetCode: localStorage.getItem('queue-widget-code') || '',  
22  22      };  
23  23  
24      - /* eslint-disable default-case, no-param-reassign */  
25  24      const queueReducer = (state = initialState, action) =>  
26  25          produce(state, (draft) => {  
27  26              switch (action.type) {
```



## ▼ src/utils/injectReducer.jsx



```
....      @@ -40,7 +40,7 @@ const useInjectReducer = ({ key, reducer }) => {  
40  40      const context = React.useContext(ReactReduxContext);  
41  41      React.useEffect(() => {  
42  42          getInjectors(context.store).injectReducer(key, reducer);  
43      - }, []);  
      43  + }, [context.store, key, reducer]);  
44  44      };  
45  45  
46  46      export { useInjectReducer };
```

## ▼ src/utils/injectSaga.jsx



```
....      @@ -56,7 +56,7 @@ const useInjectSaga = ({ key, saga, mode }) => {  
56  56      return () => {  
57  57          injectors.ejectSaga(key);  
58  58      };  
59      - }, []);  
      59  + }, [context.store, key, saga, mode]);  
60  60      };  
61  61  
62  62      export { useInjectSaga };
```

## ▼ src/utils/reducerInjectors.jsx



```
....      @@ -20,7 +20,7 @@ export function injectReducerFactory(store, isValid) {  
20  20      )  
21  21      return;  
22  22
```

```

23      -      store.injectedReducers[key] = reducer; // eslint-disable-line no-param-
          reassign
23      +      store.injectedReducers[key] = reducer;
24      24      store.replaceReducer(createReducer(store.injectedReducers));
25      25      };
26      26      }

```



src/utils/sagaInjectors.jsx



```

...      @@ -38,7 +38,7 @@ export function injectSagaFactory(store, isValid) {
38      38
39      39      let hasSaga = Reflect.has(store.injectedSagas, key);
40      40
41      -      if (process.env.NODE_ENV !== 'production') {
41      +      if (import.meta.env.DEV) {
42      42      const oldDescriptor = store.injectedSagas[key];
43      43      // enable hot reloading of daemon and once-till-unmount sagas
44      44      if (hasSaga && oldDescriptor.saga !== saga) {
...      @@ -51,12 +51,10 @@ export function injectSagaFactory(store, isValid) {
51      51      !hasSaga ||
52      52      (hasSaga && mode !== DAEMON && mode !== ONCE_TILL_UNMOUNT)
53      53      ) {
54      -      /* eslint-disable no-param-reassign */
55      54      store.injectedSagas[key] = {
56      55      ...newDescriptor,
57      56      task: store.runSaga(saga, args),
58      57      };
59      -      /* eslint-enable no-param-reassign */
60      58      }
61      59      };
62      60      }
...      @@ -72,9 +70,9 @@ export function ejectSagaFactory(store, isValid) {
72      70      if (descriptor.mode && descriptor.mode !== DAEMON) {
73      71      descriptor.task.cancel();
74      72      // Clean up in production; in development we need `descriptor.saga`
          for hot reloading
75      -      if (process.env.NODE_ENV === 'production') {
73      +      if (import.meta.env.PROD) {
76      74      // Need some value to be able to detect `ONCE_TILL_UNMOUNT` sagas
          in `injectSaga`
77      -      store.injectedSagas[key] = 'done'; // eslint-disable-line no-param-
          reassign
75      +      store.injectedSagas[key] = 'done';

```

```
78 76      }
79 77      }
80 78      }
  ↓
```

src/App.jsx

```
... @@ -1,18 +1,15 @@
1      - import { useState, useEffect } from 'react';
1      + import { useState } from 'react';
2      2      import YoutubeWorker from './components/YoutubeWorker';
3      3      import WelcomeDialog from './components/WelcomeDialog';
4      - import GiveawayPage from './containers/GiveawayPage';
5      4      export default function App() {
6      -      const [channelConfig, setChannelConfig] = useState(null);
7      -
8      -      useEffect(() => {
9      5      +      const [channelConfig, setChannelConfig] = useState(() => {
10     6          const savedChannel = localStorage.getItem('gv-channel');
11     7          const savedPlatform = localStorage.getItem('gv-platform');
12     8
13     -      if (savedChannel && savedPlatform) {
14     -          setChannelConfig({ channel: savedChannel, platform: savedPlatform });
15     -      }
16     -      }, []);
17     9      +      return savedChannel && savedPlatform
18     10     +      ? { channel: savedChannel, platform: savedPlatform }
19     11     +      : null;
20     12     +      });
21     13
22     14      const handleStartStream = (channelName, platformName) => {
23     15          localStorage.setItem('gv-channel', channelName);
  ↓
```

src/configureStore.jsx

```
↑ ... @@ -6,7 +6,7 @@ export default function configureStore(initialState = {})
{
6     6      let composeEnhancers = compose;
7     7      const reduxSagaMonitorOptions = {};
8     8
9     -      if (process.env.NODE_ENV !== 'production' && typeof window === 'object') {
10    9      +      if (import.meta.env.DEV && typeof window === 'object') {
11    10          if (window.__REDUX_DEVTOOLS_EXTENSION_COMPOSE__)
```

```
11 11      composeEnhancers = window.__REDUX_DEVTOOLS_EXTENSION_COMPOSE__({});
12 12      }
    ↓
```

## src/main.jsx

```
... @@ -1,7 +1,7 @@
1 1      import React from 'react';
2 2      import { createRoot } from 'react-dom/client';
3 3      import { Provider } from 'react-redux';
4      - import { translationMessages, DEFAULT_LOCALE } from './i18n';
4  + import { translationMessages } from './i18n';
5 5      import LanguageProvider from './containers/LanguageProvider';
6 6      import StyleProvider from './containers/StyleProvider';
7 7      import configureStore from './configureStore';
    ↓
```

## src/reducers.jsx

```
↑... @@ -4,8 +4,6 @@
4 4
5 5      import { combineReducers } from 'redux';
6 6      //import { connectRouter } from 'connected-react-router';
7      -
8      - import history from './utils/history';
9 7      import giveawayRulesReducer from './components/GiveawayRules/reducer';
10 8      import giveawayPageReducer from './containers/GiveawayPage/reducer';
11 9      import languageProviderReducer from './containers/LanguageProvider/reducer';
    @@ -17,7 +15,7 @@ import queueReducer from
    ↓
    './containers/QueuePage/reducer';
17 15      * Merges the main reducer with the router state and dynamically injected
    reducers
18 16      */
19 17      export default function createReducer(injectedReducers = {}) {
20      - const rootReducer = combineReducers({
18  + return combineReducers({
21 19          language: languageProviderReducer,
22 20          theme: styleProviderReducer,
23 21          raffleWrapper: raffleWrapperReducer,
    @@ -27,6 +25,4 @@ export default function createReducer(injectedReducers =
    ↓
    {}) {
27 25          //router: connectRouter(history),
28 26          ...injectedReducers,
29 27      });
```

```
30      -  
31      -   return rootReducer;  
32  28    }
```

package-lock.json



### Load Diff

Some generated files are not rendered by default. Learn more about [customizing how changed files appear on GitHub](#).



You made it to the end!