

# FSML – A Modern Fortran Statistics and Machine

- Learning Library
- 1 School of Geographical and Earth Sciences, University of Glasgow

#### DOI: 10.xxxxx/draft

#### **Software**

- Review 🗗
- Repository 🗗
- Archive ♂

## Editor: Open Journals ♂

#### Reviewers:

@openjournals

**Submitted:** 01 January 1970 **Published:** unpublished

#### License

Authors of papers retain copyrighte and release the work under a Creative Commons Attribution 4.05 International License (CC BY 4.036.

32

33

34

35

36

37

38

# **Summary**

FSML is a modern Fortran statistics and machine learning library suitable for contemporary research problems and teaching. It includes procedures for basic statistics, hypothesis tests, linear and non-linear methods, and statistical distribution functions.

## Statement of Need

The advances in computing technology over the past two decades have expanded the practical scope of statistics and allowed the widespread use of machine learning (ML). This also transformed research practices and enhanced predictive modelling across many disciplines, including Earth sciences (Boateng & Mutz, 2023), operational weather forecasting (Lang et al., 2024), and more.

Fortran is a well-established general purpose programming language that is commonly adopted in science due to its stability, reliability, performance, and array functionality. It is widely used for parallelised high-performance computing and numerical modelling (e.g., Giorgetta et al., 2018). The same strengths make it suitable for computationally demanding ML procedures and data-driven predictions. However, despite Fortran's long history in data-driven prediction and ML (e.g., Breiman, 2001; Gutmann et al., 2022; Tomassetti et al., 2009), it has not been as widely adopted in these fields as other languages and lacks well documented, accessible toolkits for statistics and classic ML.

Although projects like Neural-Fortran (Curcic, 2019), ATHENA (Taylor, 2024), and FStats cover some important procedures for deep-learning and classic statistics, the Fortran statistics and ML ecosystem remains relatively small. This potentially deters from the use of Fortran, which is already perceived as less accessible than other popular languages due to 1) the lack of familiarity with modern Fortran features, which is exacerbated by stagnating adoption of Fortran at universities, and 2) shortcomings that are currently being addressed by Fortran-lang community projects (Kedward et al., 2022).

FSML (Fortran Statistics and Machine Learning) purposefully integrates these projects: It uses stdlib for linear algebra, leverages fpm for easier building and distribution, and is developed to support compilation with the interactive LFortran compiler in addition to GFortran. As such, it builds on recent community efforts and addresses two needs:

- 1. It adds to the modern Fortran statistics and ML software ecosytem; a richer ecosystem makes Fortran a more attractive choice as a well-established, robust, high-performance language.
- 2. The use of fpm, the support of free open-source compilers, the extensive documentation, and its permissive license (MIT) facilitate its early adoption and integration into various



statistics and ML projects by students, early career researchers, and teachers. It can thus promote the adoption of Fortran.

## 41 Software Description

### 42 Scope

47

48

50

51

52

53

- FSML consists of a set of accessible and well-documented statistics and ML procedures, suitable
- 44 for many contemporary research problems and teaching. These procedures are subdivided into
- 45 five categories:
  - DST: Statistical distribution functions (e.g., the probability density, cumulative distribution, and quantile functions of the Student's t and generalised Pareto distributions).
  - STS: Basic statistics for describing and understanding data (e.g., mean, variance, correlation).
  - TST: Parametric and non-parametric hypothesis tests (e.g., analysis of variance, Mann–Whitney U).
    - LIN: Statistical procedures relying heavily on linear algebra (e.g., principal component analysis, ridge regression, linear discriminant analysis).
    - NLP: Non-linear and algorithmic procedures (e.g., k-means clustering).




Figure 1: FSML has five thematic modules: Basic statistics (STS), hypothesis tests (TST), linear procedures (LIN), non-linear procedures (NLP), and statistical distribution functions (DST).

- FSML has minimal requirements. It uses Fortran 2008 features, Fortran-lang stdlib for linear algebra, and fpm for easy building and distribution.
- Note: At the time of publication, LFortran does not reliably compile stdlib. Therefore, early users of FSML are advised to use GFortran.

## 59 Documentation

- The FSML handbook is hosted on fsml.mutz.science and can be re-generated from its source
- 61 files. It includes a detailed, example-rich documentation of the covered procedures, as well as
- installation instructions and information for contributors.

## **Examples**

- The examples below demonstrate the use of FSML interfaces, using double precision (dp):
- statistical distribution functions:



```
! exponential distribution probability density function
! with x=0.8 and lambda=0.5
fx = fsml_exp_pdf(0.8_dp, lambda=0.5_dp)
! generalised Pareto cumulative distribution function
! with modified shape (xi) and location (mu) parameters
fx = fsml_gpd_cdf(1.9_dp, xi=1.2_dp, mu=0.6_dp)
```

sample statistics and dependency measures:

```
! mean of vector x
mean = fsml_mean(x)
! sample standard deviation of vector x
std = fsml_std(x, ddf=1.0_dp)
! Pearson correlation coefficient for vectors x1 and x2
pcc = fsml_pcc(x1, x2)
```

bypothesis tests:

```
! two-sample t-test for unequal variances (Welch's t-test);
! returns test statistic (t), degrees of freedom (df), and p
call fsml_ttest_2sample(x1, x2, t, df, p, eq_var=.false.)
! one-way ANOVA on a rank-2 array (x2d);
! returns f-statistic (f), degrees of freedom (df1, df2) and p
call fsml_anova_1way(x2d, f, df1, df2, p)
```

multiple linear ridge regression:

```
! ridge regression for 100 data points, 5 variables, and lambda=0.2;
! returns y intercept (b0), regression coefficients (b), and R^2 (rsq)
call fsml_ridge(x, y, 100, 5, 0.2_dp, b0, b, rsq)
```

69 FSML's repository and handbook includes examples for every public interface.

## 70 Past and Ongoing FSML Projects

- The FSML procedures for clustering and linear discriminant analysis were reworked from the code used for climate pattern detection and explanation (Mutz et al., 2018; Mutz & Ehlers,
- 2010) FSMI's amplified of the small function and analysis of units against a small in Mate
- <sup>73</sup> 2019). FSML's empirical orthogonal functions and analysis of variance were used in Mutz
- <sup>74</sup> (2025). FSML's distribution functions are currently used for modelling climate extremes.

## 75 Acknowledgements

- <sup>76</sup> I gratefully acknowledge the Fortran-lang community efforts that this project integrates (fpm,
- stdlib, and LFortran), as well as the always helpful discussions the with the same community on Fortran-lang discourse and GitHub. I also extend my gratitude to Herbert Peck.

### References

- Boateng, D., & Mutz, S. G. (2023). pyESDv1.0.1: An open-source python framework for empirical-statistical downscaling of climate information. *Geoscientific Model Development*, 16(22), 6479–6514. https://doi.org/10.5194/gmd-16-6479-2023
- Breiman, L. (2001). Random forests. *Machine Learning*, 45(1), 5–32. https://doi.org/10. 1023/A:1010933404324
- <sup>85</sup> Curcic, M. (2019). A parallel fortran framework for neural networks and deep learning. <sup>86</sup> SIGPLAN Fortran Forum, 38(1), 4–21. https://doi.org/10.1145/3323057.3323059



- Giorgetta, M. A., Brokopf, R., Crueger, T., Esch, M., Fiedler, S., Helmert, J., Hohenegger, C., Kornblueh, L., Köhler, M., Manzini, E., Mauritsen, T., Nam, C., Raddatz, T., Rast, S., Reinert, D., Sakradzija, M., Schmidt, H., Schneck, R., Schnur, R., ... Stevens, B. (2018). ICON-a, the atmosphere component of the ICON earth system model: I. Model description. *Journal of Advances in Modeling Earth Systems*, 10(7), 1613–1637. https://doi.org/10.1029/2017MS001242
- Gutmann, E. D., Hamman, Joseph. J., Clark, M. P., Eidhammer, T., Wood, A. W., & Arnold, J. R. (2022). En-GARD: A statistical downscaling framework to produce and test large ensembles of climate projections. *Journal of Hydrometeorology*, 23(10), 1545–1561. https://doi.org/10.1175/JHM-D-21-0142.1
- Kedward, L. J., Aradi, B., Čertík, O., Curcic, M., Ehlert, S., Engel, P., Goswami, R., Hirsch,
   M., Lozada-Blanco, A., Magnin, V., Markus, A., Pagone, E., Pribec, I., Richardson, B.,
   Snyder, H., Urban, J., & Vandenplas, J. (2022). The state of fortran. Computing in
   Science & Engineering, 24(2), 63–72. https://doi.org/10.1109/MCSE.2022.3159862
- Lang, S., Alexe, M., Chantry, M., Dramsch, J., Pinault, F., Raoult, B., Clare, M. C., Lessig, C., Maier-Gerber, M., Magnusson, L., & others. (2024). AIFS-ECMWF's data-driven forecasting system. arXiv Preprint arXiv:2406.01465. https://doi.org/10.48550/arXiv.2406.01465
- Mutz, S. G. (2025). The effect of high-mountain asia topography on northern hemisphere atmospheric flow. *EGU General Assembly 2025, Vienna, Austria, 27 Apr–2 May 2025, EGU25-7283*. https://doi.org/10.5194/egusphere-egu25-7283
- Mutz, S. G., & Ehlers, T. A. (2019). Detection and explanation of spatiotemporal patterns in late cenozoic palaeoclimate change relevant to earth surface processes. *Earth Surface Dynamics*, 7(3), 663–679. https://doi.org/10.5194/esurf-7-663-2019
- Mutz, S. G., Ehlers, T. A., Werner, M., Lohmann, G., Stepanek, C., & Li, J. (2018). Estimates of late cenozoic climate change relevant to earth surface processes in tectonically active orogens. *Earth Surface Dynamics*, 6(2), 271–301. https://doi.org/10.5194/esurf-6-271-2018
- Taylor, N. T. (2024). ATHENA: A fortran package for neural networks. *Journal of Open*Source Software, 9(99), 6492. https://doi.org/10.21105/joss.06492
- Tomassetti, B., Verdecchia, M., & Giorgi, F. (2009). NN5: A neural network based approach for the downscaling of precipitation fields model description and preliminary results.

  Journal of Hydrology, 367(1), 14–26. https://doi.org/10.1016/j.jhydrol.2008.12.017