

Model			ART-HF24DDMR3-D01/SE160	ART-HF30DDMR3-D01/SE160	ART-HF36DDMR3-D01/SE160	ART-HF48DDMR3-C01/SE160	ART-HF60DDMR3-C01/SE160
Tonnage			2Ton	2.5Ton	3Ton	4Ton	5Ton
Power supply			208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz
Cooling	Norminal Capacity	Btu/h	23000	27400	33000	44000	54000
Heating	Norminal Capacity	Btu/h	24000	28400	34000	44500	54000
SEER2		Btu/h/W	16.00	16.00	16.00	16.00	16.00
Compressor	Model		KTM240D46UKT2	KTM240D46UKT2	KTM240D46UKT2	KTF420D62UNT	KTF420D62UNT
	Type		Rotary DC	Rotary DC	Rotary DC	Rotary DC	Rotary DC
	Brand		GMCC	GMCC	GMCC	GMCC	GMCC
	Qty		1	1	1	1	1
	Capacity	W	7600	7600	7600	13710	13710
	Input	W	2045	2045	2045	3570	3570
	Rated current(RLA)	A	4.15	4.15	4.15	6.85	6.85
	Thermal protector		/	/	/	/	/
	Capacitor	uF	/	/	/	/	/
	Refrigerant oil	ml	ESTER OIL VG74 620ml	ESTER OIL VG74 620ml	ESTER OIL VG74 620ml	POE VG74 1000ml	POE VG74 1000ml
Refrigerant	Refrigerant		R32	R32	R32	R32	R32
Outdoor fan motor	Model		ZKSN-200-8-6L	ZKSN-200-8-6L	ZKSN-200-8-6L	ZKSN-200-8-6L	ZKSN-200-8-6L
	Brand		WELLING	WELLING	WELLING	WELLING	WELLING
	Input	W	200	200	200	200	200
	Capacitor	uF	/	/	/	/	/
	Speed	r/min	200-1050	200-1050	200-1050	200-1050	200-1050
Indoor fan motor	Model		HDA0375J12T	HDA0375J12T	HDA0375J12T	HDA0560J12T	HDA0560J12T
	Brand		LG	LG	LG	LG	LG
	Input	W	373	373	373	560	560
	Capacitor	uF	/	/	/	/	/
	Speed	r/min	1050	1050	1050	1050	1050
Outdoor coil	Number of rows		2	2	2	2	2
	Fin spacing	mm	1.4	1.4	1.4	1.4	1.4
	Fin type		Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum
	Coil length x height x width	mm	1740×546×26.74	1740×546×26.74	1740×546×26.74	1955×756×26.74	1955×756×26.74
	Number of circuits		4	4	4	7	7
	Tube O.D and type	mm	7 Inner grooved	7 Inner grooved	7 Inner grooved	7 Inner grooved	7 Inner grooved
Indoor coil	Number of rows		4	4	4	4	4
	Fin spacing	mm	1.5	1.5	1.5	1.5	1.5
	Fin type		Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum	Hydrophilic aluminum
	Coil length x height x width	mm	670×504×53.34	670×504×53.34	670×504×53.34	836.8×714×53.34	836.8×714×53.34
	Number of circuits		6	6	6	12	12
	Tube O.D and type	mm	7 Inner grooved	7 Inner grooved	7 Inner grooved	7 Inner grooved	7 Inner grooved
Outdoor noise level		dB(A)	73	73	73	75	75
Dimension	Bady (HxDxW)	mm	1321x958x630	1321x958x630	1321x958x630	1486x1068x840	1486x1068x840
	Packing (HxDxW)	mm	1330x965x655	1330x965x655	1330x965x655	1495x1070x860	1495x1070x860
Net/Gross weight		kg	151	151	151	187	187
Refrigerant charge		g	2400	2400	2400	3000	3000
Throttle type			EXV	EXV	EXV	EXV	EXV
Refrigerant piping	Liquid side/ Gas side	mm	/	/	/	/	/
	Max. refrigerant pipe length	m	/	/	/	/	/
	Max. difference between outdoor unit and indoor unit	m	/	/	/	/	/
Ambient temp		°C	Cooling: 5~52 Heating: 32~-20	Cooling: 5~52 Heating: 32~-20	Cooling: 5~52 Heating: 32~-20	Cooling: 5~52 Heating: 32~-20	Cooling: 5~52 Heating: 32~-20
Loading QTY (40HQ)		Pcs	79	79	79	45	45