

Tonnage			1.5 Ton	2.0 Ton	2.5 Ton	3.0 Ton
iAIR - R32 Cooling Only			ATD-CF18SMR3-A02/SE143	ATD-CF24SMR3-A02/SE143	ATD-CF30SMR3-A02/SE143	ATD-CF36SMR3-B01/SE143
Power Supply			208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz
Minimum Circuit Amp.		A	10.5	13.5	16.7	19.5
Max. Overcurrent Protection		A	15	20	25	30
Cooling	Capacity	Btu/h	17000	22000	26400	32000
	SEER2 / EER2	Btu/h.W	14.3 / 11.7	14.3 / 11.7	14.3 / 11.7	14.3 / 11.7
Heating	Capacity	Btu/h	/	/	/	/
	HSPF2	Btu/h.W	/	/	/	/
Compressor Type / Brand			Scroll	Scroll	Scroll	Scroll
Fan Motor	Type		PSC	PSC	PSC	PSC
	Rated HP		1/9	1/9	1/5	1/7
Outdoor Coil			Inner Grooved Copper Tube and Hydrophilic Aluminum Fin			
Air Flow		CFM	1600	1600	2000	2250
Sound Pressure Level		dB(A)	60	60	63	63
Dimension	Unit (WxHxD)	inch	23-3/5 x 25 x 23-3/5	23-3/5 x 25 x 23-3/5	23-3/5 x 25 x 23-3/5	29-1/7 x 25 x 29-1/7
	Packing(WxHxD)	inch	24-4/5 x 26-1/5 x 24-4/5	24-4/5 x 26-1/5 x 24-4/5	24-4/5 x 26-1/5 x 24-4/5	30-1/2 x 26-1/5 x 30-1/2
Net / Gross weight		lbs	132 / 139	132 / 139	134 / 141	151 / 160
Refrigerant Connection	Liquid Side	inch	3/8	3/8	3/8	3/8
	Gas Side	inch	3/4	3/4	3/4	3/4
Refrigerant Chargeless		ft[m]	25[7.5]	25[7.5]	25[7.5]	25[7.5]
Shipping per SDT40HQ			228	228	228	180

Tonnage			3.5 Ton	4.0 Ton	5.0 Ton
iAIR - R32 Cooling Only			ATD-CF42SMR3-C01/SE143	ATD-CF48SMR3-C01/SE143	ATD-CF60SMR3-C01/SE143
Power Supply			208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz
Minimum Circuit Amp.		A	23.9	23.4	39.9
Max. Overcurrent Protection		A	35	40	60
Cooling	Capacity	Btu/h	38500	44500	55000
	SEER2 / EER2	Btu/h.W	14.3 / 11.7	14.3 / 11.7	13.8 / 11.2
Heating	Capacity	Btu/h	/	/	/
	HSPF2	Btu/h.W	/	/	/
Compressor Type / Brand			Scroll	Scroll	Scroll
Fan Motor	Type		PSC	PSC	PSC
	Rated HP		1/7	1/3	1/3
Outdoor Coil			Inner Grooved Copper Tube and Hydrophilic Aluminum Fin		
Air Flow		CFM	2600	3200	3200
Sound Pressure Level		dB(A)	65	65	65
Dimension	Unit (WxHxD)	inch	29-1/7 x 32-7/8 x 29-1/7	29-1/7 x 32-7/8 x 29-1/7	29-1/7 x 32-7/8 x 29-1/7
	Packing(WxHxD)	inch	30-1/2 x 34-1/20 x 30-1/2	30-1/2 x 34-1/20 x 30-1/2	30-1/2 x 34-1/20 x 30-1/2
Net / Gross weight		lbs	185 / 195	204 / 214	205 / 215
Refrigerant Connection	Liquid Side	inch	3/8	3/8	3/8
	Gas Side	inch	3/4	7/8	7/8
Refrigerant Chargeless		ft[m]	25[7.5]	25[7.5]	25[7.5]
Shipping per SDT40HQ			135	135	135

Tonnage			1.5 Ton	2.0 Ton	2.5 Ton	3.0 Ton
iAIR - R32 Cooling & Heating			ATD-HF18SMR3-A01/SE143	ATD-HF24SMR3-A01/SE143	ATD-HF30UMR3-A01/SE143	ATD-HF36SMR3-B01/SE143
Power Supply			208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz
Minimum Circuit Amp.	A		12.1	15.9	18.6	19.1
Max. Overcurrent Protection	A		15	20	25	30
Cooling	Capacity	Btu/h	16000	22000	27000	32000
	SEER2 / EER2	Btu/h.W	14.3 / 11.7	14.3 / 11.7	14.3 / 11.7	14.3 / 11.7
Heating	Capacity	Btu/h	16400	22200	26400	32000
	HSPF2	Btu/h.W	7.5	7.5	7.5	7.5
Compressor Type / Brand			Scroll	Scroll	Scroll	Scroll
Fan Motor	Type		PSC	PSC	DC	PSC
	Rated HP		1/9	1/9	1/6	1/7
Outdoor Coil			Inner Grooved Copper Tube and Hydrophilic Aluminum Fin			
Air Flow	CFM		1600	1600	2000	2250
Sound Pressure Level	dB(A)		60	60	63	63
Dimension	Unit (WxHxD)	inch	23-3/5 x 25 x 23-3/5	23-3/5 x 25 x 23-3/5	23-3/5 x 25 x 23-3/5	29-1/7 x 25 x 29-1/7
	Packing(WxHxD)	inch	24-4/5 x 26-1/5 x 24-4/5	24-4/5 x 26-1/5 x 24-4/5	24-4/5 x 26-1/5 x 24-4/5	30-1/2 x 26-1/5 x 30-1/2
Net / Gross weight	lbs		144 / 150	143 / 150	146 / 152	172 / 181
Refrigerant	Liquid side	inch	3/8	3/8	3/8	3/8
Connection	Gas side	inch	3/4	3/4	3/4	3/4
Refrigerant Chargeless	ft[m]		25[7.5]	25[7.5]	25[7.5]	25[7.5]
Shipping per SDT40HQ			228	228	228	180

Tonnage			3.5 Ton	4.0 Ton	5.0 Ton
iAIR - R32 Cooling & Heating			ATD-HF42SMR3-C01/SE143	ATD-HF48SMR3-C01/SE143	ATD-HF60SMR3-C01/SE143
Power Supply			208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz
Minimum Circuit Amp.	A		23	28.3	39.8
Max. Overcurrent Protection	A		40	45	60
Cooling	Capacity	Btu/h	38000	44000	55000
	SEER2 / EER2	Btu/h.W	14.3 / 11.7	14.3 / 11.7	14.3 / 11.2
Heating	Capacity	Btu/h	39000	43000	55000
	HSPF2	Btu/h.W	7.5	7.5	7.5
Compressor Type / Brand			Scroll	Scroll	Scroll
Fan Motor	Type		PSC	PSC	PSC
	Rated HP		1/7	1/3	1/3
Outdoor Coil			Inner Grooved Copper Tube and Hydrophilic Aluminum Fin		
Air Flow	CFM		2600	3200	3200
Sound Pressure Level	dB(A)		65	65	65
Dimension	Unit (WxHxD)	inch	29-1/7 x 32-7/8 x 29-1/7	29-1/7 x 32-7/8 x 29-1/7	29-1/7 x 32-7/8 x 29-1/7
	Packing(WxHxD)	inch	30-1/2 x 34-1/20 x 30-1/2	30-1/2 x 34-1/20 x 30-1/2	30-1/2 x 34-1/20 x 30-1/2
Net / Gross weight	lbs		202 / 212	221 / 231	224 / 234
Refrigerant	Liquid side	inch	3/8	3/8	3/8
Connection	Gas side	inch	3/4	7/8	7/8
Refrigerant Chargeless	ft[m]		25[7.5]	25[7.5]	25[7.5]
Shipping per SDT40HQ			135	135	135



Tonnage			1.5 Ton	2.0 Ton	2.5 Ton	3.0 Ton
iAIR - R32 Multi-Position Air Handler			AAH-CF18SMR3-A03/SE143	AAH-CF24SMR3-A03/SE143	AAH-CF30SMR3-A03/SE143	AAH-CF36SMR3-A03/SE143
Power Supply			208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz
Minimum Circuit		AMPS	2.25	2.25	2.79	2.79
Max. Overcurrent Protection		AMPS	3	3	3	3
Motor	Type		PSC	PSC	PSC	PSC
	Capacitor	uF	10	10	15	15
	Rated HP		1/5	1/5	3/10	3/10
	Rated RPM	r/min	855	940	865	865
Blower	Diameter	inch	11	11	11	11
	Width	inch	11	11	11	11
Indoor Coil Type			All Aluminum Tube and Aluminum Fin			
Indoor Air Flow			820	820	910	1060
Sound Pressure Level		dB(A)	53	53	53	55
Refrigerant Leakage			Installed	Installed	Installed	Installed
Indoor Unit	Dimension(WxHxD)	inch	19-5/8 x 45-3/4 x 22	19-5/8 x 45-3/4 x 22	19-5/8 x 45-3/4 x 22	19-5/8 x 45-3/4 x 22
	Packing(WxHxD)	inch	25-3/5 x 47-5/8 x 22-5/6	25-3/5 x 47-5/8 x 22-5/6	25-3/5 x 47-5/8 x 22-5/6	25-3/5 x 47-5/8 x 22-5/6
	Net / Gross weight	lbs	118 / 131	119 / 132	128 / 142	128 / 142
Refrigerant Control			Orifice	Orifice	Orifice	Orifice
Refrigerant Connection	Liquid Side	inch	3/8	3/8	3/8	3/8
	Gas Side	inch	3/4	3/4	3/4	3/4
Shipping per SDT40HQ			144	144	144	144

Tonnage			3.5 Ton	4.0 Ton	5.0 Ton
iAIR - R32 Multi-Position Air Handler			AAH-CF42SMR3-A03/SE143	AAH-CF48SMR3-B03/SE143	AAH-CF60UMR3-B01/SE143
Power Supply			208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz
Minimum Circuit		AMPS	3.76	3.76	7.1
Max. Overcurrent Protection		AMPS	6	6	10
Motor	Type		PSC	PSC	ECM
	Capacitor	uF	20	20	/
	Rated HP		1/2	1/2	3/4
	Rated RPM	r/min	925	925	1000
Blower	Diameter	inch	11	11	11
	Width	inch	11	11	11
Indoor Coil Type			All Aluminum Tube and Aluminum Fin		
Indoor Air Flow			1200	1450	1520
Sound Pressure Level		dB(A)	54	57	57
Refrigerant Leakage			Installed	Installed	Installed
Indoor Unit	Dimension(WxHxD)	inch	19-5/8 x 45-3/4 x 22	22 x 53-1/8 x 24-1/2	22 x 53-1/8 x 24-1/2
	Packing(WxHxD)	inch	25-3/5 x 47-5/8 x 22-5/6	27-3/4 x 54-7/8 x 25-1/4	27-3/4 x 54-7/8 x 25-1/4
	Net / Gross weight	lbs	128 / 142	163 / 183	163 / 183
Refrigerant Control			Orifice	Orifice	Orifice
Refrigerant Connection	Liquid Side	inch	3/8	3/8	3/8
	Gas Side	inch	3/4	7/8	7/8
Shipping per SDT40HQ			144	106	106

Tonnage			1.5 Ton	2.0 Ton	2.5 Ton	3.0 Ton
iAIR - R32 Wall-Hung Air Handler			AAH-CF18SMR3-C03/SE143	AAH-CF24SMR3-C03/SE143	AAH-CF30SMR3-D03/SE143	AAH-CF36SMR3-D03/SE143
Power Supply			208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz	208-230V/1N/60Hz
Minimum Circuit Amp.	AMPS		2.25	2.25	2.79	2.79
Max. Overcurrent Protection	AMPS		3	3	3	3
Motor	Type		PSC	PSC	PSC	PSC
	Capacitor	uF	10	10	15	15
	Rated HP		1/5	1/5	3/10	3/10
	Rated RPM	r/min	900	900	865	865
Blower	Diameter	inch	9	9	11	11
	Width	inch	7	7	10	10
Indoor Coil Type			All Aluminum Tube and Aluminum Fin			
Indoor Air Flow			630	710	960	1100
Sound Pressure Level		dB(A)	53	54	55	57
Refrigerant Leakage Sensor			Installed	Installed	Installed	Installed
Indoor Unit	Dimension(WxHxD)	inch	20-3/5 x 36-1/2 x 16-3/5	20-3/5 x 36-1/2 x 16-3/5	22 x 39-3/5 x 19	22 x 39-3/5 x 19
	Packing(WxHxD)	inch	22-9/10 x 39-4/5 x 19-1/3	22-9/10 x 39-4/5 x 19-1/3	24-3/5 x 42-7/8 x 22-1/4	24-3/5 x 42-7/8 x 22-1/4
	Net / Gross weight	lbs	90 / 103	90 / 103	110/119	110/119
Refrigerant Control			Orifice	Orifice	Orifice	Orifice
Refrigerant	Liquid Side	inch	3/8	3/8	3/8	3/8
Connection Valve	Gas Side	inch	3/4	3/4	3/4	3/4
Shipping per SDT40HQ			232	232	156	156