

APP CRS	Rwy Idg	12001
094°	TDZE	883
	Apt Elev	896

RNAV (RNP) Z RWY 9

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

GPS Required. For uncompensated Baro-VNAV systems, procedure NA below -16° C (4° F) or above 47° C (116° F). For inoperative MALSR, increase RNP 0.18 visibility to RVR 5000, RNP 0.30 visibility to RVR 6000.

MALSR

MISSED APPROACH: Climb to 3000 via 094° track to BLOCK and via 134° track to CALIF and hold.

D-ATIS	CINCINNATI APP CON	CINCINNATI TOWER	GND CON	CLNC DEL	CPDLC
ARR	DEP				
134.375	135.3	119.7 363.15 (090°-269°) 123.875 363.15 (270°-089°)	118.975 360.85 (RWY 18L/36R) 118.3 (RWYS 18C/36C, 09/27) 133.325 (RWY 18R/36L)	121.7	127.175

RADAR REQUIRED

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 70).

3000

BLOCK

tr 134°

CALIF

JADOP

SEMSE

KAVME

RW09

5000

4000

2400

2400

GP 3.00°

TCH 52

3.1 NM

5 NM

4.5 NM

CATEGORY	A	B	C	D
RNP 0.18 DA	1199/24	316 (400-½)		
RNP 0.30 DA	1233/40	350 (400-¾)		

AUTHORIZATION REQUIRED

COVINGTON, KENTUCKY

Orig-A 28JUL11

CINCINNATI/NORTHERN KENTUCKY INTL (CVG)

39°03'N-84°40'W

RNAV (RNP) Z RWY 9